The Coot User Manual

Paul Emsley
pemsley at mrc dash lmb dot cam dot ac dot uk



This Manual is for Coot version 0.7 and beyond

Copyright © 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012 Paul Emsley

Table of Contents

1 Introduction . . . 1

1.1 Citing Coot and Friends . . . 1
1.2 What is Coot? . . . 1
1.3 What Coot is Not . . . 1
1.4 Hardware Requirements . . . 2
1.4.1 Mouse . . . 2
1.5 Environment Variables . . . 2
1.6 Command Line Arguments . . . 3
1.7 Web Page . . . 4
1.8 Crash . . . 4

2 Mousing and Keyboarding . . . 5

2.1 Next Residue . . . 5
2.2 Keyboard Contouring . . . 5
2.3 Mouse Z Translation and Clipping . . . 5
2.4 Keyboard Translation . . . 6
2.5 Keyboard Zoom and Clip . . . 6
2.6 Scrollwheel . . . 6
2.7 Selecting Atoms . . . 6
2.8 Virtual Trackball . . . 6
2.9 More on Zooming . . . 7

3 General Features . . . 8

3.1 Version number . . . 8
3.2 Antialiasing . . . 8
3.3 Molecule Number . . . 8
3.4 Display Issues . . . 9
3.4.1 Stereo . . . 9
3.4.2 Pick Cursor . . . 9
3.4.3 Origin Marker . . . 9
3.5 Screenshot . . . 9
3.6 Raster3D output . . . 10
3.7 Display Manager . . . 10
3.8 The Modelling Toolbar . . . 11
3.9 The file selector . . . 11
3.9.1 File-name Filtering . . . 11
3.9.2 Filename Sorting . . . 11
3.9.3 Save Coordinates Directory . . . 11
3.10 Scripting . . . 11
3.10.1 Python . . . 12
3.10.1.1 Python Commands . . . 12
3.10.2 Scheme . . . 12

3.10.3 Coot State . . . 12
3.10.4 Key Binding . . . 13
3.10.5 User-Defined Functions . . . 13
3.11 Backups and Undo . . . 13
3.11.1 Redo . . . 14
3.11.2 Restoring from Backup . . . 14
3.12 View Matrix . . . 14
3.13 Space Group and Symmetry . . . 15
3.14 Recentring View . . . 15
3.15 Views . . . 16
3.16 Clipping Manipulation . . . 16
3.17 Background colour . . . 16
3.18 Unit Cell . . . 16
3.19 Rotation Centre Pointer . . . 16
3.20 Orientation Axes . . . 16
3.21 Pointer Distances . . . 17
3.22 Crosshairs . . . 17
3.23 3D Annotations . . . 17
3.24 Frame Rate . . . 17
3.25 Program Output . . . 17

4 Coordinate-Related Features . . . 18

4.1 Reading coordinates . . . 18
4.1.1 A Note on Space Groups Names . . . 18
4.1.2 Read multiple coordinate files . . . 18
4.1.3 SHELX .ins/.res files . . . 18
4.2 Atom Info . . . 19
4.3 Atom Labeling . . . 19
4.4 Atom Colouring . . . 19
4.5 Bond Parameters . . . 20
4.5.1 Bond Thickness . . . 20
4.5.2 Display Hydrogens . . . 20
4.5.3 NCS Ghosts Coordinates . . . 20
4.5.4 NCS Maps . . . 21
4.5.5 Using Strict NCS . . . 21
4.6 Download coordinates . . . 21
4.7 Get Coordinates and Map from EDS . . . 21
4.8 Save Coordinates . . . 22
4.9 Setting the Space Group . . . 22
4.10 Anisotropic Atoms . . . 22
4.11 Symmetry . . . 22
4.11.1 Missing symmetry . . . 23
4.12 Sequence View . . . 23
4.13 Print Sequence . . . 23
4.14 Environment Distances . . . 23
4.15 Distances and Angles . . . 23
4.16 Zero Occupancy Marker . . . 23
4.17 Atomic Dots . . . 24

4.18 Ball and Stick Representation . . . 24
4.19 Mean, Median Temperature Factors . . . 24
4.20 Secondary Structure Matching (SSM) . . . 24
4.21 Least-Squares Fitting . . . 25
4.22 Ligand Overlaying . . . 25
4.23 Writing PDB files . . . 26

5 Modelling and Building . . . 27

5.1 Regularization and Real Space Refinement . . . 27
5.1.1 Dictionary . . . 28
5.1.2 Sphere Refinement . . . 28
5.1.3 Refining Specific Residues . . . 29
5.1.4 Refining Carbohydrates . . . 29
5.1.5 Planar Peptide Restraints . . . 29
5.1.6 The UNK residue type . . . 30
5.1.7 Moving Zero Occupancy Atoms . . . 30
5.2 Changing the Map for Building/Refinement . . . 30
5.3 Rotate/Translate Zone . . . 30
5.4 Rigid Body Refinement . . . 30
5.5 Simplex Refinement . . . 31
5.6 Post-manipulation-hook . . . 31
5.7 Baton Building . . . 31
5.7.1 Undo . . . 32
5.7.2 Missing Skeleton . . . 32
5.7.3 Building Backwards . . . 32
5.8 Reversing Direction of Fragment . . . 33
5.9 C*alpha* -> Mainchain . . . 33
5.10 Backbone Torsion Angles . . . 33
5.11 Docking Sidechains . . . 33
5.12 Rotamers . . . 34
5.12.1 Auto Fit Rotamer . . . 34
5.12.1.1 Backrub Rotamers . . . 35
5.12.2 De-clashing residues . . . 35
5.13 Editing chi Angles . . . 35
5.14 Torsion General . . . 36
5.14.1 Ligand Torsion angles . . . 36
5.15 Pep-flip . . . 36
5.16 Add Alternate Conformation . . . 36
5.17 Mutation . . . 37
5.17.1 Mutating DNA/RNA . . . 37
5.17.2 Multiple mutations . . . 37
5.17.3 Mutating to a Non-Standard Residue . . . 38
5.17.4 Mutate and Autofit . . . 38
5.17.5 Renumbering . . . 38
5.18 Importing Lignds/Monomers . . . 38
5.19 Ligand from SMILES strings . . . 38
5.20 Find Ligands . . . 39
5.20.1 Flexible Ligands . . . 39

5.20.2 Adding Ligands to Model . . . 39
5.21 Flip Ligand . . . 40
5.22 Find Waters . . . 40
5.22.1 Refinement Failure . . . 40
5.22.2 Blobs . . . 41
5.23 Add Terminal Residue . . . 41
5.24 Add OXT Atom to Residue . . . 41
5.25 Add Atom at Pointer . . . 42
5.26 Place Helix . . . 42
5.27 Building Ideal DNA and RNA . . . 42
5.28 Merge Molecules . . . 42
5.29 Temperature Factor for New Atoms . . . 43
5.30 Applying NCS Edits . . . 43
5.31 Running Refmac . . . 43
5.32 Running SHELXL . . . 44
5.33 Clear Pending Picks . . . 44
5.34 Delete . . . 44
5.35 Sequence Assignment . . . 45
5.36 Building Links and Loops . . . 45
5.37 Fill Partial Residues . . . 45
5.38 Changing Chain IDs . . . 46
5.39 Setting Occupancies . . . 46
5.40 Fix Nomenclature Errors . . . 46
5.41 Rotamer Fix Whole Protein . . . 46
5.42 Refine All Waters . . . 46
5.43 Moving Molecules/Ligands . . . 47
5.44 Modifying the Labels on the Model/Fit/Refine dialog . . . 47

6 Map-Related Features . . . 48

6.1 Maps in General . . . 48
6.1.1 Map Reading Bug . . . 48
6.2 Create a Map . . . 48
6.2.1 Auto-read MTZ file . . . 48
6.2.2 Reading CIF data . . . 48
6.2.3 Reading PHS data . . . 49
6.3 Map Contouring . . . 49
6.4 Map Extent . . . 50
6.5 Map Contour “Scrolling” Limits . . . 50
6.6 Map Line Width . . . 50
6.7 “Dynamic” Map colouring . . . 50
6.8 Difference Map Colouring . . . 51
6.9 Make a Difference Map . . . 51
6.10 Make an Averaged Map . . . 51
6.11 Map Sampling . . . 51
6.12 Dragged Map . . . 51
6.13 Dynamic Map Sampling and Display Size . . . 51
6.14 Skeletonization . . . 52
6.15 Map Sharpening . . . 52

6.16 Pattersons . . . 52
6.17 Map Re-Interpolation . . . 52
6.18 Masks . . . 53
6.18.1 Example . . . 53
6.19 Trimming . . . 53
6.20 Map Transformation . . . 53
6.21 Export Map . . . 54

7 Validation . . . 55

7.1 Ramachandran Plots . . . 55
7.2 Geometry Analysis . . . 55
7.3 Chiral Volumes . . . 55
7.3.1 Fixing Chiral Volume Errors . . . 56
7.4 Blobs: a.k.a. Unmodelled density . . . 56
7.5 Difference Map Peaks . . . 56
7.6 Check Waters by Difference Map . . . 56
7.7 Molprobity Tools Interface . . . 57
7.8 GLN and ASN B-factor Outliers . . . 57
7.9 Validation Graphs . . . 58
7.9.1 Residue Density Fit . . . 58
7.9.2 Rotamer Analysis . . . 58
7.9.3 Temperature Factor Variance . . . 58
7.9.4 Peptide Omega Angle Distortion . . . 58

8 Representation . . . 59

8.1 Surfaces . . . 59

9 Hints and Usage Tips . . . 60

9.1 Documentation . . . 60
9.2 Low Resolution . . . 60
9.3 Coot Droppings . . . 60
9.4 Clearing Backups . . . 61
9.5 Getting out of “Translate” Mode . . . 61
9.6 Getting out of “Continuous Rotation” Mode . . . 61
9.7 Getting out of “Label Atom Only” Mode . . . 61
9.8 Button Labels . . . 61
9.9 Picking . . . 61
9.10 Resizing View . . . 62
9.11 Scroll-wheel . . . 62
9.12 Slow Computer Configuration . . . 62

10 Other Programs . . . 63

10.1 findligand . . . 63

11 Scripting Functions 64
11.1 Startup Functions 64
11.1.1 set-prefer-python 64
11.1.2 prefer-python 64
11.2 File System Functions 64
11.2.1 make-directory-maybe 64
11.2.2 set-show-paths-in-display-manager 64
11.2.3 show-paths-in-display-manager-state 64
11.2.4 add-coordinates-glob-extension 65
11.2.5 add-data-glob-extension 65
11.2.6 add-dictionary-glob-extension 65
11.2.7 add-map-glob-extension 65
11.2.8 remove-coordinates-glob-extension 65
11.2.9 remove-data-glob-extension 65
11.2.10 remove-dictionary-glob-extension 65
11.2.11 remove-map-glob-extension 65
11.2.12 set-sticky-sort-by-date 66
11.2.13 unset-sticky-sort-by-date 66
11.2.14 set-filter-fileselection-filenames 66
11.2.15 filter-fileselection-filenames-state 66
11.2.16 file-type-coords 66
11.2.17 open-coords-dialog 66
11.2.18 set-file-chooser-selector 66
11.3 Widget Utilities 66
11.3.1 set-main-window-title 66
11.4 MTZ and data handling utilities 67
11.4.1 manage-column-selector 67
11.5 Molecule Info Functions 67
11.5.1 chain-n-residues 67
11.5.2 seqnum-from-serial-number 67
11.5.3 insertion-code-from-serial-number 67
11.5.4 n-models 68
11.5.5 n-chains 68
11.5.6 is-solvent-chain-p 68
11.5.7 is-protein-chain-p 68
11.5.8 is-nucleotide-chain-p 69
11.5.9 n-residues 69
11.5.10 sort-chains 69
11.5.11 sort-residues 69
11.5.12 remarks-dialog 69
11.5.13 print-header-secondary-structure-info 69
11.5.14 copy-molecule 70
11.5.15 add-ligand-delete-residue-copy-molecule 70
11.5.16 exchange-chain-ids-for-seg-ids 70
11.5.17 show-remarks-browswer 70
11.6 Library and Utility Functions 70
11.6.1 git-revision-count 70
11.6.2 svn-revision 71

11.6.3 molecule-name . . . 71
11.6.4 set-molecule-name . . . 71
11.6.5 coot-real-exit . . . 71
11.6.6 coot-no-state-real-exit . . . 71
11.6.7 coot-clear-backup-or-real-exit . . . 71
11.6.8 coot-save-state-and-exit . . . 71
11.6.9 first-coords-imol . . . 72
11.6.10 first-small-coords-imol . . . 72
11.6.11 first-unsaved-coords-imol . . . 72
11.6.12 mmcif-sfs-to-mtz . . . 72
11.7 Graphics Utility Functions . . . 72
11.7.1 set-do-anti-aliasing . . . 72
11.7.2 do-anti-aliasing-state . . . 72
11.7.3 set-do-GL-lighting . . . 72
11.7.4 do-GL-lighting-state . . . 73
11.7.5 use-graphics-interface-state . . . 73
11.7.6 python-at-prompt-at-startup-state . . . 73
11.7.7 start-graphics-interface . . . 73
11.7.8 reset-view . . . 73
11.7.9 graphics-n-molecules . . . 73
11.7.10 toggle-idle-spin-function . . . 73
11.7.11 toggle-idle-rock-function . . . 74
11.7.12 set-rocking-factors . . . 74
11.7.13 set-idle-function-rotate-angle . . . 74
11.7.14 idle-function-rotate-angle . . . 74
11.7.15 handle-read-draw-molecule . . . 74
11.7.16 allow-duplicate-sequence-numbers . . . 74
11.7.17 set-convert-to-v2-atom-names . . . 74
11.7.18 handle-read-draw-molecule-with-recentre . . . 75
11.7.19 handle-read-draw-molecule-and-move-molecule-here . . . 75
11.7.20 read-pdb . . . 75
11.7.21 assign-hetatms . . . 75
11.7.22 hetify-residue . . . 75
11.7.23 residue-has-hetatms . . . 76
11.7.24 het-group-n-atoms . . . 76
11.7.25 replace-fragment . . . 76
11.7.26 copy-residue-range . . . 76
11.7.27 clear-and-update-model-molecule-from-file . . . 77
11.7.28 screendump-image . . . 77
11.7.29 check-for-dark-blue-density . . . 77
11.7.30 set-draw-solid-density-surface . . . 77
11.7.31 set-draw-map-standard-lines . . . 77
11.7.32 set-solid-density-surface-opacity . . . 78
11.7.33 set-flat-shading-for-solid-density-surface . . . 78
11.8 Interface Preferences . . . 78
11.8.1 set-scroll-by-wheel-mouse . . . 78
11.8.2 scroll-by-wheel-mouse-state . . . 78
11.8.3 set-default-initial-contour-level-for-map . . . 78

11.8.4 set-default-initial-contour-level-for-difference-map 78
11.8.5 print-view-matrix 79
11.8.6 get-view-quaternion-internal 79
11.8.7 set-view-quaternion 79
11.8.8 apply-ncs-to-view-orientation 79
11.8.9 apply-ncs-to-view-orientation-and-screen-centre 79
11.8.10 set-fps-flag 80
11.8.11 get-fps-flag 80
11.8.12 set-show-origin-marker 80
11.8.13 show-origin-marker-state 80
11.8.14 hide-modelling-toolbar 80
11.8.15 show-modelling-toolbar 80
11.8.16 hide-main-toolbar 80
11.8.17 show-main-toolbar 80
11.8.18 show-model-toolbar-all-icons 80
11.8.19 show-model-toolbar-main-icons 81
11.8.20 reattach-modelling-toolbar 81
11.8.21 set-model-toolbar-docked-position 81
11.8.22 suck-model-fit-dialog 81
11.8.23 add-status-bar-text 81
11.8.24 set-model-fit-refine-dialog-stays-on-top 81
11.8.25 model-fit-refine-dialog-stays-on-top-state 81
11.8.26 accept-reject-dialog-docked-state 81
11.8.27 set-accept-reject-dialog-docked-show 81
11.8.28 accept-reject-dialog-docked-show-state 82
11.9 Mouse Buttons 82
11.9.1 set-control-key-for-rotate 82
11.9.2 control-key-for-rotate-state 82
11.9.3 blob-under-pointer-to-screen-centre 82
11.10 Cursor Function 82
11.10.1 normal-cursor 82
11.10.2 fleur-cursor 82
11.10.3 pick-cursor-maybe 82
11.10.4 rotate-cursor 82
11.10.5 set-pick-cursor-index 83
11.11 Model/Fit/Refine Functions 83
11.11.1 post-model-fit-refine-dialog 83
11.11.2 unset-model-fit-refine-dialog 83
11.11.3 unset-refine-params-dialog 83
11.11.4 show-select-map-dialog 83
11.11.5 set-model-fit-refine-rotate-translate-zone-label 83
11.11.6 set-model-fit-refine-place-atom-at-pointer-label 83
11.11.7 post-other-modelling-tools-dialog 83
11.11.8 set-refinement-move-atoms-with-zero-occupancy 83
11.11.9 refinement-move-atoms-with-zero-occupancy-state 84
11.12 Backup Functions 84
11.12.1 make-backup 84
11.12.2 turn-off-backup 84

11.12.3 turn-on-backup 84
11.12.4 backup-state 84
11.12.5 apply-undo 84
11.12.6 apply-redo 84
11.12.7 set-have-unsaved-changes 84
11.12.8 have-unsaved-changes-p 85
11.12.9 set-undo-molecule 85
11.12.10 show-set-undo-molecule-chooser 85
11.12.11 set-unpathed-backup-file-names 85
11.12.12 unpathed-backup-file-names-state 85
11.12.13 backup-compress-files-state 85
11.12.14 set-backup-compress-files 85
11.13 Recover Session Function 85
11.13.1 recover-session 86
11.14 Map Functions 86
11.14.1 calc-phases-generic 86
11.14.2 map-from-mtz-by-refmac-calc-phases 86
11.14.3 map-from-mtz-by-calc-phases 86
11.14.4 set-scroll-wheel-map 87
11.14.5 set-scrollable-map 87
11.14.6 scroll-wheel-map 87
11.14.7 save-previous-map-colour 87
11.14.8 restore-previous-map-colour 87
11.14.9 set-active-map-drag-flag 87
11.14.10 get-active-map-drag-flag 87
11.14.11 set-last-map-colour 88
11.14.12 set-map-colour 88
11.14.13 set-last-map-sigma-step 88
11.14.14 set-contour-by-sigma-step-by-mol 88
11.14.15 data-resolution 88
11.14.16 model-resolution 89
11.14.17 export-map 89
11.14.18 export-map-fragment 89
11.14.19 export-map-fragment-with-origin-shift 89
11.14.20 difference-map 90
11.14.21 reinterp-map 90
11.14.22 smooth-map 90
11.15 Density Increment 90
11.15.1 set-iso-level-increment 90
11.15.2 set-diff-map-iso-level-increment 90
11.15.3 get-diff-map-iso-level-increment 91
11.15.4 set-diff-map-iso-level-increment-from-text 91
11.15.5 set-map-sampling-rate-text 91
11.15.6 set-map-sampling-rate 91
11.15.7 get-map-sampling-rate 91
11.15.8 change-contour-level 91
11.15.9 set-last-map-contour-level 91
11.15.10 set-last-map-contour-level-by-sigma 92

11.15.11 set-stop-scroll-diff-map . . . 92
11.15.12 set-stop-scroll-iso-map . . . 92
11.15.13 set-stop-scroll-iso-map-level . . . 92
11.15.14 set-stop-scroll-diff-map-level . . . 92
11.15.15 set-residue-density-fit-scale-factor . . . 92
11.16 Density Functions . . . 92
11.16.1 set-map-line-width . . . 92
11.16.2 map-line-width-state . . . 93
11.16.3 make-and-draw-map . . . 93
11.16.4 make-and-draw-map-with-refmac-params . . . 93
11.16.5 make-and-draw-map-with-reso-with-refmac-params . . . 94
11.16.6 valid-labels . . . 94
11.16.7 mtz-file-has-phases-p . . . 94
11.16.8 is-mtz-file-p . . . 95
11.16.9 cns-file-has-phases-p . . . 95
11.16.10 auto-read-do-difference-map-too-state . . . 95
11.16.11 set-auto-read-column-labels . . . 95
11.16.12 set-map-radius . . . 95
11.16.13 set-density-size . . . 95
11.16.14 set-display-intro-string . . . 95
11.16.15 get-map-radius . . . 96
11.16.16 set-esoteric-depth-cue . . . 96
11.16.17 esoteric-depth-cue-state . . . 96
11.16.18 set-swap-difference-map-colours . . . 96
11.16.19 set-map-is-difference-map . . . 96
11.16.20 map-is-difference-map . . . 96
11.16.21 another-level . . . 96
11.16.22 another-level-from-map-molecule-number . . . 97
11.16.23 residue-density-fit-scale-factor . . . 97
11.16.24 density-at-point . . . 97
11.17 Parameters from map . . . 97
11.17.1 mtz-hklin-for-map . . . 97
11.17.2 mtz-fp-for-map . . . 97
11.17.3 mtz-phi-for-map . . . 98
11.17.4 mtz-weight-for-map . . . 98
11.17.5 mtz-use-weight-for-map . . . 98
11.18 PDB Functions . . . 98
11.18.1 write-pdb-file . . . 98
11.18.2 write-residue-range-to-pdb-file . . . 98
11.18.3 quick-save . . . 99
11.19 Info Dialog . . . 99
11.19.1 info-dialog . . . 99
11.19.2 info-dialog-and-text . . . 99
11.20 Refmac Functions . . . 99
11.20.1 set-refmac-counter . . . 99
11.20.2 swap-map-colours . . . 99
11.20.3 set-keep-map-colour-after-refmac . . . 100
11.20.4 keep-map-colour-after-refmac-state . . . 100

11.21 Symmetry Functions . . . 100
11.21.1 set-symmetry-size . . . 100
11.21.2 get-show-symmetry . . . 100
11.21.3 set-show-symmetry-master . . . 100
11.21.4 set-show-symmetry-molecule . . . 100
11.21.5 symmetry-as-calphas . . . 100
11.21.6 get-symmetry-as-calphas-state . . . 101
11.21.7 set-symmetry-molecule-rotate-colour-map . . . 101
11.21.8 symmetry-molecule-rotate-colour-map-state . . . 101
11.21.9 set-symmetry-colour-by-symop . . . 101
11.21.10 set-symmetry-whole-chain . . . 101
11.21.11 set-symmetry-atom-labels-expanded . . . 102
11.21.12 has-unit-cell-state . . . 102
11.21.13 undo-symmetry-view . . . 102
11.21.14 first-molecule-with-symmetry-displayed . . . 102
11.21.15 save-symmetry-coords . . . 102
11.21.16 new-molecule-by-symmetry . . . 103
11.21.17 new-molecule-by-symmetry-with-atom-selection . . . 103
11.21.18 new-molecule-by-symop . . . 104
11.21.19 n-symops . . . 104
11.21.20 set-space-group . . . 105
11.21.21 set-symmetry-shift-search-size . . . 105
11.22 History Functions . . . 105
11.22.1 print-all-history-in-scheme . . . 105
11.22.2 print-all-history-in-python . . . 105
11.22.3 set-console-display-commands-state . . . 105
11.22.4 set-console-display-commands-hilights . . . 105
11.23 State Functions . . . 106
11.23.1 save-state . . . 106
11.23.2 save-state-file . . . 106
11.23.3 save-state-file-py . . . 106
11.23.4 set-save-state-file-name . . . 106
11.23.5 set-run-state-file-status . . . 106
11.23.6 run-state-file . . . 106
11.23.7 run-state-file-maybe . . . 106
11.24 The Virtual Trackball . . . 107
11.24.1 vt-surface . . . 107
11.24.2 vt-surface-status . . . 107
11.25 Clipping Functions . . . 107
11.25.1 set-clipping-back . . . 107
11.25.2 set-clipping-front . . . 107
11.26 Unit Cell interface . . . 107
11.26.1 get-show-unit-cell . . . 107
11.26.2 set-show-unit-cells-all . . . 107
11.26.3 set-show-unit-cell . . . 108
11.27 Colour . . . 108
11.27.1 set-colour-map-rotation-on-read-pdb . . . 108
11.27.2 set-colour-map-rotation-on-read-pdb-flag . . . 108

11.27.3 set-colour-map-rotation-on-read-pdb-c-only-flag 108
11.27.4 set-colour-by-chain 108
11.27.5 set-colour-by-molecule 108
11.27.6 set-symmetry-colour 108
11.28 Map colour 109
11.28.1 set-colour-map-rotation-for-map 109
11.28.2 set-molecule-bonds-colour-map-rotation 109
11.28.3 get-molecule-bonds-colour-map-rotation 109
11.29 Anisotropic Atoms Interface 109
11.29.1 get-limit-aniso 109
11.29.2 get-show-limit-aniso 109
11.29.3 get-show-aniso 109
11.29.4 set-limit-aniso 109
11.29.5 set-show-aniso 110
11.29.6 set-aniso-probability 110
11.29.7 get-aniso-probability 110
11.30 Display Functions 110
11.30.1 set-graphics-window-size 110
11.30.2 set-graphics-window-position 110
11.30.3 store-graphics-window-position 110
11.30.4 graphics-draw 110
11.30.5 zalman-stereo-mode 111
11.30.6 hardware-stereo-mode 111
11.30.7 stereo-mode-state 111
11.30.8 mono-mode 111
11.30.9 side-by-side-stereo-mode 111
11.30.10 set-hardware-stereo-angle-factor 111
11.30.11 hardware-stereo-angle-factor-state 111
11.30.12 set-model-fit-refine-dialog-position 111
11.30.13 set-display-control-dialog-position 112
11.30.14 set-go-to-atom-window-position 112
11.30.15 set-delete-dialog-position 112
11.30.16 set-rotate-translate-dialog-position 112
11.30.17 set-accept-reject-dialog-position 112
11.30.18 set-ramachandran-plot-dialog-position 112
11.30.19 set-edit-chi-angles-dialog-position 113
11.30.20 set-rotamer-selection-dialog-position 113
11.31 Smooth Scrolling 113
11.31.1 set-smooth-scroll-flag 113
11.31.2 get-smooth-scroll 113
11.31.3 set-smooth-scroll-steps 113
11.31.4 set-smooth-scroll-limit 113
11.32 Font Parameters 114
11.32.1 set-font-size 114
11.32.2 get-font-size 114
11.32.3 set-font-colour 114
11.32.4 set-use-stroke-characters 114
11.33 Rotation Centre 114

11.33.1 set-rotation-centre-size . . . 114
11.33.2 recentre-on-read-pdb . . . 114
11.33.3 set-recentre-on-read-pdb . . . 114
11.33.4 set-rotation-centre . . . 115
11.33.5 go-to-ligand . . . 115
11.33.6 set-go-to-ligand-n-atoms-limit . . . 115
11.34 Atom Selection Utilities . . . 115
11.34.1 median-temperature-factor . . . 115
11.34.2 average-temperature-factor . . . 115
11.34.3 standard-deviation-temperature-factor . . . 115
11.34.4 clear-pending-picks . . . 115
11.34.5 set-default-temperature-factor-for-new-atoms . . . 116
11.34.6 default-new-atoms-b-factor . . . 116
11.34.7 set-reset-b-factor-moved-atoms . . . 116
11.34.8 get-reset-b-factor-moved-atoms-state . . . 116
11.34.9 set-atom-attribute . . . 116
11.34.10 set-atom-string-attribute . . . 116
11.34.11 set-residue-name . . . 117
11.35 Skeletonization Interface . . . 117
11.35.1 skeletonize-map . . . 117
11.35.2 unskeletonize-map . . . 117
11.35.3 set-max-skeleton-search-depth . . . 118
11.35.4 set-skeleton-box-size . . . 118
11.36 Skeleton Colour . . . 118
11.36.1 set-skeleton-colour . . . 118
11.37 Read Maps . . . 118
11.37.1 handle-read-ccp4-map . . . 118
11.38 Save Coordinates . . . 118
11.38.1 save-coordinates . . . 118
11.38.2 set-save-coordinates-in-original-directory . . . 119
11.39 Read Phases File Functions . . . 119
11.39.1 read-phs-and-coords-and-make-map . . . 119
11.39.2 read-phs-and-make-map-using-cell-symm-from-previous-mol . . . 119
11.39.3 read-phs-and-make-map-using-cell-symm-from-mol . . . 119
11.39.4 read-phs-and-make-map-using-cell-symm . . . 119
11.39.5 read-phs-and-make-map-with-reso-limits . . . 120
11.40 Graphics Move . . . 120
11.40.1 undo-last-move . . . 120
11.40.2 translate-molecule-by . . . 120
11.40.3 transform-molecule-by . . . 120
11.40.4 transform-zone . . . 121
11.41 Go To Atom Widget Functions . . . 122
11.41.1 post-go-to-atom-window . . . 122
11.41.2 go-to-atom-molecule-number . . . 122
11.41.3 go-to-atom-chain-id . . . 122
11.41.4 go-to-atom-atom-name . . . 122
11.41.5 go-to-atom-residue-number . . . 122

11.41.6 go-to-atom-ins-code 122
11.41.7 go-to-atom-alt-conf 122
11.41.8 set-go-to-atom-chain-residue-atom-name 122
11.41.9 set-go-to-atom-chain-residue-atom-name-full 123
11.41.10 set-go-to-atom-chain-residue-atom-name-no-redraw . . . 123
11.41.11 update-go-to-atom-from-current-position 123
11.41.12 atom-spec-to-atom-index 123
11.41.13 full-atom-spec-to-atom-index 124
11.41.14 update-go-to-atom-window-on-changed-mol 124
11.41.15 update-go-to-atom-window-on-new-mol 124
11.41.16 set-go-to-atom-molecule 124
11.42 Map and Molecule Control 124
11.42.1 post-display-control-window 124
11.42.2 set-map-displayed 125
11.42.3 set-mol-displayed 125
11.42.4 set-display-only-model-mol 125
11.42.5 set-mol-active 125
11.42.6 mol-is-displayed 125
11.42.7 mol-is-active 125
11.42.8 map-is-displayed 126
11.42.9 set-all-maps-displayed 126
11.42.10 set-all-models-displayed-and-active 126
11.42.11 show-spacegroup 126
11.43 Align and Mutate 126
11.43.1 align-and-mutate 126
11.43.2 set-alignment-gap-and-space-penalty 126
11.44 Renumber Residue Range 127
11.44.1 renumber-residue-range 127
11.44.2 change-residue-number 127
11.45 Scripting Interface 127
11.45.1 probe-available-p 127
11.45.2 post-scripting-window 127
11.45.3 post-scheme-scripting-window 127
11.45.4 post-python-scripting-window 128
11.46 Monomer 128
11.46.1 get-coords-for-accession-code 128
11.46.2 run-script 128
11.46.3 run-guile-script 128
11.46.4 run-python-script 128
11.46.5 import-python-module 128
11.47 Regularization and Refinement 128
11.47.1 add-planar-peptide-restraints 128
11.47.2 remove-planar-peptide-restraints 129
11.47.3 set-use-trans-peptide-restraints 129
11.47.4 add-omega-torsion-restriants 129
11.47.5 remove-omega-torsion-restriants 129
11.47.6 set-refinement-immediate-replacement 129
11.47.7 refinement-immediate-replacement-state 129

11.47.8 set-residue-selection-flash-frames-number 129
11.47.9 accept-regularizement 130
11.47.10 set-refine-with-torsion-restraints 130
11.47.11 refine-with-torsion-restraints-state 130
11.47.12 set-matrix 130
11.47.13 matrix-state 130
11.47.14 set-refine-auto-range-step 130
11.47.15 set-refine-max-residues 131
11.47.16 refine-zone-atom-index-define 131
11.47.17 refine-zone 131
11.47.18 refine-auto-range 131
11.47.19 regularize-zone 132
11.47.20 set-dragged-refinement-steps-per-frame 132
11.47.21 dragged-refinement-steps-per-frame 132
11.47.22 set-refinement-refine-per-frame 132
11.47.23 refinement-refine-per-frame-state 132
11.47.24 set-refinement-drag-elasticity 132
11.47.25 set-refine-ramachandran-angles 133
11.47.26 set-fix-chiral-volumes-before-refinement 133
11.47.27 check-chiral-volumes 133
11.47.28 set-show-chiral-volume-errors-dialog 133
11.47.29 set-secondary-structure-restraints-type 133
11.47.30 secondary-structure-restraints-type 133
11.47.31 imol-refinement-map 133
11.47.32 set-imol-refinement-map 134
11.47.33 does-residue-exist-p 134
11.47.34 add-extra-bond-restraint 134
11.47.35 delete-all-extra-restraints 135
11.47.36 delete-extra-restraints-for-residue 135
11.47.37 set-extra-restraints-prosmart-sigma-limits 135
11.47.38 write-interpolated-extra-restraints 135
11.47.39 write-interpolated-models-and-extra-restraints 135
11.47.40 set-use-only-extra-torsion-restraints-for-torsions 136
11.47.41 use-only-extra-torsion-restraints-for-torsions-state 136
11.47.42 show-restraints-editor 136
11.47.43 show-restraints-editor-by-index 136
11.47.44 write-restraints-cif-dictionary 136
11.48 Simplex Refinement Interface 136
11.48.1 fit-residue-range-to-map-by-simplex 136
11.48.2 score-residue-range-fit-to-map 137
11.49 Nomenclature Errors 137
11.49.1 fix-nomenclature-errors 137
11.49.2 set-nomenclature-errors-on-read 137
11.50 Atom Info Interface 137
11.50.1 output-atom-info-as-text 137
11.51 Residue Info 138
11.51.1 residue-info-dialog 138
11.52 Residue Environment Functions 138

11.52.1 set-show-environment-distances 138
11.52.2 set-show-environment-distances-bumps 138
11.52.3 set-show-environment-distances-h-bonds 138
11.52.4 show-environment-distances-state 138
11.52.5 set-environment-distances-distance-limits 139
11.53 Pointer Functions 139
11.53.1 set-show-pointer-distances 139
11.53.2 show-pointer-distances-state 139
11.54 Zoom Functions 139
11.54.1 scale-zoom 139
11.54.2 zoom-factor 139
11.54.3 set-smooth-scroll-do-zoom 139
11.54.4 smooth-scroll-do-zoom 139
11.55 CNS Data Functions 140
11.55.1 handle-cns-data-file 140
11.55.2 handle-cns-data-file-with-cell 140
11.56 mmCIF Functions 140
11.56.1 open-cif-dictionary-file-selector-dialog 140
11.57 SHELXL Functions 140
11.57.1 read-shelx-ins-file 140
11.57.2 write-shelx-ins-file 141
11.58 Validation Functions 141
11.58.1 difference-map-peaks 141
11.58.2 gln-asn-b-factor-outliers 141
11.59 Ramachandran Plot Functions 141
11.59.1 do-ramachandran-plot 141
11.59.2 set-kleywegt-plot-n-diffs 141
11.59.3 set-ramachandran-plot-contour-levels 142
11.59.4 set-ramachandran-plot-background-block-size 142
11.59.5 ramachandran-plot-differences 142
11.59.6 ramachandran-plot-differences-by-chain 142
11.60 Sequence View Interface 142
11.60.1 do-sequence-view 142
11.61 Atom Labelling 143
11.61.1 set-brief-atom-labels 143
11.61.2 brief-atom-labels-state 143
11.62 Screen Rotation 143
11.62.1 rotate-y-scene 143
11.62.2 rotate-x-scene 143
11.62.3 rotate-z-scene 143
11.62.4 spin-zoom-trans 143
11.63 Screen Translation 144
11.63.1 translate-scene-x 144
11.63.2 translate-scene-y 144
11.63.3 translate-scene-z 144
11.64 Views Interface 144
11.64.1 add-view-here 144
11.64.2 add-view-raw 144

11.64.3 remove-named-view . . . 145
11.64.4 remove-view . . . 145
11.64.5 add-view-description . . . 145
11.64.6 add-action-view . . . 145
11.64.7 insert-action-view-after-view . . . 145
11.64.8 save-views . . . 146
11.64.9 clear-all-views . . . 146
11.65 Background Colour . . . 146
11.65.1 set-background-colour . . . 146
11.65.2 redraw-background . . . 146
11.65.3 background-is-black-p . . . 146
11.66 Ligand Fitting Functions . . . 146
11.66.1 set-ligand-acceptable-fit-fraction . . . 146
11.66.2 set-ligand-cluster-sigma-level . . . 147
11.66.3 set-ligand-flexible-ligand-n-samples . . . 147
11.66.4 set-find-ligand-n-top-ligands . . . 147
11.66.5 set-find-ligand-multi-solutions-per-cluster . . . 147
11.66.6 set-find-ligand-mask-waters . . . 147
11.66.7 set-ligand-search-protein-molecule . . . 147
11.66.8 set-ligand-search-map-molecule . . . 148
11.66.9 add-ligand-search-ligand-molecule . . . 148
11.66.10 add-ligand-search-wiggly-ligand-molecule . . . 148
11.66.11 set-find-ligand-here-cluster . . . 148
11.66.12 ligand-expert . . . 148
11.66.13 do-find-ligands-dialog . . . 148
11.66.14 match-ligand-atom-names . . . 148
11.66.15 match-ligand-atom-names-to-comp-id . . . 149
11.66.16 flip-ligand . . . 149
11.67 Water Fitting Functions . . . 150
11.67.1 wrapped-create-find-waters-dialog . . . 150
11.67.2 renumber-waters . . . 150
11.67.3 execute-find-waters-real . . . 150
11.67.4 move-waters-to-around-protein . . . 150
11.67.5 move-hetgroups-to-around-protein . . . 150
11.67.6 max-water-distance . . . 150
11.67.7 set-water-check-spherical-variance-limit . . . 151
11.67.8 set-ligand-water-to-protein-distance-limits . . . 151
11.67.9 set-ligand-water-n-cycles . . . 151
11.67.10 execute-find-blobs . . . 151
11.67.11 split-water . . . 151
11.68 Bond Representation . . . 152
11.68.1 set-default-bond-thickness . . . 152
11.68.2 set-bond-thickness . . . 152
11.68.3 set-bond-thickness-intermediate-atoms . . . 152
11.68.4 set-bond-colour-rotation-for-molecule . . . 152
11.68.5 get-bond-colour-rotation-for-molecule . . . 152
11.68.6 set-default-representation-type . . . 152
11.68.7 get-default-bond-thickness . . . 152

11.68.8 set-draw-zero-occ-markers 153
11.68.9 set-draw-cis-peptide-markups 153
11.68.10 set-draw-hydrogens 153
11.68.11 draw-hydrogens-state 153
11.68.12 set-draw-stick-mode-atoms 153
11.68.13 graphics-to-ca-representation 153
11.68.14 graphics-to-ca-plus-ligands-representation 154
11.68.15 graphics-to-ca-plus-ligands-and-sidechains-representation 154
11.68.16 graphics-to-bonds-no-waters-representation 154
11.68.17 graphics-to-bonds-representation 154
11.68.18 graphics-to-ca-plus-ligands-sec-struct-representation . . 154
11.68.19 graphics-to-sec-struct-bonds-representation 154
11.68.20 graphics-to-rainbow-representation 154
11.68.21 graphics-to-b-factor-representation 154
11.68.22 graphics-to-b-factor-cas-representation 155
11.68.23 graphics-to-occupancy-representation 155
11.68.24 graphics-to-user-defined-atom-colours-representation . . 155
11.68.25 graphics-to-user-defined-atom-colours-all-atoms-representation 155
11.68.26 graphics-molecule-bond-type 155
11.68.27 set-b-factor-bonds-scale-factor 155
11.68.28 change-model-molecule-representation-mode 155
11.68.29 set-use-grey-carbons-for-molecule 156
11.68.30 set-grey-carbon-colour 156
11.68.31 make-ball-and-stick 156
11.68.32 clear-ball-and-stick 156
11.68.33 additional-representation-by-string 156
11.68.34 additional-representation-by-attributes 157
11.69 Dots Representation 157
11.69.1 dots 157
11.69.2 set-dots-colour 158
11.69.3 unset-dots-colour 158
11.69.4 clear-dots 158
11.69.5 clear-dots-by-name 158
11.69.6 n-dots-sets 158
11.70 Pep-flip Interface 159
11.70.1 pepflip 159
11.71 Rigid Body Refinement Interface 159
11.71.1 rigid-body-refine-zone 159
11.71.2 set-rigid-body-fit-acceptable-fit-fraction 159
11.72 Add Terminal Residue Functions 159
11.72.1 set-add-terminal-residue-immediate-addition 159
11.72.2 add-terminal-residue 160
11.72.3 add-terminal-residue-using-phi-psi 160
11.72.4 set-add-terminal-residue-default-residue-type 160
11.72.5 set-add-terminal-residue-do-post-refine 160

11.72.6 add-terminal-residue-do-post-refine-state 160
11.73 Delete Residues 161
11.73.1 delete-residue-range 161
11.73.2 delete-residue 161
11.73.3 delete-residue-with-full-spec 161
11.73.4 delete-residue-hydrogens 161
11.73.5 delete-atom 162
11.73.6 delete-residue-sidechain 162
11.73.7 delete-hydrogens 162
11.74 Mainchain Building Functions 162
11.74.1 db-mainchain 162
11.75 Rotamer Functions 163
11.75.1 set-rotamer-search-mode 163
11.75.2 set-rotamer-lowest-probability 163
11.75.3 set-rotamer-check-clashes 163
11.75.4 auto-fit-best-rotamer 163
11.75.5 set-auto-fit-best-rotamer-clash-flag 164
11.75.6 n-rotamers 164
11.75.7 set-residue-to-rotamer-number 164
11.75.8 set-residue-to-rotamer-name 164
11.75.9 fill-partial-residues 165
11.76 180 Flip Side chain 165
11.76.1 do-180-degree-side-chain-flip 165
11.77 Mutate Functions 165
11.77.1 setup-mutate-auto-fit 165
11.77.2 mutate 165
11.77.3 mutate-base 166
11.77.4 set-mutate-auto-fit-do-post-refine 166
11.77.5 mutate-auto-fit-do-post-refine-state 166
11.77.6 set-rotamer-auto-fit-do-post-refine 166
11.77.7 rotamer-auto-fit-do-post-refine-state 166
11.77.8 mutate-single-residue-by-serial-number 166
11.77.9 set-residue-type-chooser-stub-state 167
11.78 Pointer Atom Functions 167
11.78.1 create-pointer-atom-molecule-maybe 167
11.78.2 pointer-atom-molecule 167
11.79 Baton Build Interface Functions 167
11.79.1 set-baton-mode 167
11.79.2 try-set-draw-baton 167
11.79.3 accept-baton-position 167
11.79.4 baton-tip-try-another 168
11.79.5 baton-tip-previous 168
11.79.6 shorten-baton 168
11.79.7 lengthen-baton 168
11.79.8 baton-build-delete-last-residue 168
11.79.9 set-baton-build-params 168
11.80 Crosshairs Interface 168
11.80.1 set-draw-crosshairs 168

11.81 Edit Chi Angles . . . 168
11.81.1 set-find-hydrogen-torsions . . . 169
11.81.2 edit-chi-angles . . . 169
11.81.3 setup-torsion-general . . . 169
11.82 Masks . . . 169
11.82.1 mask-map-by-molecule . . . 169
11.82.2 set-map-mask-atom-radius . . . 169
11.82.3 map-mask-atom-radius . . . 170
11.83 check Waters Interface . . . 170
11.83.1 delete-checked-waters-baddies . . . 170
11.84 Trim . . . 170
11.84.1 trim-molecule-by-map . . . 170
11.85 External Ray-Tracing . . . 170
11.85.1 raster3d . . . 170
11.85.2 set-raster3d-bond-thickness . . . 171
11.85.3 set-raster3d-atom-radius . . . 171
11.85.4 set-raster3d-density-thickness . . . 171
11.85.5 set-renderer-show-atoms . . . 171
11.85.6 set-raster3d-bone-thickness . . . 171
11.85.7 set-raster3d-shadows-enabled . . . 171
11.85.8 set-raster3d-water-sphere . . . 171
11.85.9 raster-screen-shot . . . 171
11.86 Superposition (SSM) . . . 172
11.86.1 superpose . . . 172
11.86.2 superpose-with-chain-selection . . . 172
11.86.3 superpose-with-atom-selection . . . 172
11.87 NCS . . . 173
11.87.1 set-draw-ncs-ghosts . . . 173
11.87.2 draw-ncs-ghosts-state . . . 173
11.87.3 set-ncs-ghost-bond-thickness . . . 173
11.87.4 ncs-update-ghosts . . . 173
11.87.5 make-dynamically-transformed-ncs-maps . . . 173
11.87.6 add-ncs-matrix . . . 174
11.87.7 add-strict-ncs-matrix . . . 174
11.87.8 show-strict-ncs-state . . . 175
11.87.9 set-show-strict-ncs . . . 175
11.87.10 set-ncs-homology-level . . . 175
11.87.11 copy-chain . . . 175
11.87.12 copy-from-ncs-master-to-others . . . 175
11.87.13 copy-residue-range-from-ncs-master-to-others . . . 176
11.87.14 ncs-control-change-ncs-master-to-chain . . . 176
11.87.15 ncs-control-change-ncs-master-to-chain-id . . . 176
11.87.16 ncs-control-display-chain . . . 176
11.88 Helices and Strands . . . 176
11.88.1 place-helix-here . . . 177
11.88.2 place-strand-here . . . 177
11.88.3 place-strand-here-dialog . . . 177
11.88.4 find-helices . . . 177

11.88.5 find-strands . . . 177
11.88.6 find-secondary-structure . . . 178
11.88.7 find-secondary-structure-local . . . 178
11.89 Nucleotides . . . 178
11.89.1 find-nucleic-acids-local . . . 178
11.90 New Molecule by Section Interface . . . 179
11.90.1 new-molecule-by-residue-type-selection . . . 179
11.90.2 new-molecule-by-atom-selection . . . 179
11.90.3 new-molecule-by-sphere-selection . . . 179
11.91 RNA/DNA . . . 179
11.91.1 ideal-nucleic-acid . . . 179
11.91.2 watson-crick-pair . . . 180
11.91.3 watson-crick-pair-for-residue-range . . . 180
11.92 Sequence (Assignment) . . . 180
11.92.1 print-sequence-chain . . . 180
11.92.2 assign-fasta-sequence . . . 181
11.92.3 assign-pir-sequence . . . 181
11.92.4 assign-sequence-from-file . . . 181
11.92.5 assign-sequence-from-string . . . 181
11.92.6 delete-all-sequences-from-molecule . . . 181
11.92.7 delete-sequence-by-chain-id . . . 182
11.93 Surface Interface . . . 182
11.93.1 do-surface . . . 182
11.93.2 set-transparent-electrostatic-surface . . . 182
11.93.3 get-electrostatic-surface-opacity . . . 182
11.94 FFFearing . . . 182
11.94.1 fffear-search . . . 182
11.94.2 set-fffear-angular-resolution . . . 183
11.94.3 fffear-angular-resolution . . . 183
11.95 Remote Control . . . 183
11.95.1 make-socket-listener-maybe . . . 183
11.95.2 set-socket-string-waiting . . . 183
11.95.3 set-socket-python-string-waiting . . . 183
11.96 Display Lists for Maps . . . 183
11.96.1 set-display-lists-for-maps . . . 183
11.96.2 display-lists-for-maps-state . . . 183
11.97 Browser Interface . . . 184
11.97.1 browser-url . . . 184
11.97.2 set-browser-interface . . . 184
11.97.3 handle-online-coot-search-request . . . 184
11.98 Molprobity Interface . . . 184
11.98.1 handle-read-draw-probe-dots . . . 184
11.98.2 handle-read-draw-probe-dots-unformatted . . . 184
11.98.3 set-do-probe-dots-on-rotamers-and-chis . . . 184
11.98.4 do-probe-dots-on-rotamers-and-chis-state . . . 185
11.98.5 set-do-probe-dots-post-refine . . . 185
11.98.6 do-probe-dots-post-refine-state . . . 185
11.98.7 unmangle-hydrogen-name . . . 185

11.98.8 set-interactive-probe-dots-molprobity-radius 185
11.98.9 interactive-probe-dots-molprobity-radius 185
11.99 Map Sharpening Interface 185
11.99.1 sharpen 185
11.99.2 set-map-sharpening-scale-limit 185
11.100 Marking Fixed Atom Interface 186
11.100.1 clear-all-fixed-atoms 186
11.101 Partial Charges 186
11.101.1 show-partial-charge-info 186
11.102 EM interface 186
11.102.1 scale-cell 186
11.103 CCP4mg Interface 186
11.103.1 write-ccp4mg-picture-description 186
11.103.2 get-atom-colour-from-mol-no 187
11.104 Aux functions 187
11.104.1 laplacian 187
11.105 SMILES 187
11.105.1 do-smiles-gui 187
11.106 PHENIX Support 187
11.106.1 set-button-label-for-external-refinement 187
11.107 Graphics Text 187
11.107.1 place-text 187
11.107.2 remove-text 188
11.107.3 text-index-near-position 188
11.108 PISA Interaction 188
11.108.1 pisa-interaction 188
11.109 Jiggle Fit 188
11.109.1 fit-to-map-by-random-jiggle 188
11.110 SBase interface 189
11.110.1 get-ccp4srs-monomer-and-dictionary 189
11.110.2 get-sbase-monomer 189
11.111 FLE-View 189
11.111.1 fle-view-set-water-dist-max 189
11.111.2 fle-view-set-h-bond-dist-max 189
11.112 LSQ-improve 189
11.112.1 lsq-improve 189
11.113 single-model view 190
11.113.1 single-model-view-model-number 190
11.113.2 single-model-view-this-model-number 190
11.113.3 single-model-view-next-model-number 190
11.113.4 single-model-view-prev-model-number 190
11.114 graphics 2D ligand view 190
11.114.1 set-show-graphics-ligand-view 190

12 More Scripting Functions ... 191
12.1 More Symmetry Functions ... 191
12.1.1 get-symmetry ... 191
12.2 Extra Map Functions ... 191
12.2.1 auto-read-make-and-draw-maps ... 191
12.2.2 auto-read-make-and-draw-maps-from-mtz ... 191
12.2.3 map-colour-components ... 191
12.3 Multi-Residue Torsion ... 191
12.3.1 multi-residue-torsion-fit-scm ... 191
12.4 Execute Refmac ... 192
12.4.1 execute-refmac-real ... 192
12.4.2 refmac-name ... 192
12.5 Dictionary Functions ... 193
12.5.1 dictionaries-read ... 193
12.6 Restraints Interface ... 193
12.6.1 set-monomer-restraints ... 193
12.7 Atom Information functions ... 193
12.7.1 resname-from-serial-number ... 193
12.7.2 residue-name ... 193
12.7.3 residue-info ... 194
12.7.4 chain-fragments-scm ... 194
12.7.5 add-molecule ... 194
12.7.6 clear-and-update-molecule ... 194
12.7.7 active-residue ... 195
12.7.8 closest-atom-simple-scm ... 195
12.7.9 closest-atom ... 195
12.7.10 residues-near-residue ... 195
12.7.11 residues-near-position-scm ... 195
12.7.12 hydrogenate-region ... 196
12.7.13 add-hydrogens-from-file ... 196
12.8 Refinement with specs ... 196
12.8.1 regularize-residues ... 196
12.8.2 mtz-file-name ... 196
12.8.3 refine-zone-with-full-residue-spec-scm ... 196
12.9 Water Chain Functions ... 197
12.9.1 water-chain-from-shelx-ins-scm ... 197
12.9.2 water-chain-scm ... 197
12.10 Glyco Tools ... 197
12.10.1 print-glyco-tree ... 197
12.11 Spin Search Functions ... 197
12.11.1 spin-search ... 197
12.12 Rotamer Scoring ... 198
12.12.1 score-rotamers-scm ... 198
12.13 protein-db ... 198
12.13.1 protein-db-loops ... 198
12.14 Coot's Hole implementation ... 199
12.14.1 hole ... 199
12.14.2 make-link ... 199

12.15 Drag and Drop Functions . . . 199
12.15.1 handle-drag-and-drop-string . . . 199
12.16 Map to Model Correlation . . . 200
12.16.1 set-map-correlation-atom-radius . . . 200
12.16.2 map-to-model-correlation . . . 200
12.16.3 map-to-model-correlation-stats . . . 200
12.16.4 map-to-model-correlation-per-residue . . . 200
12.16.5 qq-plot-map-and-model-scm . . . 201
12.16.6 density-score-residue . . . 201
12.16.7 map-mean-scm . . . 201
12.16.8 map-statistics-scm . . . 201

13 Scheme Scripting Functions . . . 202

13.1 fascinating-things . . . 202
13.2 refmac . . . 202
13.3 coot-utils . . . 203
13.4 filter . . . 213
13.5 remote-control . . . 214
13.6 3d-generator-import . . . 214
13.7 fitting . . . 215
13.8 libcheck . . . 216
13.9 extra-top-level . . . 216
13.10 gui-add-linked-cho . . . 217
13.11 tips-gui . . . 217
13.12 jligand-gui . . . 217
13.13 hello . . . 217
13.14 mutate-from-scheme . . . 217
13.15 coot-gui . . . 218
13.16 cns2coot . . . 222
13.17 clear-backup . . . 222
13.18 redefine-functions . . . 222
13.19 check-for-updates . . . 223
13.20 coot-lsq . . . 223
13.21 get-ebi . . . 223
13.22 coot-crash-catcher . . . 224
13.23 get-recent-pdbe . . . 224
13.24 contact-score-isolated-ligand . . . 225
13.25 snarf-coot-docs . . . 225
13.26 run-mogul . . . 226
13.27 group-settings . . . 226
13.28 brute-lsqman . . . 226
13.29 generic-objects . . . 226
13.30 gui-ligand-sliders . . . 227
13.31 ligand-check . . . 227
13.32 coot . . . 228
13.33 ncs . . . 228
13.34 parse-pisa-xml . . . 229
13.35 americanisms . . . 230

13.36 c-interface_8h . . . 230
13.37 Startup Functions . . . 230
13.37.1 set-prefer-python . . . 230
13.37.2 prefer-python . . . 230
13.38 File System Functions . . . 231
13.38.1 make-directory-maybe . . . 231
13.38.2 set-show-paths-in-display-manager . . . 231
13.38.3 show-paths-in-display-manager-state . . . 231
13.38.4 add-coordinates-glob-extension . . . 231
13.38.5 add-data-glob-extension . . . 231
13.38.6 add-dictionary-glob-extension . . . 231
13.38.7 add-map-glob-extension . . . 232
13.38.8 remove-coordinates-glob-extension . . . 232
13.38.9 remove-data-glob-extension . . . 232
13.38.10 remove-dictionary-glob-extension . . . 232
13.38.11 remove-map-glob-extension . . . 232
13.38.12 set-sticky-sort-by-date . . . 232
13.38.13 unset-sticky-sort-by-date . . . 232
13.38.14 set-filter-fileselection-filenames . . . 232
13.38.15 filter-fileselection-filenames-state . . . 233
13.38.16 file-type-coords . . . 233
13.38.17 open-coords-dialog . . . 233
13.38.18 set-file-chooser-selector . . . 233
13.39 Widget Utilities . . . 233
13.39.1 set-main-window-title . . . 233
13.40 MTZ and data handling utilities . . . 233
13.40.1 manage-column-selector . . . 233
13.41 Molecule Info Functions . . . 233
13.41.1 chain-n-residues . . . 233
13.41.2 seqnum-from-serial-number . . . 234
13.41.3 insertion-code-from-serial-number . . . 234
13.41.4 n-models . . . 234
13.41.5 n-chains . . . 234
13.41.6 is-solvent-chain-p . . . 235
13.41.7 is-protein-chain-p . . . 235
13.41.8 is-nucleotide-chain-p . . . 235
13.41.9 n-residues . . . 235
13.41.10 sort-chains . . . 236
13.41.11 sort-residues . . . 236
13.41.12 remarks-dialog . . . 236
13.41.13 print-header-secondary-structure-info . . . 236
13.41.14 copy-molecule . . . 236
13.41.15 add-ligand-delete-residue-copy-molecule . . . 236
13.41.16 exchange-chain-ids-for-seg-ids . . . 237
13.41.17 show-remarks-browswer . . . 237
13.42 Library and Utility Functions . . . 237
13.42.1 git-revision-count . . . 237
13.42.2 svn-revision . . . 237

13.42.3 molecule-name . . . 237
13.42.4 set-molecule-name . . . 237
13.42.5 coot-real-exit . . . 238
13.42.6 coot-no-state-real-exit . . . 238
13.42.7 coot-clear-backup-or-real-exit . . . 238
13.42.8 coot-save-state-and-exit . . . 238
13.42.9 first-coords-imol . . . 238
13.42.10 first-small-coords-imol . . . 238
13.42.11 first-unsaved-coords-imol . . . 238
13.42.12 mmcif-sfs-to-mtz . . . 239
13.43 Graphics Utility Functions . . . 239
13.43.1 set-do-anti-aliasing . . . 239
13.43.2 do-anti-aliasing-state . . . 239
13.43.3 set-do-GL-lighting . . . 239
13.43.4 do-GL-lighting-state . . . 239
13.43.5 use-graphics-interface-state . . . 239
13.43.6 python-at-prompt-at-startup-state . . . 239
13.43.7 start-graphics-interface . . . 240
13.43.8 reset-view . . . 240
13.43.9 graphics-n-molecules . . . 240
13.43.10 toggle-idle-spin-function . . . 240
13.43.11 toggle-idle-rock-function . . . 240
13.43.12 set-rocking-factors . . . 240
13.43.13 set-idle-function-rotate-angle . . . 240
13.43.14 idle-function-rotate-angle . . . 241
13.43.15 handle-read-draw-molecule . . . 241
13.43.16 allow-duplicate-sequence-numbers . . . 241
13.43.17 set-convert-to-v2-atom-names . . . 241
13.43.18 handle-read-draw-molecule-with-recentre . . . 241
13.43.19 handle-read-draw-molecule-and-move-molecule-here . . . 241
13.43.20 read-pdb . . . 241
13.43.21 assign-hetatms . . . 242
13.43.22 hetify-residue . . . 242
13.43.23 residue-has-hetatms . . . 242
13.43.24 het-group-n-atoms . . . 242
13.43.25 replace-fragment . . . 242
13.43.26 copy-residue-range . . . 243
13.43.27 clear-and-update-model-molecule-from-file . . . 243
13.43.28 screendump-image . . . 243
13.43.29 check-for-dark-blue-density . . . 243
13.43.30 set-draw-solid-density-surface . . . 243
13.43.31 set-draw-map-standard-lines . . . 244
13.43.32 set-solid-density-surface-opacity . . . 244
13.43.33 set-flat-shading-for-solid-density-surface . . . 244
13.44 Interface Preferences . . . 244
13.44.1 set-scroll-by-wheel-mouse . . . 244
13.44.2 scroll-by-wheel-mouse-state . . . 244
13.44.3 set-default-initial-contour-level-for-map . . . 245

13.44.4 set-default-initial-contour-level-for-difference-map 245
13.44.5 print-view-matrix 245
13.44.6 get-view-quaternion-internal 245
13.44.7 set-view-quaternion 245
13.44.8 apply-ncs-to-view-orientation 245
13.44.9 apply-ncs-to-view-orientation-and-screen-centre 246
13.44.10 set-fps-flag 246
13.44.11 get-fps-flag 246
13.44.12 set-show-origin-marker 246
13.44.13 show-origin-marker-state 246
13.44.14 hide-modelling-toolbar 246
13.44.15 show-modelling-toolbar 246
13.44.16 hide-main-toolbar 246
13.44.17 show-main-toolbar 247
13.44.18 show-model-toolbar-all-icons 247
13.44.19 show-model-toolbar-main-icons 247
13.44.20 reattach-modelling-toolbar 247
13.44.21 set-model-toolbar-docked-position 247
13.44.22 suck-model-fit-dialog 247
13.44.23 add-status-bar-text 247
13.44.24 set-model-fit-refine-dialog-stays-on-top 247
13.44.25 model-fit-refine-dialog-stays-on-top-state 247
13.44.26 accept-reject-dialog-docked-state 248
13.44.27 set-accept-reject-dialog-docked-show 248
13.44.28 accept-reject-dialog-docked-show-state 248
13.45 Mouse Buttons 248
13.45.1 set-control-key-for-rotate 248
13.45.2 control-key-for-rotate-state 248
13.45.3 blob-under-pointer-to-screen-centre 248
13.46 Cursor Function 248
13.46.1 normal-cursor 248
13.46.2 fleur-cursor 249
13.46.3 pick-cursor-maybe 249
13.46.4 rotate-cursor 249
13.46.5 set-pick-cursor-index 249
13.47 Model/Fit/Refine Functions 249
13.47.1 post-model-fit-refine-dialog 249
13.47.2 unset-model-fit-refine-dialog 249
13.47.3 unset-refine-params-dialog 249
13.47.4 show-select-map-dialog 249
13.47.5 set-model-fit-refine-rotate-translate-zone-label 249
13.47.6 set-model-fit-refine-place-atom-at-pointer-label 250
13.47.7 post-other-modelling-tools-dialog 250
13.47.8 set-refinement-move-atoms-with-zero-occupancy 250
13.47.9 refinement-move-atoms-with-zero-occupancy-state 250
13.48 Backup Functions 250
13.48.1 make-backup 250
13.48.2 turn-off-backup 250

13.48.3 turn-on-backup 250
13.48.4 backup-state 250
13.48.5 apply-undo 251
13.48.6 apply-redo 251
13.48.7 set-have-unsaved-changes 251
13.48.8 have-unsaved-changes-p 251
13.48.9 set-undo-molecule 251
13.48.10 show-set-undo-molecule-chooser 251
13.48.11 set-unpathed-backup-file-names 251
13.48.12 unpathed-backup-file-names-state 251
13.48.13 backup-compress-files-state 252
13.48.14 set-backup-compress-files 252
13.49 Recover Session Function 252
13.49.1 recover-session 252
13.50 Map Functions 252
13.50.1 calc-phases-generic 252
13.50.2 map-from-mtz-by-refmac-calc-phases 252
13.50.3 map-from-mtz-by-calc-phases 253
13.50.4 set-scroll-wheel-map 253
13.50.5 set-scrollable-map 253
13.50.6 scroll-wheel-map 253
13.50.7 save-previous-map-colour 253
13.50.8 restore-previous-map-colour 253
13.50.9 set-active-map-drag-flag 253
13.50.10 get-active-map-drag-flag 254
13.50.11 set-last-map-colour 254
13.50.12 set-map-colour 254
13.50.13 set-last-map-sigma-step 254
13.50.14 set-contour-by-sigma-step-by-mol 254
13.50.15 data-resolution 254
13.50.16 model-resolution 255
13.50.17 export-map 255
13.50.18 export-map-fragment 255
13.50.19 export-map-fragment-with-origin-shift 255
13.50.20 difference-map 256
13.50.21 reinterp-map 256
13.50.22 smooth-map 256
13.51 Density Increment 256
13.51.1 set-iso-level-increment 256
13.51.2 set-diff-map-iso-level-increment 256
13.51.3 get-diff-map-iso-level-increment 257
13.51.4 set-diff-map-iso-level-increment-from-text 257
13.51.5 set-map-sampling-rate-text 257
13.51.6 set-map-sampling-rate 257
13.51.7 get-map-sampling-rate 257
13.51.8 change-contour-level 257
13.51.9 set-last-map-contour-level 257
13.51.10 set-last-map-contour-level-by-sigma 258

13.51.11 set-stop-scroll-diff-map 258
13.51.12 set-stop-scroll-iso-map 258
13.51.13 set-stop-scroll-iso-map-level 258
13.51.14 set-stop-scroll-diff-map-level 258
13.51.15 set-residue-density-fit-scale-factor 258
13.52 Density Functions 258
13.52.1 set-map-line-width 258
13.52.2 map-line-width-state 259
13.52.3 make-and-draw-map 259
13.52.4 make-and-draw-map-with-refmac-params 259
13.52.5 make-and-draw-map-with-reso-with-refmac-params 260
13.52.6 valid-labels 260
13.52.7 mtz-file-has-phases-p 260
13.52.8 is-mtz-file-p 261
13.52.9 cns-file-has-phases-p 261
13.52.10 auto-read-do-difference-map-too-state 261
13.52.11 set-auto-read-column-labels 261
13.52.12 set-map-radius 261
13.52.13 set-density-size 261
13.52.14 set-display-intro-string 261
13.52.15 get-map-radius 262
13.52.16 set-esoteric-depth-cue 262
13.52.17 esoteric-depth-cue-state 262
13.52.18 set-swap-difference-map-colours 262
13.52.19 set-map-is-difference-map 262
13.52.20 map-is-difference-map 262
13.52.21 another-level 262
13.52.22 another-level-from-map-molecule-number 263
13.52.23 residue-density-fit-scale-factor 263
13.52.24 density-at-point 263
13.53 Parameters from map 263
13.53.1 mtz-hklin-for-map 263
13.53.2 mtz-fp-for-map 263
13.53.3 mtz-phi-for-map 264
13.53.4 mtz-weight-for-map 264
13.53.5 mtz-use-weight-for-map 264
13.54 PDB Functions 264
13.54.1 write-pdb-file 264
13.54.2 write-residue-range-to-pdb-file 264
13.54.3 quick-save 265
13.55 Info Dialog 265
13.55.1 info-dialog 265
13.55.2 info-dialog-and-text 265
13.56 Refmac Functions 265
13.56.1 set-refmac-counter 265
13.56.2 swap-map-colours 265
13.56.3 set-keep-map-colour-after-refmac 266
13.56.4 keep-map-colour-after-refmac-state 266

13.57 Symmetry Functions . . . 266
13.57.1 set-symmetry-size . . . 266
13.57.2 get-show-symmetry . . . 266
13.57.3 set-show-symmetry-master . . . 266
13.57.4 set-show-symmetry-molecule . . . 266
13.57.5 symmetry-as-calphas . . . 266
13.57.6 get-symmetry-as-calphas-state . . . 267
13.57.7 set-symmetry-molecule-rotate-colour-map . . . 267
13.57.8 symmetry-molecule-rotate-colour-map-state . . . 267
13.57.9 set-symmetry-colour-by-symop . . . 267
13.57.10 set-symmetry-whole-chain . . . 267
13.57.11 set-symmetry-atom-labels-expanded . . . 268
13.57.12 has-unit-cell-state . . . 268
13.57.13 undo-symmetry-view . . . 268
13.57.14 first-molecule-with-symmetry-displayed . . . 268
13.57.15 save-symmetry-coords . . . 268
13.57.16 new-molecule-by-symmetry . . . 269
13.57.17 new-molecule-by-symmetry-with-atom-selection . . . 269
13.57.18 new-molecule-by-symop . . . 270
13.57.19 n-symops . . . 270
13.57.20 set-space-group . . . 271
13.57.21 set-symmetry-shift-search-size . . . 271
13.58 History Functions . . . 271
13.58.1 print-all-history-in-scheme . . . 271
13.58.2 print-all-history-in-python . . . 271
13.58.3 set-console-display-commands-state . . . 271
13.58.4 set-console-display-commands-hilights . . . 271
13.59 State Functions . . . 272
13.59.1 save-state . . . 272
13.59.2 save-state-file . . . 272
13.59.3 save-state-file-py . . . 272
13.59.4 set-save-state-file-name . . . 272
13.59.5 set-run-state-file-status . . . 272
13.59.6 run-state-file . . . 272
13.59.7 run-state-file-maybe . . . 272
13.60 The Virtual Trackball . . . 273
13.60.1 vt-surface . . . 273
13.60.2 vt-surface-status . . . 273
13.61 Clipping Functions . . . 273
13.61.1 set-clipping-back . . . 273
13.61.2 set-clipping-front . . . 273
13.62 Unit Cell interface . . . 273
13.62.1 get-show-unit-cell . . . 273
13.62.2 set-show-unit-cells-all . . . 273
13.62.3 set-show-unit-cell . . . 274
13.63 Colour . . . 274
13.63.1 set-colour-map-rotation-on-read-pdb . . . 274
13.63.2 set-colour-map-rotation-on-read-pdb-flag . . . 274

13.63.3 set-colour-map-rotation-on-read-pdb-c-only-flag 274
13.63.4 set-colour-by-chain 274
13.63.5 set-colour-by-molecule 274
13.63.6 set-symmetry-colour 274
13.64 Map colour 275
13.64.1 set-colour-map-rotation-for-map 275
13.64.2 set-molecule-bonds-colour-map-rotation 275
13.64.3 get-molecule-bonds-colour-map-rotation 275
13.65 Anisotropic Atoms Interface 275
13.65.1 get-limit-aniso 275
13.65.2 get-show-limit-aniso 275
13.65.3 get-show-aniso 275
13.65.4 set-limit-aniso 275
13.65.5 set-show-aniso 276
13.65.6 set-aniso-probability 276
13.65.7 get-aniso-probability 276
13.66 Display Functions 276
13.66.1 set-graphics-window-size 276
13.66.2 set-graphics-window-position 276
13.66.3 store-graphics-window-position 276
13.66.4 graphics-draw 276
13.66.5 zalman-stereo-mode 277
13.66.6 hardware-stereo-mode 277
13.66.7 stereo-mode-state 277
13.66.8 mono-mode 277
13.66.9 side-by-side-stereo-mode 277
13.66.10 set-hardware-stereo-angle-factor 277
13.66.11 hardware-stereo-angle-factor-state 277
13.66.12 set-model-fit-refine-dialog-position 277
13.66.13 set-display-control-dialog-position 278
13.66.14 set-go-to-atom-window-position 278
13.66.15 set-delete-dialog-position 278
13.66.16 set-rotate-translate-dialog-position 278
13.66.17 set-accept-reject-dialog-position 278
13.66.18 set-ramachandran-plot-dialog-position 278
13.66.19 set-edit-chi-angles-dialog-position 279
13.66.20 set-rotamer-selection-dialog-position 279
13.67 Smooth Scrolling 279
13.67.1 set-smooth-scroll-flag 279
13.67.2 get-smooth-scroll 279
13.67.3 set-smooth-scroll-steps 279
13.67.4 set-smooth-scroll-limit 279
13.68 Font Parameters 280
13.68.1 set-font-size 280
13.68.2 get-font-size 280
13.68.3 set-font-colour 280
13.68.4 set-use-stroke-characters 280
13.69 Rotation Centre 280

13.69.1 set-rotation-centre-size 280
13.69.2 recentre-on-read-pdb 280
13.69.3 set-recentre-on-read-pdb 280
13.69.4 set-rotation-centre 281
13.69.5 go-to-ligand 281
13.69.6 set-go-to-ligand-n-atoms-limit 281
13.70 Atom Selection Utilities 281
13.70.1 median-temperature-factor 281
13.70.2 average-temperature-factor 281
13.70.3 standard-deviation-temperature-factor 281
13.70.4 clear-pending-picks 281
13.70.5 set-default-temperature-factor-for-new-atoms 282
13.70.6 default-new-atoms-b-factor 282
13.70.7 set-reset-b-factor-moved-atoms 282
13.70.8 get-reset-b-factor-moved-atoms-state 282
13.70.9 set-atom-attribute 282
13.70.10 set-atom-string-attribute 282
13.70.11 set-residue-name 283
13.71 Skeletonization Interface 283
13.71.1 skeletonize-map 283
13.71.2 unskeletonize-map 283
13.71.3 set-max-skeleton-search-depth 284
13.71.4 set-skeleton-box-size 284
13.72 Skeleton Colour 284
13.72.1 set-skeleton-colour 284
13.73 Read Maps 284
13.73.1 handle-read-ccp4-map 284
13.74 Save Coordinates 284
13.74.1 save-coordinates 284
13.74.2 set-save-coordinates-in-original-directory 285
13.75 Read Phases File Functions 285
13.75.1 read-phs-and-coords-and-make-map 285
13.75.2 read-phs-and-make-map-using-cell-symm-from-previous-mol 285
13.75.3 read-phs-and-make-map-using-cell-symm-from-mol 285
13.75.4 read-phs-and-make-map-using-cell-symm 285
13.75.5 read-phs-and-make-map-with-reso-limits 286
13.76 Graphics Move 286
13.76.1 undo-last-move 286
13.76.2 translate-molecule-by 286
13.76.3 transform-molecule-by 286
13.76.4 transform-zone 287
13.77 Go To Atom Widget Functions 288
13.77.1 post-go-to-atom-window 288
13.77.2 go-to-atom-molecule-number 288
13.77.3 go-to-atom-chain-id 288
13.77.4 go-to-atom-atom-name 288
13.77.5 go-to-atom-residue-number 288

13.77.6 go-to-atom-ins-code 288
13.77.7 go-to-atom-alt-conf 288
13.77.8 set-go-to-atom-chain-residue-atom-name 288
13.77.9 set-go-to-atom-chain-residue-atom-name-full 289
13.77.10 set-go-to-atom-chain-residue-atom-name-no-redraw . . . 289
13.77.11 update-go-to-atom-from-current-position 289
13.77.12 atom-spec-to-atom-index 289
13.77.13 full-atom-spec-to-atom-index 290
13.77.14 update-go-to-atom-window-on-changed-mol 290
13.77.15 update-go-to-atom-window-on-new-mol 290
13.77.16 set-go-to-atom-molecule 290
13.78 Map and Molecule Control 290
13.78.1 post-display-control-window 290
13.78.2 set-map-displayed 291
13.78.3 set-mol-displayed 291
13.78.4 set-display-only-model-mol 291
13.78.5 set-mol-active 291
13.78.6 mol-is-displayed 291
13.78.7 mol-is-active 291
13.78.8 map-is-displayed 292
13.78.9 set-all-maps-displayed 292
13.78.10 set-all-models-displayed-and-active 292
13.78.11 show-spacegroup 292
13.79 Align and Mutate 292
13.79.1 align-and-mutate 292
13.79.2 set-alignment-gap-and-space-penalty 292
13.80 Renumber Residue Range 293
13.80.1 renumber-residue-range 293
13.80.2 change-residue-number 293
13.81 Scripting Interface 293
13.81.1 probe-available-p 293
13.81.2 post-scripting-window 293
13.81.3 post-scheme-scripting-window 293
13.81.4 post-python-scripting-window 294
13.82 Monomer 294
13.82.1 get-coords-for-accession-code 294
13.82.2 run-script 294
13.82.3 run-guile-script 294
13.82.4 run-python-script 294
13.82.5 import-python-module 294
13.83 Regularization and Refinement 294
13.83.1 add-planar-peptide-restraints 294
13.83.2 remove-planar-peptide-restraints 295
13.83.3 set-use-trans-peptide-restraints 295
13.83.4 add-omega-torsion-restriants 295
13.83.5 remove-omega-torsion-restriants 295
13.83.6 set-refinement-immediate-replacement 295
13.83.7 refinement-immediate-replacement-state 295

13.83.8 set-residue-selection-flash-frames-number 295
13.83.9 accept-regularizement 296
13.83.10 set-refine-with-torsion-restraints 296
13.83.11 refine-with-torsion-restraints-state 296
13.83.12 set-matrix 296
13.83.13 matrix-state 296
13.83.14 set-refine-auto-range-step 296
13.83.15 set-refine-max-residues 297
13.83.16 refine-zone-atom-index-define 297
13.83.17 refine-zone 297
13.83.18 refine-auto-range 297
13.83.19 regularize-zone 298
13.83.20 set-dragged-refinement-steps-per-frame 298
13.83.21 dragged-refinement-steps-per-frame 298
13.83.22 set-refinement-refine-per-frame 298
13.83.23 refinement-refine-per-frame-state 298
13.83.24 set-refinement-drag-elasticity 298
13.83.25 set-refine-ramachandran-angles 299
13.83.26 set-fix-chiral-volumes-before-refinement 299
13.83.27 check-chiral-volumes 299
13.83.28 set-show-chiral-volume-errors-dialog 299
13.83.29 set-secondary-structure-restraints-type 299
13.83.30 secondary-structure-restraints-type 299
13.83.31 imol-refinement-map 299
13.83.32 set-imol-refinement-map 300
13.83.33 does-residue-exist-p 300
13.83.34 add-extra-bond-restraint 300
13.83.35 delete-all-extra-restraints 301
13.83.36 delete-extra-restraints-for-residue 301
13.83.37 set-extra-restraints-prosmart-sigma-limits 301
13.83.38 write-interpolated-extra-restraints 301
13.83.39 write-interpolated-models-and-extra-restraints 301
13.83.40 set-use-only-extra-torsion-restraints-for-torsions 302
13.83.41 use-only-extra-torsion-restraints-for-torsions-state 302
13.83.42 show-restraints-editor 302
13.83.43 show-restraints-editor-by-index 302
13.83.44 write-restraints-cif-dictionary 302
13.84 Simplex Refinement Interface 302
13.84.1 fit-residue-range-to-map-by-simplex 302
13.84.2 score-residue-range-fit-to-map 303
13.85 Nomenclature Errors 303
13.85.1 fix-nomenclature-errors 303
13.85.2 set-nomenclature-errors-on-read 303
13.86 Atom Info Interface 303
13.86.1 output-atom-info-as-text 303
13.87 Residue Info 304
13.87.1 residue-info-dialog 304
13.88 Residue Environment Functions 304

13.88.1 set-show-environment-distances 304
13.88.2 set-show-environment-distances-bumps 304
13.88.3 set-show-environment-distances-h-bonds 304
13.88.4 show-environment-distances-state 304
13.88.5 set-environment-distances-distance-limits 305
13.89 Pointer Functions 305
13.89.1 set-show-pointer-distances 305
13.89.2 show-pointer-distances-state 305
13.90 Zoom Functions 305
13.90.1 scale-zoom 305
13.90.2 zoom-factor 305
13.90.3 set-smooth-scroll-do-zoom 305
13.90.4 smooth-scroll-do-zoom 305
13.91 CNS Data Functions 306
13.91.1 handle-cns-data-file 306
13.91.2 handle-cns-data-file-with-cell 306
13.92 mmCIF Functions 306
13.92.1 open-cif-dictionary-file-selector-dialog 306
13.93 SHELXL Functions 306
13.93.1 read-shelx-ins-file 306
13.93.2 write-shelx-ins-file 307
13.94 Validation Functions 307
13.94.1 difference-map-peaks 307
13.94.2 gln-asn-b-factor-outliers 307
13.95 Ramachandran Plot Functions 307
13.95.1 do-ramachandran-plot 307
13.95.2 set-kleywegt-plot-n-diffs 307
13.95.3 set-ramachandran-plot-contour-levels 308
13.95.4 set-ramachandran-plot-background-block-size 308
13.95.5 ramachandran-plot-differences 308
13.95.6 ramachandran-plot-differences-by-chain 308
13.96 Sequence View Interface 308
13.96.1 do-sequence-view 308
13.97 Atom Labelling 309
13.97.1 set-brief-atom-labels 309
13.97.2 brief-atom-labels-state 309
13.98 Screen Rotation 309
13.98.1 rotate-y-scene 309
13.98.2 rotate-x-scene 309
13.98.3 rotate-z-scene 309
13.98.4 spin-zoom-trans 309
13.99 Screen Translation 310
13.99.1 translate-scene-x 310
13.99.2 translate-scene-y 310
13.99.3 translate-scene-z 310
13.100 Views Interface 310
13.100.1 add-view-here 310
13.100.2 add-view-raw 310

13.100.3 remove-named-view . . . 311
13.100.4 remove-view . . . 311
13.100.5 add-view-description . . . 311
13.100.6 add-action-view . . . 311
13.100.7 insert-action-view-after-view . . . 311
13.100.8 save-views . . . 312
13.100.9 clear-all-views . . . 312
13.101 Background Colour . . . 312
13.101.1 set-background-colour . . . 312
13.101.2 redraw-background . . . 312
13.101.3 background-is-black-p . . . 312
13.102 Ligand Fitting Functions . . . 312
13.102.1 set-ligand-acceptable-fit-fraction . . . 312
13.102.2 set-ligand-cluster-sigma-level . . . 313
13.102.3 set-ligand-flexible-ligand-n-samples . . . 313
13.102.4 set-find-ligand-n-top-ligands . . . 313
13.102.5 set-find-ligand-multi-solutions-per-cluster . . . 313
13.102.6 set-find-ligand-mask-waters . . . 313
13.102.7 set-ligand-search-protein-molecule . . . 313
13.102.8 set-ligand-search-map-molecule . . . 314
13.102.9 add-ligand-search-ligand-molecule . . . 314
13.102.10 add-ligand-search-wiggly-ligand-molecule . . . 314
13.102.11 set-find-ligand-here-cluster . . . 314
13.102.12 ligand-expert . . . 314
13.102.13 do-find-ligands-dialog . . . 314
13.102.14 match-ligand-atom-names . . . 314
13.102.15 match-ligand-atom-names-to-comp-id . . . 315
13.102.16 flip-ligand . . . 315
13.103 Water Fitting Functions . . . 316
13.103.1 wrapped-create-find-waters-dialog . . . 316
13.103.2 renumber-waters . . . 316
13.103.3 execute-find-waters-real . . . 316
13.103.4 move-waters-to-around-protein . . . 316
13.103.5 move-hetgroups-to-around-protein . . . 316
13.103.6 max-water-distance . . . 316
13.103.7 set-water-check-spherical-variance-limit . . . 317
13.103.8 set-ligand-water-to-protein-distance-limits . . . 317
13.103.9 set-ligand-water-n-cycles . . . 317
13.103.10 execute-find-blobs . . . 317
13.103.11 split-water . . . 317
13.104 Bond Representation . . . 318
13.104.1 set-default-bond-thickness . . . 318
13.104.2 set-bond-thickness . . . 318
13.104.3 set-bond-thickness-intermediate-atoms . . . 318
13.104.4 set-bond-colour-rotation-for-molecule . . . 318
13.104.5 get-bond-colour-rotation-for-molecule . . . 318
13.104.6 set-default-representation-type . . . 318
13.104.7 get-default-bond-thickness . . . 318

13.104.8 set-draw-zero-occ-markers 319
13.104.9 set-draw-cis-peptide-markups 319
13.104.10 set-draw-hydrogens 319
13.104.11 draw-hydrogens-state 319
13.104.12 set-draw-stick-mode-atoms 319
13.104.13 graphics-to-ca-representation 319
13.104.14 graphics-to-ca-plus-ligands-representation 320
13.104.15 graphics-to-ca-plus-ligands-and-sidechains-representation 320
13.104.16 graphics-to-bonds-no-waters-representation 320
13.104.17 graphics-to-bonds-representation 320
13.104.18 graphics-to-ca-plus-ligands-sec-struct-representation 320
13.104.19 graphics-to-sec-struct-bonds-representation 320
13.104.20 graphics-to-rainbow-representation 320
13.104.21 graphics-to-b-factor-representation 320
13.104.22 graphics-to-b-factor-cas-representation 321
13.104.23 graphics-to-occupancy-representation 321
13.104.24 graphics-to-user-defined-atom-colours-representation 321
13.104.25 graphics-to-user-defined-atom-colours-all-atoms-representation 321
13.104.26 graphics-molecule-bond-type 321
13.104.27 set-b-factor-bonds-scale-factor 321
13.104.28 change-model-molecule-representation-mode 321
13.104.29 set-use-grey-carbons-for-molecule 322
13.104.30 set-grey-carbon-colour 322
13.104.31 make-ball-and-stick 322
13.104.32 clear-ball-and-stick 322
13.104.33 additional-representation-by-string 322
13.104.34 additional-representation-by-attributes 323
13.105 Dots Representation 323
13.105.1 dots 323
13.105.2 set-dots-colour 324
13.105.3 unset-dots-colour 324
13.105.4 clear-dots 324
13.105.5 clear-dots-by-name 324
13.105.6 n-dots-sets 324
13.106 Pep-flip Interface 325
13.106.1 pepflip 325
13.107 Rigid Body Refinement Interface 325
13.107.1 rigid-body-refine-zone 325
13.107.2 set-rigid-body-fit-acceptable-fit-fraction 325
13.108 Add Terminal Residue Functions 325
13.108.1 set-add-terminal-residue-immediate-addition 325
13.108.2 add-terminal-residue 326
13.108.3 add-terminal-residue-using-phi-psi 326

13.108.4 set-add-terminal-residue-default-residue-type 326
13.108.5 set-add-terminal-residue-do-post-refine 326
13.108.6 add-terminal-residue-do-post-refine-state 326
13.109 Delete Residues 327
13.109.1 delete-residue-range 327
13.109.2 delete-residue 327
13.109.3 delete-residue-with-full-spec 327
13.109.4 delete-residue-hydrogens 327
13.109.5 delete-atom 328
13.109.6 delete-residue-sidechain 328
13.109.7 delete-hydrogens 328
13.110 Mainchain Building Functions 328
13.110.1 db-mainchain 328
13.111 Rotamer Functions 329
13.111.1 set-rotamer-search-mode 329
13.111.2 set-rotamer-lowest-probability 329
13.111.3 set-rotamer-check-clashes 329
13.111.4 auto-fit-best-rotamer 329
13.111.5 set-auto-fit-best-rotamer-clash-flag 330
13.111.6 n-rotamers 330
13.111.7 set-residue-to-rotamer-number 330
13.111.8 set-residue-to-rotamer-name 330
13.111.9 fill-partial-residues 331
13.112 180 Flip Side chain 331
13.112.1 do-180-degree-side-chain-flip 331
13.113 Mutate Functions 331
13.113.1 setup-mutate-auto-fit 331
13.113.2 mutate 331
13.113.3 mutate-base 332
13.113.4 set-mutate-auto-fit-do-post-refine 332
13.113.5 mutate-auto-fit-do-post-refine-state 332
13.113.6 set-rotamer-auto-fit-do-post-refine 332
13.113.7 rotamer-auto-fit-do-post-refine-state 332
13.113.8 mutate-single-residue-by-serial-number 332
13.113.9 set-residue-type-chooser-stub-state 333
13.114 Pointer Atom Functions 333
13.114.1 create-pointer-atom-molecule-maybe 333
13.114.2 pointer-atom-molecule 333
13.115 Baton Build Interface Functions 333
13.115.1 set-baton-mode 333
13.115.2 try-set-draw-baton 333
13.115.3 accept-baton-position 333
13.115.4 baton-tip-try-another 334
13.115.5 baton-tip-previous 334
13.115.6 shorten-baton 334
13.115.7 lengthen-baton 334
13.115.8 baton-build-delete-last-residue 334
13.115.9 set-baton-build-params 334

13.116 Crosshairs Interface . . . 334
13.116.1 set-draw-crosshairs . . . 334
13.117 Edit Chi Angles . . . 334
13.117.1 set-find-hydrogen-torsions . . . 335
13.117.2 edit-chi-angles . . . 335
13.117.3 setup-torsion-general . . . 335
13.118 Masks . . . 335
13.118.1 mask-map-by-molecule . . . 335
13.118.2 set-map-mask-atom-radius . . . 335
13.118.3 map-mask-atom-radius . . . 336
13.119 check Waters Interface . . . 336
13.119.1 delete-checked-waters-baddies . . . 336
13.120 Trim . . . 336
13.120.1 trim-molecule-by-map . . . 336
13.121 External Ray-Tracing . . . 336
13.121.1 raster3d . . . 336
13.121.2 set-raster3d-bond-thickness . . . 337
13.121.3 set-raster3d-atom-radius . . . 337
13.121.4 set-raster3d-density-thickness . . . 337
13.121.5 set-renderer-show-atoms . . . 337
13.121.6 set-raster3d-bone-thickness . . . 337
13.121.7 set-raster3d-shadows-enabled . . . 337
13.121.8 set-raster3d-water-sphere . . . 337
13.121.9 raster-screen-shot . . . 337
13.122 Superposition (SSM) . . . 338
13.122.1 superpose . . . 338
13.122.2 superpose-with-chain-selection . . . 338
13.122.3 superpose-with-atom-selection . . . 338
13.123 NCS . . . 339
13.123.1 set-draw-ncs-ghosts . . . 339
13.123.2 draw-ncs-ghosts-state . . . 339
13.123.3 set-ncs-ghost-bond-thickness . . . 339
13.123.4 ncs-update-ghosts . . . 339
13.123.5 make-dynamically-transformed-ncs-maps . . . 339
13.123.6 add-ncs-matrix . . . 340
13.123.7 add-strict-ncs-matrix . . . 340
13.123.8 show-strict-ncs-state . . . 341
13.123.9 set-show-strict-ncs . . . 341
13.123.10 set-ncs-homology-level . . . 341
13.123.11 copy-chain . . . 341
13.123.12 copy-from-ncs-master-to-others . . . 341
13.123.13 copy-residue-range-from-ncs-master-to-others . . . 342
13.123.14 ncs-control-change-ncs-master-to-chain . . . 342
13.123.15 ncs-control-change-ncs-master-to-chain-id . . . 342
13.123.16 ncs-control-display-chain . . . 342
13.124 Helices and Strands . . . 342
13.124.1 place-helix-here . . . 343
13.124.2 place-strand-here . . . 343

13.124.3 place-strand-here-dialog . . . 343
13.124.4 find-helices . . . 343
13.124.5 find-strands . . . 343
13.124.6 find-secondary-structure . . . 344
13.124.7 find-secondary-structure-local . . . 344
13.125 Nucleotides . . . 344
13.125.1 find-nucleic-acids-local . . . 344
13.126 New Molecule by Section Interface . . . 345
13.126.1 new-molecule-by-residue-type-selection . . . 345
13.126.2 new-molecule-by-atom-selection . . . 345
13.126.3 new-molecule-by-sphere-selection . . . 345
13.127 RNA/DNA . . . 345
13.127.1 ideal-nucleic-acid . . . 345
13.127.2 watson-crick-pair . . . 346
13.127.3 watson-crick-pair-for-residue-range . . . 346
13.128 Sequence (Assignment) . . . 346
13.128.1 print-sequence-chain . . . 346
13.128.2 assign-fasta-sequence . . . 347
13.128.3 assign-pir-sequence . . . 347
13.128.4 assign-sequence-from-file . . . 347
13.128.5 assign-sequence-from-string . . . 347
13.128.6 delete-all-sequences-from-molecule . . . 347
13.128.7 delete-sequence-by-chain-id . . . 348
13.129 Surface Interface . . . 348
13.129.1 do-surface . . . 348
13.129.2 set-transparent-electrostatic-surface . . . 348
13.129.3 get-electrostatic-surface-opacity . . . 348
13.130 FFFearing . . . 348
13.130.1 fffear-search . . . 348
13.130.2 set-fffear-angular-resolution . . . 349
13.130.3 fffear-angular-resolution . . . 349
13.131 Remote Control . . . 349
13.131.1 make-socket-listener-maybe . . . 349
13.131.2 set-socket-string-waiting . . . 349
13.131.3 set-socket-python-string-waiting . . . 349
13.132 Display Lists for Maps . . . 349
13.132.1 set-display-lists-for-maps . . . 349
13.132.2 display-lists-for-maps-state . . . 349
13.133 Browser Interface . . . 350
13.133.1 browser-url . . . 350
13.133.2 set-browser-interface . . . 350
13.133.3 handle-online-coot-search-request . . . 350
13.134 Molprobity Interface . . . 350
13.134.1 handle-read-draw-probe-dots . . . 350
13.134.2 handle-read-draw-probe-dots-unformatted . . . 350
13.134.3 set-do-probe-dots-on-rotamers-and-chis . . . 350
13.134.4 do-probe-dots-on-rotamers-and-chis-state . . . 351
13.134.5 set-do-probe-dots-post-refine . . . 351

13.134.6 do-probe-dots-post-refine-state 351
13.134.7 unmangle-hydrogen-name 351
13.134.8 set-interactive-probe-dots-molprobity-radius 351
13.134.9 interactive-probe-dots-molprobity-radius 351
13.135 Map Sharpening Interface 351
13.135.1 sharpen 351
13.135.2 set-map-sharpening-scale-limit 351
13.136 Marking Fixed Atom Interface 352
13.136.1 clear-all-fixed-atoms 352
13.137 Partial Charges 352
13.137.1 show-partial-charge-info 352
13.138 EM interface 352
13.138.1 scale-cell 352
13.139 CCP4mg Interface 352
13.139.1 write-ccp4mg-picture-description 352
13.139.2 get-atom-colour-from-mol-no 353
13.140 Aux functions 353
13.140.1 laplacian 353
13.141 SMILES 353
13.141.1 do-smiles-gui 353
13.142 PHENIX Support 353
13.142.1 set-button-label-for-external-refinement 353
13.143 Graphics Text 353
13.143.1 place-text 353
13.143.2 remove-text 354
13.143.3 text-index-near-position 354
13.144 PISA Interaction 354
13.144.1 pisa-interaction 354
13.145 Jiggle Fit 354
13.145.1 fit-to-map-by-random-jiggle 354
13.146 SBase interface 355
13.146.1 get-ccp4srs-monomer-and-dictionary 355
13.146.2 get-sbase-monomer 355
13.147 FLE-View 355
13.147.1 fle-view-set-water-dist-max 355
13.147.2 fle-view-set-h-bond-dist-max 355
13.148 LSQ-improve 355
13.148.1 lsq-improve 355
13.149 single-model view 356
13.149.1 single-model-view-model-number 356
13.149.2 single-model-view-this-model-number 356
13.149.3 single-model-view-next-model-number 356
13.149.4 single-model-view-prev-model-number 356
13.150 graphics 2D ligand view 356
13.150.1 set-show-graphics-ligand-view 356
13.151 dictionary-generators 357
13.152 raster3d-from-scheme 357
13.153 tips 357

13.154 cc-interface_8hh . . . 357
13.155 More Symmetry Functions . . . 357
13.155.1 get-symmetry . . . 357
13.156 Extra Map Functions . . . 357
13.156.1 auto-read-make-and-draw-maps . . . 357
13.156.2 auto-read-make-and-draw-maps-from-mtz . . . 358
13.156.3 map-colour-components . . . 358
13.157 Multi-Residue Torsion . . . 358
13.157.1 multi-residue-torsion-fit-scm . . . 358
13.158 Execute Refmac . . . 358
13.158.1 execute-refmac-real . . . 358
13.158.2 refmac-name . . . 359
13.159 Dictionary Functions . . . 359
13.159.1 dictionaries-read . . . 359
13.160 Restraints Interface . . . 359
13.160.1 set-monomer-restraints . . . 359
13.161 Atom Information functions . . . 359
13.161.1 resname-from-serial-number . . . 359
13.161.2 residue-name . . . 360
13.161.3 residue-info . . . 360
13.161.4 chain-fragments-scm . . . 360
13.161.5 add-molecule . . . 360
13.161.6 clear-and-update-molecule . . . 361
13.161.7 active-residue . . . 361
13.161.8 closest-atom-simple-scm . . . 361
13.161.9 closest-atom . . . 361
13.161.10 residues-near-residue . . . 361
13.161.11 residues-near-position-scm . . . 362
13.161.12 hydrogenate-region . . . 362
13.161.13 add-hydrogens-from-file . . . 362
13.162 Refinement with specs . . . 362
13.162.1 regularize-residues . . . 362
13.162.2 mtz-file-name . . . 362
13.162.3 refine-zone-with-full-residue-spec-scm . . . 363
13.163 Water Chain Functions . . . 363
13.163.1 water-chain-from-shelx-ins-scm . . . 363
13.163.2 water-chain-scm . . . 363
13.164 Glyco Tools . . . 363
13.164.1 print-glyco-tree . . . 363
13.165 Spin Search Functions . . . 364
13.165.1 spin-search . . . 364
13.166 Rotamer Scoring . . . 364
13.166.1 score-rotamers-scm . . . 364
13.167 protein-db . . . 364
13.167.1 protein-db-loops . . . 364
13.168 Coot's Hole implementation . . . 365
13.168.1 hole . . . 365
13.168.2 make-link . . . 365

13.169 Drag and Drop Functions 366
13.169.1 handle-drag-and-drop-string 366
13.170 Map to Model Correlation 366
13.170.1 set-map-correlation-atom-radius 366
13.170.2 map-to-model-correlation 366
13.170.3 map-to-model-correlation-stats 366
13.170.4 map-to-model-correlation-per-residue 367
13.170.5 qq-plot-map-and-model-scm 367
13.170.6 density-score-residue 367
13.170.7 map-mean-scm 367
13.170.8 map-statistics-scm 368
13.171 shelx 368
13.172 jligand 368
13.173 mutate-in-scheme 368
13.174 user-define-restraints 369
13.175 background-demo 369

Concept Index 370

Function Index 373

1 Introduction

This document is the Coot User Manual, giving an overview of the interactive features. Other documentation includes the Coot Reference Manual and the Coot Tutorial. These documents should be distributed with the source code.

1.1 Citing Coot and Friends

If have found this software to be useful, you are requested (if appropriate) to cite:

> "Features and Development of Coot" P Emsley, B Lohkamp, W Scott, and K Cowtan Acta Cryst. (2010). D66, 486-501 *Acta Crystallographica Section D-Biological Crystallography* **66**: 486-501

The reference for the REFMAC5 Dictionary is:

> REFMAC5 dictionary: "Organization of Prior Chemical Knowledge and Guidelines for its Use" Vagin AA, Steiner RA, Lebedev AA, Potterton L, McNicholas S Long F, Murshudov GN *Acta Crystallographica Section D-Biological Crystallography* **60**: 2184-2195 Part 12 Sp. Iss. 1 DEC 2004"

If using "SSM Superposition", please cite:

> "Secondary-structure matching (SSM), a new tool for fast protein structure alignment in three dimensions" Krissinel E, Henrick K *Acta Crystallographica Section D-Biological Crystallography* **60**: 2256-2268 Part 12 Sp. Iss. 1 DEC 2004

The reference for the the Electron Density Server is:

> GJ Kleywegt, MR Harris, JY Zou, TC Taylor, A Wählby, TA Jones (2004), "The Uppsala Electron-Density Server", *Acta Crystallographica Section D-Biological Crystallography* **60**, 2240-2249.
>
> Please also cite the primary literature for the received structures.

1.2 What is Coot?

Coot is a molecular graphics application. Its primary focus is crystallographic macromolecular model-building and manipulation rather than representation *i.e.* more like Frodo than Rasmol. Having said that, Coot can work with small molecule (SHELXL) and electron microscopy data, be used for homology modelling, make passably pretty pictures and display NMR structures.

Coot is Free Software. You can give it away. If you don't like the way it behaves, you can fix it yourself.

1.3 What Coot is Not

Coot is not:

- CCP4's official Molecular Graphics program[1]

[1] The official CCP4 graphics program (which contains parts of Coot (and Coot contains parts of CCP4MG)), CCP4MG is under the direct control of Liz Potterton and Stuart McNicholas.

- a program to do refinement[2]
- a protein crystallographic suite[3].

1.4 Hardware Requirements

The code is designed to be portable to any Unix-like operating system. Coot certainly runs on RedHat Linux of various sorts, Fedora, Ubuntu, Debian, SuSe Linux and MacOS X. There is also a Window port (called WinCoot).

If you want to port to some other operating system, you are welcome[4]. Note that your task will be eased by using GNU GCC to compile the programs components.

1.4.1 Mouse

Coot works best with a 3-button mouse and works better if it has a scroll-wheel too (see Chapter 2 for more details)[5].

1.5 Environment Variables

Coot responds to several environment variables that modify its behaviour.

- `COOT_STANDARD_RESIDUES` The filename of the pdb file containing the standard amino acid residues in "standard conformation"[6]
- `COOT_SCHEME_DIR` The directory containing standard (part of the distribution) scheme files
- `COOT_SCHEME_EXTRAS_DIR` A ':'-separated list of directories containing bespoke scheme files. This variable is not set by default. If you set it, Coot will test each ':'-separated string that it points to a directory, and if it does, Coot will load all the `.scm` files in that directory.
- `COOT_PYTHON_EXTRAS_DIR` A ':'-separated list of directories containing bespoke python files. This variable is not set by default. If you set it, Coot will test each ':'-separated string that it points to a directory, and if it does, Coot will load all the `.py` files in that directory.
- `COOT_REF_STRUCTS` The directory containing a set of high resolution pdb files used as reference structures to build backbone atoms from Cα positions
- `COOT_REF_SEC_STRUCTS` The directory containing a set of high-quality structures to be used as templates for fitting beta strands. If this is not set, then the directory COOT_REF_SEC_STRUCTS will be used to find the reference pdb files.
- `COOT_REFMAC_LIB_DIR` Refmac's CIF directory containing the monomers and link descriptions. In the future this may simply be the same directory in which refmac looks to find the library dictionary.
- `COOT_SBASE_DIR` The directory to find the SBASE dictionary (often comes with CCP4).

[2] although it does have a local refinement algorithm it is no substitute for refmac (a wrapper for refmac is available).

[3] that's the job of the CCP4 Program Suite.

[4] it's Free Software after all and I could give you a hand.

[5] I can get by with a one button Macintosh - but it's not ideal.

[6] as it is known in Clipper.

- `COOT_RESOURCES_DIR` The directory that contains the splash screen image and the GTK+ application resources.
- `COOT_BACKUP_DIR` The directory to which backup are written (if it exists as a directory). If it is not, then backups are written to the current directory (the directory in which coot was started).

And of course extension language environment variables are used too:

- `PYTHONPATH` (for python modules)
- `GUILE_LOAD_PATH` (for guile modules)

Normally, these environment variables will be set correctly in the coot shell script.

1.6 Command Line Arguments

Rather that using the GUI to read in information, you can use the following command line arguments:

- `--c` *`cmd`* to run a command *`cmd`* on start up
- `--script` *`filename`* to run a script on start up (but see Section Section 3.10 [Scripting], page 11)
- `--no-state-script` don't run the `0-coot.state.scm` script on start up. Don't save a state script on exit either.
- `--pdb` *`filename`* for pdb/coordinates file
- `--coords` *`filename`* for SHELX .ins/.res and CIF files
- `--data` *`filename`* for mtz, phs or mmCIF data file
- `--auto` *`filename`* for auto-reading mtz files (mtz file has the default labels FWT, PHWT)
- `--map` *`filename`* for a map (currently CCP4-format only)
- `--dictionary` *`filename`* read in a cif monomer dictionary
- `--help` print command line options
- `--stereo` start up in hardware stereo mode
- `--version` print the version of coot and exit
- `--code` *`accession-code`* on starting Coot, get the pdb file and mtz file (if it exists) from the EDS
- `--no-guano` don't leave "Coot droppings" i.e. don't write state and history files on exit
- `--side-by-side` start in side-by-side stereo mode
- `--update-self` command-line mode to update the coot to the latest pre-release on the server
- `--python` an argument with no parameters - used to tell Coot that the -c arguments should be process as python (rather than as scheme).
- `--small-screen` start with smaller icons and font to fit on small screen displays
- `--zalman-stereo` start in Zalman stereo mode

So, for example, one might use:

- `coot --pdb post-refinement.pdb --auto refmac-2.mtz --dictionary lig.cif`

1.7 Web Page

Coot has a web page:

- `http://www2.mrc-lmb.cam.ac.uk/personal/pemsley/coot/`

There you can read more about the CCP4 molecular graphics project in general and other projects which are important for Coot[7].

1.8 Crash

Coot might crash on you - it shouldn't.

Whenever Coot manipulates the model, it saves a backup pdb file. There are backup files in the directory `coot-backup`[8]. You can recover the session (until the last edit) by reading in the pdb file that you started with last time and then use `File -> Recover Session...`.

I would like to know about coot crashing[9] so that I can fix it as soon as possible. If you want your problem fixed, this involves some work on your part sadly.

First please make sure that you are using the most recent version of coot. I will often need to know as much as possible about what you did to cause the bug. If you can reproduce the bug and send me the files that are needed to cause it, I can almost certainly fix it[10] - especially if you use the debugger (gdb) and send a backtrace too[11]. Note that you may have to source the contents of `bin/coot` so that the libraries are can be found when the executable dynamically links.

---

[7] coot has several influences and dependencies, but these will not be discussed here in the User Manual.

[8] COOT_BACKUP_DIR is used in preference if set

[9] The map-reading problem (documented in Section Section 6.1 [Maps in General], page 48) is already known.

[10] now there's a hostage to fortune.

[11] to do so, please send me the output of the following: `$ gdb ‘which coot-real‘ corefile` and then at the `(gdb)` prompt type: `where`, where *`corefile`* is the core dump file, ‘`core`’ or ‘`core.4536`’ or some such.

2 Mousing and Keyboarding

How do we move around and select things?

`Left-mouse Drag`
: Rotate view

`Ctrl Left-Mouse Drag`
: Translates view

`Shift Left-Mouse`
: Label Atom

`Right-Mouse Drag`
: Zoom in and out

`Ctrl Shift Right-Mouse Drag`
: Rotate View around Screen Z axis

`Middle-mouse`
: Centre on atom

`Scroll-wheel Forward`
: Increase map contour level

`Scroll-wheel Backward`
: Decrease map contour level

See also Chapter Chapter 9 [Hints and Usage Tips], page 60 for more help.

2.1 Next Residue

`‘‘Space’’`
: Next Residue

`‘‘Shift’’ ‘‘Space’’`
: Previous Residue

See also “Recentring View” (Section Section 3.14 [Recentring View], page 15).

2.2 Keyboard Contouring

Use `+` or `-` on the keyboard if you don’t have a scroll-wheel.

2.3 Mouse Z Translation and Clipping

Here we can change the clipping and Translate in Screen Z

`Ctrl Right-Mouse Drag Up/Down`
: changes the slab (clipping planes)

`Ctrl Right-Mouse Drag Left/Right`
: translates the view in screen Z

2.4 Keyboard Translation

`Keypad 3` Push View (+Z translation)

`Keypad .` Pull View (-Z translation)

2.5 Keyboard Zoom and Clip

`N` Zoom out

`M` Zoom in

`D` Slim clip

`F` Fatten clip

2.6 Scrollwheel

When there is no map, using the scroll-wheel has no effect. If there is exactly one map displayed, the scroll-wheel will change the contour level of that map. If there are two or more maps, the map for which the contour level is changed can be set using either `HID -> Scrollwheel -> Attach scroll-wheel to which map?` and selecting a map number or clicking the "Scroll" radio button for the map in the Display Manager.

You can turn off the map contour level changing by the scroll wheel using:

`(set-scroll-by-wheel-mouse 0)`

(the default is 1 [on]).

2.7 Selecting Atoms

Several Coot functions require the selecting of atoms to specify a residue range (for example: Regularize, Refine (Section Section 5.1 [Regularization and Real Space Refinement], page 27) or Rigid Body Fit Zone (Section Section 5.4 [Rigid Body Refinement], page 30)). Select atoms with the Left-mouse. See also Picking (Section Section 9.9 [sec_picking], page 61).

Use the scripting function `(quanta-buttons)` to make the mouse functions more like other molecular graphics programs to which you may be more accustomed[1].

2.8 Virtual Trackball

You may not completely like the way the molecule is moved by the mouse movement[2]. To change this, try: `HID -> Virtual Trackball -> Flat`. To do this from the scripting interface: `(vt-surface 1)`[3].

If you *do* want `screen-z rotation` screen-z rotation, you can either use Shift Right-Mouse Drag or set the Virtual Trackball to Spherical Surface mode and move the mouse along the bottom edge of the screen.

---

[1] See also Section 2.9 [more on zooming], page 7

[2] Mouse movement in "Spherical Surface" mode generates a component of (often undesirable) screen z-rotation, particularly noticeable when the mouse is at the edge of the screen.

[3] `(vt-surface 0)` to turn it back to "Spherical" mode.

2.9 More on Zooming

The function `(quanta-like-zoom)` adds the ability to zoom the view using just Shift `+` Mouse movement[4].

There is also a Zoom slider (`Draw -> Zoom`) for those without a right-mouse button.

[4] this is off by default because I find it annoying.

3 General Features

The map-fitting and model-building tools can be accessed by using `Calculate -> Model/Fit/Refine...`. Many functions have tooltips[1] describing the particular features and are documented in Chapter Chapter 5 [Modelling and Building], page 27.

`F5:` posts the Model/Fit/Refine dialog

`F6:` posts the Go To Atom Window

`F7:` posts the Display Control Window

3.1 Version number

The version number of Coot can be found at the top of the "About" window (`Help -> About`).

This will return the version of coot:

```
$ coot --version
```

There is also a script function to return the version of coot:

```
(coot-version)
```

3.2 Antialiasing

The built-in antialiasing (for what it's worth) can be enabled using:

```
(set-do-anti-aliasing 1)
```

The default is `0` (off).

This can also be activated using `Edit Preferences -> Others -> Antialiasing -> Yes`.

If you have an nVidia graphics card, external antialiasing can be actived setting the environment variable `__GL_FSAA_MODE`. For me a setting of `5` works nicely and gives a better image than using Coot's built-in antialiasing.

Also for nVidia graphics card users, there is the application nvidia-settings:

`Antialiasing Setting -> Override Application Settings` and slide the slider to the right. On restarting Coot, it should be in antialias mode[2].

3.3 Molecule Number

Coot is based on the concept of molecules. Maps and coordinates are different representations of molecules. The access to the molecule is *via* the *molecule number*. It is often important therefore to know the molecule number of a particular molecule.

The Molecule Number of a molecule can be found by clicking on an atom of that molecule (if it has coordinates of course). The first number in brackets in the resulting text in the status bar and console is the Molecule Number. The Molecule Number can also be found in Display Control window (Section Section 3.7 [Display Manager], page 10). It is also displayed on the left-hand side of the molecule name in the option menus of the "Save Coordinates" and "Go To Atom" windows.

[1] Put your mouse over a widget for a couple of seconds, if that widget has a tooltip, it will pop-up in a yellow box (or a grey box for some reason if you are using Macintosh).

[2] that works for me, at least.

3.4 Display Issues

The "graphics" window is drawn using OpenGL. It is considerably smoother (i.e. more frames/sec) when using a 3D accelerated X server.

The view is orthographic (*i.e.* the back is the same size as the front). The default clipping is about right for viewing coordinate data, but is often a little too "thick" for viewing electron density. It is easily changed (see Section Section 3.16 [Clipping Manipulation], page 16).

Depth-cueing is linear and fixed on.

The graphics window can be resized, but it has a minimum size of 400x400 pixels.

3.4.1 Stereo

Hardware Stereo is an option for Coot (`Draw -> Stereo... -> Hardware Stereo -> OK`), side-by-side stereo is not an option.

The angle between the stereo pairs (the stereo separation) can be changed to suit your personal tastes using:

`(set-hardware-stereo-angle-factor` *`angle-factor`*`)`

where *`angle-factor`* would typically be between 1.0 and 2.0

3.4.2 Pick Cursor

When asked to pick a residue or atom, the cursor changes from the normal arrow shape to a "pick" cursor. Sometimes it is difficult to see the default pick cursor, so you can change it using the function

`(set-pick-cursor-index` *`i`*`)`

where *`i`* is an integer less than 256. The cursors can be viewed using an external X program:

`xfd -fn cursor`

3.4.3 Origin Marker

A yellow box called the "origin marker" marks the origin. It can be removed using:

`(set-show-origin-marker 0)`

Its state can be queried like this:

`(show-origin-marker-state)`

which returns an number (0 if it is not displayed, 1 if it is).

3.5 Screenshot

A simple screenshot (image dump) can be made using `Draw -> Screenshot -> Simple...`. Note that in side by side stereo mode you only get the left-hand image.

3.6 Raster3D output

Output suitable for use by Raster3D's "render" can be generated using the scripting function

`(raster3d file-name)`

where *file-name* is such as `"test.r3d"`[3].

There is a keyboard key to generate this file, run "render" and display the image: Function key F8.

You can also use the function

`(render-image)`

which will create a file '`coot.r3d`', from which "render" produces '`coot.png`'. This png file is displayed using ImageMagick's display program (by default). Use something like:

`(set! coot-png-display-program "gqview")`

to change that to different display program (`"gqview"` in this case).

`(set! coot-png-display-program "open")`

would use Preview (by default) on Macintosh.

To change the widths of the bonds and density "lines" use (for example):

`(set-raster3d-bond-thickness 0.1)`

and

`(set-raster3d-density-thickness 0.01)`

Similarly for bones:

`(set-raster3d-bone-thickness 0.05)`

To turn off the representations of the atoms (spheres):

`(set-renderer-show-atoms 0)`

3.7 Display Manager

This is also known as "Map and molecule (coordinates) display control". Here you can select which maps and molecules you can see and how they are drawn[4]. The "Display" and "Active" are toggle buttons, either depressed (active) or undepressed (inactive). The "Display" buttons control whether a molecule (or map) is drawn and the "Active" button controls if the molecule is clickable[5] (*i.e.* if the molecule's atoms can be labeled).

The `"Scroll"` radio buttons sets which map is has its contour level changed by scrolling the mouse scroll wheel.

By default, the path names of the files are not displayed in the Display Manager. To turn them on:

`(set-show-paths-in-display-manager 1)`

If you pull across the horizontal scrollbar in a Molecule view, you will see the "Render as" menu. You can use this to change between normal "Bonds (Colour by Atom)","Bonds (Colour by Chain)" and "Cα" representation There is also available "No Waters" and "Cα + ligands" representations.

---

[3] Povray support is only semi-working, there is a problem with the orientation of the image.

[4] to a limited extent.

[5] the substantial majority of the time you will want your the buttons to be both either depressed or undepressed, rarely one but not the other.

3.8 The Modelling Toolbar

You might not want to have the right-hand-side vertical toolbar that contains icons for some modelling operations[6] displayed:

```
(hide-modelling-toolbar)
```

to bring it back again:

```
(show-modelling-toolbar)
```

3.9 The file selector

3.9.1 File-name Filtering

The "Filter" button in the fileselection filters the filenames according to extension. For coordinates files the extensions are ".pdb" ".brk" ".mmcif" and others. For data: ".mtz", ".hkl", ".phs", ".cif" and for (CCP4) maps ".ext", ".msk" and ".map". If you want to add to the extensions, the following functions are available:

- `(add-coordinates-glob-extension` *`extension`*`)`
- `(add-data-glob-extension` *`extension`*`)`
- `(add-map-glob-extension` *`extension`*`)`
- `(add-dictionary-glob-extension` *`extension`*`)`

where *`extension`* is something like: `".mycif"`.

If you want the fileselection to be filtered without having to use the "Filter" button, use the scripting function

```
(set-filter-fileselection-filenames 1)
```

3.9.2 Filename Sorting

If you like your files initially sorted by date (rather than lexicographically, which is the default) use:

```
(set-sticky-sort-by-date)
```

3.9.3 Save Coordinates Directory

Some people prefer that the fileselection for saving coordinates starts in the original directory (rather than the directory from which they last imported coordinates). This option is for them:

```
(set-save-coordinates-in-original-directory 1)
```

3.10 Scripting

There is an compile-time option of adding a script interpreter. Currently the options are python and guile. It seems possible that in future you will be able to use both in the same executable. The binary distribution of Coot are linked with guile, others with python.

Hundreds of commands are made available for use in scripting by using SWIG, some of which are documented here. Other functions documented less well, but descriptions for them can be found at the end of this manual.

[6] British modelling, of course

Commands described throughout this manual (such as `(vt-surface 1))` can be evaluated directly by Coot by using the "Scripting Window" (`Calculate -> Scripting...`). Note that you type the commands in the upper entry widget and the command gets echoed (in red) and the return value and any output is displayed in the text widget lower (green). The typed command should be terminated with a carriage return[7]. Files[8] can be evaluated (executed) using `Calculate -> Run Script...`.

Note that in scheme (the usual scripting language of Coot), the parentheses are important.

To execute a script file from the command line use the `--script` *`filename`* arguments (except when also using the command line argument `--no-graphics`, in which case you should use `-s` *`filename`*).

After you have used the scripting window, you may have noticed that you can no longer kill Coot by using Ctrl-C in the console. To recover this ability:

```
(exit)
```

in the scripting window.

3.10.1 Python

Coot has an (optional) embedded python interpreter. Thus the full power of python is available to you. Coot will look for an initialization script (`$HOME/.coot.py`) and will execute it if found. This file should contain python commands that set your personal preferences.

3.10.1.1 Python Commands

The scripting functions described in this manual are formatted suitable for use with guile, *i.e.*:

```
(function arg1 arg2...)
```

If you are using Python instead: the format needs to be changed to:

```
function(arg1,arg2...)
```

Note that dashes in guile function names become underscores for python, so that (for example) `(raster-screen-shot)` becomes `raster_screen_shot()`.

3.10.2 Scheme

The scheme interpreter is made available by embedding guile. The initialization script used by this interpreter is `$HOME/.coot`. This file should contain scheme commands that set your personal preferences.

3.10.3 Coot State

The "state" of Coot is saved on Exit and written to a file called `0-coot.state.scm` (scheme) `0-coot.state.py` (python). This state file contains information about the screen centre, the clipping, colour map rotation size, the symmetry radius, and other molecule related parameters such as filename, column labels, coordinate filename *etc.*.

---

[7] which causes the evaluation of the command.

[8] such as the Coot state file (Section Section 3.10.3 [Coot State], page 12).

Use `Calculate -> Run Script...` to use this file to re-create the loaded maps and models that you had when you finished using Coot[9] last time. A state file can be saved at any time using `(save-state)` which saves to file `0-coot.state.scm` or `(save-state-filename "thing.scm")` which saves to file `thing.scm`.

When Coot starts it can optionally run the commands in `0-coot.state.scm`.

Use `(set-run-state-file-status i)` to change the behaviour: `i` is `0` to never run this state file at startup, `i` is `1` to get a dialog option (this is the default) and `i` is `2` to run the commands without question.

3.10.4 Key Binding

"Power users" of Coot might like to write their own functions and bind that function to a keyboard key. How do they do that?

By using the add-key-binding function:

`(add-key-binding` *`function-name key function`*`)`

where *`key`* is a quoted string (note that upper case and lower case keys are distinguished - activate get upper case key binding you need to chord the shift key[10]).

for example:

`(add-key-binding "Refine Active Residue with Auto-accept" "x" refine-active-residue)`

Have a look at the key bindings section on the Coot wiki for several more examples.

3.10.5 User-Defined Functions

"Power users" of Coot might also like to write their own functions that occur after picking an atom (or a number of atoms)

`(user-defined-click` *`n_clicks udfunc`*`)`

define a function *`func`* which runs after the user has made *`n_clicked`* atom picks. *`func`* is called with a list of atom specifiers - the first member of which is the molecule number.

3.11 Backups and Undo

By default, each time a modification is made to a model, the old coordinates are written out[11]. The backups are kept in a backup directory and are tagged with the date and the history number (lower numbers are more ancient[12]). The "Undo" function discards the current molecule and loads itself from the most recent backup coordinates. Thus you do not have to remember to "Save Changes" - coot will do it for you[13].

If you have made changes to more than one molecule, Coot will pop-up a dialog box in which you should set the "Undo Molecule" *i.e.* the molecule to which the Undo operations

[9] in that particular directory.

[10] funny that

[11] this might be initially surprising since this could chew up a lot of disk space. However, disk space is cheap compared to losing you molecule.

[12] The coordinates are written in pdb format - that's OK, isn't it?.

[13] unless you tell it not to, of course - use (*e.g.*) `(turn-off-backup 0)` to turn off the backup (for molecule 0 in this case).

will apply. Further Undo operations will continue to apply to this molecule until there are none left. If another Undo is requested Coot checks to see if there are other molecules that can be undone, if there is exactly one, then that molecule becomes the "Undo Molecule", if there are more than one, then another Undo selection dialog will be displayed.

You can set the undo molecule using the scripting function:

`(set-undo-molecule` *`imol`*`)`

If for reasons of strange system[14] requirements you want to remove the path components of the backup file name you can do so using:

`(set-unpathed-backup-file-names 1)`

3.11.1 Redo

The "undone" modifications can be re-done using this button. This is not available immediately after a modification[15].

3.11.2 Restoring from Backup

There may be certain circumstances[16] in which you wish to restore from a backup but can't get it by the "Undo" mechanism described above. In that case, start coot as normal and then open the (typically most recent) coordinates file in the directory `coot-backup` (or the directory pointed to the environment variable `COOT_BACKUP_DIR` if it was set) . This file should contain your most recent edits. In such a case, it is sensible for neatness purposes to immediately save the coordinates (probably to the current directory) so that you are not modifying a file in the backup directory.

See also Section Section 1.8 [Crash], page 4.

3.12 View Matrix

It is sometimes useful to use this to orient the view and export this orientation to other programs. The orientation matrix of the view can be displayed (in the console) using:

`(view-matrix)`

Also, the internal representation of the view can be returned and set using:

`(view-quaternion)` to return a 4-element list

`(set-view-quaternion i j k l)` which sets the view quaternion.

So the usage of these functions would be something like:

```
(let ((v (view-quaternion)))
   ;; manipulate v here, maybe
   (apply set-view-quaternion v))
```

[14] or system manager.

[15] It works like the "Forwards" buttons in a web browser - which is not available immediately after viewing a new page.

[16] for example, if coot crashes.

3.13 Space Group and Symmetry

Occasionally you may want to know the space group of a particular molecule. Interactively (for maps) you can see it using the Map Properties button in the Molecule Display Control dialog.

There is a scripting interface function that returns the space group for a given molecule[17]:

`(show-spacegroup imol)`

You can force a space group onto a molecule using the following:

`(set-space-group imol space-group)`

where *space-group* is one of the standard CCP4 space group names (*e.g.* `"P 21 21 21"`).

To show the symmetry operators of a particular molecule use: `(get-symmetry imol)` which will return a list of strings.

Sometimes molecular replacement solutions (for example) create models with chains non-optimally placed relative to each other - a symmetry-related copy would be more apealling (but would be equivalent, crystalographically). For example, to move the B chain to a symmetry-related position:

Centre on an atom in the symmetry-related B chain (where you want the B chain to be)

`Extensions -> Modelling -> Symm Shift Reference Chain Here.`

3.14 Recentring View

- Use Control + left-mouse to drag around the view
- or
- middle-mouse over an atom. In this case, you will often see "slide-recentring", the graphics smoothly changes between the current centre and the newly selected centre.
- or
- Use `Draw -> Go To Atom...` to select an atom using the keyboard. Note that you can subsequently use "Space" in the "graphics" window (OpenGL canvas) to recentre on the next Cα.
- or
- To centre on an arbitrary position (x,y,z), use the scripting function `(set-rotation-centre x y z)`.
- or
- Use the keyboard: [Ctrl G] then key in a residue number and (optionally) a chainid and press Return

If you don't want smooth recentring (sliding) `Edit -> Preferences -> Smooth Recentring -> Off`. You can also use this dialog to speed it up a bit (by decreasing the number of steps instead of turning it off).

[17] if no space group has been assigned it returns `''No spacegroup for this molecule''`

3.15 Views

Coot has a views interface (you might call them "scenes") that define a particular orientation, zoom and view centre. Coot and linearly interpolate between the views. The animation play back speed can be set with the "Views Play Speed" menu item - default is a speed of 10.

The views interface can be found under the Extensions menu item.

3.16 Clipping Manipulation

The clipping planes (a.k.a. "slab") can be adjusted using `Edit -> Clipping` and adjusting the slider. There is only one parameter to change and it affects both the front and the back clipping planes[18]. The clipping can also be changed using keyboard "D" and "F".

It can also be changed with Ctrl + Right-mouse drag up and down. Likewise the screen-Z can be changed with Ctrl + Right-mouse left and right[19].

One can "push" and "pull" the view in the screen-Z direction using keypad 3 and keypad "." (see Section Section 2.4 [Keyboard Z Translation], page 6).

3.17 Background colour

The background colour can be set either using a GUI dialog (`Edit$ -> Background Colour`) or the function `(set-background-colour 0.00 0.00 0.00)`, where the arguments are 3 numbers between 0.0 and 1.0, which respectively represent the red, green and blue components of the background colour. The default is (0.0, 0.0, 0.0) (black).

3.18 Unit Cell

If coordinates have symmetry available then unit cells can be drawn for molecules (`Draw -> Cell & Symmetry -> Show Unit Cell?`).

3.19 Rotation Centre Pointer

There is a pink pointer at the centre of the screen that marks the rotation centre. The size of the pointer can be changed using `Edit -> Pink Pointer Size...` or using scripting commands: `(set-rotation-centre-size 0.3)`.

3.20 Orientation Axes

The green axes showing the orientation of the molecule are displayed by default. To remove them use the scripting function;

```
(set-draw-axes 0)
```

[18] I find a clipping level of about 3.5 to 4 comfortable for viewing electron density maps - it is a little "thinner" than the default startup thickness.

[19] Inspired by PyMol? Yep... sure was!

3.21 Pointer Distances

The Rotation Centre Pointer is sometimes called simply "Pointer". One can find distances to the pointer from any active set of atoms using "Pointer Distances" (under Measures). If you move the Pointer (*e.g.* by centering on an atom) and want to update the distances to it, you have to toggle off and on the "Show Pointer Distances" on the Pointer Distances dialog.

3.22 Crosshairs

Crosshairs can be drawn at the centre of the screen, using either the C key[20] in graphics window or `Draw -> Crosshairs...`. The ticks are at 1.54Å, 2.7Å and 3.8Å.

3.23 3D Annotations

Positions in 3D space can be annotated with 3D text. The mechanism to do this can be found under Extensions -> Representations -> 3D Annotations. 3D Annotations can be saved to and loaded from a file.

3.24 Frame Rate

Sometimes, you might as yourself "how fast is the computer?"[21]. Using `Calculate -> Frames/Sec` you can see how fast the molecule is rotating, giving an indication of graphics performance. It is often better to use a map that is more realistic and stop the picture whizzing round. The output is written to the status bar and the console, you need to give it a few seconds to "settle down". It is best not to have other widgets overlaying the GL canvas as you do this.

The contouring elapsed time[22] gives an indication of CPU performance.

3.25 Program Output

Due to its "in development" nature (at the moment), Coot produces a lot of "console"[23] output - much of it debugging or "informational". This will go away in due course. You are advised to run Coot so that you can see the console and the graphics window at the same time, since feedback from atom clicking (for example) is often written there rather than displayed in the graphics window.

- Output that starts "ERROR..." is a programming problem (and ideally, you should never see it).
- Output that starts "WARNING..." means that something probably unintended happened due to the unexpected nature of your input or file(s).
- Output that starts "DEBUG..." has (obviously enough) been added to aid debugging. Most of them should have been cleaned up before release, but as Coot is constantly being developed, a few may slip through. Just ignore them.

[20] and C again to toggle them off.
[21] compared to some other one.
[22] prompted by changing the contour level.
[23] *i.e.* the terminal in which you started Coot.

4 Coordinate-Related Features

4.1 Reading coordinates

The format of coordinates that can be read by coot is either PDB or mmCIF. To read coordinates, choose `File -> Read Coordinates` from the menu-bar. Immediately after the coordinates have been read, the view is (by default) recentred to the centre of this new molecule and the molecule is displayed. The recentring of the view after the coordinates have been read can be turned off by unclicking the "Recentre?" radio-button.

To disable the recentring of the view on reading a coordinates file via scripting, use: `(set-recentre-on-read-pdb 0)`. However, when reading a coordinates file from a script it is just as good (if not better) to use `(handle-read-draw-molecule-with-recentre` *`filename`* `0)` - the additional `0` means "don't recentre". And that affects just the reading of *`filename`* and not subsequent files.

By default coot does not allow reading coordinates with duplicated sequence numbers. To enable the reading of files with duplicated sequence numbers use the function:

`(allow-duplicate-sequence-numbers)`

Coot can read MDL mol files.

4.1.1 A Note on Space Groups Names

Coot uses the space group on the "CRYST1" line of the pdb file. The space group should be one of the xHM symbols listed (for example) in the CCP4 dictionary file '`syminfo.lib`'. So, for example, `"R 3 2 :H"` should be used in preference to `"H32"`.

4.1.2 Read multiple coordinate files

The reading multiple files using the GUI is not available (at the moment). However the following scripting functions are available:

`(read-pdb-all)`

which reads all the "*.pdb" files in the current directory

`(multi-read-pdb` *`glob-pattern dir`*`)`

which reads all the files matching *`glob-pattern`* in directory *`dir`*. Typical usage of this might be:

`(multi-read-pdb "a*.pdb" ".")`

Alternatively you can specify the files to be opened on the command line when you start coot (see Section Section 1.6 [Command Line Arguments], page 3).

4.1.3 SHELX .ins/.res files

SHELX `".res"` (and `".ins"` of course) files can be read into Coot, either using the GUI `File -> Open Coordinates...` or by the scripting function:

`(read-shelx-ins-file` *`file-name`*`)`

where *`file-name`* is quoted, such as `"thox.ins"`.

Although Coot should be able to read any SHELX `".res"` file, it may currently have trouble displaying the bonds for centro-symmetric structures.

ShelxL atoms with negative `PART` numbers are given alternative configuration identifiers in lower case.

To write a SHELX ".ins" file:

`(write-shelx-ins-file` *`imol file-name`*`)`

where *`imol`* is the number of the molecule you wish to export.

This will be a rudimentary file if the coordinates were initially from a "PDB" file, but will contain substantial SHELX commands if the coordinates were initially generated from a SHELX `ins` file.

4.2 Atom Info

Information about about a particular atom is displayed in the text console when you click using middle-mouse. Information for all the atoms in a residue is available using `Info -> Residue Info...`.

The temperature factors and occupancy of the atoms in a residue can be set by using `Edit -> Residue Info...`.

4.3 Atom Labeling

Use Shift `+` left-mouse to label atom. Do the same to toggle off the label. The font size is changeable using `Edit -> Font Size...`. The newly centred atom is labelled by default. To turn this off use:

`(set-label-on-recentre-flag 0)`

Some people prefer to have atom labels that are shorter, without the slashes and residue name:

`(set-brief-atom-labels 1)`

To change the atom label colour, use:

`(set-font-colour 0.9 0.9 0.9)`

4.4 Atom Colouring

The atom colouring system in coot is unsophisticated. Typically, atoms are coloured by element: carbons are yellow, oxygens red, nitrogens blue, hydrogens white and everything else green (see Section Section 3.7 [Display Manager], page 10 for colour by chain). However, it is useful to be able to distinguish different molecules by colour, so by default coot rotates the colour map of the atoms (*i.e.* changes the H value in the HSV[1] colour system). The amount of the rotation depends on the molecule number and a user-settable parameter:

- `(set-colour-map-rotation-on-read-pdb 30)`.

The default value is 31°.

Also one is able to select only the Carbon atoms to change colour in this manner: `(set-colour-map-rotation-on-read-pdb-c-only-flag 1)`.

The colour map rotation can be set individually for each molecule by using the GUI: `Edit -> Bond Colours...`.

[1] Hue Saturation Value (Intensity).

4.5 Bond Parameters

The various bond parameters can be set using the GUI dialog `Draw -> Bond Parameters` or *via* scripting functions.

The represention style of the molecule that has the active residue (if any) can be changed using the scroll wheel with Ctrl and Shift.

4.5.1 Bond Thickness

The thickness (width) of bonds of individual molecules can be changed. This can be done via the `Bond Parameters` dialog or the scripting interface:

`(set-bond-thickness` *`thickness imol`*`)`

where `imol` is the molecule number.

The default thickness is 3 pixels. The bond thickness also applies to the symmetry atoms of the molecule. The default bond thickness for new molecules can be set using:

`(set-default-bond-thickness` *`thick`*`)`

where *`thick`* is an integer.

There is no means to change the bond thickness of a residue selection within a molecule.

4.5.2 Display Hydrogens

Initially, hydrogens are displayed. They can be undisplayed using

`(set-draw-hydrogens` *`mol-no`* `0)`[2]

where *`mol-no`* is the molecule number.

There is a GUI to control this too, under "Edit -> Bond Parameters".

4.5.3 NCS Ghosts Coordinates

It is occasionally useful when analysing non-crystallographically related molecules to have "images" of the other related molecules appear matched onto the current coordinates. It is important to understand that these ghosts are for displaying differences of NCS-related molecules by structure superposition, not displaying neighbouring NCS related molecules. As you read in coordinates in Coot, they are checked for NCS relationships and clicking on "Edit -> Bond Parameters -> Show NCS Ghosts" -> "Yes" -> "Apply" will create "ghost" copies of them over the reference chain[3].

Sometimes SSM does not provide a good (or even useful) matrix. In that case, we can specify the residue range ourselves and let the LSQ algorithm provide the matrix. A gui dialog for this operation can be found under `Extensions -> NCS -> NCS Ghosts by Residue Range...`.

The scripting function is used like this:

`(manual-ncs-ghosts` *`imol resno-start resno-end ncs-chain-ids`*`)`

Typical usage: `(manual-ncs-ghosts 0 1 10 (list "A" "B" "C"))`

note that in *`ncs-chain-ids`*, the NCS master/reference chain-id goes first.

---

[2] they can be redisplayed using `(set-draw-hydrogens` *`mol-no`* `1)`.

[3] the reference chain is, by default, the first chain of that type in the coordinates file. The reference (master) chain can be changed using the NCS Ghosts Control dialog.

4.5.4 NCS Maps

Coot can use the relative transformations of the NCS-related molecules in a coordinates molecule to transform maps. Use `Calculate -> NCS Maps...` to do this (note the NCS maps only make sense in the region of the reference chain (see above).

Note also that the internal representation of the map is not transformed. If you try to export a NCS overlay map you will get an untransformed map. A transformed map only makes sense around a given point (and when using transformed maps in Coot, this reference point is changed on the fly, thus allowing map transformations on the fly). [This applies to NCS overlap maps, NCS averaged maps are transformed].

This will also create an NCS averaged map[4].

4.5.5 Using Strict NCS

Coot can use a set of strict NCS matrices to specify NCS which means that NCS-related molecules can appear like convention symmetry-related molecules.

`(add-strict-ncs-matrix` *`imol ncs-chain-id ncs-target-chain-id m11 m12 m13 m21 m22 m23 m31 m32 m33 t1 t2 t3`*`)`

where *`ncs-chain-id`* might be "B", "C" "D" (etc.) and *`ncs-target-chain-id`* is "A", i.e. the B, C, D molecules are NCS copies of the A chain.

for icosahedral symmetry the translation components *`t1`*, *`t2`*, *`t3`* will be 0.

You need to turn on symmetry for molecule *`imol`* and set the displayed symmetry object type to "Display Near Chains".

4.6 Download coordinates

Coot provides the possibility to download coordinates from an OCA[5]. (*e.g.* EBI) server[6] (`File -> Get PDB Using Code...`). A pop-up entry box is displayed into which you can type a PDB accession code. Coot will then connect to the web server and transfer the file. Coot blocks as it does this (which is not ideal) but on a semi-decent internet connection, it's not too bad. The downloaded coordinates are saved into a directory called '`coot-download`'.

It is also possible to download mmCIF data and generate a map. This currently requires a properly formatted database structure factors mmCIF file[7].

4.7 Get Coordinates and Map from EDS

Using this function we have the ability to download coordinates and view the map from structures in the Electron Density Server (EDS) at Uppsala University. This is a much more robust and faster way to see maps from deposited structures. This function can be found under the File menu item.

This feature was added with the assistance of Gerard Kleywegt. If you use the EDS, please cite GJ Kleywegt, MR Harris, JY Zou, TC Taylor, A Wählby & TA Jones (2004), "*The Uppsala Electron-Density Server*", *Acta Cryst.* **D**60, 2240-2249.

---

[4] that also only makes sense in the region of the reference chain.

[5] OCA is "goose" in Spanish (and Italian)

[6] the default is the Weizmann Institute - which for reasons I won't go into here is currently much faster than the EBI server.

[7] which (currently) only a fraction are.

4.8 Save Coordinates

On selecting from the menus `File -> Save Coordinates...` you are first presented with a list of molecules which have coordinates. As well as the molecule number, there is the molecule name - very frequently the name of the file that was read in to generate the coordinates in coot initially. However, this is only a *molecule* name and should not be confused with the filename to which the coordinates are saved. The coordinates *filename* can be selected using the `Select Filename...` button.

If your filename ends in `.cif`, `.mmcif` or `.mmCIF` then an mmCIF file will be written (not a "PDB" file).

4.9 Setting the Space Group

If for some reason, the pdb file that you read does not have a space group, or has the wrong space group, then you can set it using the following function:

`(set-space-group` *`imol symbol`*`)`

e.g.:

`(set-space-group 0 "P 41 21 2")`

4.10 Anisotropic Atoms

By default anisotropic atom information is not represented[8]. To turn them on, use `Draw -> Anisotropic Atoms -> Show Anisotropic Atoms? -> Yes`, or the command: `(set-show-aniso 1)`.

You cannot currently display thermal ellipsoids[9] for isotropic atoms.

4.11 Symmetry

Coordinates symmetry is "dynamic". Symmetry atoms can be labeled[10].

Every time you recentre, the symmetry coordinates are updated. The information shown contains the atom information and the symmetry operation number and translations needed to generate the atom in that position. To show the symmetry operator as a string (rather than a (1-based) index into the list of symmetry operators (as is the default)) Use `Draw -> Show Symmetry> -> Expanded Symmetry Atom Labels`. Coot generates symmetry related atoms by moving the current set close to the origin by a translation, performing the symmetry expansion around the origin and moving the the symmetry coordinates back by applying the inverse of the origin translation. The origin translation is also displayed in curly braces, e.g. "`{1 -1 0}`".

By default symmetry atoms are not displayed.

If you want coot to display symmetry coordinates without having to use the gui, add to your '`~/.coot`' the following:

`(set-show-symmetry-master 1)`

---

[8] using thermal ellipsoids

[9] in the case of isotropic atoms, ellipsoids are spherical, of course.

[10] symmetry labels are in pale blue/purple and also provide the symmetry operator number and the translations along the a, b and c axes.

The symmetry can be represented as Cαs. This along with representation of the molecule as Cαs (Section Section 3.7 [Display Manager], page 10) allow the production of a packing diagram.

4.11.1 Missing symmetry

Sometimes (rarely) coot misses symmetry-related molecules that should be displayed. In that case you need to expand the shift search (the default is 1):

```
(set-symmetry-shift-search-size 2)
```

This is a hack, until the symmetry search algorithm is improved.

4.12 Sequence View

The protein is represented by one letter codes and coloured according to secondary structure. These one letter codes are active - if you click on them, they will change the centre of the graphics window - in much the same way as clicking on a residue in the Ramachandran plot.

4.13 Print Sequence

The single letter code (of the *imol*th molecule) is written out to the console in FASTA format. Use can use this to cut and paste into other applications:

```
(print-sequence imol)
```

4.14 Environment Distances

Environment distances are turned on using `Info -> Environment Distances...`. Contacts to other residues are shown and to symmetry-related atoms if symmetry is being displayed. The contacts are coloured by atom type[11].

4.15 Distances and Angles

The distance between atoms can be found using `Info -> Distance`[12]. The result is displayed graphically, and written to the console.

4.16 Zero Occupancy Marker

Atoms of zero occupancy are marked with a grey spot. To turn off these markers, use:

```
(set-draw-zero-occ-markers 0)
```

Use an argument of 1 to turn them on.

---

[11] contacts involving two hydrogens or at least one carbon atom are yellow, denoting 'bump'. Hydrogen contacts display cut-off are based on the user-defined maximum distance, but shortened by 0.5Å per hydrogen atom.

[12] Use `Angle` for an angle, of course.

4.17 Atomic Dots

You can draw dots round arbitrary atom selections

`(dots` *`imol atom-selection dot-density radius`*`)` The function returns a handle.

e.g. put a sphere of dots around all atoms of the 0th molecule (it might be a set of heavy atom coordinates) at the default dot density and radius:

```
(dots 0 "/1" "heavy-atom-sites" 1 1)
```

You can't change the colour of the dots.

There is no internal mechanism to change the radius according to atom type. With some cleverness you might be able to call this function several times and change the radius according to the atom selection.

There is a function to clear up the dots for a particular molecule *`imol`* and dots set identifier *`dots-handle`*

`(clear-dots` *`imol dots-handle`*`)`

There is a function to return how many dots sets there are for a particular molecule *`imol`*:

`(n-dots-set` *`imol`*`)`

4.18 Ball and Stick Representation

Fragments of the molecule can be rendered as a "ball and stick" molecule:

`(make-ball-and-stick` *`imol atom-selection bond-thickness sphere-size draw-spheres-flag`*`)`

e.g. `(make-ball-and-stick 0 "/1/A/10-20" 0.3 0.4 1)`

The ball-and-stick representation can be cleared using:

`(clear-ball-and-stick` *`imol`*`)`

4.19 Mean, Median Temperature Factors

Coot can be used to calculate the mean (average) and median temperatures factors:

`(average-temperature-factor` *`imol`*`)`

`(median-temperature-factor` *`imol`*`)`

-1 is returned if there was a problem[13].

4.20 Secondary Structure Matching (SSM)

The excellent SSM alogrithm[14] of Eugene Krissinel is available in Coot. The GUI interface is straight-forward and can be found under `Calculate -> SSM Superpose`. You can specify the specific chains that you wish to match using the "Use Specific Chain" check-button.

There is a scripting level function which gives even finer control:

`(superpose-with-atom-selection` *`imol1 imol2 mmdb-atom-selection-string-1 mmdb-atom-selection-string-2 move-copy-flag`* `)`

[13] *e.g.* this molecule was a map or a closed molecule.

[14] the same one as in the CCP4 program SUPERPOSE

the *move-copy-flag* should be 1 if you want to apply the transformation to a copy of *imol2* (rather than *imol2* itself). Otherwise, *move-copy-flag* should be 0.

mmdb atom selection strings (Coordinate-IDs) are explained in detail in the mmdb manual.

Briefly, the string should be formed in this manner:

`/mdl/chn/seq(res).ic/atm[elm]:aloc`

e.g. `"/1/A/12-130/CA"`

4.21 Least-Squares Fitting

There is a simple GUI for this `Calculate -> LSQ Superpose...`

The scripting interface to LSQ fitting is as follows:

`(simple-lsq-match` *ref-start-resno ref-end-resno ref-chain-id imol-ref mov-start-resno mov-end-resno mov-chain-id imol-mov match-type*`)`

where:

- *ref-start-resno* is the starting residue number of the reference molecule
- *ref-end-resno* is the last residue number of the reference molecule
- *mov-start-resno* is the starting residue number of the moving molecule
- *mov-end-resno* is the last residue number of the moving molecule
- *match-type* is one of `'CA`, `'main`, or `'all`.

e.g.: `(simple-lsq-match 940 950 "A" 0 940 950 "A" 1 'main)`

More sophisticated (match molecule number 1 chain "B" on to molecule number 0 chain "A"):

```
(define match1 (list 840 850 "A" 440 450 "B" 'all))
(define match2 (list 940 950 "A" 540 550 "B" 'main))
(clear-lsq-matches)
(set-match-element match1)
(set-match-element match2)
(apply-lst-matches 0 1) ; match molecule number 1 onto molecule number 0.
```

4.22 Ligand Overlaying

The scripting function

`(overlap-ligands` *imol-ligand imol-ref chain-id-ref resno-ref*`)`

returns a rotation+translation operator which can be applied to other molecules (and maps). Here, *imol-ligand* is the molecule number of the ligand (which is presumed to be a a molecule on its own - Coot simply takes the first residue that it finds). *imol-ref chain-id-ref resno-ref* collectively describe the target position for the moving *imol-ligand* molecule.

The convenience function

`(overlay-my-ligands` *imol-mov chain-id-mov resno-mov imol-ref chain-id-ref resno-ref*`)`

wraps `overlap-ligands`.

The GUI for the function can be found under

`Extensions -> Modelling -> Supperpose Ligands...`

4.23 Writing PDB files

As well as the GUI option `File -> Save Coordinates...` there is a scripting options available:

`(write-pdb-file` *`imol pdb-file-name`*`)`

which writes the *`imol`*th coordinates molecule to *`filename`*.

To write a specific residue range:

`(write-residue-range-to-pdb-file` *`imol chain-id start-resno endresno pdb-file-name`*`)`

5 Modelling and Building

The functions described in this chapter manipulate, extend or build molecules and can be found under `Calculate -> Model/Fit/Refine...`. When activated, the dialog "stays on top" of the main graphics window[1]. Some people think that this is not always desirable, so this behaviour can be undone using:

```
(set-model-fit-refine-dialog-stays-on-top 0)
```

5.1 Regularization and Real Space Refinement

Coot will read the geometry restraints for refmac and use them in fragment (zone) idealization - this is called "Regularization". The geometrical restraints are, by default, bonds, angles, planes and non-bonded contacts. You can additionally use torsion restraints by `Calculate -> Model/Fit/Refine... -> Refine/Regularize Control -> Use Torsion Restraints`. Truth to tell, this has not been successful in my hands (sadly).

"RS (Real Space) Refinement" (after Diamond, 1971[2]) in Coot is the use of the map in addition to geometry terms to improve the positions of the atoms. Select "Regularize" from the "Model/Fit/Refine" dialog and click on 2 atoms to define the zone (you can of course click on the same atom twice if you only want to regularize one residue). Coot then regularizes the residue range. At the end Coot, displays the intermediate atoms in white and also displays a dialog, in which you can accept or reject this regularization. In the console are displayed the χ^2 values of the various geometrical restraints for the zone before and after the regularization. Usually the χ^2 values are considerably decreased - structure idealization such as this should drive the χ^2 values toward zero.

The use of "Refinement" is similar - with the addition of using a map. The map used to refine the structure is set by using the "Refine/Regularize Control" dialog. If you have read/created only one map into Coot, then that map will be used (there is no need to set it explicitly).

Use, for example, `(set-matrix 20.0)`

to change the weight of the map gradients to geometric gradients. The higher the number the more weight that is given to the map terms[3]. The default is 60.0. This will be needed for maps generated from data not on (or close to) the absolute scale or maps that have been scaled (for example so that the sigma level has been scaled to 1.0).

For both "Regularize Zone" and "Refine Zone" one is able to use a single click to refine a residue range. Pressing A on the keyboard while selecting an atom in a residue will automatically create a residue range with that residue in the middle. By default the zone is extended one residue either size of the central residue. This can be changed to 2 either side using `(set-refine-auto-range-step 2)`.

Intermediate (white) atoms can be moved around with the mouse (click and drag with left-mouse, by default). Refinement will proceed from the new atom positions when the mouse button is released. It is possible to create incorrect atom nomenclature and/or chiral

[1] given a half-decent window manager

[2] Diamond, R. (1971). A Real-Space Refinement Procedure for Proteins. *Acta Crystallographica* **A**27, 436-452.

[3] but the resulting χ^2 values are higher.

volumes in this manner - so some care must be taken. Press the A key as you left-mouse click to move atoms more "locally" (rather than a linear shear) and CTRL key as you left-mouse click to move just one atom.

In more up to date versions, Coot will display colour patches (something like a traffic light system) representing the chi squared values of each of types of geometric feature refined. Typically "5 greens" is the thing to aim for, the colour changes occurring at chi squared values 2, 5 and 8 (8 being the most red).

To prevent the unintentional refinement of a large number of residues, there is a "heuristic fencepost" of 20 residues. A selection of than 20 residues will not be regularized or refined. The limit can be changed using the scripting function: *e.g.* `(set-refine-max-residues 30)`.

5.1.1 Dictionary

The geometry description for residues, monomers and links used by Coot are in the standard mmCIF format. Because this format alows multiple comp_ids (residue types) to be described within a cif loop, it is hard to tell when a dictionary entry needs to be overwritten when reading a new file. Therefore Coot makes this extra constraint: that the "chem_comp" loop should appear first in the comp list data item - if this is the case, then Coot can overwrite an old restraint table for a particular comp_id/residue-type when a new one is read.

By default, the geometry dictionary entries for only the standard residues are read in at the start[4]. It may be that your particular ligand is not amongst these. To interactively add a dictionary entry use `File -> Import CIF Dictionary`. Alternatively, you can use the function:

`(read-cif-dictionary` *`filename`*`)`

and add this to your `.coot` file (this may be the preferred method if you want to read the file on more than one occasion).

Note: the dictionary also provides the description of the ligand's torsions.

5.1.2 Sphere Refinement

Sphere refinement selects residues within a certain distance of the residue at the centre of the screen and includes them for real space refinement. In this way, one can select residues that are not in a linear range. This technique is useful for refining disulfide bonds and glycosidic linkages.

To enable sphere refinement, Right-mouse click in the right hand side of the horizontal toolbutton menu, Manage buttons -> [Tick] Sphere Refine -> Apply. You will need a python-enabled Coot to do this.

The following adds a key binding (Shift-R) that refines resides that are within 3.5Å of the residue at the centre of the screen:

```
(define *sphere-refine-radius* 3.5)

(add-key-binding "Refine residues in a sphere" "R"
    (lambda ()
```

[4] And a few extras, such as phosphate

```
(using-active-atom

 (let* ((rc-spec (list aa-chain-id aa-res-no aa-ins-code))
        (ls (residues-near-residue aa-imol rc-spec *sphere-refine-radius*)))
   (refine-residues aa-imol (cons rc-spec ls))))))
```

5.1.3 Refining Specific Residues

You can specify the residues that you want to refine without using a linear or sphere selection usine `refine-residues`. For example:

```
(refine-residues 0 '(("L" 501 "") ("L" 503 "")))
```

will refine residues A501 and A503 (and residue A502 (if it exists) will be an anchoring residue - used in optimizing the link geometry of the atoms in A501 and A503).

5.1.4 Refining Carbohydrates

Refining carbohydrates monomers should be as straightforward as refining a protein residue. Coot will look in the dictionary for the 3-letter code for the particular residue type, if it does not find it, Coot will try to search for dictionary files using "-b-D" or "-a-L" extensions.

When refining a group of carbohydrates, the situation needs a bit more explanation. For each residue pair with tandem residue numbers specified in the refinement range selection, Coot checks if these residue types are are furanose or pyranose in the dictionary, and if the are both one or the other, then it tries to see if there are any of the 11 link types (BETA1-4, BETA2-3, ALPHA1-2 and so on) specified in the dictionary. It does this by a distance check of the potentially bonding atoms. If the distance is less than 3.0Å, then a glycosidic bond is made and used in the refinement.

Bonds between protein and carbohydrate and branched carbohydrates can be refined using "Sphere Refinement".

Instead of using a sphere to make a residue selection, you can specify the residues directly using `refine-residues`, for example:

```
(refine-residues 0 '(("L" 501 "") ("L" 503 "")))
```

LINK and LINKR cards are not yet used to determine the geometry of the restraints.

5.1.5 Planar Peptide Restraints

By default, Coot uses a 5 atom (CA-1, C-1, O-1, N-2, CA-2) planar peptide restraints. These restraints should help in low resolution fitting (the main-chains becomes less distorted), reduce accidental cis-peptides and may help "clean up" Ramachandran plots.

```
(add-planar-peptide-restraints)
```

And similarly they can be removed:

```
(remove-planar-peptide-restraints)
```

There is also a GUI to add and remove these restraints in `Extensions -> Refine... -> Peptide Restraints...`

5.1.6 The UNK residue type

The `UNK` residue type is a special residue type to Coot. It has been added for use with Buccaneer. Don't give you ligand (or anything else) the 3-letter-code `UNK` or confusion will result[5].

5.1.7 Moving Zero Occupancy Atoms

By default, atoms with zero occupancy are moved when refining and regularizing. This can sometimes be inconvenient. To turn of the movement of atoms with zero occupancy when refining and regularizing:

```
(set-refinement-move-atoms-with-zero-occupancy 0)
```

5.2 Changing the Map for Building/Refinement

You can change the map that is used for the fitting and refinement tools using the `Select Map...` button on the Model/Fit/Refine dialog.

5.3 Rotate/Translate Zone

"Rotate/Translate Zone" from the "Model/Fit/Refine" menu allows manual movement of a zone. After pressing the "Rotate/Translate Zone" button, select two atoms in the graphics canvas to define a residue range[6], the second atom that you click will be the local rotation centre for the zone. The atoms selected in the moving fragment have the same alternate conformation code as the first atom you click. To actuate a transformation, click and drag horizontally across the relevant button in the newly-created "Rotation & Translation" dialog. The axis system of the rotations and translations are the screen coordinates. Alternatively[7], you can click using left-mouse on an atom in the fragment and drag the fragment around. Use Control Left-mouse to move just one atom, rather than the whole fragment. If you click Control Left-mouse whilst *not* over an atom then you can rotate the fragment using mouse drag. Click "OK" (or press Return) when the transformation is complete.

To change the rotation point to the centre of the intermediate atoms (rather than the second clicked atom), use the setting:

```
(set-rotate-translate-zone-rotates-about-zone-centre 1)
```

5.4 Rigid Body Refinement

"Rigid Body Fit Zone" from the "Model/Fit/Refine" dialog provides rigid body refinement. The selection is zone-based[8]. So to refine just one residue, click on one atom twice.

Sometimes no results are displayed after Rigid Body Fit Zone. This is because the final model positions had too many final atom positions in negative density. If you want to over-rule the default fraction of atoms in the zone that have an acceptable fit (0.75), to be (say) 0.25:

```
(set-rigid-body-fit-acceptable-fit-fraction 0.25)
```

[5] unless you are using Buccaneer, of course

[6] if you want to move only one residue, then click the same atom twice.

[7] like Refinement and Regularization

[8] like Regularization and Refinement.

5.5 Simplex Refinement

Rigid body refinement via Nelder-Mead Simplex minimization is available in Coot. Simplex refinement has a larger radius of convergence and thus is useful in a position where simple rigid body refinement finds the wrong minimum. However the Simplex algorithm is much slower. Simplex refinement for a residue range *start-resno* to *end-resno* (inclusive) in chain *chain-id* can be accessed as follows:

`(fit-residue-range-to-map-by-simplex` *start-resno end-resno alt-loc chain-id imol imol-for-map*`)`

There is currently no GUI interface to Simplex refinement.

5.6 Post-manipulation-hook

If you wanted automatically run a function after a model has been manipulated then you can do so using by creating a function that takes 2 arguments, such as:

`(post-manipulation-hook` *imol manipulation-mode*`)`

manipulation-mode is one of *(DELETED)*, *(MUTATED)* or *(MOVINGATOMS)*.

And of course *imol* is the model number of the maniplated molecule.

(It would of course be far more useful if this function was also passed a list of residues - that is something for the future).

5.7 Baton Building

Baton build is most useful if a skeleton is already calculated and displayed (see Section Section 6.14 [Skeletonization], page 52). When three or more atoms have been built in a chain, Coot will use a prior probability distribution for the next position based on the position of the previous three. The analysis is similar to that of Oldfield & Hubbard (1994)[9], however it is based on a more recent and considerably larger database.

Little crosses are drawn representing directions in which is is possible that the chain goes, and a baton is drawn from the current point to one of these new positions. If you don't like this particular direction[10], use `Try Another`. The list of directions is scored according to the above criterion and sorted so that the most likely is at the top of the list and displayed first as the baton direction.

When starting baton building, be sure to be about 3.8Å from the position of the first-placed Cα, this is because the next Cα is placed at the end of the baton, the baton root being at the centre of the screen. So, when trying to baton-build a chain starting at residue 1, centre the screen at about the position of residue 2.

It seems like a good idea to increase the map sampling to 2 or even 2.5 (before reading in your mtz file) [a grid sampling of about 0.5Å seems reasonable] when trying to baton-build a low resolution map. You can set the map sampling using `Edit -> Map Parameters -> Map Sampling`.

---

[9] T. J. Oldfield & R. E. Hubbard (1994). "Analysis of Cα Geometry in Protein Structures" *Proteins-Structure Function and Genetics* **18(4)** 324 – 337.

[10] which is quite likely at first since coot has no knowledge of where the chain has been and cannot score according to geometric criteria.

Occasionally, every point is not where you want to position the next atom. In that case you can either shorten or lengthen the baton, or position it yourself using the mouse. Use "b" on the keyboard to swap to baton mode for the mouse[11].

Baton-built atoms are placed into a molecule called "Baton Atom" and it is often sensible to save the coordinates of this molecule before quitting coot.

If you try to trace a high resolution map (1.5Å or better) you will need to increase the skeleton search depth from the default (10), for example:

`(set-max-skeleton-search-depth 20)`

Alternatively, you could generate a new map using data to a more moderate resolution (2Å), the map may be easier to interpret at that resolution anyhow[12].

The guide positions are updated every time the "Accept" button is clicked. The molecule name for these atoms is "Baton Build Guide Points" and is is not usually necessary to keep them.

5.7.1 Undo

There is also an "Undo" button for baton-building. Pressing this will delete the most recently placed Cα and the guide points will be recalculated for the previous position. The number of "Undo"s is unlimited. Note that you should use the "Undo" button in the Baton Build dialog, not the one in the "Model/Fit/Refine" dialog (Section Section 3.11 [Backups and Undo], page 13).

5.7.2 Missing Skeleton

Sometimes (especially at loops) you can see the direction in which the chain should go, but there is no skeleton (see Section Section 6.14 [Skeletonization], page 52) is displayed (and consequently no guide points) in that direction. In that case, "Undo" the previous atom and decrease the skeletonization level (`Edit -> Skeleton Parameters -> Skeletonization Level`). Accept the atom (in the same place as last time) and now when the new guide points are displayed, there should be an option to build in a new direction.

5.7.3 Building Backwards

The following scenario is not uncommon: you find a nice stretch of density and start baton building in it. After a while you come to a point where you stop (dismissing the baton build dialog). You want to go back to where you started and build the other way. How do you do that?

- Use the command:

  `(set-baton-build-params` *`start-resno chain-id`* `"backwards")`

  where *`start-resno`* would typically be 0[13] and *`chain-id`* would be `""` (default).
- Recentre the graphics window on the first atom of the just-build fragment
- Select "Ca Baton Mode" and select a baton direction that goes in the "opposite" direction to what is typically residue 2. This is slightly awkward because the initial

[11] "b" again toggles the mode off.

[12] high-resolution map interpretation is planned.

[13] *i.e.* one less than the starting residue in the forward direction (defaults to 1).

baton atoms build in the "opposite" direction are not dependent on the first few atoms of the previously build fragment.

5.8 Reversing Direction of Fragment

After you've build a fragment, sometimes you might want to change the direction of that fragment (this function changes an already existing fragment, as opposed to Backwards Building which sets up Baton Building to place new points in reverse order).

The fragment is defined as a contiguous set of residues numbers. So that you should be sure that other partial fragments which have the same chain id and that are not connected to this fragment have residue numbers that are not contiguous with the fragment you are trying to reverse.

5.9 C*alpha* -> Mainchain

Mainchain can be generated using a set of Cαs as guide-points (such as those from Baton-building) along the line of Esnouf[14] or Jones and coworkers[15]. Briefly, 6-residue fragments of are generated from a list of high-quality[16] structures. The Cα atoms of these fragments are matched against overlapping sets of the guide-point Cαs. The resulting matches are merged to provide positions for the mainchain (and Cβ) atoms. This procedure works well for helices and strands, but less well[17] for less common structural features.

This function is also available from the scripting interface:

`(db-mainchain` *`imol chain-id resno-start resno-end direction`*`)`

where direction is either `"backwards"` or `"forwards"`.

Recall that the *`chain-id`* needs to be quoted, *i.e.* use `"A"` not `A`. Note that *`chain-id`* is `""` when the Cαs have been built with Baton Mode in Coot.

5.10 Backbone Torsion Angles

It is possible to edit the backbone ϕ and ψ angles indirectly using an option in the Model/Fit/Refine's dialog: "Edit Backbone Torsions..". When clicked and an atom of a peptide is selected, this produces a new dialog that offers "Rotate Peptide" which changes this residues ψ and "Rotate Carbonyl" which changes ϕ. Click and drag across the button[18] to rotate the moving atoms in the graphics window. You should know, of course, that making these modifications alter the ϕ/ψ angles of more than one residue.

5.11 Docking Sidechains

Docking sidechains means adding sidechains to a model or fragment that has currently only poly-Ala, where the sequence assignment is unknown. The algorithm is basically the

[14] R. M. Esnouf "Polyalanine Reconstruction from Cα Positions Using the Program *CALPHA* Can Aid Initial Phasing of Data by Molecular Replacement Procedures" *Acta Cryst.* , D**53**, 666-672 (1997).

[15] T.A. Jones & S. Thirup "Using known substructures in protein model building and crystallography" *EMBO J.* **5**, 819–822 (1986).

[16] and high resolution

[17] *i.e.* there are severely misplaced atoms

[18] as for Rotate/Translate Zone (Section Section 5.3 [Rotate/Translate Zone], page 30).

same as in Cowtan's Buccaneer, but with some corners cut to make things (more or less) interactive. The algorithm uses the shape of the density around the C-beta position to estimate the probability of each sidechain type at that position.

The function is accessed via the `Extensions -> Dock Sequence` menu item. First, a sequence should be assigned from a PIR file to a particular chain-id and model number. Secondly `Extensions -> Dock Sequence -> Dock Sequence on this fragment...`. Choose the model to build on and then `Dock Sequence!` If all goes well, the model will be updated with mutated residues and undergo rotamer seach for each of the new residues. If the sequence alignment is not sufficiently clear, then you will get a dialog suggesting that you extend or improve the fragment.

5.12 Rotamers

The rotamers are generated[19] from the backbone independent sidechain library of the Richardsons group[20].

The m, t and p stand for "minus (-60)", "trans (180)" and "plus (+60)". There is one letter per χ angle.

Use keyboard . and , to cycle round the rotamers.

5.12.1 Auto Fit Rotamer

"Auto Fit Rotamer" will try to fit the rotamer to the electron density. Each rotamer is generated, rigid body refined and scored according to the fit to the map. Fitting the second conformation of a dual conformation in this way will often fail - the algorithm will pick the best fit to the density - ignoring the position of the other atoms.

The algorithm doesn't know if the other atoms in the structure are in sensible positions. If they are, then it is sensible not to put this residue too close to them, if they are not then there should be no restriction from the other atoms as to the position of this residue - the default is "are sensible", which means that the algorithm is prevented from finding solutions that are too close to the atoms of other residues. `(set-rotamer-check-clashes 0)` will stop this.

There is a scripting interface to auto-fitting rotamers:

`(auto-fit-best-rotamer` *`resno alt-loc ins-code chain-id imol-coords imol-map clash-flag lowest-rotamer-probability`*`)`

where:

`resno` is the residue number

`alt-loc` is the alternate/alternative location symbol (*e.g.* `"A"` or `"B"`, but most often `""`)

`ins-code` is the insertion code (usually `""`)

`imol-coords` is the molecule number of the coordinates molecule

`imol-map` is the molecule number of the map to which you wish to fit the side chains

[19] since version 0.4

[20] SC Lovell, JM Word, JS Richardson and DC Richardson (2000) "The Penultimate Rotamer Library" Proteins: Structure Function and Genetics 40: 389-408. You can get the paper from `http://kinemage.biochem.duke.edu/databases/rotamer.php`

clash-flag should the positions of other residues be included in the scoring of the rotamers (*i.e.* clashing with other other atoms gets marked as bad/unlikely)

lowest-rotamer-probability: some rotamers of some side chains are so unlikely that they shouldn't be considered - typically 0.01 (1%).

You can change the auto-fit rotamer fitting algorithms using

`(set-rotamer-search-mode` *mode*`)`

where *mode* is one of `(ROTAMERSEARCHAUTOMATIC)`, `(ROTAMERSEARCHLOWRES)` (*i.e.* "Backrub Rotamers" (*vide infra*)) or `(ROTAMERSEARCHHIGHRES)` (the conventional/high-resolution method using rigid-body fitting).

By default, the auto-fit rotamer method is `(ROTAMERSEARCHAUTOMATIC)`.

5.12.1.1 Backrub Rotamers

By default, Auto Fit Rotamer will switch to "Backrub Rotamer"[21] mode when fitting against a map of worse than 2.7Å. This search mode moves the some atoms of the mainchain of the neighbouring residues. After rotation of the central residue and neighbouring atoms around the "backrub vector", the individual peptides are back-rotated (along the peptide axis) so that the carbonyl oxygen are placed as near as possible to their original position. The Ramachandran plot is not used in this fitting algorithm.

5.12.2 De-clashing residues

Sometimes you don't have a map[22] but nevertheless there are clashing residues [23] (for example after mutation of a residue range) and you need to rotate side-chains to a non-clashing rotamer. There is a scripting interface:

`(de-clash` *imol chain-id start-resno end-resno*`)`

start-resno is the residue number of the first residue you wish to de-clash

end-resno is the residue number of the last residue you wish to de-clash

imol is the molecule number of the coordinates molecule

This interface will not change residues with insertion codes or alternate conformation. The *lowest-rotamer-probability* is set to 0.01.

5.13 Editing chi Angles

Instead of using Rotamers, one can instead change the χ angles (often called "torsions") "by hand" (using "Edit Chi Angles" from the "Model/Fit/Refine" dialog). To edit a residue's χ_1 press "1": to edit χ_2, "2": χ_3 "3" and χ_4 "4". Use left-mouse click and drag to change the χ value. Use keyboard "0"[24] to go back to ordinary view mode at any time during the editing. Alternatively, one can use the "View Rotation Mode" or use the CTRL key when moving the mouse in the graphics window. Use the Accept/Reject dialog when you have finished editing the χ angles.

---

[21] "The Backrub Motion: How Protein Backbone Shrugs When a Sidechain Dances" *Structure*, Volume **14**, Issue 2, Pages 265-274 I. Davis, W. Bryan Arendall III, D. Richardson, J. Richardson

[22] for example, in preparation of a model for molecular replacement

[23] atoms of residues that are too close to each other

[24] that's "zero".

For non-standard residues, the clicked atom defines the base of the atom tree, which defines the "head" of the molecule (it's the "tail" (twigs/leaves) that wags). To emphasise, then: it matters on which atom you click!

By default torsions for hydrogen atoms are turned off. To turn them on:

```
(set-find-hydrogen-torsions 1)
```

To edit the rotatable bonds of a ligand using this tool, you will need to have read in the mmCIF dictionary beforehand.

5.14 Torsion General

You need to click on the torsion-general button, then click 4 atoms that describe the torsion - the first atom will be the base (non moving) part of the atom tree, on clicking the 4th atom a dialog will pop up with a "Reverse" button. Move this dialog out of the way and then left mouse click and drag in the main window will rotate the "top" part of the residue round the clicked atoms 2 and 3. When you are happy, click "Accept".

If you are torsion generaling a residue that has an alt conf, then the atoms of residue that are moved are those that have the same alt conf as the 4th clicked atom (or have an blank alt conf).

5.14.1 Ligand Torsion angles

For ligands, you will need to read the mmCIF file that contains a description of the ligand's geometry (see Section Section 5.1 [Regularization and Real Space Refinement], page 27). By default, torsions that move hydrogens are not included. Only 9 torsion angles are available from the keyboard torsion angle selection.

5.15 Pep-flip

Coot uses the same pepflip scheme as is used in `O` (*i.e.* the C, N and O atoms are rotated 180° round a line joining the Cα atoms of the residues involved in the peptide). Flip the peptide again to return the atoms to their previous position.

5.16 Add Alternate Conformation

The allows the addition alternate (dual, triple *etc.*) conformations to the picked residue. By default, this provides a choice of rotamer (Section Section 5.12 [Rotamers], page 34). If there are not the correct main chain atoms a rotamer choice cannot be provided, and Coot falls back to providing intermediate atoms.

The default occupancy for new atoms is 0.5. This can be changed by using use slider on the rotamer selection window or by using the scripting function:

```
(set-add-alt-conf-new-atoms-occupancy 0.4)
```

The remaining occupancy of the atoms (after the new occupancy has been added) is split amongst the atoms that existed in the residue before the split. It is important therefore that the residues atoms have sane occupancies before adding an alternative conformation.

The default Split Type is to split the whole residue. If you want the default to be to split a residue after (and including) the CA, then add to your '`.coot`' file:

```
(set-add-alt-conf-split-type-number 0)
```

5.17 Mutation

Mutations are available on a 1-by-1 basis using the graphics. After selecting "Mutate. . ." from the "Model/Fit/Refine" dialog, click on an atom in the graphics. A "Residue Type" window will now appear. Select the new residue type you wish and the residue in the graphics is updated to the new residue type[25]. The initial position of the new rotamer is the *a priori* most likely rotamer. Note that in interactive mode, such as this, a residue type match[26] will not stop the mutation action occurring.

5.17.1 Mutating DNA/RNA

Mutation of DNA or RNA can be performed using "Simple Mutate" from the Model/Fit/Refine dialog. Residues need to be named `"Ad"`, `"Gr"`, `"Ur"` etc.

5.17.2 Multiple mutations

This dialog can be found under `Calculate -> Mutate Residue Range`. A residue range can be assigned a sequence and optionally fitted to the map. This is useful converting a poly-ALA model to the correct sequence[27].

Multiple mutations are also supported *via* the scripting interface. Unlike the single residue mutation function, a residue type match *will* prevent a modification of the residue[28]. Two functions are provided: To mutate a whole chain, use `(mutate-chain` *`imol chain-id sequence`*`)` where:

`chain-id` is the chain identifier of the chain that you wish to mutate (*e.g.* `"A"`) and

`imol` is molecule number.

`sequence` is a list of single-letter residue codes, such as `"GYRESDF"` (this should be a straight string with no additional spaces or carriage returns).

Note that the number of residues in the sequence chain and those in the chain of the protein must match exactly (*i.e.* the whole of the chain is mutated (except residues that have a matching residue type).)

To mutate a residue range, use

- `(mutate-residue-range` *`imol chain-id start-res-no stop-res-no sequence`*`)`

where

`start-res-no` is the starting residue for mutation

`stop-res-no` is the last residue for mutation, *i.e.* using values of 2 and 3 for *`start-res-no`* and *`stop-res-no`* respectively will mutate 2 residues.

Again, the length of the sequence must correspond to the residue range length. Note also that this is a protein sequence - not nucleic acid.

For mutation of nucleic acids, use:

`(mutate-nucleotide-range` *`imol chain-id resno-start resno-end sequence`*`)`

[25] Note that selecting a residue type that matches the residue in the graphics will also result in a mutation

[26] *i.e.* the current residue type matches the residue type to which you wish to mutate the residue

[27] *e.g.* after using Ca -> Mainchain.

[28] *i.e.* the residue atoms will remain untouched

5.17.3 Mutating to a Non-Standard Residue

Sometimes one might like to model post-translational or other such modifications. How is that done, if the new residue type is not one of the standard residue types?

There is a scripting function:

`(mutate-by-overlap` *`imol chain-id resno new-three-letter-code`*`)`

This imports a model residue for the new residue type and overlays it on to the given residue by using graph-matching to determine the equivalent atoms.

The GUI for this can be found under `Extensions -> Modelling -> Replace Residue...` (for this to work, you need to be centred on the residue you wish to replace).

Note that if you are replacing are conventional protein residue with a modified form (*e.g.* replacing a TYR with a phoso-tyrosine or a LYS with an acetyl-lysine) you will need to make sure that the group of the resulting restraints is an `L-peptide` (use `Edit -> Restraints` to check and modify the restraints group. Likewise for modified RNA/DNA nucleotides, you need to specify the group as `RNA` or `DNA` as appropriate.

5.17.4 Mutate and Autofit

The function combines Mutation and Auto Fit Rotamer and is the easiest way to make a mutation and then fit to the map. You can currently only "Mutate and Autofit" protein residues (*i.e.* things with a rotamer dictionary.

5.17.5 Renumbering

Renumbering is straightforward using the renumber dialog available under `Calculate -> Renumber Residue Range...`. There is also a scripting interface:

`(renumber-residue-range` *`imol chain-id start-res-no last-resno offset`*`)`

5.18 Importing Lignds/Monomers

You can import monomers (often ligands) using `File -> Get Monomer...`[29] by providing the 3-letter code of your monomer/ligand. The resulting molecule will be moved so that it placed at the current screen centre.

Typically, when you are happy about the placement of the ligand, you'd then use `Merge Molecules` to add the ligand/monomer to the main set of coordinates.

This procedure creates a pdb file '`monomer-XXX.pdb`' and a dictionary file '`libcheck_XXX.cif`' in the directory in which Coot was started.

A future invocation of Get Monomer uses these file so that the monomer appears quickly[30].

5.19 Ligand from SMILES strings

Similarly, you can generate ligands using `File -> SMILES...` and providing a SMILES string and a code for the residue name (this is your name for the residue type and a dictionary will be generated for the monomer of this type). This function is also a wrapper to LIBCHECK.

[29] this is a wrapper round LIBCHECK, so you must have CCP4 suite to installed for this function to work

[30] rather than running LIBCHECK again

5.20 Find Ligands

You are offered a selection of maps to search (you can only choose one at a time) and a selection of molecules that act as a mask to this map. Finally you must choose which ligand types you are going to search for in this map[31]. Only molecules with less than 400 atoms are suggested as potential ligands.

If you do not have any molecules with less that 400 atoms loaded in Coot, you will get the message:

"Error: you must have at least one ligand to search for!"

New ligands are placed where the map density is and protein (mask) atoms are *not*). The masked map is searched for clusters using a default cut-off of 1.0σ. In weak density this cut-off may be too high and in such a case the cut-off value can be changed using something such as:

`(set-ligand-cluster-sigma-level 0.8)`

However, if the map to be searched for ligands is a difference map, a cluster level of 2.0 or 3.0 would probably be more appropriate (less likely to generate spurious sites).

Each ligand is fitted with rigid body refinement to each potential ligand site in the map and the best one for each site selected and written out as a pdb file. The clusters are sorted by size, the biggest one first (with an index of 0). The output placed ligands files have a prefix "best-overall" and are tagged by the cluster index and residue type of the best fit ligand in that site.

By default, the top 10 sites are tested for ligands - to increase this use:

`(set-ligand-n-top-ligands 20)`

5.20.1 Flexible Ligands

If the "Flexible?" checkbutton is activated, coot will generate a number of variable conformations (default 100) by rotating around the rotatable bonds (torsions). Each of these conformations will be fitted to each of the potential ligand sites in the map and the best one will be selected (again, if it passes the fitting criteria above).

Before you search for flexible ligands you must have read the mmCIF dictionary for that particular ligand residue type (`File -> Import CIF dictionary`).

Use:

`(set-ligand-flexible-ligand-n-samples` *`n-samples`*`)`

where *`n-samples`* is the number of samples of flexibility made for each ligand. Generally speaking, The more the number of rotatable bonds, the bigger this number should be.

By default the options to change these values are not in the GUI. To enable these GUI options, use the scripting function:

`(ligand-expert)`

5.20.2 Adding Ligands to Model

After successful ligand searching, one may well want to add that displayed ligand to the current model (the coordinates set that provided the map mask). To do so, use Merge Molecules (Section Section 5.28 [Merge Molecules], page 42).

[31] you can search for many different ligand types.

5.21 Flip Ligand

Sometimes a ligand is placed more or less in the correct position, but the orientation is wrong - or at least you might want to explore other possible orientation. To do that easily a function has been provided:

`(flip-ligand` *`imol chain-id residue-number`*`)`

This will flip the orientation of the residue around the Eigen vector corresponding to the largest Eigen value, exploring 4 possible orientations.

This function has been further wrapped to provide flipping for the active residue:

`(flip-active-ligand)`

This function can easily be bound to a key.

5.22 Find Waters

As with finding ligands, you are given a choice of maps, protein (masking) atoms. A final selection has to be made for the cut-off level, note that this value is the number of standard deviation of the density of the map *before* the map has been masked. The default sigma level (water positions must have density above this level) is set for a "2Fo-Fc"-style map. If you want to use a difference map, you must change the sigma level (typically to 3 sigma) otherwise you run the risk of fitting waters to difference map noise peaks.

Then the map is masked by the masking atoms and a search is made of features in the map about the electron density cut-off value. Waters are added if the feature is approximately water-sized and can make sensible hydrogen bonds to the protein atoms. The new waters are optionally created in a new molecule called "Waters".

You have control over several parameters used in the water finding:

`(set-write-peaksearched-waters)`

which writes `ligand-waters-peaksearch-results.pdb`, which contains the water peaks (from the clusters) without any filtering and `ligand-waters.pdb` which are a disk copy filtered waters that have been either added to the molecule or from which a new molecule has been created.

`(set-ligand-water-to-protein-distance-limits` *`min-d max-d`*`)` sets the minimum and maximum allowable distances between new waters and the masking molecule (usually the protein). Defaults are 2.4 and 3.2Å.

`(set-ligand-water-spherical-variance-limit` *`varlim`*`)` sets the upper limit for the density variance around water atoms. The default is 0.12.

The map that is marked by the protein and is searched to find the waters is written out in CCP4 format as `"masked-for-waters.map"`.

5.22.1 Refinement Failure

Sometimes as a result of water fitting, you may see something like:

```
WARNING:: refinement failure
          start pos: xyz = (      17.1,     34.76,     60.42)
          final pos: xyz = (     17.19,     34.61,     60.59)
```

When Coot finds a blob, it does a crude positioning of an atom at the centre of the grid points. It then proceeds to move to the peak of the blob by a series of translations. There

are a certain number of cycles, and if it doesn't reach convergence by the end of those cycles then you get the error message.

Often when you go to the position indicated, you can see why Coot had a problem in the refinement.

5.22.2 Blobs

After a water search, Coot will create a blobs dialog (see Section Section 7.4 [sec_blobs], page 56).

5.23 Add Terminal Residue

This creates a new residue at the C or N terminal extension of the residue clicked by fitting to the map. ϕ, ψ angle pairs are selected at random based on the Ramachandran plot probability (for a generic residue) and fitted to the density. By default there are 100 trials. It is possible that a wrong position will be selected for the terminal residue and if so, you can reject this fit and try again with Fit Terminal Residue[32]. Each of the trial positions are scored according to their fit to the map[33] and the best one selected. It is probably a good idea to run "Refine Zone" on these new residues.

If you use the Extensions (`Dock Sequence... -> Associate Sequence with Model`) to apply a PIR sequence file to a model then `Add Terminal Residue` will use the sequence alignment to determine the residue type of the added residue.

Sometimes, particularly with low resolution maps, the added terminal residue will wander off to somewhere inappropriate. This can be addressed in a number of ways:

1. `(set-terminal-residue-do-rigid-body-refine 0)` will disable rigid body fitting of the terminal residue fragment for each trial residue position (the default is 1 (on)) - this may help if the search does not provide good results.
2. to anneal the newly added residue back to the clicked residue (no matter where it ended up being positioned): `(set-add-terminal-residue-do-post-refine 1)`
3. `(set-add-terminal-residue-n-phi-psi-trials 200)` will change the number of trials (default is 100). This is useful if you think that Coot needs to search harder to find a good solution to the positioning of the next residue.

5.24 Add OXT Atom to Residue

At the C-terminus of a chain of amino-acid residues, there is a "modification" so that the C-O becomes a carbonyl, *i.e.* an extra (terminal) oxygen (OXT) needs to be added. This atom is added so that it is in the plane of the Cα, C and O atoms of the residue.

Scripting usage:

`(add-OXT-to-residue imol residue-number insertion-code chain-id)`[34],

where `insertion-code` is typically `""`.

Note, in order to place OXT, the N, CA, C and O atoms must be present in the residue - if (for example) the existing carbonyl oxygen atom is called "OE1" then this function will not work.

[32] usually if this still fails after two repetitions then it never seems to work.

[33] The map is selected using "Refine/Regularize Control"

[34] *e.g.* `(add-OXT-to-residue 0 428 "" "A")`

5.25 Add Atom at Pointer

By default, "Add Atom At Pointer" will pop-up a dialog from which you can choose the atom type you wish to insert[35]. Using `(set-pointer-atom-is-dummy 1)` you can by-pass this dialog and immediately create a dummy atom at the pointer position. Use an argument of `0` to revert to using the atom type selection pop-up on a button press.

The atoms are added to a new molecule called "Pointer Atoms". They should be saved and merged with your coordinates outside of Coot.

5.26 Place Helix

The idea is to place a helix more or less "here" (the screen centre) by fitting to the electron density map. The algorithm is straightforward. First we move to the local centre of density, then examine the density for characteristic directions and fit ideal helices (of length 20 residues) to these directions. The helix is then extended if possible (by checking the fit to the map of residues added in ideal helix conformation) and chopped back if not. If the fit is successful, the helix is created in a new molecule called "Helix". If the fit is not successful, there is instead a message added to the status bar. You can build the majority of a helical protein in a few minutes using this method (you will of course have to assemble the helices and assign residue numbers and sequence later).

This is available as a scripting function `(place-helix-here)` and in the GUI (in the "Other Modelling Tools" dialog).

5.27 Building Ideal DNA and RNA

The interface to building ideal polynucleotides can be found by pressing the "Ideal RNA/DNA. . ." button on the "Other Modelling Tools" dialog.

For a given sequence, a choice of DNA or RNA, A or B form, single or double stranded is presented.

The interface may not gracefully handle uracils in DNA, thymines in RNA or B form RNA.

The ideal B-form DNA is somewhat under-wound, needing 11 base-pairs to repeat (instead of the expected 10.5). There is no easy fix for this currently.

5.28 Merge Molecules

The dialog for this opperation can be found under "Calculate" in the main menubar. This is typically used to add molecule fragments or residues that are in one molecule to the "working" coordinates[36].

The scripting interface is used like this

`(merge-molecules` *`molecule-list target-molecule`*`)`

e.g.

`(merge-molecules (list 1 2 ) 0)`

merges molecules 1 and 2 into molecule 0.

[35] including sulfate or phosphate ions (in such a case, it is probably useful to do a "Rigid Body Fit Zone" on that new residue).

[36] For example, after a ligand search has been performed.

5.29 Temperature Factor for New Atoms

The default temperature factor for new atoms is 30.0. This can be changed by the following

```
(set-default-temperature-factor-for-new-atoms 50.0)
```

5.30 Applying NCS Edits

Let's imagine that you have 3-fold NCS. You have molecule "A" as your master molecule and you make edits to that molecule. Now you want to apply the edits that you made to "A" (the NCS master chain ID) to the "B" and "C" molecules (i.e. you want the "B" and "C" molecules to be rotated/translated versions of the "A" molecule). How is that done?

There are now guis to NCS command to help you out (under Extensions). However, for completeness here are the scripting versions:

```
(copy-from-ncs-master-to-others imol master-chain-id)
```

If you have only a range of residues, rather than a whole chain to replace:

```
(copy-residue-range-from-ncs-master-to-others imol master-chain-id
start-resno end-resno)
```

e.g.

```
(copy-residue-range-from-ncs-master-to-others 0 "A" 1 5)
```

If you want to copy a residue range to a specific chain, or specific list of chains (rather than all NCS peer chains) then make a list of the chain-ids that you wish replaced:

```
(copy-residue-range-from-ncs-master-to-chains 0 "A" 1 5 (list "C"))
```

in this case, just the residues in the "C" chain is replaced.

5.31 Running Refmac

Use the "Run Refmac..." button to select the dataset and the coordinates on which you would like to run Refmac. Note that here Coot only allows the use of datasets which has Refmac parameters set as the MTZ file was read. By default, Coot displays the new coordinates and the new map generated from refmac's output MTZ file. Optionally, you can also display the difference map.

You can add extra parameters (data lines) to refmac's input by storing them in a file called `refmac-extra-params` in the directory in which you started coot.

You can also provide extra/replacement parameters for refmac by setting the variable `refmac-extra-params` to a list of strings, for example:

```
(set! refmac-extra-params (list "REFINE MATRIX 0.1" "MAKE HYDROGENS NO"))
```

Coot "blocks"[37] until Refmac has terminated[38].

The default refmac executable is `refmac5` it is presumed to be in the path. If you don't want this, it can be overridden using a re-definition either at the scripting interface or in one's `~/.coot` file *e.g.*:

- `(define refmac-exec "/e/refmac-new/bin/refmac5.6.3")`

[37] *i.e.* Coot is idle and ignores all input.

[38] This is not an ideal feature, of course and will be addressed in future.... Digressive Musing: If only computers were fast enough to run Refmac interactively...

After running refmac several times, you may find that you prefer if the new map that refmac creates (after refmac refinement) is the same colour as the previous one (from before this refmac refinement). If so, use:

```
(set-keep-map-colour-after-refmac 1)
```

which will swap the colours of then new and old refmac map so that the post-refmac map has the same colour as the pre-refmac map and the pre-refmac map is coloured with a different colour.

5.32 Running SHELXL

Coot can read shelx `.res` files and write `.ins` files, and thus one can refine using SHELXL in a convenient manner using the function

```
(shelxl-refine imol . hkl-file-name)
```

(the *`hkl-file-name`* is an optional argument)

e.g.

```
(shelxl-refine 0)
```

or

```
(shelxl-refine 0 "insulin.hkl")
```

In the former case, coot will presume that there is a SHELX `hkl` file corresponding to the `res` file that you read in; if there is not coot will print a warning and not try to run shelxl. In the latter case, you can specify the location of the `hkl` file.

After shelxl has finished, coot will automatically read in the resulting `res` coordinates, the `fcf` file, convert the data to `mmCIF` format and read that, which generates a σ_A map and a difference map.

Coot creates a time stamped `ins` file and a time-stamped sym-link to the `hkl` file in the `coot-shelxl` directory.

Please note that the output `ins` file will not be particularly useful (and thus shelxl will fail) if the input file was not in SHELX `ins` format.

There is a GUI for this operation under the "Extensions" menu item.

5.33 Clear Pending Picks

Sometimes one can click on a button[39] unintentionally. This button is there for such a case. It clears the expectation of an atom pick. This works not only for modelling functions, but also geometry functions (such as Distance and Angle).

5.34 Delete

Single atoms or residues can be deleted from the molecule using "Delete..." from the "Model/Fit/Refine"dialog. Pressing this button results in a new dialog, with the options of "Residue" (the default), "Atom" and "Hydrogen Atoms". Now click on an atom in the graphics - the deleted object will be the whole residue of the atom if "Residue" was selected and just that atom if "Atom" was selected. Note that if a residue has an alternative

[39] such that Coot would subsequently expect an atom selection "pick" in the graphics window.

conformation, then "Delete Residue" will delete only the conformation that matches that alternative conformation specifier of the clicked atom.

Only waters are deletable if the "Water" check button is active and waters are not deletable if the "Residue/Monomer" check button is active. This is to reduce mis-clicking.

To rotate the view when in "Delete Mode", use Ctrl left-mouse.

If you want to delete multiple items you can use check the "Keep Delete Active" check-button on this dialog This will will keep the dialog open, ready for deletion of next item.

5.35 Sequence Assignment

You can assign a (FASTA format) sequence to a molecule using:

```
(assign-fasta-sequence imol chain-id fasta-seq)
```

This function has been provided as a precursor to functions that will (as automatically as possible) mutate your current coordinates to one that has the desired sequence. It will be used in automatic side-chain assignment (at some stage in the future).

5.36 Building Links and Loops

Coot can make an attempt to build missing linking regions or loops[40]. This is an area of Coot that needs to be improved, currently O does it much better. We will have several different loop tools here[41]. For now there is `Calculate -> Fit Gap` or the scripting function:

```
(fit-gap imol chain-id start-resno stop-resno)
```

and

```
(fit-gap imol chain-id start-resno stop-resno sequence)
```

the second form will also mutate and try to rotamer fit the provided sequence.

Example usage: let's say for molecule number 0 in chain `"A"` we have residues up to 56 and then a gap after which we have residues 62 and beyond:

```
(fit-gap 0 "A" 57 61 "TYPWS")
```

5.37 Fill Partial Residues

After molecular replacement, the residues of your protein could well have the correct sequence but be chopped back to CG or CB atoms. There is a function to fill such partially-filled residues:

```
(fill-partial-residues imol)
```

This identifies residues with missing atoms, then fills them and does a rotamer fit and real-space refinement.

If you want to fill the side chain of just one residue

```
(fill-partial-residue imol chain-id res-no ins-code)
```

this does a auto-fit-best-rotamer and a refinement on the resulting side-chain position.

[40] the current single function doesn't always perform very well in tests

[41] I suspect that there is not one tool that fits for all.

5.38 Changing Chain IDs

You can change the chain ids of chains using `Calculate -> Change Chain IDs...`. Coot will block an attempt to change the whole of a chain and the target chain id already exists in the molecule.

If you use the "Residue Range" option then you can insert residues with non-conflicting residue number into pre-existing chains.

5.39 Setting Occupancies

As well as the editing "Residue Info" to change occupancies of individual atoms, one can use a scripting function to change occupancies of a whole residue range:

- `(zero-occupancy-residue-range` *`imol chain-id resno-start resno-last`*`)`

  example usage:

  `(zero-occupancy-residue-range 0 "A" 23 28)`

This is often useful to zero out a questionable loop before submitting for refinement. After refinement (with refmac) there should be relatively unbiased density in the resulting 2Fo-Fc-style and difference maps.

Similarly there is a function to reverse this operation:

- `(fill-occupancy-residue-range` *`imol chain-id resno-start resno-last`*`)`

5.40 Fix Nomenclature Errors

Currently this is available only in scripting form:

`(fix-nomenclature-errors` *`imol`*`)`

This will fix atoms nomenclature problems in molecule number *`imol`* according to the same criteria as WATCHECK[42] *e.g.* Chi-2 for Phe, Tyr, Asp, and Glu should be between -90 and 90 degrees. Note that Val and Leu nomenclature errors are also corrected.

5.41 Rotamer Fix Whole Protein

There is an experimental scripting function

`(fit-protein` *`imol`*`)`

which does a auto-fit rotamer and Real Space Refinement for each residue. The graphics follow the refinement.

5.42 Refine All Waters

All the waters in a model can be refined (that is, moved to the local density peak) using

`(fit-waters` *`imol`*`)`

This is a non-interactive function (the waters are moved without user intervention).

[42] R.W.W. Hooft, G. Vriend, C. Sander, E.E. Abola, Errors in protein structures. *Nature* (1996) **381**, 272-272.

5.43 Moving Molecules/Ligands

Often you want to move a ligand (or some such) from wherever it was read in to the position of interest in your molecule (*i.e.* the current view centre). There is a GUI to do this: `Calculate -> Move Molecule Here`.

There are scripting functions available for this sort of thing:

`(molecule-centre imol)`

will tell you the molecule centre of the *imol*th molecule.

`(translate-molecule-by imol x-shift y-shift z-shift)`

will translate all the atoms in molecule *imol* by the given amount (in Ångströms).

`(move-molecule-to-screen-centre imol)`

will move the *imol*th molecule to the current centre of the screen (sometimes useful for imported ligands). Note that this moves the atoms of the molecule - not just the view of the molecule.

5.44 Modifying the Labels on the Model/Fit/Refine dialog

If you don't like the labels "Rotate/Translate Zone" or "Place Atom at Pointer" and rather they said something else, you can change the button names using:

`(set-model-fit-refine-rotate-translate-zone-label "Move Zone")`

and

`(set-model-fit-refine-place-atom-at-pointer "Add Atom")`

6 Map-Related Features

6.1 Maps in General

Maps are "infinite," not limited to pre-calculated volume (the "Everywhere You Click - There Is Electron Density" (EYC-TIED) paradigm) symmetry-related electron density is generated automatically. Maps are easily re-contoured. Simply use the scroll wheel on you mouse to alter the contour level (or `-`/`+` on the keyboard).

Maps follow the molecule. As you recentre or move about the crystal, the map quickly follows. If your computer is not up to re-contouring all the maps for every frame, then use `Draw -> Dragged Map...` to turn off this feature.

6.1.1 Map Reading Bug

Unfortunately, there is a bug in map-reading. If the map is not a bona-fide CCP4 map[1], then coot will crash. Sorry. A fix is in the works but "it's complicated". That's why maps are limited to the extension `".ext"` and `".map"`, to make it less likely a non-CCP4 map is read.

6.2 Create a Map

From MTZ, mmCIF and .phs data use `File -> Open MTZ, CIF or phs...`. You can then choose the MTZ columns for the Fourier synthesis. The button "Expert mode" also adds to the options any anomalous columns you may have in the MTZ file (a -90 degree phase shift will be applied). It also provides the option to apply resolution limits.

From a CCP4 map use `File -> Read Map`. After being generated/read, the map is immediately contoured and centred on the current rotation centre.

6.2.1 Auto-read MTZ file

This function allows Coot to read an MTZ file and make a map directly (without going through the column selection procedure). The default column labels for auto-reading are `"FWT"` and `"PHWT"` for the 2Fo-Fc-style map, `"DELFWT"` and `"PHDELWT"` for the difference map. You can change the column labels that Coot uses for auto-reading - here is an example of how to do that:

`(set-auto-read-column-labels "2FOFCWT" "PHIWT" 0)` `(set-auto-read-column-labels "FOFCWT" "DELPHIWT" 1)`

By default the difference map is created in auto-reading the MTZ file. If you don't want a difference map, you can use the function:

`(set-auto-read-do-difference-map-too 0)`

6.2.2 Reading CIF data

There are several maps that can be generated from CIF files that contain observed Fs, calculated Fs and calculated phases:

- `(read-cif-data-with-phases-fo-alpha-calc` *`cif-file-name`*`)` Calculate an atom map using F_obs and α_calc

[1] *e.g.* it's a directory or a coordinate filename.

- `(read-cif-data-with-phases-2fo-fc` *`cif-file-name`*`)` Calculate an atom map using F_obs, F_calc and α_calc
- `(read-cif-data-with-phases-fo-fc` *`cif-file-name`*`)` Calculate an difference map using F_obs, F_calc and α_calc.

6.2.3 Reading PHS data

There are 2 ways to read data by scripting:

`(read-phs-and-make-map-using-cell-symm` *`phs-file-name space-group-name a b c alpha beta gamma`*`)`

`(read-pdb-and-make-map-with-reso-limits` *`imol-previous phs-file-name reso-limit-low reso-limit-high`*`)`

The first specifies the cell explicitly, and *`alpha, beta`* and *`gamma`* are specified in degrees.

The second form allows the specification of resolution limits and takes the cell and symmetry from a previous molecule (typically a pdb file).

6.3 Map Contouring

Maps can be re-contoured using the middle-mouse scroll-wheel (buttons 4 and 5 in X Window System(TM) terminology). Scrolling the mouse wheel will change the map contour level and the map it redrawn. If you have several maps displayed then the map that has its contour level changed can be set using `HID -> Scrollwheel -> Attach scroll-wheel to which map?`. If there is only one map displayed, then that is the map that has its contour level changed (no matter what the scroll-wheel is attached to in the menu). The level of the electron density is displayed in the top right hand corner of the OpenGL canvas.

Use keyboard `+` or `-` to change the contour level if you don't have a scroll-wheel[2].

If you are creating your map from an MTZ file, you can choose to click on the "is difference map" button on the Column Label selection widget (after a data set filename has been selected) then this map will be displayed in 2 colours corresponding to `+` and `-` the map contour level.

If you read in a map and it is a difference map then there is a checkbutton to tell Coot that.

If you want to tell Coot that a map is a difference map after it has been read, use:

`(set-map-is-difference-map` *`imol`*`)`

where *`imol`* is the molecule number.

By default the change of the contour level is determined from the sigma of the map. You can change this in the map properties dialog or by using the scripting function:

`(set-contour-by-sigma-step-by-mol` *`step on/off? imol`*`)`

where

`step` is the difference in sigma from one level to the next (typically 0.2)

`on/off?` is either 0 (sigma stepping off) or 1 (sigma stepping on)

[2] like I don't on my Mac.

By default the map radius[3] is 10Å. The default increment to the electron density depends on whether or not this is a difference map (0.05 $e^-/\mathring{A}^3$ for a "2Fo-Fc" style map and 0.005 $e^-/\mathring{A}^3$ for a difference map). You can change these using `Edit -> Map Parameters` or by using the "Properties" button of a particular map in the Display Control (Display Manager) window.

6.4 Map Extent

The extent of the map can be set using the GUI (`Edit -> Map Parameters -> Map Radius`) or by using the scripting function, *e.g.*:

```
(set-map-radius 13.2)
```

6.5 Map Contour "Scrolling" Limits

Usually one doesn't want to look at negative contour levels of a map[4], so Coot has by default a limit that stops the contour level going beyond (less than) 0. To remove the limit:

`(set-stop-scroll-iso-map 0)` for a 2Fo-Fc style map

`(set-stop-scroll-diff-map 0)` for a difference map

To set the limits to negative (*e.g.* -0.6) levels:

```
(set-stop-scroll-iso-map-level -0.6)
```

and similarly:

```
(set-stop-scroll-diff-map-level -0.6)
```

where the level is specified in $e^-/\mathring{A}^3$.

6.6 Map Line Width

The width of the lines that describe the density can be changed like this:

```
(set-map-line-width 2)
```

The default line width is 1.

6.7 "Dynamic" Map colouring

By default, maps get coloured according to their molecule number. The starting colour (*i.e.* for molecule 0) is blue. The colour of a map can be changed by `Edit -> Map Colour...` The map colour gets updated as you change the value in the colour selector[5]. Use "OK" to fix that colour.

As subsequent maps are read, they are coloured by rotation round a colour wheel. The default colour map step is 31 degrees. You can change this using:

```
(set-colour-map-rotation-for-map step)
```

[3] actually, it's a box.

[4] in a coot difference map you will get to see the negative level contoured at the inverted level of the positive level, what I mean is that you don't want to see the "positive" level going less than 0.

[5] takes you right back to the good old Frodo days, no?

6.8 Difference Map Colouring

For some strange reason, some crystallographers[6] like to have their difference maps coloured with red as positive and green as negative, this option is for them:

```
(set-swap-difference-map-colours 1)
```

This option will allow the "blue is positive, red is negative" colour scheme on "Edit -> Map Colour".

6.9 Make a Difference Map

Using the "Make a Difference Map" function in the Extensions menu, one can make a difference from two arbitrary maps. The maps need not be on the same griding, or in the same space group even. The resulting map will be on the same griding and space group as the "Reference" map.

6.10 Make an Averaged Map

There is a scripting interface to the generation of map averages. As above, the maps need not be on the same grid or in the same space group. The resulting map will have the same gridding and space group as the first map in the list. Typical usage:

```
(average-map '((1 1.0) (2 1.0))))
```

The argument to `(average-map` is a list of lists, each list element is a list of the map number and a weighting factor (1.0 in this case).

6.11 Map Sampling

By default, the Shannon sampling factor is the conventional 1.5. Use larger values (`Edit -> Map Parameters -> Sampling Rate`) for smoother maps[7].

This value can be set by the scripting command

```
(set-map-sampling-rate 2.5)
```

6.12 Dragged Map

By default, the map is re-contoured at every frame during a drag (Ctrl Left-mouse). Sometimes this can be annoyingly slow and jerky so it is possible to turn it off: `Draw -> Dragged Map -> No`.

To change this by scripting:

```
(set-active-map-drag-flag 0)
```

6.13 Dynamic Map Sampling and Display Size

If activated (`Edit -> Map Parameters -> Dynamic Map Sampling`) the map will be re-sampled on a more coarse grid when the view is zoomed out. If "Display Size" is also activated, the box of electron density will be increased in size also. In this way, you can see electron density for big maps (many unit cells) and the graphics still remain rotatable.

[6] Jan Dohnalek, for instance.

[7] a value of 2.5 is often sufficient.

If you want to have these functions active for all maps, add the following to your initialization file Section 3.10.2 [Scheme], page 12:

```
(set-dynamic-map-sampling-on) (set-dynamic-map-size-display-on)
```

6.14 Skeletonization

The skeleton (also known as "Bones"[8]) can be displayed for any map. A map can be skeletonized using `Calculate -> Map Skeleton...`. Use the option menu to choose the map and click "On" then "OK" to the generate the map (the skeleton is off by default).

The level of the skeleton can be changed by using `Edit -> Skeleton Parameters... -> Skeletonization Level...` and corresponds to the electron density level in the map. By default this value is 1.2 map standard deviations. The amount of map can be changed using `Edit -> Skeleton Parameters... -> Skeleton Box Radius...`[9]. The units are in Ångströms, with 40 as the default value.

The skeleton is often recalculated as the screen centre changes - but not always since it can be an irritatingly slow calculation. If you want to force a regeneration of the displayed skeleton, simply centre on an atom (using the middle mouse button) or press the S key.

6.15 Map Sharpening

It can be educational (even useful at lower resolutions) to sharpen or blur a map. This can be achieved with the sharpening tool `Calculate -> Map Sharpening...`. By default, the maximum and minimum sharpness is +/- $200\AA^2$, this can be changed (in this case to 300) using:

```
(set-map-sharpening-scale-limit 300)
```

This currently only works on maps created by reading an MTZ (or other) reflection data file.

6.16 Pattersons

Pattersons can be generated using the `make-and-draw-patterson` function. Example usage:

(`make-and-draw-patterson` *`mtz-file-name f-col sig-f-col`*)

where *`use-weights-flag`* is either `0` or `1`.

e.g.

```
(make-and-draw-patterson "native.mtz" "FP_nat" "SIGFP_nat")
```

6.17 Map Re-Interpolation

Maps can be re-interpolated to match a reference map.

(`reinterp-map` *`map-no reference-map-no`*)

will create a copy of *`map-no`* in the same cell, spacegroup and grid spacing as the *`reference-map-no`* map.

[8] If you're living in Sweden... or Captain Kirk, that is.

[9] you may think it strange that a box has a radius, this is an idiosyncrasy of Coot.

6.18 Masks

A map can be masked by a set of coordinates. Use the scripting function:

`(mask-map-by-molecule imol-map imol-model invert-mask?)`

If *invert-mask?* is 0, this will create a new map that has density only where there are no (close) coordinates. If *invert-mask?* is 1 then the map density values will be set to zero everywhere *except* close to the atoms of molecule number *imol-model*.

The radius of the mask around each atom is 2.0Å by default. You can change this using:

`(set-map-mask-atom-radius radius)`

There is a GUI interface to Map Masking under the Extensions menu.

6.18.1 Example

If one wanted to show just the density around a ligand:

1. Make a pdb file the contains just the ligand and read it in to Coot - let's say it is molecule 1 and the ligand is residue 3 of chain "L".
2. Get a map that covers the ligand (*e.g.* from refmac). Let's say this map is molecule number 2.
3. Mask the map:

   `(mask-map-by-molecule 2 1 1)`

   This creates a new map. Turn the other maps off, leaving only the masked map.

To get a nice rendered image, press F8 (see Section Section 3.6 [Raster3D], page 10).

6.19 Trimming

If you want to remove all the atoms[10] that lie "outside the map" (*i.e.* in low density) you can use

`(trim-molecule-by-map imol-coords imol-map density-level delete/zero-occ?)`

where *delete/zero-occ?* is `0` to remove the atoms and `1` to set their occupancy to zero.

There is a GUI interface for this feature under the "Extensions" menu item.

6.20 Map Transformation

If you want to transform a map, you can do it thusly:

`(transform-map imol rotation-matrix trans point radius)`

where:

rotation-matrix is a 9-membered list of numbers for an orthogonal rotation matrix.

trans is a 3-membered list of numbers (distances in Ångstöms).

point is a 3-membered list of numbers (centre point in Ångstöms).

radius is a single number (also in Ångstöms).

This applies the rotation *rotation-matrix* and a translation *trans* to a map fragment, so that when the transformation is applied the centre of the new map is at *point*.

[10] or set their occupancy to zero

Example usage:

`(transform-map 2 '(1 0 0 0 1 0 0 0 1) '(0 0 1) (rotation-centre) 10)`

which transforms map number 2 by a translation of 1Å along the Z axis, centred at the screen centre for 10Å around that centre.

Here's a more real-world example:

Let's say we want to tranform the density over the "B" molecule to a position over the "A" molecule. First we do a LSQ transformation to get the rotation and translation that moves the "B" coordinates over the "A" coordinates:

In the terminal output we get:

```
|    0.9707,    0.2351,   0.05033|
|  -0.04676,      0.39,   -0.9196|
|   -0.2358,    0.8903,    0.3896|
(    -33.34,     21.14,     18.82)
```

The centre of the "A" molecule is at (58.456, 5.65, 11.108). So we do:

`(transform-map 3 (list 0.9707 0.2351 0.05033 -0.04676 0.39 -0.9196 -0.2358 0.8903 0.3896) (list -33.34 21.14 18.82) (list 58.456 5.65 11.108) 8)`

Which creates a map over the middle of the "A" molecule. Note that using a too high *radius* can cause overlap problems, so try with a small *radius* (*e.g.* 5.0) if the resulting map looks problematic.

Alternatively, instead of typing the whole matrix, you can use a coordinates least-squares fit to generate the matrix for you. `(transform-map-using-lsq-matrix)` does just that.

Heres how to use it:

`(transform-map-using-lsq-matrix` *imol-ref ref-chain ref-resno-start ref-resno-end imol-mov mov-chain mov-resno-start mov-resno-end imol-map about-pt radius*`)`

Hopefully the arguments are self explanatory (*ref* refers to the reference molecule, of course and *about-pt* is a 3-number list such as is returned by `(rotation-centre)`).

We can now export that map, if we want.

6.21 Export Map

You can write out a map from Coot (e.g. one from NCS averaging, or masking or general transformation) using the export map function:

`(export-map` *imol filename*`)`

e.g.

`(export-map 4 "ncs-averaged.map")`

7 Validation

The validation functions are still being added to from time to time. In future there will be more functions, particularly those that will interface to other programs.

7.1 Ramachandran Plots

Ramachandran plots are "dynamic". When you edit the molecule (*i.e.* move the coordinates of some of atoms) the Ramachandran plot gets updated to reflect those changes. Also the underlying ϕ/ψ probability density changes according to the selected residue type (*i.e.* the residue under the mouse in the plot). There are 3 different residue types: GLY, PRO, and not-GLY-or-PRO[1].

When you mouse over a representation of a residue (a little square or triangle[2]) the residue label pops up. The residue is "active" *i.e.* it can be clicked. The "graphics" view changes so that the Cα of the selected residue is centred. In the Ramachandran plot window, the current residue is highlighted by a green square.

The underlying distributions are taken from the Richardson's Top500 structures `http://kinemage.biochem.duke.edu/databases/top500.php`.

The probability levels for acceptable (yellow) and preferred (red) are 0.2% and 2% respectively.

You can change the contour levels:

```
(set-ramachandran-plot-contour-levels 0.025 0.003)
```

You can change the "blocksize" (the default is 10 degrees) of the contours using

```
(set-ramachandran-plot-background-block-size 5)
```

These comes into effect when a new plot is created (it doesn't change plots currently displayed).

7.2 Geometry Analysis

A restraints-based geometry analysis of the molecule. The distortion is weighted by atom occupancy. The distortion of the geometry due to links is shared between the contributing residues.

Note that only the first model of a multi-model molecule is analysed.

7.3 Chiral Volumes

The dictionary is used to identify the chiral atoms of each of the model's residues. A clickable list is created of atoms whose chiral volume in the model is of a different sign to that in the dictionary.

During refinement and regularization, Coot will pop-up dialogs warning about chiral volume errors - if you have them. This can be annoying[3]. You can inhibit this dialog like this:

```
(set-show-chiral-volume-errors-dialog 0)
```

[1] the not-GLY-or-PRO is the most familiar Ramachandran plot.

[2] prolines have a grey outline rather than a black one, triangles are glycines.

[3] but that's partly the idea, I suppose.

7.3.1 Fixing Chiral Volume Errors

There are two obvious ways:

1) mutate and auto-fit rotamer (mutate it to the residue type that it is)

2) RS Refine the residue and invert the chiral centre by pulling an atom. Usually you can pull the CA to the other side of the plane made by the chiral neighbouring atoms (using ctrl left-click). Sometimes giving the CB a good old tweak is the easier way.

Inverting the CB of THR is easier, just move the OG so that the plane of the neighbours is on the other side of the CB (again with ctrl left-click).

7.4 Blobs: a.k.a. Unmodelled density

This is an interface to the Blobs dialog. A map and a set of coordinates that model the protein are required.

A blob is region of relatively high residual election density that cannot be explained by a simple water. So, for example, sulfates, ligands, mis-placed sidechains or unbuilt terminal residues might appear as blobs. The blobs are in order, the biggest[4] at the top.

7.5 Difference Map Peaks

This is one of the fastest ways to validate a model and its data (presuming that the difference map comes from a post-refinement mFo-DFc map). It highlights regions where the model and the data do not agree.

Lesser peaks within a certain distance (by default, 2.0Å) of a large peak are not shown. This cuts down on the number of times one is navigated to a particular region because of ripple or other noise peaks around a central peak.

This value can be queried:

```
(difference-map-peaks-max-closeness)
```

and adjusted:

```
(set-difference-map-peaks-max-closeness 0.1)
```

7.6 Check Waters by Difference Map

Sometimes waters can be misplaced - taking the place of sidechains or ligands or crystallization agents such as phosphate for example[5]. In such cases the variance of the difference map can be used to identify these problems.

This function is also useful to check anomalous maps. Often waters are placed in density that is really a something else, perhaps a cation, anion, sulphate or a ligand. If such an atom diffracts anomalously this can be identified and corrected.

By default the waters with a map variance greater than 3.5σ are listed. One can be more rigorous by using a lower cut-off:

```
(set-check-waters-by-difference-map-sigma-level 3.0)
```

The scripting interface is:

[4] and therefore most interesting

[5] or the water should be more properly modelled as anistrotropic or a split partial site

`(check-waters-by-difference-map imol-coords imol-diff-map)`

where *imol-coords* is the molecule number of the coordinates that contain the waters to be checked

imol-diff-map is the molecule number of the difference map (it must be a difference map, not an "ordinary" map). This difference map must have been calculated using the waters. So there is no point in doing this check immediately after "Find Waters". You will need to run Refmac or some other refinement first first[6].

7.7 Molprobity Tools Interface

The molprobity tools '`probe`' and '`reduce`' have been interfaced into Coot (currently, the interface is not as slick as it might be). However, the tools are useful and can be used in the following way:

first we need to tell Coot where to find the relevant executables (typically you would add the following lines to you '`~/.coot`' file):

```
(define *probe-command* "/path/to/probe/executable")
(define *reduce-command* "/path/to/reduce/executable")
```

now the probe hydrogens and probe dots can be generated using `Validate -> Probe Clashes` (or in the Scripting Window):

`(probe imol)`

where *imol* is the molecule number of coordinates to be probed. A new molecule with Hydrogens is created (by '`reduce`') and read in.

By default Coot creates a new molecule for the molecule that now has hydrogens. To change this:

`(set! reduce-molecule-updates-current #t)`

and that, as you can guess, replaces, rather than adds to the "probed" molecule.

This gives a "static" view of the molecule's interactions.

To get a dynamic view (which is currently only enabled on rotating chi angles) add these to your '`~/.coot`' file:

`(set-do-probe-dots-on-rotamers-and-chis 1)`

To get a semi-static view (dots are regenerated in the region of zone after a "Real Space Refinement"):

`(set-do-probe-dots-post-refine 1)`

7.8 GLN and ASN B-factor Outliers

It is often difficult to detect by eye the correct orientation of the amino-carbonylo group of GLN and ASNs. However, we can use (properly refined) temperature factors to detect outliers. We take the Z value as half the difference between the B-factor of the NE2 and OE1 divided by the standard deviation of the B-factors of the rest of the residue. An analysis of GLNs and ASNs of high resolutions structures indicates that a Z value of greater than 2.25 indicates a potential (if not probable) flip. A "Fix" button is provided in the resultant dialog make this easy to do.

[6] and remember to check the difference map button in the "Run Refmac" dialog

This analysis was added after discussions with Atsushi Nakagawa and so is called "Nakagawa's Bees".

The analysis does not check residues with multiple conformations.

7.9 Validation Graphs

Coot provides several graphs that are useful for model validation (on a residue by residue basis): residue density fit, geometry distortion, temperature factor variance, peptide distortion and rotamer analysis.

7.9.1 Residue Density Fit

The density fit graph shows the density fit for residues. The score is the average electron density level at the atom centres of the atoms in the residue. The height of the blocks is inversely proportional to the density average.

The residue density fit is by default scaled to a map that is calculated on the absolute scale. Sometimes you might be using a map with density levels considerably different to this, which makes the residue density fit graph less useful. To correct for this you can use the scripting function:

`(set-residue-density-fit-scale-factor` *`factor`*`)`

where *`factor`* would be $1/(4 * rmd_{map})$ (as a rule of thumb).

`(residue-density-fit-scale-factor)` returns the current scale factor (default 1.0).

There is also a GUI to this:

`Extensions -> Refine... -> Set Density Fit Graph Weight...`

7.9.2 Rotamer Analysis

Residue rotamers are scored according to the prior likelihood. Note that when CD1 and CD2 of a PHE residue are exchanged (simply a nomenclature error) this can lead to large red blocks in the graph (apparently due to very unlikely rotamers). There are several other residues that can have nomenclature errors like this. To fix these problems use

`(fix-nomenclature-errors` *`imol`*`)`

7.9.3 Temperature Factor Variance

This idea is from Eleanor Dodson, who liked to use the standard deviation of a residue's temperature factors to highlight regions of questionable structure.

Note that Hydrogens are ignored in this analysis.

7.9.4 Peptide Omega Angle Distortion

Some variability of the ω is to be expected in the peptide bond. But not too much. Anything more than 13 degrees is suspicicous. Unexpected peptide bonds show up red by default. If cis peptides *are* to be expected, and should not marked as bad, then you can tell this to Coot using:

`Edit -> Preferences -> Geometry -> Cis-Peptides -> No`

8 Representation

8.1 Surfaces

Coot uses the surface code from Gruber and Noble (2004).

Coot uses the partial charges of the atoms (the *partial_charge* field in the *_chem_comp_atom* block) from the charge dictionary item in the refmac (or other) cif dictionary. However, partial charges are only used under certain conditions

1) the molecule consists of less than 100 atoms

or

2) the number of atoms in the molecule that are hydrogens is at least 15% of the total number of atoms in the molecule

If partial charges are not used, then the fall-back is to use charges from side-chains charged at physiological pH (Arg, Lys, Asp, Glu).

9 Hints and Usage Tips

9.1 Documentation

This manual is on the web where it can be searched:

- `http://www.biop.ox.ac.uk/coot/doc/user-manual.html` monolithic version
- `http://www.biop.ox.ac.uk/coot/doc/chapters/user-manual_toc.html` which is split into sections

In the Menu item "About", under "Online Docs URL..." there is a entry bar that can be used to search the Coot documentation via Google. The results are returned as a web page in web browser. The browser type can be specified as in this example:

```
(set-browser-interface "firefox")
```

Example usage can be found in '`xxx/share/coot/scheme/group-settings.scm`'

9.2 Low Resolution

Building structures using low resolution data is a pain. We hope to make it less of a pain in future, but there are some things that you can do now.

- [Add Planar Peptide Restraints] Add restraints via scripting command
- [Use Secondary Structure Restraints] where appropriate under Refinement Control
- [Check Chirals] Check Chiral Volumes regularly
- [Change the Weighing Scheme] `(set-matrix 20.0)` [Default is 60, the lower the number the more the geometry is idealised]

9.3 Coot Droppings

This describes the files and directory that coot leaves behind after it has been fed (sorry, I mean "used"). Everything except the `0-coot.state.scm` state file can comfortably be deleted if needed after coot has finished.

You can stop the state and history files being written if you start coot with the `--no-guano` option.

- `0-coot.state.scm` The most important file. This contains the state of coot when you last exited. It contains things like which molecules were read, the maps, the colours of the molecules and map, the screen centre, map size and so on. When restarting a coot session, this file should usually be used.
- `0-coot-history.scm` The history of coot commands you used in your last coot session in scheme format. Incomplete history. One day this will be a complete history of the session suitable for uploading into a database describing the model modification.
- `0-coot-history.py` The history of coot commands you used in your last coot session in python format.
- `coot-download` directory where the files downloaded from the network (e.g. from the EBI and EDS) go.
- `coot-backup` Each model modification generates the saving of coordinates as a pdb file in this directory.

- `coot-refmac` When running REFMAC using the Coot interface, the input to refmac and the output go in this directory.
- `coot-molprobity` When running Molprobity's Probe and Reduce using the Coot interface, the input and output go in this directory.

9.4 Clearing Backups

Coot will occasionally ask you to clear up the '`coot-backup`' directory. You can adjust the behaviour in a number of ways:

- `(define *clear-out-backup-run-n-days* 3)` will run the backup clearance every 3 days (the default is every 7).
- `(define *clear-out-backup-old-days* 1)` will clear out files older then 1 day (rather than the default 7 days).
- You can create your own version of the function that is run on exiting Coot: `(clear-backups-maybe)`

So, if you wanted to clear out everything more than 1 day old, every time, without Coot asking you about it:

```
(define *clear-out-backup-run-n-days* 0)
(define *clear-out-backup-old-days* 1)
(define (clear-backups-maybe)
  (delete-coot-backup-files 'delete)
  (coot-real-exit 0))
```

9.5 Getting out of "Translate" Mode

If you get stuck in "translate" mode in the GL canvas (*i.e.* mouse does not rotate the view as you would expect) simply press and release the Ctrl key to return to "rotate" mode.

9.6 Getting out of "Continuous Rotation" Mode

The keyboard I key toggles the "continuous rotation" mode. The menu item `Draw -> Spin View On/Off` does the same thing.

9.7 Getting out of "Label Atom Only" Mode

Similarly, if you are stuck in a mode where the "Model/Fit/Refine" buttons don't work (the atoms are not selected, only the atom gets labelled), press and release the Shift key.

9.8 Button Labels

Button labels ending in "..." mean that a new dialog will pop-up when this button is pressed.

9.9 Picking

Note that left-mouse in the graphics window is used for both atom picking and rotating the view, so try not to click over an atom when trying to rotate the view when in atom selection mode.

9.10 Resizing View

Click and drag using right-mouse (up and down or left and right) to zoom in and out.

9.11 Scroll-wheel

To change the map to which the scroll-wheel is attached, use the scroll check button in the Display Manager or use `HID -> Scrollwheel -> Attach Scrollwheel to which map?`

9.12 Slow Computer Configuration

Several of the parameters of Coot are chosen because they are reasonable on my "middle-ground" development machine. However, these parameters can be tweaked so that slower computers perform better:

- `(set-use-stroke-characters 1) ; default is to use bitmap characters`
- `(set-smooth-scroll-steps 8) ; default 40`
- `(set-smooth-scroll-limit 30) ; Angstroms`
- `(set-residue-selection-flash-frames-number 3);`
- `(set-skeleton-box-size 20.0) ; A (default 40).`
- `(set-active-map-drag-flag 0) ; turn off recontouring every step`
- `(set-idle-function-rotate-angle 1.5) ; continuous spin speed`

10 Other Programs

10.1 findligand

`findligand` is a stand-alone command-line program that uses the libraries of Coot.

`findligand` provides a number of command line arguments for increased flexibility:

- `--pdbin` *`pdb-in-filename`*

  where *`pdb-in-filename`* is the protein (typically)
- `--hklin` *`mtz-filename`*
- `--f` *`f_col_label`*
- `--phi` *`phi_col_label`*
- `--clusters` *`nclust`*

  where *`nclust`* is the number of density clusters (potential ligand sites) to search for
- `--sigma` *`sigma-level`*

  where *`sigma-level`* the density level (in sigma) above which the map is searched for ligands
- `--fit-fraction` *`frac`*

  where *`frac`* is the minimum fraction of atoms in density allowed after fit [default 0.75]
- `--flexible`

  means use torsional conformation ligand search
- `--samples` *`nsamples`*

  `nsamples` is the number of flexible conformation samples [default 30]
- `--dictionary` *`cif-dictionary-name`*

  the file containing the CIF ligand dictionary description

One uses `findligand` like this:

```
$ findligand various-args ligand-pdb-file-name(s)
```

i.e. the example ligand pdb files that you wish to search for are given at the end of the command line.

11 Scripting Functions

11.1 Startup Functions

11.1.1 set-prefer-python

`set-prefer-python` [function]

tell coot that you prefer to run python scripts if/when there is an option to do so.

11.1.2 prefer-python

`prefer-python` [function]

the python-prefered mode.

This is available so that the scripting functions know whether on not to put themselves onto in as menu items.

If you consider using this, consider in preference use_gui_qm == 2, which is used elsewhere to stop python functions adding to the gui, when guile-gtk functions have alread done so. We should clean up this (rather obscure) interface at some stage.

return 1 for python is prefered, 0 for not.

11.2 File System Functions

11.2.1 make-directory-maybe

`make-directory-maybe` *dir* [function]

Where *dir* is a string

make a directory dir (if it doesn't exist) and return error code

If it can be created, create the directory dir, return the success status like mkdir: mkdir

Returns: zero on success, or -1 if an error occurred. If dir already exists as a directory, return 0 of course.

11.2.2 set-show-paths-in-display-manager

`set-show-paths-in-display-manager` *i* [function]

Where *i* is an integer number

Show Paths in Display Manager?

Some people don't like to see the full path names in the display manager here is the way to turn them off, with an argument of 1.

11.2.3 show-paths-in-display-manager-state

`show-paths-in-display-manager-state` [function]

return the internal state

What is the internal flag?

Returns: 1 for "yes, display paths" , 0 for not

11.2.4 add-coordinates-glob-extension

`add-coordinates-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as coordinate files

11.2.5 add-data-glob-extension

`add-data-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as data (reflection) files

11.2.6 add-dictionary-glob-extension

`add-dictionary-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as geometry dictionary files

11.2.7 add-map-glob-extension

`add-map-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as geometry map files

11.2.8 remove-coordinates-glob-extension

`remove-coordinates-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as coordinate files

11.2.9 remove-data-glob-extension

`remove-data-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as data (reflection) files

11.2.10 remove-dictionary-glob-extension

`remove-dictionary-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as geometry dictionary files

11.2.11 remove-map-glob-extension

`remove-map-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as geometry map files

11.2.12 set-sticky-sort-by-date

`set-sticky-sort-by-date` [function]

sort files in the file selection by date?

some people like to have their files sorted by date by default

11.2.13 unset-sticky-sort-by-date

`unset-sticky-sort-by-date` [function]

do not sort files in the file selection by date?

removes the sorting of files by date

11.2.14 set-filter-fileselection-filenames

`set-filter-fileselection-filenames` *istate* [function]

Where *istate* is an integer number

on opening a file selection dialog, pre-filter the files.

set to 1 to pre-filter, [0 (off, non-pre-filtering) is the default

11.2.15 filter-fileselection-filenames-state

`filter-fileselection-filenames-state` [function]

, return the state of the above variable

11.2.16 file-type-coords

`file-type-coords` *file_name* [function]

Where *file_name* is a string

is the given file name suitable to be read as coordinates?

11.2.17 open-coords-dialog

`open-coords-dialog` [function]

display the open coordinates dialog

11.2.18 set-file-chooser-selector

`set-file-chooser-selector` *istate* [function]

Where *istate* is an integer number

this flag set chooser as default for windows, otherwise use selector 0 is selector 1 is chooser

11.3 Widget Utilities

11.3.1 set-main-window-title

`set-main-window-title` *s* [function]

Where *s* is a string

set the main window title.

function added for Lothar Esser

11.4 MTZ and data handling utilities

11.4.1 manage-column-selector

`manage-column-selector` *filename* [function]

Where *filename* is a string

given a filename, try to read it as a data file

We try as .phs and .cif files first

11.5 Molecule Info Functions

11.5.1 chain-n-residues

`chain-n-residues` *chain_id imol* [function]

Where:

- *chain_id* is a string
- *imol* is an integer number

the number of residues in chain chain_id and molecule number imol

Returns: the number of residues

11.5.2 seqnum-from-serial-number

`seqnum-from-serial-number` *imol chain_id serial_num* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *serial_num* is an integer number

a residue seqnum (normal residue number) from a residue serial number

Returns: < -9999 on failure

11.5.3 insertion-code-from-serial-number

`insertion-code-from-serial-number` *imol chain_id serial_num* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *serial_num* is an integer number

the insertion code of the residue.

Returns: NULL (scheme False) on failure.

11.5.4 n-models

`n-models` *imol* [function]

Where *imol* is an integer number

the chain_id (string) of the ichain-th chain molecule number imol

return the number of models in molecule number imol

useful for NMR or other such multi-model molecules.

return the number of models or -1 if there was a problem with the given molecule.

Returns: the chain-id

11.5.5 n-chains

`n-chains` *imol* [function]

Where *imol* is an integer number

number of chains in molecule number imol

Returns: the number of chains

11.5.6 is-solvent-chain-p

`is-solvent-chain-p` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

is this a solvent chain? [Raw function]

This is a raw interface function, you should generally not use this, but instead use (is-solvent-chain? imol chain-id)

This wraps the mmdb function isSolventChain().

Returns: -1 on error, 0 for no, 1 for is "a solvent chain". We wouldn't want to be doing rotamer searches and the like on such a chain.

11.5.7 is-protein-chain-p

`is-protein-chain-p` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

is this a protein chain? [Raw function]

This is a raw interface function, you should generally not use this, but instead use (is-protein-chain? imol chain-id)

This wraps the mmdb function isAminoacidChain().

Returns: -1 on error, 0 for no, 1 for is "a protein chain". We wouldn't want to be doing rotamer searches and the like on such a chain.

11.5.8 is-nucleotide-chain-p

`is-nucleotide-chain-p` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

is this a nucleic acid chain? [Raw function]

This is a raw interface function, you should generally not use this, but instead use (is-nucleicacid-chain? imol chain-id)

This wraps the mmdb function isNucleotideChain(). For completeness.

Returns: -1 on error, 0 for no, 1 for is "a nucleicacid chain". We wouldn't want to be doing rotamer searches and the like on such a chain.

11.5.9 n-residues

`n-residues` *imol* [function]

Where *imol* is an integer number

return the number of residues in the molecule,

return -1 if this is a map or closed.

11.5.10 sort-chains

`sort-chains` *imol* [function]

Where *imol* is an integer number

return a list of the remarks of hte molecule number imol

sort the chain ids of the imol-th molecule in lexographical order

11.5.11 sort-residues

`sort-residues` *imol* [function]

Where *imol* is an integer number

sort the residues of the imol-th molecule

11.5.12 remarks-dialog

`remarks-dialog` *imol* [function]

Where *imol* is an integer number

a gui dialog showing remarks header info (for a model molecule).

11.5.13 print-header-secondary-structure-info

`print-header-secondary-structure-info` *imol* [function]

Where *imol* is an integer number

simply print secondardy structure info to the terminal/console. In future, this could/should return the info.

11.5.14 copy-molecule

`copy-molecule` *imol* [function]

Where *imol* is an integer number

copy molecule imol

Returns: the new molecule number. Return -1 on failure to copy molecule (out of range, or molecule is closed)

11.5.15 add-ligand-delete-residue-copy-molecule

`add-ligand-delete-residue-copy-molecule` *imol_ligand_new chain_id_ligand_new resno_ligand_new imol_current chain_id_ligand_current resno_ligand_current* [function]

Where:

- *imol_ligand_new* is an integer number
- *chain_id_ligand_new* is a string
- *resno_ligand_new* is an integer number
- *imol_current* is an integer number
- *chain_id_ligand_current* is a string
- *resno_ligand_current* is an integer number

Copy a molecule with addition of a ligand and a deletion of current ligand.

This function is used when adding a new (modified) ligand to a structure. It creates a new molecule that is a copy of the current molecule except that the new ligand is added and the current ligand/residue is deleted.

11.5.16 exchange-chain-ids-for-seg-ids

`exchange-chain-ids-for-seg-ids` *imol* [function]

Where *imol* is an integer number

Experimental interface for Ribosome People.

Ribosome People have many chains in their pdb file, they prefer segids to chainids (chainids are only 1 character). But coot uses the concept of chain ids and not seg-ids. mmdb allow us to use more than one char in the chainid, so after we read in a pdb, let's replace the chain ids with the segids. Will that help?

11.5.17 show-remarks-browswer

`show-remarks-browswer` [function]

show the remarks browser

11.6 Library and Utility Functions

11.6.1 git-revision-count

`git-revision-count` [function]

return the git revision count for for this build.

11.6.2 svn-revision

`svn-revision` [function]

an alias to git_revision_count() for backwards compatibility

11.6.3 molecule-name

`molecule-name` *imol* [function]

Where *imol* is an integer number

return the name of molecule number imol

Returns: 0 if not a valid name (-> False in scheme) e.g. "/a/b/c.pdb" for "d/e/f.mtz FWT PHWT"

11.6.4 set-molecule-name

`set-molecule-name` *imol new_name* [function]

Where:

- *imol* is an integer number
- *new_name* is a string

set the molecule name of the imol-th molecule

11.6.5 coot-real-exit

`coot-real-exit` *retval* [function]

Where *retval* is an integer number

exit from coot, give return value retval back to invoking process.

11.6.6 coot-no-state-real-exit

`coot-no-state-real-exit` *retval* [function]

Where *retval* is an integer number

exit without writing a state file

11.6.7 coot-clear-backup-or-real-exit

`coot-clear-backup-or-real-exit` *retval* [function]

Where *retval* is an integer number

exit coot doing clear-backup maybe

11.6.8 coot-save-state-and-exit

`coot-save-state-and-exit` *retval save_state_flag* [function]

Where:

- *retval* is an integer number
- *save_state_flag* is an integer number

exit coot, write a state file

11.6.9 first-coords-imol

`first-coords-imol` [function]

What is the molecule number of first coordinates molecule?

return -1 when there is none.

11.6.10 first-small-coords-imol

`first-small-coords-imol` [function]

molecule number of first small (<400 atoms) molecule.

return -1 on no such molecule

11.6.11 first-unsaved-coords-imol

`first-unsaved-coords-imol` [function]

What is the molecule number of first unsaved coordinates molecule?

return -1 when there is none.

11.6.12 mmcif-sfs-to-mtz

`mmcif-sfs-to-mtz` *cif_file_name mtz_file_name* [function]

Where:

- *cif_file_name* is a string
- *mtz_file_name* is a string

convert the structure factors in cif_file_name to an mtz file.

Return 1 on success. Return 0 on a file without Rfree, return -1 on complete failure to write a file.

11.7 Graphics Utility Functions

11.7.1 set-do-anti-aliasing

`set-do-anti-aliasing` *state* [function]

Where *state* is an integer number

set the bond lines to be antialiased

11.7.2 do-anti-aliasing-state

`do-anti-aliasing-state` [function]

return the flag for antialiasing the bond lines

11.7.3 set-do-GL-lighting

`set-do-GL-lighting` *state* [function]

Where *state* is an integer number

turn the GL lighting on (state = 1) or off (state = 0)

slows down the display of simple lines

11.7.4 do-GL-lighting-state

`do-GL-lighting-state` [function]

return the flag for GL lighting

11.7.5 use-graphics-interface-state

`use-graphics-interface-state` [function]

shall we start up the Gtk and the graphics window?

if passed the command line argument

no-graphics, coot will not start up gtk itself.

An interface function for Ralf.

11.7.6 python-at-prompt-at-startup-state

`python-at-prompt-at-startup-state` [function]

is the python interpreter at the prompt?

Returns: 1 for yes, 0 for no.

11.7.7 start-graphics-interface

`start-graphics-interface` [function]

start Gtk (and graphics)

This function is useful if it was not started already (which can be achieved by using the command line argument

no-graphics).

An interface for Ralf

11.7.8 reset-view

`reset-view` [function]

"Reset" the view

return 1 if we moved, else return 0.

centre on last-read molecule with zoom 100. If we are there, then go to the previous molecule, if we are there, then go to the origin.

11.7.9 graphics-n-molecules

`graphics-n-molecules` [function]

return the number of molecules (coordinates molecules and map molecules combined) that are currently in coot

Returns: the number of molecules (closed molecules are not counted)

11.7.10 toggle-idle-spin-function

`toggle-idle-spin-function` [function]

Spin spin spin (or not)

11.7.11 toggle-idle-rock-function

`toggle-idle-rock-function` [function]

Rock (not roll) (self-timed)

11.7.12 set-rocking-factors

`set-rocking-factors` *width_scale frequency_scale* [function]

Where:

- *width_scale* is a number
- *frequency_scale* is a number

Settings for the inevitable discontents who dislike the default rocking rates (defaults 1 and 1)

11.7.13 set-idle-function-rotate-angle

`set-idle-function-rotate-angle` *f* [function]

Where *f* is a number

how far should we rotate when (auto) spinning? Fast computer? set this to 0.1

11.7.14 idle-function-rotate-angle

`idle-function-rotate-angle` [function]

what is the idle function rotation angle?

11.7.15 handle-read-draw-molecule

`handle-read-draw-molecule` *filename* [function]

Where *filename* is a string

a synonym for read-pdb. Read the coordinates from filename (can be pdb, cif or shelx format)

11.7.16 allow-duplicate-sequence-numbers

`allow-duplicate-sequence-numbers` [function]

enable reading PDB/pdbx files with duplicate sequence numbers

11.7.17 set-convert-to-v2-atom-names

`set-convert-to-v2-atom-names` *state* [function]

Where *state* is an integer number

shall we convert nucleotides to match the old dictionary names?

Usually (after 2006 or so) we do not want to do this (given current Coot architecture). Coot should handle the residue synonyms transparently.

default off (0).

11.7.18 handle-read-draw-molecule-with-recentre

`handle-read-draw-molecule-with-recentre` *filename recentre_on_read_pdb_flag* [function]

Where:

- *filename* is a string
- *recentre_on_read_pdb_flag* is an integer number

read coordinates from filename with option to not recentre.

set recentre_on_read_pdb_flag to 0 if you don't want the view to recentre on the new coordinates.

11.7.19 handle-read-draw-molecule-and-move-molecule-here

`handle-read-draw-molecule-and-move-molecule-here` *filename* [function]

Where *filename* is a string

read coordinates from filename and recentre the new molecule at the screen rotation centre.

11.7.20 read-pdb

`read-pdb` *filename* [function]

Where *filename* is a string

read coordinates from filename

11.7.21 assign-hetatms

`assign-hetatms` *imol* [function]

Where *imol* is an integer number

some programs produce PDB files with ATOMs where there should be HETATMs. This is a function to assign HETATMs as per the PDB definition.

11.7.22 hetify-residue

`hetify-residue` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

if this is not a standard group, then turn the atoms to HETATMs.

Return 1 on atoms changes, 0 on not. Return -1 if residue not found.

11.7.23 residue-has-hetatms

`residue-has-hetatms` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

residue has HETATMs?

return 1 if all atoms of the specified residue are HETATMs, else, return 0. If residue not found, return -1.

11.7.24 het-group-n-atoms

`het-group-n-atoms` *comp_id* [function]

Where *comp_id* is a string

return the number of non-hydrogen atoms in the given het-group (comp-id).

Return -1 on comp-id not found in dictionary.

11.7.25 replace-fragment

`replace-fragment` *imol_target imol_fragment atom_selection* [function]

Where:

- *imol_target* is an integer number
- *imol_fragment* is an integer number
- *atom_selection* is a string

replace the parts of molecule number imol that are duplicated in molecule number imol_frag

11.7.26 copy-residue-range

`copy-residue-range` *imol_target chain_id_target imol_reference chain_id_reference resno_range_start resno_range_end* [function]

Where:

- *imol_target* is an integer number
- *chain_id_target* is a string
- *imol_reference* is an integer number
- *chain_id_reference* is a string
- *resno_range_start* is an integer number
- *resno_range_end* is an integer number

copy the given residue range from the reference chain to the target chain

resno_range_start and resno_range_end are inclusive.

11.7.27 clear-and-update-model-molecule-from-file

`clear-and-update-model-molecule-from-file` *molecule_number file_name* [function]

Where:

- *molecule_number* is an integer number
- *file_name* is a string

replace the given residues from the reference molecule to the target molecule

replace pdb. Fail if molecule_number is not a valid model molecule. Return -1 on failure. Else return molecule_number

11.7.28 screendump-image

`screendump-image` *filename* [function]

Where *filename* is a string

dump the current screen image to a file. Format ppm

You can use this, in conjunction with spinning and view moving functions to make movies

11.7.29 check-for-dark-blue-density

`check-for-dark-blue-density` [function]

give a warning dialog if density it too dark (blue)

11.7.30 set-draw-solid-density-surface

`set-draw-solid-density-surface` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

sets the density map of the given molecule to be drawn as a (transparent) solid surface.

11.7.31 set-draw-map-standard-lines

`set-draw-map-standard-lines` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

toggle for standard lines representation of map.

This turns off/on standard lines representation of map. transparent surface is another representation type.

If you want to just turn off a map, don't use this, use

.

11.7.32 set-solid-density-surface-opacity

`set-solid-density-surface-opacity` *imol opacity* [function]

Where:

- *imol* is an integer number
- *opacity* is a number

set the opacity of density surface representation of the given map.

0.0 is totally transparent, 1.0 is completely opaque and (because the objects are no longer depth sorted) considerably faster to render. 0.3 is a reasonable number.

11.7.33 set-flat-shading-for-solid-density-surface

`set-flat-shading-for-solid-density-surface` *state* [function]

Where *state* is an integer number

set the flag to do flat shading rather than smooth shading for solid density surface.

Default is 1 (on.

11.8 Interface Preferences

11.8.1 set-scroll-by-wheel-mouse

`set-scroll-by-wheel-mouse` *istate* [function]

Where *istate* is an integer number

Some people (like Phil Evans) don't want to scroll their map with the mouse-wheel.

To turn off mouse wheel recontouring call this with istate value of 0

11.8.2 scroll-by-wheel-mouse-state

`scroll-by-wheel-mouse-state` [function]

return the internal state of the scroll-wheel map contouring

11.8.3 set-default-initial-contour-level-for-map

`set-default-initial-contour-level-for-map` *n_sigma* [function]

Where *n_sigma* is a number

set the default inital contour for 2FoFc-style map

in sigma

11.8.4 set-default-initial-contour-level-for-difference-map

`set-default-initial-contour-level-for-difference-map` *n_sigma* [function]

Where *n_sigma* is a number

set the default inital contour for FoFc-style map

in sigma

11.8.5 print-view-matrix

`print-view-matrix` [function]

print the view matrix to the console, useful for molscript, perhaps

11.8.6 get-view-quaternion-internal

`get-view-quaternion-internal` *element* [function]

Where *element* is an integer number

internal function to get an element of the view quaternion. The whole quaternion is returned by the scheme function view-quaternion

11.8.7 set-view-quaternion

`set-view-quaternion` *i j k l* [function]

Where:

- *i* is a number
- *j* is a number
- *k* is a number
- *l* is a number

Set the view quaternion.

11.8.8 apply-ncs-to-view-orientation

`apply-ncs-to-view-orientation` *imol current_chain next_ncs_chain* [function]

Where:

- *imol* is an integer number
- *current_chain* is a string
- *next_ncs_chain* is a string

Given that we are in chain current_chain, apply the NCS operator that maps current_chain on to next_ncs_chain, so that the relative view is preserved. For NCS skipping.

11.8.9 apply-ncs-to-view-orientation-and-screen-centre

`apply-ncs-to-view-orientation-and-screen-centre` *imol current_chain next_ncs_chain forward_flag* [function]

Where:

- *imol* is an integer number
- *current_chain* is a string
- *next_ncs_chain* is a string
- *forward_flag* is an integer number

as above, but shift the screen centre also.

11.8.10 set-fps-flag

`set-fps-flag` *t* [function]

Where *t* is an integer number

set show frame-per-second flag

11.8.11 get-fps-flag

`get-fps-flag` [function]

set the state of show frames-per-second flag

11.8.12 set-show-origin-marker

`set-show-origin-marker` *istate* [function]

Where *istate* is an integer number

set a flag: is the origin marker to be shown? 1 for yes, 0 for no.

11.8.13 show-origin-marker-state

`show-origin-marker-state` [function]

return the origin marker shown? state

11.8.14 hide-modelling-toolbar

`hide-modelling-toolbar` [function]

hide the vertical modelling toolbar in the GTK2 version

11.8.15 show-modelling-toolbar

`show-modelling-toolbar` [function]

show the vertical modelling toolbar in the GTK2 version (the toolbar is shown by default)

11.8.16 hide-main-toolbar

`hide-main-toolbar` [function]

hide the horizontal main toolbar in the GTK2 version

11.8.17 show-main-toolbar

`show-main-toolbar` [function]

show the horizontal main toolbar in the GTK2 version (the toolbar is shown by default)

11.8.18 show-model-toolbar-all-icons

`show-model-toolbar-all-icons` [function]

show all available icons in the modelling toolbar (same as MFR dialog)

11.8.19 show-model-toolbar-main-icons

`show-model-toolbar-main-icons` [function]

show only a selection of icons in the modelling toolbar

11.8.20 reattach-modelling-toolbar

`reattach-modelling-toolbar` [function]

reattach the modelling toolbar to the last attached position

11.8.21 set-model-toolbar-docked-position

`set-model-toolbar-docked-position` *state* [function]

Where *state* is an integer number

to swap sides of the Model/Fit/Refine toolbar 0 (default) is right, 1 is left, 2 is top, 3 is bottom

11.8.22 suck-model-fit-dialog

`suck-model-fit-dialog` [function]

reparent the Model/Fit/Refine dialog so that it becomes part of the main window, next to the GL graphics context

11.8.23 add-status-bar-text

`add-status-bar-text` *s* [function]

Where *s* is a string

Put text s into the status bar.

use this to put info for the user in the statusbar (less intrusive than popup).

11.8.24 set-model-fit-refine-dialog-stays-on-top

`set-model-fit-refine-dialog-stays-on-top` *istate* [function]

Where *istate* is an integer number

model-fit-refine dialog stays on top

11.8.25 model-fit-refine-dialog-stays-on-top-state

`model-fit-refine-dialog-stays-on-top-state` [function]

return the state model-fit-refine dialog stays on top

11.8.26 accept-reject-dialog-docked-state

`accept-reject-dialog-docked-state` [function]

the accept/reject dialog docked state

11.8.27 set-accept-reject-dialog-docked-show

`set-accept-reject-dialog-docked-show` *state* [function]

Where *state* is an integer number

set the accept/reject dialog docked show state

11.8.28 accept-reject-dialog-docked-show-state

`accept-reject-dialog-docked-show-state` [function]

what is the accept/reject dialog docked show state?

11.9 Mouse Buttons

11.9.1 set-control-key-for-rotate

`set-control-key-for-rotate` *state* [function]

Where *state* is an integer number

Alternate mode for rotation.

Prefered by some, including Dirk Kostrewa. I don't think this mode works properly yet

11.9.2 control-key-for-rotate-state

`control-key-for-rotate-state` [function]

return the control key rotate state

11.9.3 blob-under-pointer-to-screen-centre

`blob-under-pointer-to-screen-centre` [function]

Put the blob under the cursor to the screen centre. Check only positive blobs. Useful function if bound to a key.

The refinement map must be set. (We can't check all maps because they are not (or may not be) on the same scale).

Returns: 1 if successfully found a blob and moved there. return 0 if no move.

11.10 Cursor Function

11.10.1 normal-cursor

`normal-cursor` [function]

normal cursor

11.10.2 fleur-cursor

`fleur-cursor` [function]

fleur cursor

11.10.3 pick-cursor-maybe

`pick-cursor-maybe` [function]

pick cursor maybe

11.10.4 rotate-cursor

`rotate-cursor` [function]

rotate cursor

11.10.5 set-pick-cursor-index

`set-pick-cursor-index` *icursor_index* [function]

Where *icursor_index* is an integer number

let the user have a different pick cursor

sometimes (the default) GDK_CROSSHAIR is hard to see, let the user set their own

11.11 Model/Fit/Refine Functions

11.11.1 post-model-fit-refine-dialog

`post-model-fit-refine-dialog` [function]

display the Model/Fit/Refine dialog

11.11.2 unset-model-fit-refine-dialog

`unset-model-fit-refine-dialog` [function]

unset model/fit/refine dialog

11.11.3 unset-refine-params-dialog

`unset-refine-params-dialog` [function]

unset refine params dialog

11.11.4 show-select-map-dialog

`show-select-map-dialog` [function]

display the Display Manager dialog

11.11.5 set-model-fit-refine-rotate-translate-zone-label

`set-model-fit-refine-rotate-translate-zone-label` *txt* [function]

Where *txt* is a string

Allow the changing of Model/Fit/Refine button label from "Rotate/Translate Zone".

11.11.6 set-model-fit-refine-place-atom-at-pointer-label

`set-model-fit-refine-place-atom-at-pointer-label` *txt* [function]

Where *txt* is a string

Allow the changing of Model/Fit/Refine button label from "Place Atom at Pointer".

11.11.7 post-other-modelling-tools-dialog

`post-other-modelling-tools-dialog` [function]

display the Other Modelling Tools dialog

11.11.8 set-refinement-move-atoms-with-zero-occupancy

`set-refinement-move-atoms-with-zero-occupancy` *state* [function]

Where *state* is an integer number

shall atoms with zero occupancy be moved when refining? (default 1, yes)

11.11.9 refinement-move-atoms-with-zero-occupancy-state

`refinement-move-atoms-with-zero-occupancy-state` [function]

return the state of "shall atoms with zero occupancy be moved when refining?"

11.12 Backup Functions

11.12.1 make-backup

`make-backup` *imol* [function]

Where *imol* is an integer number

make backup for molecule number imol

11.12.2 turn-off-backup

`turn-off-backup` *imol* [function]

Where *imol* is an integer number

turn off backups for molecule number imol

11.12.3 turn-on-backup

`turn-on-backup` *imol* [function]

Where *imol* is an integer number

turn on backups for molecule number imol

11.12.4 backup-state

`backup-state` *imol* [function]

Where *imol* is an integer number

return the backup state for molecule number imol

return 0 for backups off, 1 for backups on, -1 for unknown

11.12.5 apply-undo

`apply-undo` [function]

apply undo - the "Undo" button callback

11.12.6 apply-redo

`apply-redo` [function]

apply redo - the "Redo" button callback

11.12.7 set-have-unsaved-changes

`set-have-unsaved-changes` *imol* [function]

Where *imol* is an integer number

set the molecule number imol to be marked as having unsaved changes

11.12.8 have-unsaved-changes-p

`have-unsaved-changes-p` *imol* [function]

Where *imol* is an integer number

does molecule number imol have unsaved changes?

Returns: -1 on bad imol, 0 on no unsaved changes, 1 on has unsaved changes

11.12.9 set-undo-molecule

`set-undo-molecule` *imol* [function]

Where *imol* is an integer number

set the molecule to which undo operations are done to molecule number imol

11.12.10 show-set-undo-molecule-chooser

`show-set-undo-molecule-chooser` [function]

show the Undo Molecule chooser - i.e. choose the molecule to which the "Undo" button applies.

11.12.11 set-unpathed-backup-file-names

`set-unpathed-backup-file-names` *state* [function]

Where *state* is an integer number

set the state for adding paths to backup file names

by default directories names are added into the filename for backup (with / to _ mapping). call this with state=1 to turn off directory names

11.12.12 unpathed-backup-file-names-state

`unpathed-backup-file-names-state` [function]

return the state for adding paths to backup file names

11.12.13 backup-compress-files-state

`backup-compress-files-state` [function]

return the state for compression of backup files

11.12.14 set-backup-compress-files

`set-backup-compress-files` *state* [function]

Where *state* is an integer number

set if backup files will be compressed or not using gzip

11.13 Recover Session Function

11.13.1 recover-session

`recover-session` [function]

recover session

After a crash, we provide this convenient interface to restore the session. It runs through all the molecules with models and looks at the coot backup directory looking for related backup files that are more recent that the read file. (Not very good, because you need to remember which files you read in before the crash - should be improved.)

11.14 Map Functions

11.14.1 calc-phases-generic

`calc-phases-generic` *mtz_file_name* [function]

Where *mtz_file_name* is a string

fire up a GUI, which asks us which model molecule we want to calc phases from. On "OK" button there, we call map_from_mtz_by_refmac_calc_phases()

11.14.2 map-from-mtz-by-refmac-calc-phases

`map-from-mtz-by-refmac-calc-phases` *mtz_file_name f_col sigf_col imol_coords* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *sigf_col* is a string
- *imol_coords* is an integer number

Calculate SFs (using refmac optionally) from an MTZ file and generate a map. Get F and SIGF automatically (first of their type) from the mtz file.

Returns: the new molecule number, -1 on a problem.

11.14.3 map-from-mtz-by-calc-phases

`map-from-mtz-by-calc-phases` *mtz_file_name f_col sigf_col imol_coords* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *sigf_col* is a string
- *imol_coords* is an integer number

Calculate SFs from an MTZ file and generate a map.

Returns: the new molecule number.

11.14.4 set-scroll-wheel-map

`set-scroll-wheel-map` *imap* [function]

Where *imap* is an integer number

set the map that is moved by changing the scroll wheel and change_contour_level().

11.14.5 set-scrollable-map

`set-scrollable-map` *imol* [function]

Where *imol* is an integer number

return the molecule number to which the mouse scroll wheel is attached

set the map that has its contour level changed by the scrolling the mouse wheel to molecule number imol (same as

).

11.14.6 scroll-wheel-map

`scroll-wheel-map` [function]

the contouring of which map is altered when the scroll wheel changes?

11.14.7 save-previous-map-colour

`save-previous-map-colour` *imol* [function]

Where *imol* is an integer number

save previous colour map for molecule number imol

11.14.8 restore-previous-map-colour

`restore-previous-map-colour` *imol* [function]

Where *imol* is an integer number

restore previous colour map for molecule number imol

11.14.9 set-active-map-drag-flag

`set-active-map-drag-flag` *t* [function]

Where *t* is an integer number

set the state of immediate map upate on map drag.

By default, it is on (t=1). On slower computers it might be better to set t=0.

11.14.10 get-active-map-drag-flag

`get-active-map-drag-flag` [function]

return the state of the dragged map flag

11.14.11 set-last-map-colour

`set-last-map-colour` *f1 f2 f3* [function]

Where:

- *f1* is a number
- *f2* is a number
- *f3* is a number

set the colour of the last (highest molecule number) map

11.14.12 set-map-colour

`set-map-colour` *imol red green blue* [function]

Where:

- *imol* is an integer number
- *red* is a number
- *green* is a number
- *blue* is a number

set the colour of the imolth map

11.14.13 set-last-map-sigma-step

`set-last-map-sigma-step` *f* [function]

Where *f* is a number

set the sigma step of the last map to f sigma

11.14.14 set-contour-by-sigma-step-by-mol

`set-contour-by-sigma-step-by-mol` *f state imol* [function]

Where:

- *f* is a number
- *state* is an integer number
- *imol* is an integer number

set the contour level step

set the contour level step of molecule number imol to f and variable state (setting state to 0 turns off contouring by sigma level)

11.14.15 data-resolution

`data-resolution` *imol* [function]

Where *imol* is an integer number

return the resolution of the data for molecule number imol. Return negative number on error, otherwise resolution in A (eg. 2.0)

11.14.16 model-resolution

`model-resolution` *imol* [function]

Where *imol* is an integer number

return the resolution set in the header of the model/coordinates file. If this number is not available, return a number less than 0.

11.14.17 export-map

`export-map` *imol filename* [function]

Where:

- *imol* is an integer number
- *filename* is a string

export (write to disk) the map of molecule number imol to filename.

Return 0 on failure, 1 on success.

11.14.18 export-map-fragment

`export-map-fragment` *imol x y z radius filename* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number
- *radius* is a number
- *filename* is a string

export a fragment of the map about (x,y,z)

11.14.19 export-map-fragment-with-origin-shift

`export-map-fragment-with-origin-shift` *imol x y z radius filename* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number
- *radius* is a number
- *filename* is a string

export a fragment of the map about (x,y,z)

11.14.20 difference-map

`difference-map` *imol1 imol2 map_scale* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *map_scale* is a number

make a difference map, taking map_scale * imap2 from imap1, on the grid of imap1. Return the new molecule number. Return -1 on failure.

11.14.21 reinterp-map

`reinterp-map` *map_no reference_map_no* [function]

Where:

- *map_no* is an integer number
- *reference_map_no* is an integer number

make a new map (a copy of map_no) that is in the cell, spacegroup and gridding of the map in reference_map_no.

Return the new map molecule number - return -1 on failure

11.14.22 smooth-map

`smooth-map` *map_no sampling_multiplier* [function]

Where:

- *map_no* is an integer number
- *sampling_multiplier* is a number

make a new map (a copy of map_no) that is in the cell, spacegroup and a multiple of the sampling of the input map (a sampling factor of more than 1 makes the output maps smoother)

11.15 Density Increment

11.15.1 set-iso-level-increment

`set-iso-level-increment` *val* [function]

Where *val* is a number

set the contour scroll step (in absolute e/A3) for 2Fo-Fc-style maps to val

The is only activated when scrolling by sigma is turned off

11.15.2 set-diff-map-iso-level-increment

`set-diff-map-iso-level-increment` *val* [function]

Where *val* is a number

set the contour scroll step for difference map (in absolute e/A3) to val

The is only activated when scrolling by sigma is turned off

11.15.3 get-diff-map-iso-level-increment

`get-diff-map-iso-level-increment` [function]

return difference maps iso-map level increment

11.15.4 set-diff-map-iso-level-increment-from-text

`set-diff-map-iso-level-increment-from-text` *text imol* [function]

Where:

- *text* is a string
- *imol* is an integer number

set the difference maps iso-map level increment

11.15.5 set-map-sampling-rate-text

`set-map-sampling-rate-text` *text* [function]

Where *text* is a string

sampling rate

find the molecule for which the single map dialog applies and set the contour level and redraw

11.15.6 set-map-sampling-rate

`set-map-sampling-rate` *r* [function]

Where *r* is a number

set the map sampling rate (default 1.5)

Set to something like 2.0 or 2.5 for more finely sampled maps. Useful for baton-building low resolution maps.

11.15.7 get-map-sampling-rate

`get-map-sampling-rate` [function]

return the map sampling rate

11.15.8 change-contour-level

`change-contour-level` *is_increment* [function]

Where *is_increment* is an integer number

change the contour level of the current map by a step

if is_increment=1 the contour level is increased. If is_increment=0 the map contour level is decreased.

11.15.9 set-last-map-contour-level

`set-last-map-contour-level` *level* [function]

Where *level* is a number

set the contour level of the map with the highest molecule number to level

11.15.10 set-last-map-contour-level-by-sigma

`set-last-map-contour-level-by-sigma` *n_sigma* [function]

Where *n_sigma* is a number

set the contour level of the map with the highest molecule number to n_sigma sigma

11.15.11 set-stop-scroll-diff-map

`set-stop-scroll-diff-map` *i* [function]

Where *i* is an integer number

create a lower limit to the "Fo-Fc-style" map contour level changing

(default 1 on)

11.15.12 set-stop-scroll-iso-map

`set-stop-scroll-iso-map` *i* [function]

Where *i* is an integer number

create a lower limit to the "2Fo-Fc-style" map contour level changing

(default 1 on)

11.15.13 set-stop-scroll-iso-map-level

`set-stop-scroll-iso-map-level` *f* [function]

Where *f* is a number

set the actual map level changing limit

(default 0.0)

11.15.14 set-stop-scroll-diff-map-level

`set-stop-scroll-diff-map-level` *f* [function]

Where *f* is a number

set the actual difference map level changing limit

(default 0.0)

11.15.15 set-residue-density-fit-scale-factor

`set-residue-density-fit-scale-factor` *f* [function]

Where *f* is a number

set the scale factor for the Residue Density fit analysis

11.16 Density Functions

11.16.1 set-map-line-width

`set-map-line-width` *w* [function]

Where *w* is an integer number

draw the lines of the chickenwire density in width w

11.16.2 map-line-width-state

`map-line-width-state` [function]

return the width in which density contours are drawn

11.16.3 make-and-draw-map

`make-and-draw-map` *mtz_file_name f_col phi_col weight use_weights is_diff_map* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *phi_col* is a string
- *weight* is a string
- *use_weights* is an integer number
- *is_diff_map* is an integer number

make a map from an mtz file (simple interface)

given mtz file mtz_file_name and F column f_col and phases column phi_col and optional weight column weight_col (pass use_weights=0 if weights are not to be used). Also mark the map as a difference map (is_diff_map=1) or not (is_diff_map=0) because they are handled differently inside coot.

Returns: -1 on error, else return the new molecule number

11.16.4 make-and-draw-map-with-refmac-params

`make-and-draw-map-with-refmac-params` *mtz_file_name a b weight use_weights is_diff_map have_refmac_params fobs_col sigfobs_col r_free_col sensible_f_free_col* [function]

Where:

- *mtz_file_name* is a string
- *a* is a string
- *b* is a string
- *weight* is a string
- *use_weights* is an integer number
- *is_diff_map* is an integer number
- *have_refmac_params* is an integer number
- *fobs_col* is a string
- *sigfobs_col* is a string
- *r_free_col* is a string
- *sensible_f_free_col* is an integer number

as the above function, execpt set refmac parameters too

pass along the refmac column labels for storage (not used in the creation of the map)

Returns: -1 on error, else return imol

11.16.5 make-and-draw-map-with-reso-with-refmac-params

`make-and-draw-map-with-reso-with-refmac-params` *mtz_file_name a b weight use_weights is_diff_map have_refmac_params fobs_col sigfobs_col r_free_col sensible_f_free_col is_anomalous use_reso_limits low_reso_limit high_reso_lim* [function]

Where:

- *mtz_file_name* is a string
- *a* is a string
- *b* is a string
- *weight* is a string
- *use_weights* is an integer number
- *is_diff_map* is an integer number
- *have_refmac_params* is an integer number
- *fobs_col* is a string
- *sigfobs_col* is a string
- *r_free_col* is a string
- *sensible_f_free_col* is an integer number
- *is_anomalous* is an integer number
- *use_reso_limits* is an integer number
- *low_reso_limit* is a number
- *high_reso_lim* is a number

as the above function, except set expert options too.

11.16.6 valid-labels

`valid-labels` *mtz_file_name f_col phi_col weight_col use_weights* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *phi_col* is a string
- *weight_col* is a string
- *use_weights* is an integer number

does the mtz file have the columms that we want it to have?

11.16.7 mtz-file-has-phases-p

`mtz-file-has-phases-p` *mtz_file_name* [function]

Where *mtz_file_name* is a string

does the mtz file have phases?

11.16.8 is-mtz-file-p

`is-mtz-file-p` *filename* [function]

Where *filename* is a string

is the given filename an mtz file?

11.16.9 cns-file-has-phases-p

`cns-file-has-phases-p` *cns_file_name* [function]

Where *cns_file_name* is a string

does the given file have cns phases?

11.16.10 auto-read-do-difference-map-too-state

`auto-read-do-difference-map-too-state` [function]

return the flag to do a difference map (too) on auto-read MTZ

Returns: 0 means no, 1 means yes.

11.16.11 set-auto-read-column-labels

`set-auto-read-column-labels` *fwt phwt is_for_diff_map_flag* [function]

Where:

- *fwt* is a string
- *phwt* is a string
- *is_for_diff_map_flag* is an integer number

set the expected MTZ columns for Auto-reading MTZ file.

Not every program uses the default refmac labels ("FWT"/"PHWT") for its MTZ file. Here we can tell coot to expect other labels so that coot can "Auto-open" such MTZ files.

e.g. (set-auto-read-column-labels "2FOFCWT" "PH2FOFCWT" 0)

11.16.12 set-map-radius

`set-map-radius` *f* [function]

Where *f* is a number

set the extent of the box/radius of electron density contours

11.16.13 set-density-size

`set-density-size` *f* [function]

Where *f* is a number

another (old) way of setting the radius of the map

11.16.14 set-display-intro-string

`set-display-intro-string` *str* [function]

Where *str* is a string

Give me this nice message str when I start coot.

11.16.15 get-map-radius

`get-map-radius` [function]

return the extent of the box/radius of electron density contours

11.16.16 set-esoteric-depth-cue

`set-esoteric-depth-cue` *istate* [function]

Where *istate* is an integer number

not everone likes coot's esoteric depth cueing system

Pass an argument istate=1 to turn it off

(this function is currently disabled).

11.16.17 esoteric-depth-cue-state

`esoteric-depth-cue-state` [function]

native depth cueing system

return the state of the esoteric depth cueing flag

11.16.18 set-swap-difference-map-colours

`set-swap-difference-map-colours` *i* [function]

Where *i* is an integer number

not everone likes coot's default difference map colouring.

Pass an argument i=1 to swap the difference map colouring so that red is positive and green is negative.

11.16.19 set-map-is-difference-map

`set-map-is-difference-map` *imol* [function]

Where *imol* is an integer number

post-hoc set the map of molecule number imol to be a difference map

Returns: success status, 0 -> failure (imol does not have a map)

11.16.20 map-is-difference-map

`map-is-difference-map` *imol* [function]

Where *imol* is an integer number

map is difference map?

11.16.21 another-level

`another-level` [function]

Add another contour level for the last added map.

Currently, the map must have been generated from an MTZ file.

Returns: the molecule number of the new molecule or -1 on failure

11.16.22 another-level-from-map-molecule-number

`another-level-from-map-molecule-number` *imap* [function]

Where *imap* is an integer number

Add another contour level for the given map.

Currently, the map must have been generated from an MTZ file.

Returns: the molecule number of the new molecule or -1 on failure

11.16.23 residue-density-fit-scale-factor

`residue-density-fit-scale-factor` [function]

return the scale factor for the Residue Density fit analysis

11.16.24 density-at-point

`density-at-point` *imol_map x y z* [function]

Where:

- *imol_map* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number

return the density at the given point for the given map. Return 0 for bad imol

11.17 Parameters from map

11.17.1 mtz-hklin-for-map

`mtz-hklin-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the mtz file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say).

11.17.2 mtz-fp-for-map

`mtz-fp-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the FP column in the file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say).

Caller should dispose of returned pointer.

11.17.3 mtz-phi-for-map

`mtz-phi-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the phases column in mtz file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say). Caller should dispose of returned pointer.

11.17.4 mtz-weight-for-map

`mtz-weight-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the weight column in the mtz file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say) or no weights were used. Caller should dispose of returned pointer.

11.17.5 mtz-use-weight-for-map

`mtz-use-weight-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return flag for whether weights were used that was use to generate the map

return 0 when no weights were used or there is no mtz file associated with that map.

11.18 PDB Functions

11.18.1 write-pdb-file

`write-pdb-file` *imol file_name* [function]

Where:

- *imol* is an integer number
- *file_name* is a string

write molecule number imol as a PDB to file file_name

11.18.2 write-residue-range-to-pdb-file

`write-residue-range-to-pdb-file` *imol chainid resno_start resno_end filename* [function]

Where:

- *imol* is an integer number
- *chainid* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number
- *filename* is a string

write molecule number imol's residue range as a PDB to file file_name

11.18.3 quick-save

`quick-save` [function]

save all modified coordinates molecules to the default names and save the state too.

11.19 Info Dialog

11.19.1 info-dialog

`info-dialog` *txt* [function]

Where *txt* is a string

create a dialog with information

create a dialog with information string txt. User has to click to dismiss it, but it is not modal (nothing in coot is modal).

11.19.2 info-dialog-and-text

`info-dialog-and-text` *txt* [function]

Where *txt* is a string

create a dialog with information and print to console

as info_dialog but print to console as well.

11.20 Refmac Functions

11.20.1 set-refmac-counter

`set-refmac-counter` *imol refmac_count* [function]

Where:

- *imol* is an integer number
- *refmac_count* is an integer number

set counter for runs of refmac so that this can be used to construct a unique filename for new output

11.20.2 swap-map-colours

`swap-map-colours` *imol1 imol2* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number

swap the colours of maps

swap the colour of maps imol1 and imol2. Useful to some after running refmac, so that the map to be build into is always the same colour

11.20.3 set-keep-map-colour-after-refmac

`set-keep-map-colour-after-refmac` *istate* [function]

Where *istate* is an integer number

flag to enable above

call this with istate=1

11.20.4 keep-map-colour-after-refmac-state

`keep-map-colour-after-refmac-state` [function]

the keep-map-colour-after-refmac internal state

Returns: 1 for "yes", 0 for "no"

11.21 Symmetry Functions

11.21.1 set-symmetry-size

`set-symmetry-size` *f* [function]

Where *f* is a number

set the size of the displayed symmetry

11.21.2 get-show-symmetry

`get-show-symmetry` [function]

is symmetry master display control on?

11.21.3 set-show-symmetry-master

`set-show-symmetry-master` *state* [function]

Where *state* is an integer number

set display symmetry, master controller

11.21.4 set-show-symmetry-molecule

`set-show-symmetry-molecule` *mol_no state* [function]

Where:

- *mol_no* is an integer number
- *state* is an integer number

set display symmetry for molecule number mol_no

pass with state=0 for off, state=1 for on

11.21.5 symmetry-as-calphas

`symmetry-as-calphas` *mol_no state* [function]

Where:

- *mol_no* is an integer number
- *state* is an integer number

display symmetry as CAs?

pass with state=0 for off, state=1 for on

11.21.6 get-symmetry-as-calphas-state

`get-symmetry-as-calphas-state` *imol* [function]

Where *imol* is an integer number

what is state of display CAs for molecule number mol_no?

return state=0 for off, state=1 for on

11.21.7 set-symmetry-molecule-rotate-colour-map

`set-symmetry-molecule-rotate-colour-map` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set the colour map rotation (i.e. the hue) for the symmetry atoms of molecule number imol

11.21.8 symmetry-molecule-rotate-colour-map-state

`symmetry-molecule-rotate-colour-map-state` *imol* [function]

Where *imol* is an integer number

should there be colour map rotation (i.e. the hue) change for the symmetry atoms of molecule number imol?

return state=0 for off, state=1 for on

11.21.9 set-symmetry-colour-by-symop

`set-symmetry-colour-by-symop` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set symmetry colour by symop mode

11.21.10 set-symmetry-whole-chain

`set-symmetry-whole-chain` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set symmetry colour for the chain

11.21.11 set-symmetry-atom-labels-expanded

`set-symmetry-atom-labels-expanded` *state* [function]

Where *state* is an integer number

set use expanded symmetry atom labels

11.21.12 has-unit-cell-state

`has-unit-cell-state` *imol* [function]

Where *imol* is an integer number

molecule number imol has a unit cell?

Returns: 1 on "yes, it has a cell", 0 for "no"

11.21.13 undo-symmetry-view

`undo-symmetry-view` [function]

Undo symmetry view. Translate back to main molecule from this symmetry position.

11.21.14 first-molecule-with-symmetry-displayed

`first-molecule-with-symmetry-displayed` [function]

return the molecule number.

Returns: -1 if there is no molecule with symmetry displayed.

11.21.15 save-symmetry-coords

`save-symmetry-coords` *imol filename symop_no shift_a shift_b shift_c pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *filename* is a string
- *symop_no* is an integer number
- *shift_a* is an integer number
- *shift_b* is an integer number
- *shift_c* is an integer number
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

save the symmetry coordinates of molecule number imol to filename

Allow a shift of the coordinates to the origin before symmetry expansion is apllied (this is how symmetry works in Coot internals).

11.21.16 new-molecule-by-symmetry

`new-molecule-by-symmetry` *imol name m11 m12 m13 m21 m22 m23 m31 m32 m33 tx ty tz pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *name* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *tx* is a number
- *ty* is a number
- *tz* is a number
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

create a new molecule (molecule number is the return value) from imol.

The rotation/translation matrix components are given in

coordinates.

Allow a shift of the coordinates to the origin before symmetry expansion is aplied.

Pass `""` as the name-in and a name will be constructed for you.

Return -1 on failure.

11.21.17 new-molecule-by-symmetry-with-atom-selection

`new-molecule-by-symmetry-with-atom-selection` *imol name mmdb_atom_selection_string m11 m12 m13 m21 m22 m23 m31 m32 m33 tx ty tz pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *name* is a string
- *mmdb_atom_selection_string* is a string
- *m11* is a number
- *m12* is a number

- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *tx* is a number
- *ty* is a number
- *tz* is a number
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

create a new molecule (molecule number is the return value) from imol, but only for atom that match the mmdb_atom_selection_string.

The rotation/translation matrix components are given in

coordinates.

Allow a shift of the coordinates to the origin before symmetry expansion is aplied.

Pass `""` as the name-in and a name will be constructed for you.

Return -1 on failure.

11.21.18 new-molecule-by-symop

`new-molecule-by-symop` *imol symop_string pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *symop_string* is a string
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

create a new molecule (molecule number is the return value) from imol.

11.21.19 n-symops

`n-symops` *imol* [function]

Where *imol* is an integer number

return the number of symmetry operators for the given molecule

return -1 on no-symmetry for molecule or inappropriate imol number

11.21.20 set-space-group

`set-space-group` *imol spg* [function]

Where:

- *imol* is an integer number
- *spg* is a string

set the space group for a coordinates molecule

for shelx FA pdb files, there is no space group. So allow the user to set it. This can be initted with a HM symbol or a symm list for clipper. Return the succes status of the setting.

11.21.21 set-symmetry-shift-search-size

`set-symmetry-shift-search-size` *shift* [function]

Where *shift* is an integer number

set the cell shift search size for symmetry searching.

When the coordinates for one (or some) symmetry operator are missing (which happens sometimes, but rarely), try changing setting this to 2 (default is 1). It slows symmetry searching, which is why it is not set to 2 by default.

11.22 History Functions

11.22.1 print-all-history-in-scheme

`print-all-history-in-scheme` [function]

print the history in scheme format

11.22.2 print-all-history-in-python

`print-all-history-in-python` [function]

print the history in python format

11.22.3 set-console-display-commands-state

`set-console-display-commands-state` *istate* [function]

Where *istate* is an integer number

set a flag to show the text command equivalent of gui commands in the console as they happen.

1 for on, 0 for off.

11.22.4 set-console-display-commands-hilights

`set-console-display-commands-hilights` *bold_flag colour_flag colour_index* [function]

Where:

- *bold_flag* is an integer number

- *colour_flag* is an integer number
- *colour_index* is an integer number

set a flag to show the text command equivalent of gui commands in the console as they happen in bold and colours.

colour_flag: pass 1 for on, 0 for off.

colour_index 0 to 7 inclusive for various different colourings.

11.23 State Functions

11.23.1 save-state

`save-state` [function]

save the current state to the default filename

11.23.2 save-state-file

`save-state-file` *filename* [function]

Where *filename* is a string

save the current state to file filename

11.23.3 save-state-file-py

`save-state-file-py` *filename* [function]

Where *filename* is a string

save the current state to file filename

11.23.4 set-save-state-file-name

`set-save-state-file-name` *filename* [function]

Where *filename* is a string

set the default state file name (default 0-coot.state.scm)

11.23.5 set-run-state-file-status

`set-run-state-file-status` *istat* [function]

Where *istat* is an integer number

set run state file status

0: never run it 1: ask to run it 2: run it, no questions

11.23.6 run-state-file

`run-state-file` [function]

run the state file (reading from default filenname)

11.23.7 run-state-file-maybe

`run-state-file-maybe` [function]

run the state file depending on the state variables

11.24 The Virtual Trackball

11.24.1 vt-surface

`vt-surface` *mode* [function]

Where *mode* is an integer number

How should the mouse move the view?

mode=1 for "Flat", mode=2 for "Spherical Surface"

11.24.2 vt-surface-status

`vt-surface-status` [function]

return the mouse view status mode

mode=1 for "Flat", mode=2 for "Spherical Surface"

11.25 Clipping Functions

11.25.1 set-clipping-back

`set-clipping-back` *v* [function]

Where *v* is a number

set clipping plane back

11.25.2 set-clipping-front

`set-clipping-front` *v* [function]

Where *v* is a number

set clipping plane front

11.26 Unit Cell interface

11.26.1 get-show-unit-cell

`get-show-unit-cell` *imol* [function]

Where *imol* is an integer number

return the stage of show unit cell for molecule number imol

11.26.2 set-show-unit-cells-all

`set-show-unit-cells-all` *istate* [function]

Where *istate* is an integer number

set the state of show unit cell for all molecules

1 for displayed 0 for undisplayed

11.26.3 set-show-unit-cell

`set-show-unit-cell` *imol istate* [function]

Where:

- *imol* is an integer number
- *istate* is an integer number

set the state of show unit cell for the particular molecule number imol

1 for displayed 0 for undisplayed

11.27 Colour

11.27.1 set-colour-map-rotation-on-read-pdb

`set-colour-map-rotation-on-read-pdb` *f* [function]

Where *f* is a number

set the hue change step on reading a new molecule

11.27.2 set-colour-map-rotation-on-read-pdb-flag

`set-colour-map-rotation-on-read-pdb-flag` *i* [function]

Where *i* is an integer number

shall the hue change step be used?

11.27.3 set-colour-map-rotation-on-read-pdb-c-only-flag

`set-colour-map-rotation-on-read-pdb-c-only-flag` *i* [function]

Where *i* is an integer number

shall the colour map rotation apply only to C atoms?

11.27.4 set-colour-by-chain

`set-colour-by-chain` *imol* [function]

Where *imol* is an integer number

colour molecule number imol by chain type

11.27.5 set-colour-by-molecule

`set-colour-by-molecule` *imol* [function]

Where *imol* is an integer number

colour molecule number imol by molecule

11.27.6 set-symmetry-colour

`set-symmetry-colour` *r g b* [function]

Where:

- *r* is a number
- *g* is a number

- *b* is a number

set the symmetry colour base

11.28 Map colour

11.28.1 set-colour-map-rotation-for-map

`set-colour-map-rotation-for-map` *f* [function]

Where *f* is a number

set the colour map rotation (hue change) for maps

default: for maps is 14 degrees.

11.28.2 set-molecule-bonds-colour-map-rotation

`set-molecule-bonds-colour-map-rotation` *imol theta* [function]

Where:

- *imol* is an integer number
- *theta* is a number

set the colour map rotation for molecule number imol

theta is in degrees

11.28.3 get-molecule-bonds-colour-map-rotation

`get-molecule-bonds-colour-map-rotation` *imol* [function]

Where *imol* is an integer number

Get the colour map rotation for molecule number imol.

11.29 Anisotropic Atoms Interface

11.29.1 get-limit-aniso

`get-limit-aniso` [function]

get the aniso radius limit

11.29.2 get-show-limit-aniso

`get-show-limit-aniso` [function]

get show the aniso limit

11.29.3 get-show-aniso

`get-show-aniso` [function]

return show-aniso-atoms state

11.29.4 set-limit-aniso

`set-limit-aniso` *state* [function]

Where *state* is an integer number

set the aniso atom limit

11.29.5 set-show-aniso

`set-show-aniso` *state* [function]

Where *state* is an integer number

set show aniso atoms

11.29.6 set-aniso-probability

`set-aniso-probability` *f* [function]

Where *f* is a number

set aniso probability

11.29.7 get-aniso-probability

`get-aniso-probability` [function]

get aniso probability

11.30 Display Functions

11.30.1 set-graphics-window-size

`set-graphics-window-size` *x_size y_size* [function]

Where:

- *x_size* is an integer number
- *y_size* is an integer number

set the window size

11.30.2 set-graphics-window-position

`set-graphics-window-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set the graphics window position

11.30.3 store-graphics-window-position

`store-graphics-window-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

store the graphics window position

11.30.4 graphics-draw

`graphics-draw` [function]

draw a frame

11.30.5 zalman-stereo-mode

`zalman-stereo-mode` [function]

try to turn on Zalman stereo mode

11.30.6 hardware-stereo-mode

`hardware-stereo-mode` [function]

try to turn on stereo mode

11.30.7 stereo-mode-state

`stereo-mode-state` [function]

what is the stero state?

Returns: 1 for in hardware stereo, 2 for side by side stereo, else return 0.

11.30.8 mono-mode

`mono-mode` [function]

try to turn on mono mode

11.30.9 side-by-side-stereo-mode

`side-by-side-stereo-mode` *use_wall_eye_mode* [function]

Where *use_wall_eye_mode* is an integer number

turn on side bye side stereo mode

11.30.10 set-hardware-stereo-angle-factor

`set-hardware-stereo-angle-factor` *f* [function]

Where *f* is a number

how much should the eyes be separated in stereo mode?

11.30.11 hardware-stereo-angle-factor-state

`hardware-stereo-angle-factor-state` [function]

return the hardware stereo angle factor

11.30.12 set-model-fit-refine-dialog-position

`set-model-fit-refine-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Model/Fit/Refine dialog

11.30.13 set-display-control-dialog-position

`set-display-control-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Display Control dialog

11.30.14 set-go-to-atom-window-position

`set-go-to-atom-window-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Go To Atom dialog

11.30.15 set-delete-dialog-position

`set-delete-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Delete dialog

11.30.16 set-rotate-translate-dialog-position

`set-rotate-translate-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of the Rotate/Translate Residue Range dialog

11.30.17 set-accept-reject-dialog-position

`set-accept-reject-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of the Accept/Reject dialog

11.30.18 set-ramachandran-plot-dialog-position

`set-ramachandran-plot-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of the Ramachadran Plot dialog

11.30.19 set-edit-chi-angles-dialog-position

`set-edit-chi-angles-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set edit chi angles dialog position

11.30.20 set-rotamer-selection-dialog-position

`set-rotamer-selection-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set rotamer selection dialog position

11.31 Smooth Scrolling

11.31.1 set-smooth-scroll-flag

`set-smooth-scroll-flag` *v* [function]

Where *v* is an integer number

set smooth scrolling

11.31.2 get-smooth-scroll

`get-smooth-scroll` [function]

return the smooth scrolling state

11.31.3 set-smooth-scroll-steps

`set-smooth-scroll-steps` *i* [function]

Where *i* is an integer number

set the number of steps in the smooth scroll

Set more steps (e.g. 50) for more smoothness (default 10).

11.31.4 set-smooth-scroll-limit

`set-smooth-scroll-limit` *lim* [function]

Where *lim* is a number

do not scroll for distances greater this limit

11.32 Font Parameters

11.32.1 set-font-size

`set-font-size` *i* [function]

Where *i* is an integer number

set the font size

11.32.2 get-font-size

`get-font-size` [function]

return the font size

Returns: 1 (small) 2 (medium, default) 3 (large)

11.32.3 set-font-colour

`set-font-colour` *red green blue* [function]

Where:

- *red* is a number
- *green* is a number
- *blue* is a number

set the colour of the atom label font - the arguments are in the range 0->1

11.32.4 set-use-stroke-characters

`set-use-stroke-characters` *state* [function]

Where *state* is an integer number

set use stroke characters

11.33 Rotation Centre

11.33.1 set-rotation-centre-size

`set-rotation-centre-size` *f* [function]

Where *f* is a number

set rotoation centre marker size

11.33.2 recentre-on-read-pdb

`recentre-on-read-pdb` [function]

return the recentre-on-pdb state

11.33.3 set-recentre-on-read-pdb

`set-recentre-on-read-pdb` *int* [function]

Where *int* is a short

set the recentre-on-pdb state

11.33.4 set-rotation-centre

`set-rotation-centre` *x y z* [function]

Where:

- *x* is a number
- *y* is a number
- *z* is a number

set the rotation centre

11.33.5 go-to-ligand

`go-to-ligand` [function]

centre on the ligand of the "active molecule", if we are already there, centre on the next hetgroup (etc)

11.33.6 set-go-to-ligand-n-atoms-limit

`set-go-to-ligand-n-atoms-limit` *n_atom_min* [function]

Where *n_atom_min* is an integer number

go to the ligand that has more than n_atom_min atoms

11.34 Atom Selection Utilities

11.34.1 median-temperature-factor

`median-temperature-factor` *imol* [function]

Where *imol* is an integer number

return the median temperature factor for imol

11.34.2 average-temperature-factor

`average-temperature-factor` *imol* [function]

Where *imol* is an integer number

return the average temperature factor for the atoms in imol

11.34.3 standard-deviation-temperature-factor

`standard-deviation-temperature-factor` *imol* [function]

Where *imol* is an integer number

return the standard deviation of the atom temperature factors for imol

11.34.4 clear-pending-picks

`clear-pending-picks` [function]

clear pending picks (stop coot thinking that the user is about to pick an atom).

11.34.5 set-default-temperature-factor-for-new-atoms

`set-default-temperature-factor-for-new-atoms` *new_b* [function]

Where *new_b* is a number

set the default temperature factor for newly created atoms (initial default 20)

11.34.6 default-new-atoms-b-factor

`default-new-atoms-b-factor` [function]

return the default temperature factor for newly created atoms

11.34.7 set-reset-b-factor-moved-atoms

`set-reset-b-factor-moved-atoms` *state* [function]

Where *state* is an integer number

reset temperature factor for all moved atoms to the default for new atoms (usually 30)

11.34.8 get-reset-b-factor-moved-atoms-state

`get-reset-b-factor-moved-atoms-state` [function]

return the state if temperature factors shoudl be reset for moved atoms

11.34.9 set-atom-attribute

`set-atom-attribute` *imol chain_id resno ins_code atom_name alt_conf attribute_name val* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atom_name* is a string
- *alt_conf* is a string
- *attribute_name* is a string
- *val* is a number

set a numberical attibute to the atom with the given specifier.

Attributes can be "x", "y","z", "B", "occ" and the attribute val is a floating point number

11.34.10 set-atom-string-attribute

`set-atom-string-attribute` *imol chain_id resno ins_code atom_name alt_conf attribute_name attribute_value* [function]

Where:

- *imol* is an integer number

- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atom_name* is a string
- *alt_conf* is a string
- *attribute_name* is a string
- *attribute_value* is a string

set a string attibute to the atom with the given specifier.

Attributes can be "atom-name", "alt-conf", "element" or "segid".

11.34.11 set-residue-name

`set-residue-name` *imol chain_id res_no ins_code new_residue_name* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *new_residue_name* is a string

set lots of atom attributes at once by-passing the rebonding and redrawing of the above 2 functions

set the residue name of the specified residue

11.35 Skeletonization Interface

11.35.1 skeletonize-map

`skeletonize-map` *imol prune_flag* [function]

Where:

- *imol* is an integer number
- *prune_flag* is an integer number

skeletonize molecule number imol

the prune_flag should almost always be 0.

NOTE:: The arguments to have been reversed for coot 0.8.3 and later (now the molecule number comes first).

11.35.2 unskeletonize-map

`unskeletonize-map` *imol* [function]

Where *imol* is an integer number

undisplay the skeleton on molecule number imol

11.35.3 set-max-skeleton-search-depth

`set-max-skeleton-search-depth` *v* [function]

Where *v* is an integer number

set the skeleton search depth, used in baton building

For high resolution maps, you need to search deeper down the skeleton tree. This limit needs to be increased to 20 or so for high res maps (it is 10 by default)

11.35.4 set-skeleton-box-size

`set-skeleton-box-size` *f* [function]

Where *f* is a number

the box size (in Angstroms) for which the skeleton is displayed

11.36 Skeleton Colour

11.36.1 set-skeleton-colour

`set-skeleton-colour` *imol r g b* [function]

Where:

- *imol* is an integer number
- *r* is a number
- *g* is a number
- *b* is a number

set the skeleton colour

11.37 Read Maps

11.37.1 handle-read-ccp4-map

`handle-read-ccp4-map` *filename is_diff_map_flag* [function]

Where:

- *filename* is a string
- *is_diff_map_flag* is an integer number

read a CCP4 map or a CNS map (despite the name).

11.38 Save Coordinates

11.38.1 save-coordinates

`save-coordinates` *imol filename* [function]

Where:

- *imol* is an integer number
- *filename* is a string

save coordinates of molecule number imol in filename

Returns: status 1 is good (success), 0 is fail.

11.38.2 set-save-coordinates-in-original-directory

`set-save-coordinates-in-original-directory` *i* [function]

Where *i* is an integer number

set save coordinates in the starting directory

11.39 Read Phases File Functions

11.39.1 read-phs-and-coords-and-make-map

`read-phs-and-coords-and-make-map` *pdb_filename* [function]

Where *pdb_filename* is a string

read phs file use coords to get cell and symm to make map

uses pending data to make the map.

11.39.2 read-phs-and-make-map-using-cell-symm-from-previous-mol

`read-phs-and-make-map-using-cell-symm-from-previous-mol` *phs_filename* [function]

Where *phs_filename* is a string

read a phs file, the cell and symm information is from previously read (most recently read) coordinates file

For use with phs data filename provided on the command line

11.39.3 read-phs-and-make-map-using-cell-symm-from-mol

`read-phs-and-make-map-using-cell-symm-from-mol` *phs_filename imol* [function]

Where:

- *phs_filename* is a string
- *imol* is an integer number

read phs file and use a previously read molecule to provide the cell and symmetry information

Returns: the new molecule number, return -1 if problem creating the map (e.g. not phs data, file not found etc).

11.39.4 read-phs-and-make-map-using-cell-symm

`read-phs-and-make-map-using-cell-symm` *phs_file_name hm_spacegroup a b c alpha beta gamma* [function]

Where:

- *phs_file_name* is a string
- *hm_spacegroup* is a string
- *a* is a number

- *b* is a number
- *c* is a number
- *alpha* is a number
- *beta* is a number
- *gamma* is a number

read phs file use coords to use cell and symm to make map

in degrees

11.39.5 read-phs-and-make-map-with-reso-limits

`read-phs-and-make-map-with-reso-limits` *imol phs_file_name reso_lim_low reso_lim_high* [function]

Where:

- *imol* is an integer number
- *phs_file_name* is a string
- *reso_lim_low* is a number
- *reso_lim_high* is a number

read a phs file and use the cell and symm in molecule number imol and use the resolution limits reso_lim_high (in Angstroems).

11.40 Graphics Move

11.40.1 undo-last-move

`undo-last-move` [function]

undo last move

11.40.2 translate-molecule-by

`translate-molecule-by` *imol x y z* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number

translate molecule number imol by (x,y,z) in Angstroms

11.40.3 transform-molecule-by

`transform-molecule-by` *imol m11 m12 m13 m21 m22 m23 m31 m32 m33 x y z* [function]

Where:

- *imol* is an integer number
- *m11* is a number

- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *x* is a number
- *y* is a number
- *z* is a number

transform molecule number imol by the given rotation matrix, then translate by (x,y,z) in Angstroms

11.40.4 transform-zone

`transform-zone` *imol chain_id resno_start resno_end ins_code m11 m12 m13 m21 m22 m23 m31 m32 m33 x y z* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number
- *ins_code* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *x* is a number
- *y* is a number
- *z* is a number

transform fragment of molecule number imol by the given rotation matrix, then translate by (x,y,z) in Angstroms

11.41 Go To Atom Widget Functions

11.41.1 post-go-to-atom-window

`post-go-to-atom-window` [function]

Post the Go To Atom Window.

11.41.2 go-to-atom-molecule-number

`go-to-atom-molecule-number` [function]

the go-to-atom molecule number

11.41.3 go-to-atom-chain-id

`go-to-atom-chain-id` [function]

the go-to-atom chain-id

11.41.4 go-to-atom-atom-name

`go-to-atom-atom-name` [function]

the go-to-atom atom name

11.41.5 go-to-atom-residue-number

`go-to-atom-residue-number` [function]

the go-to-atom residue number

11.41.6 go-to-atom-ins-code

`go-to-atom-ins-code` [function]

the go-to-atom insertion code

11.41.7 go-to-atom-alt-conf

`go-to-atom-alt-conf` [function]

the go-to-atom alt conf

11.41.8 set-go-to-atom-chain-residue-atom-name

`set-go-to-atom-chain-residue-atom-name` *t1_chain_id iresno t3_atom_name* [function]

Where:

- *t1_chain_id* is a string
- *iresno* is an integer number
- *t3_atom_name* is a string

set the go to atom specification

It seems important for swig that the char * arguments are const char *, not const gchar * (or else we get wrong type of argument error on (say) "A"

Returns: the success status of the go to. 0 for fail, 1 for success.

11.41.9 set-go-to-atom-chain-residue-atom-name-full

`set-go-to-atom-chain-residue-atom-name-full` *chain_id resno ins_code atom_name alt_conf* [function]

Where:

- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atom_name* is a string
- *alt_conf* is a string

set the go to (full) atom specification

It seems important for swig that the char * arguments are const char *, not const gchar * (or else we get wrong type of argument error on (say) `"A"`

Returns: the success status of the go to. 0 for fail, 1 for success.

11.41.10 set-go-to-atom-chain-residue-atom-name-no-redraw

`set-go-to-atom-chain-residue-atom-name-no-redraw` *t1 iresno t3 make_the_move_flag* [function]

Where:

- *t1* is a string
- *iresno* is an integer number
- *t3* is a string
- *make_the_move_flag* is an integer number

set go to atom but don't redraw

11.41.11 update-go-to-atom-from-current-position

`update-go-to-atom-from-current-position` [function]

update the Go To Atom widget entries to atom closest to screen centre.

11.41.12 atom-spec-to-atom-index

`atom-spec-to-atom-index` *mol chain resno atom_name* [function]

Where:

- *mol* is an integer number
- *chain* is a string
- *resno* is an integer number
- *atom_name* is a string

what is the atom index of the given atom?

11.41.13 full-atom-spec-to-atom-index

`full-atom-spec-to-atom-index` *imol chain resno inscode atom_name altloc* [function]

Where:

- *imol* is an integer number
- *chain* is a string
- *resno* is an integer number
- *inscode* is a string
- *atom_name* is a string
- *altloc* is a string

what is the atom index of the given atom?

11.41.14 update-go-to-atom-window-on-changed-mol

`update-go-to-atom-window-on-changed-mol` *imol* [function]

Where *imol* is an integer number

update the Go To Atom window

11.41.15 update-go-to-atom-window-on-new-mol

`update-go-to-atom-window-on-new-mol` [function]

update the Go To Atom window. This updates the option menu for the molecules.

11.41.16 set-go-to-atom-molecule

`set-go-to-atom-molecule` *imol* [function]

Where *imol* is an integer number

set the molecule for the Go To Atom

For dynarama callback sake. The widget/class knows which molecule that it was generated from, so in order to go to the molecule from dynarama, we first need to the the molecule - because

does not mention the molecule (see "Next/Previous Residue" for reasons for that). This function simply calls the graphics_info_t function of the same name.

Also used in scripting, where go-to-atom-chain-residue-atom-name does not mention the molecule number.

20090914-PE set-go-to-atom-molecule can be used in a script and it should change the go-to-atom-molecule in the Go To Atom dialog (if it is being displayed). This does mean, of course that using the ramachandran plot to centre on atoms will change the Go To Atom dialog. Maybe that is surprising (maybe not).

11.42 Map and Molecule Control

11.42.1 post-display-control-window

`post-display-control-window` [function]

display the Display Constrol window

11.42.2 set-map-displayed

`set-map-displayed` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the map displayed/undisplayed, 0 for off, 1 for on

11.42.3 set-mol-displayed

`set-mol-displayed` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the coordinates molecule displayed/undisplayed, 0 for off, 1 for on

11.42.4 set-display-only-model-mol

`set-display-only-model-mol` *imol* [function]

Where *imol* is an integer number

from all the model molecules, display only imol

This stops flashing/delayed animations with many molecules

11.42.5 set-mol-active

`set-mol-active` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the coordinates molecule active/inactve (clickable), 0 for off, 1 for on

11.42.6 mol-is-displayed

`mol-is-displayed` *imol* [function]

Where *imol* is an integer number

return the display state of molecule number imol

Returns: 1 for on, 0 for off

11.42.7 mol-is-active

`mol-is-active` *imol* [function]

Where *imol* is an integer number

return the active state of molecule number imol

Returns: 1 for on, 0 for off

11.42.8 map-is-displayed

`map-is-displayed` *imol* [function]

Where *imol* is an integer number

return the display state of molecule number imol

Returns: 1 for on, 0 for off

11.42.9 set-all-maps-displayed

`set-all-maps-displayed` *on_or_off* [function]

Where *on_or_off* is an integer number

if on_or_off is 0 turn off all maps displayed, for other values of on_or_off turn on all maps

11.42.10 set-all-models-displayed-and-active

`set-all-models-displayed-and-active` *on_or_off* [function]

Where *on_or_off* is an integer number

if on_or_off is 0 turn off all models displayed and active, for other values of on_or_off turn on all models.

11.42.11 show-spacegroup

`show-spacegroup` *imol* [function]

Where *imol* is an integer number

return the spacegroup of molecule number imol . Deprecated.

Returns: `"No Spacegroup"` when the spacegroup of a molecule has not been set.

11.43 Align and Mutate

11.43.1 align-and-mutate

`align-and-mutate` *imol chain_id fasta_maybe renumber_residues_flag* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *fasta_maybe* is a string
- *renumber_residues_flag* is an integer number

align and mutate the given chain to the given sequence

11.43.2 set-alignment-gap-and-space-penalty

`set-alignment-gap-and-space-penalty` *wgap wspace* [function]

Where:

- *wgap* is a number
- *wspace* is a number

set the penalty for affine gap and space when aligning, defaults -3.0 and -0.4

11.44 Renumber Residue Range

11.44.1 renumber-residue-range

`renumber-residue-range` *imol chain_id start_res last_res offset* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *start_res* is an integer number
- *last_res* is an integer number
- *offset* is an integer number

renumber the given residue range by offset residues

11.44.2 change-residue-number

`change-residue-number` *imol chain_id current_resno current_inscode new_resno new_inscode* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *current_resno* is an integer number
- *current_inscode* is a string
- *new_resno* is an integer number
- *new_inscode* is a string

change chain id, residue number or insertion code for given residue

11.45 Scripting Interface

11.45.1 probe-available-p

`probe-available-p` [function]

Can we run probe (was the executable variable set properly?) (predicate).

Returns: 1 for yes, 2 for no

11.45.2 post-scripting-window

`post-scripting-window` [function]

do nothing - compatibility function

11.45.3 post-scheme-scripting-window

`post-scheme-scripting-window` [function]

pop-up a scripting window for scheming

11.45.4 post-python-scripting-window

`post-python-scripting-window` [function]

pop-up a scripting window for pythoning

11.46 Monomer

11.46.1 get-coords-for-accession-code

`get-coords-for-accession-code` *code* [function]

Where *code* is a string

if possible, read in the new coords getting coords via web.

(no return value because get-url-str does not return one).

11.46.2 run-script

`run-script` *filename* [function]

Where *filename* is a string

run script file

11.46.3 run-guile-script

`run-guile-script` *filename* [function]

Where *filename* is a string

guile run script file

11.46.4 run-python-script

`run-python-script` *filename* [function]

Where *filename* is a string

run python script file

11.46.5 import-python-module

`import-python-module` *module_name use_namespace* [function]

Where:

- *module_name* is a string
- *use_namespace* is an integer number

import python module

11.47 Regularization and Refinement

11.47.1 add-planar-peptide-restraints

`add-planar-peptide-restraints` [function]

add a restraint on peptides to make them planar

This adds a 5 atom restraint that includes both CA atoms of the peptide. Use this rather than editting the mon_lib_list.cif file.

11.47.2 remove-planar-peptide-restraints

`remove-planar-peptide-restraints` [function]

remove restraints on peptides to make them planar.

11.47.3 set-use-trans-peptide-restraints

`set-use-trans-peptide-restraints` *on_off_state* [function]

Where *on_off_state* is an integer number

add a restraint on peptides to keep trans peptides trans

i.e. omega in trans-peptides is restraints to 180 degrees.

11.47.4 add-omega-torsion-restriants

`add-omega-torsion-restriants` [function]

add restraints on the omega angle of the peptides

(that is the torsion round the peptide bond). Omega angles that are closer to 0 than to 180 will be refined as cis peptides (and of course if omega is greater than 90 then the peptide will be refined as a trans peptide (this is the normal case).

11.47.5 remove-omega-torsion-restriants

`remove-omega-torsion-restriants` [function]

remove omega restraints on CIS and TRANS linked residues.

11.47.6 set-refinement-immediate-replacement

`set-refinement-immediate-replacement` *istate* [function]

Where *istate* is an integer number

set immediate replacement mode for refinement and regularization. You need this (call with istate=1) if you are scripting refinement/regularization

11.47.7 refinement-immediate-replacement-state

`refinement-immediate-replacement-state` [function]

query the state of the immediate replacement mode

11.47.8 set-residue-selection-flash-frames-number

`set-residue-selection-flash-frames-number` *i* [function]

Where *i* is an integer number

set the number of frames for which the selected residue range flashes

On fast computers, this can be set to higher than the default for more aesthetic appeal.

11.47.9 accept-regularizement

`accept-regularizement` [function]

accept the new positions of the regularized or refined residues

If you are scripting refinement and/or regularization, this is the function that you need to call after refine-zone or regularize-zone.

11.47.10 set-refine-with-torsion-restraints

`set-refine-with-torsion-restraints` *istate* [function]

Where *istate* is an integer number

turn on (or off) torsion restraints

Pass with istate=1 for on, istate=0 for off.

11.47.11 refine-with-torsion-restraints-state

`refine-with-torsion-restraints-state` [function]

return the state of above

11.47.12 set-matrix

`set-matrix` *f* [function]

Where *f* is a number

set the relative weight of the geometric terms to the map terms

The default is 60.

The higher the number the more weight that is given to the map terms but the resulting chi squared values are higher). This will be needed for maps generated from data not on (or close to) the absolute scale or maps that have been scaled (for example so that the sigma level has been scaled to 1.0).

11.47.13 matrix-state

`matrix-state` [function]

return the relative weight of the geometric terms to the map terms.

11.47.14 set-refine-auto-range-step

`set-refine-auto-range-step` *i* [function]

Where *i* is an integer number

change the +/- step for autoranging (default is 1)

Auto-ranging alow you to select a range from one button press, this allows you to set the number of residues either side of the clicked residue that becomes the selected zone

11.47.15 set-refine-max-residues

`set-refine-max-residues` *n* [function]

Where *n* is an integer number

set the heuristic fencepost for the maximum number of residues in the refinement/regularization residue range

Default is 20

11.47.16 refine-zone-atom-index-define

`refine-zone-atom-index-define` *imol ind1 ind2* [function]

Where:

- *imol* is an integer number
- *ind1* is an integer number
- *ind2* is an integer number

refine a zone based on atom indexing

11.47.17 refine-zone

`refine-zone` *imol chain_id resno1 resno2 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *resno2* is an integer number
- *altconf* is a string

refine a zone

presumes that imol_Refinement_Map has been set

11.47.18 refine-auto-range

`refine-auto-range` *imol chain_id resno1 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *altconf* is a string

refine a zone using auto-range

presumes that imol_Refinement_Map has been set

11.47.19 regularize-zone

`regularize-zone` *imol chain_id resno1 resno2 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *resno2* is an integer number
- *altconf* is a string

regularize a zone

Returns: a status, whether the regularisation was done or not. 0 for no, 1 for yes.

11.47.20 set-dragged-refinement-steps-per-frame

`set-dragged-refinement-steps-per-frame` *v* [function]

Where *v* is an integer number

set the number of refinement steps applied to the intermediate atoms each frame of graphics.

smaller numbers make the movement of the intermediate atoms slower, smoother, more elegant.

Default: 80.

11.47.21 dragged-refinement-steps-per-frame

`dragged-refinement-steps-per-frame` [function]

return the number of steps per frame in dragged refinement

11.47.22 set-refinement-refine-per-frame

`set-refinement-refine-per-frame` *istate* [function]

Where *istate* is an integer number

allow refinement of intermediate atoms after dragging, before displaying (default: 0, off).

An attempt to do something like xfit does, at the request of Frank von Delft.

Pass with istate=1 to enable this option.

11.47.23 refinement-refine-per-frame-state

`refinement-refine-per-frame-state` [function]

query the state of the above option

11.47.24 set-refinement-drag-elasticity

`set-refinement-drag-elasticity` *e* [function]

Where *e* is a number

the elasticity of the dragged atom in refinement mode.

Default 0.33

Bigger numbers mean bigger movement of the other atoms.

11.47.25 set-refine-ramachandran-angles

`set-refine-ramachandran-angles` *state* [function]

Where *state* is an integer number

turn on Ramachandran angles refinement in refinement and regularization

name consistent with

!?

11.47.26 set-fix-chiral-volumes-before-refinement

`set-fix-chiral-volumes-before-refinement` *istate* [function]

Where *istate* is an integer number

correct the sign of chiral volumes before commencing refinement?

Do we want to fix chiral volumes (by moving the chiral atom to the other side of the chiral plane if necessary). Default yes (1). Note: doesn't work currently.

11.47.27 check-chiral-volumes

`check-chiral-volumes` *imol* [function]

Where *imol* is an integer number

query the state of the above option

11.47.28 set-show-chiral-volume-errors-dialog

`set-show-chiral-volume-errors-dialog` *istate* [function]

Where *istate* is an integer number

For experienced Cooters who don't like Coot nannying about chiral volumes during refinement.

11.47.29 set-secondary-structure-restraints-type

`set-secondary-structure-restraints-type` *itype* [function]

Where *itype* is an integer number

set the type of secondary structure restraints

0 no sec str restraints

1 alpha helix restraints

2 beta strand restraints

11.47.30 secondary-structure-restraints-type

`secondary-structure-restraints-type` [function]

return the secondary structure restraints type

11.47.31 imol-refinement-map

`imol-refinement-map` [function]

the molecule number of the map used for refinement

Returns: the map number, if it has been set or there is only one map, return -1 on no map set (ambiguous) or no maps.

11.47.32 set-imol-refinement-map

`set-imol-refinement-map` *imol* [function]

Where *imol* is an integer number

set the molecule number of the map to be used for refinement/fitting.

Returns: imol on success, -1 on failure

11.47.33 does-residue-exist-p

`does-residue-exist-p` *imol chain_id resno inscode* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string

Does the residue exist? (Raw function)

Returns: 0 on not-exist, 1 on does exist.

11.47.34 add-extra-bond-restraint

`add-extra-bond-restraint` *imol chain_id_1 res_no_1 ins_code_1 atom_name_1 alt_conf_1 chain_id_2 res_no_2 ins_code_2 atom_name_2 alt_conf_2 bond_dist esd* [function]

Where:

- *imol* is an integer number
- *chain_id_1* is a string
- *res_no_1* is an integer number
- *ins_code_1* is a string
- *atom_name_1* is a string
- *alt_conf_1* is a string
- *chain_id_2* is a string
- *res_no_2* is an integer number
- *ins_code_2* is a string
- *atom_name_2* is a string
- *alt_conf_2* is a string
- *bond_dist* is a number
- *esd* is a number

add a user-define bond restraint

this extra restraint is used when the given atoms are selected in refinement or regularization.

Returns: the index of the new restraint.

Returns: -1 when the atoms were not found and no extra bond restraint was stored.

11.47.35 delete-all-extra-restraints

`delete-all-extra-restraints` *imol* [function]

Where *imol* is an integer number

clear out all the extra/user-defined restraints for molecule number imol

11.47.36 delete-extra-restraints-for-residue

`delete-extra-restraints-for-residue` *imol chain_id res_no ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string

clear out all the extra/user-defined restraints for this residue in molecule number imol

11.47.37 set-extra-restraints-prosmart-sigma-limits

`set-extra-restraints-prosmart-sigma-limits` *imol limit_high limit_low* [function]

Where:

- *imol* is an integer number
- *limit_high* is a number
- *limit_low* is a number

often we don't want to see all prosmart restraints, just the (big) violations

11.47.38 write-interpolated-extra-restraints

`write-interpolated-extra-restraints` *imol_1 imol_2 n_steps file_name_stub* [function]

Where:

- *imol_1* is an integer number
- *imol_2* is an integer number
- *n_steps* is an integer number
- *file_name_stub* is a string

proSMART interpolated restraints for model morphing

11.47.39 write-interpolated-models-and-extra-restraints

`write-interpolated-models-and-extra-restraints` *imol_1 imol_2 n_steps file_name_stub interpolation_mode* [function]

Where:

- *imol_1* is an integer number
- *imol_2* is an integer number

- *n_steps* is an integer number
- *file_name_stub* is a string
- *interpolation_mode* is an integer number

proSMART interpolated restraints for model morphing and write interpolated model

interpolation_mode is currently dummy - in due course I will addd torion angle interpolation.

11.47.40 set-use-only-extra-torsion-restraints-for-torsions

`set-use-only-extra-torsion-restraints-for-torsions` *state* [function]

Where *state* is an integer number

set use only extra torsion restraints for torsions

11.47.41 use-only-extra-torsion-restraints-for-torsions-state

`use-only-extra-torsion-restraints-for-torsions-state` [function]

return only-use-extra-torsion-restraints-for-torsions state

11.47.42 show-restraints-editor

`show-restraints-editor` *monomer_type* [function]

Where *monomer_type* is a string

show restraints editor

11.47.43 show-restraints-editor-by-index

`show-restraints-editor-by-index` *menu_item_index* [function]

Where *menu_item_index* is an integer number

show restraints editor using residue type index

11.47.44 write-restraints-cif-dictionary

`write-restraints-cif-dictionary` *monomer_type file_name* [function]

Where:

- *monomer_type* is a string
- *file_name* is a string

write cif restraints for monomer

11.48 Simplex Refinement Interface

11.48.1 fit-residue-range-to-map-by-simplex

`fit-residue-range-to-map-by-simplex` *res1 res2 altloc chain_id imol imol_for_map* [function]

Where:

- *res1* is an integer number

- *res2* is an integer number
- *altloc* is a string
- *chain_id* is a string
- *imol* is an integer number
- *imol_for_map* is an integer number

refine residue range using simplex optimization

11.48.2 score-residue-range-fit-to-map

`score-residue-range-fit-to-map` *res1 res2 altloc chain_id imol imol_for_map* [function]

Where:

- *res1* is an integer number
- *res2* is an integer number
- *altloc* is a string
- *chain_id* is a string
- *imol* is an integer number
- *imol_for_map* is an integer number

simply score the residue range fit to map

11.49 Nomenclature Errors

11.49.1 fix-nomenclature-errors

`fix-nomenclature-errors` *imol* [function]

Where *imol* is an integer number

fix nomenclature errors in molecule number imol

Returns: the number of resides altered.

11.49.2 set-nomenclature-errors-on-read

`set-nomenclature-errors-on-read` *mode* [function]

Where *mode* is a string

set way nomenclature errors should be handled on reading coordinates.

mode should be "auto-correct", "ignore", "prompt". The default is "prompt"

11.50 Atom Info Interface

11.50.1 output-atom-info-as-text

`output-atom-info-as-text` *imol chain_id resno ins_code atname altconf* [function]

Where:

- *imol* is an integer number

- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atname* is a string
- *altconf* is a string

output to the terminal the Atom Info for the give atom specs

11.51 Residue Info

11.51.1 residue-info-dialog

`residue-info-dialog` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

show residue info dialog for given residue

11.52 Residue Environment Functions

11.52.1 set-show-environment-distances

`set-show-environment-distances` *state* [function]

Where *state* is an integer number

show environment distances. If state is 0, distances are turned off, otherwise distances are turned on.

11.52.2 set-show-environment-distances-bumps

`set-show-environment-distances-bumps` *state* [function]

Where *state* is an integer number

show bumps environment distances. If state is 0, bump distances are turned off, otherwise bump distances are turned on.

11.52.3 set-show-environment-distances-h-bonds

`set-show-environment-distances-h-bonds` *state* [function]

Where *state* is an integer number

show H-bond environment distances. If state is 0, bump distances are turned off, otherwise H-bond distances are turned on.

11.52.4 show-environment-distances-state

`show-environment-distances-state` [function]

show the state of display of the environment distances

11.52.5 set-environment-distances-distance-limits

`set-environment-distances-distance-limits` *min_dist max_dist* [function]

Where:

- *min_dist* is a number
- *max_dist* is a number

min and max distances for the environment distances

11.53 Pointer Functions

11.53.1 set-show-pointer-distances

`set-show-pointer-distances` *istate* [function]

Where *istate* is an integer number

turn on (or off) the pointer distance by passing 1 (or 0).

11.53.2 show-pointer-distances-state

`show-pointer-distances-state` [function]

show the state of display of the pointer distances

11.54 Zoom Functions

11.54.1 scale-zoom

`scale-zoom` *f* [function]

Where *f* is a number

scale the view by f

external (scripting) interface (with redraw)

11.54.2 zoom-factor

`zoom-factor` [function]

return the current zoom factor

11.54.3 set-smooth-scroll-do-zoom

`set-smooth-scroll-do-zoom` *i* [function]

Where *i* is an integer number

set smooth scroll with zoom

11.54.4 smooth-scroll-do-zoom

`smooth-scroll-do-zoom` [function]

return the state of the above system

11.55 CNS Data Functions

11.55.1 handle-cns-data-file

`handle-cns-data-file` *filename imol* [function]

Where:

- *filename* is a string
- *imol* is an integer number

read CNS data (currently only a placeholder)

11.55.2 handle-cns-data-file-with-cell

`handle-cns-data-file-with-cell` *filename imol a b c alpha beta gamma spg_info* [function]

Where:

- *filename* is a string
- *imol* is an integer number
- *a* is a number
- *b* is a number
- *c* is a number
- *alpha* is a number
- *beta* is a number
- *gamma* is a number
- *spg_info* is a string

read CNS data (currently only a placeholder)

a, b,c are in Angstroems. alpha, beta, gamma are in degrees. spg is the space group info, either ;-delimited symmetry operators or the space group name

11.56 mmCIF Functions

11.56.1 open-cif-dictionary-file-selector-dialog

`open-cif-dictionary-file-selector-dialog` [function]

open the cif dictionary file selector dialog

11.57 SHELXL Functions

11.57.1 read-shelx-ins-file

`read-shelx-ins-file` *filename recentre_flag* [function]

Where:

- *filename* is a string
- *recentre_flag* is an integer number

read a SHELXL .ins file

11.57.2 write-shelx-ins-file

`write-shelx-ins-file` *imol filename* [function]

Where:

- *imol* is an integer number
- *filename* is a string

write a SHELXL .ins file for molecule number imol

11.58 Validation Functions

11.58.1 difference-map-peaks

`difference-map-peaks` *imol imol_coords level max_closeness do_positive_level_flag do_negative_level_flag* [function]

Where:

- *imol* is an integer number
- *imol_coords* is an integer number
- *level* is a number
- *max_closeness* is a number
- *do_positive_level_flag* is an integer number
- *do_negative_level_flag* is an integer number

generate a list of difference map peaks

peaks within max_closeness (2.0 A typically) of a larger peak are not listed.

11.58.2 gln-asn-b-factor-outliers

`gln-asn-b-factor-outliers` *imol* [function]

Where *imol* is an integer number

Make a gui for GLN adn ASN B-factor outiers, compairing the O and N temperatur factors difference to the distribution of temperature factors from the other atoms.

11.59 Ramachandran Plot Functions

11.59.1 do-ramachandran-plot

`do-ramachandran-plot` *imol* [function]

Where *imol* is an integer number

Ramachandran plot for molecule number imol.

11.59.2 set-kleywegt-plot-n-diffs

`set-kleywegt-plot-n-diffs` *n_diffs* [function]

Where *n_diffs* is an integer number

set the number of biggest difference arrows on the Kleywegt plot.

11.59.3 set-ramachandran-plot-contour-levels

`set-ramachandran-plot-contour-levels` *level_prefered level_allowed* [function]

Where:

- *level_prefered* is a number
- *level_allowed* is a number

set the contour levels for theremachandran plot, default values are 0.02 (prefered) 0.002 (allowed)

11.59.4 set-ramachandran-plot-background-block-size

`set-ramachandran-plot-background-block-size` *blocksize* [function]

Where *blocksize* is a number

set the ramachandran plot background block size.

Smaller is smoother but slower. Should be divisible exactly into

11.59.5 ramachandran-plot-differences

`ramachandran-plot-differences` *imol1 imol2* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number

2 molecule ramachandran plot (NCS differences) a.k.a. A Kleywegt Plot.

11.59.6 ramachandran-plot-differences-by-chain

`ramachandran-plot-differences-by-chain` *imol1 imol2 a_chain b_chain* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *a_chain* is a string
- *b_chain* is a string

A chain-specific Kleywegt Plot.

11.60 Sequence View Interface

11.60.1 do-sequence-view

`do-sequence-view` *imol* [function]

Where *imol* is an integer number

display the sequence view dialog for molecule number imol

11.61 Atom Labelling

11.61.1 set-brief-atom-labels

`set-brief-atom-labels` *istat* [function]

Where *istat* is an integer number

use brief atom names for on-screen labels

call with istat=1 to use brief labels, istat=0 for normal labels

11.61.2 brief-atom-labels-state

`brief-atom-labels-state` [function]

the brief atom label state

11.62 Screen Rotation

11.62.1 rotate-y-scene

`rotate-y-scene` *nsteps stepsize* [function]

Where:

- *nsteps* is an integer number
- *stepsize* is a number

rotate view round y axis stepsize degrees for nstep such steps

11.62.2 rotate-x-scene

`rotate-x-scene` *nsteps stepsize* [function]

Where:

- *nsteps* is an integer number
- *stepsize* is a number

rotate view round x axis stepsize degrees for nstep such steps

11.62.3 rotate-z-scene

`rotate-z-scene` *nsteps stepsize* [function]

Where:

- *nsteps* is an integer number
- *stepsize* is a number

rotate view round z axis stepsize degrees for nstep such steps

11.62.4 spin-zoom-trans

`spin-zoom-trans` *axis nstep stepsize zoom_by x_rel y_rel z_rel* [function]

Where:

- *axis* is an integer number

- *nstep* is an integer number
- *stepsize* is a number
- *zoom_by* is a number
- *x_rel* is a number
- *y_rel* is a number
- *z_rel* is a number

Bells and whistles rotation.

spin, zoom and translate.

where axis is either x,y or z, stepsize is in degrees, zoom_by and x_rel etc are how much zoom, x,y,z should have changed by after nstep steps.

11.63 Screen Translation

11.63.1 translate-scene-x

`translate-scene-x` *nsteps* [function]

Where *nsteps* is an integer number

translate rotation centre relative to screen axes for nsteps

11.63.2 translate-scene-y

`translate-scene-y` *nsteps* [function]

Where *nsteps* is an integer number

translate rotation centre relative to screen axes for nsteps

11.63.3 translate-scene-z

`translate-scene-z` *nsteps* [function]

Where *nsteps* is an integer number

translate rotation centre relative to screen axes for nsteps

11.64 Views Interface

11.64.1 add-view-here

`add-view-here` *view_name* [function]

Where *view_name* is a string

return the view number

11.64.2 add-view-raw

`add-view-raw` *rcx rcy rcz quat1 quat2 quat3 quat4 zoom view_name* [function]

Where:

- *rcx* is a number
- *rcy* is a number

- *rcz* is a number
- *quat1* is a number
- *quat2* is a number
- *quat3* is a number
- *quat4* is a number
- *zoom* is a number
- *view_name* is a string

return the view number

11.64.3 remove-named-view

`remove-named-view` *view_name* [function]

Where *view_name* is a string

the view with the given name

11.64.4 remove-view

`remove-view` *view_number* [function]

Where *view_number* is an integer number

the given view number

11.64.5 add-view-description

`add-view-description` *view_number description* [function]

Where:

- *view_number* is an integer number
- *description* is a string

Add a view description/annotation to the give view number.

11.64.6 add-action-view

`add-action-view` *view_name action_function* [function]

Where:

- *view_name* is a string
- *action_function* is a string

add a view (not add to an existing view) that does something (e.g. displays or undisplays a molecule) rather than move the graphics.

Returns: the view number for this (new) view.

11.64.7 insert-action-view-after-view

`insert-action-view-after-view` *view_number view_name action_function* [function]

Where:

- *view_number* is an integer number

- *view_name* is a string
- *action_function* is a string

add an action view after the view of the given view number

Returns: the view number for this (new) view.

11.64.8 save-views

`save-views` *view_file_name* [function]

Where *view_file_name* is a string

save views to view_file_name

11.64.9 clear-all-views

`clear-all-views` [function]

Clear the view list.

11.65 Background Colour

11.65.1 set-background-colour

`set-background-colour` *red green blue* [function]

Where:

- *red* is a number
- *green* is a number
- *blue* is a number

set the background colour

red, green and blue are numbers between 0.0 and 1.0

11.65.2 redraw-background

`redraw-background` [function]

re draw the background colour when switching between mono and stereo

11.65.3 background-is-black-p

`background-is-black-p` [function]

is the background black (or nearly black)?

Returns: 1 if the background is black (or nearly black), else return 0.

11.66 Ligand Fitting Functions

11.66.1 set-ligand-acceptable-fit-fraction

`set-ligand-acceptable-fit-fraction` *f* [function]

Where *f* is a number

set the fraction of atoms which must be in positive density after a ligand fit

11.66.2 set-ligand-cluster-sigma-level

`set-ligand-cluster-sigma-level` *f* [function]

Where *f* is a number

set the default sigma level that the map is searched to find potential ligand sites

11.66.3 set-ligand-flexible-ligand-n-samples

`set-ligand-flexible-ligand-n-samples` *i* [function]

Where *i* is an integer number

set the number of conformation samples

big ligands require more samples. Default 10.

11.66.4 set-find-ligand-n-top-ligands

`set-find-ligand-n-top-ligands` *n* [function]

Where *n* is an integer number

search the top n sites for ligands.

Default 10.

11.66.5 set-find-ligand-multi-solutions-per-cluster

`set-find-ligand-multi-solutions-per-cluster` *lim_1 lim_2* [function]

Where:

- *lim_1* is a number
- *lim_2* is a number

allow multiple ligand solutions per cluster.

The first limit is the fraction of the top scored positions that go on to correlation scoring (closer to 1 means less and faster - default 0.7).

The second limit is the fraction of the top correlation score that is considered interesting. Limits the number of solutions displayed to user. Default 0.9.

There is currently no chi-angle set redundancy filtering - I suspect that there should be.

Nino-mode.

11.66.6 set-find-ligand-mask-waters

`set-find-ligand-mask-waters` *istate* [function]

Where *istate* is an integer number

how shall we treat the waters during ligand fitting?

pass with istate=1 for waters to mask the map in the same way that protein atoms do.

11.66.7 set-ligand-search-protein-molecule

`set-ligand-search-protein-molecule` *imol* [function]

Where *imol* is an integer number

set the protein molecule for ligand searching

11.66.8 set-ligand-search-map-molecule

`set-ligand-search-map-molecule` *imol_map* [function]

Where *imol_map* is an integer number

set the map molecule for ligand searching

11.66.9 add-ligand-search-ligand-molecule

`add-ligand-search-ligand-molecule` *imol_ligand* [function]

Where *imol_ligand* is an integer number

add a rigid ligand molecule to the list of ligands to search for in ligand searching

11.66.10 add-ligand-search-wiggly-ligand-molecule

`add-ligand-search-wiggly-ligand-molecule` *imol_ligand* [function]

Where *imol_ligand* is an integer number

add a flexible ligand molecule to the list of ligands to search for in ligand searching

11.66.11 set-find-ligand-here-cluster

`set-find-ligand-here-cluster` *state* [function]

Where *state* is an integer number

Allow the user a scripting means to find ligand at the rotation centre.

11.66.12 ligand-expert

`ligand-expert` [function]

this sets the flag to have expert option ligand entries in the Ligand Searching dialog

11.66.13 do-find-ligands-dialog

`do-find-ligands-dialog` [function]

display the find ligands dialog

if maps, coords and ligands are available, that is.

11.66.14 match-ligand-atom-names

`match-ligand-atom-names` *imol_ligand chain_id_ligand resno_ligand ins_code_ligand imol_reference chain_id_reference resno_reference ins_code_reference* [function]

Where:

- *imol_ligand* is an integer number
- *chain_id_ligand* is a string
- *resno_ligand* is an integer number
- *ins_code_ligand* is a string
- *imol_reference* is an integer number
- *chain_id_reference* is a string

- *resno_reference* is an integer number
- *ins_code_reference* is a string

Overlap residue with "template"-based matching.

Overlap the first residue in imol_ligand onto the residue specified by the reference parameters. Use graph matching, not atom names.

Match ligand atom names

By using graph matching, make the names of the atoms of the given ligand/residue match those of the reference residue/ligand as closely as possible - where there would be an atom name clash, invent a new atom name.

Returns: success status, False = failed to find residue in either imol_ligand or imo_ref. If success, return the RT operator.

11.66.15 match-ligand-atom-names-to-comp-id

`match-ligand-atom-names-to-comp-id` *imol_ligand chain_id_ligand resno_ligand ins_code_ligand comp_id_ref* [function]

Where:

- *imol_ligand* is an integer number
- *chain_id_ligand* is a string
- *resno_ligand* is an integer number
- *ins_code_ligand* is a string
- *comp_id_ref* is a string

Match ligand atom names to a reference ligand type (comp_id)

By using graph matching, make the names of the atoms of the given ligand/residue match those of the reference ligand from the geometry store as closely as possible. Where there would be an atom name clash, invent a new atom name.

This doesn't create a new dictionary for the selected ligand - and that's a big problem (see match_residue_and_dictionary).

11.66.16 flip-ligand

`flip-ligand` *imol chain_id resno* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number

flip the ligand (usually active residue) around its eigen vectors to the next flip number. Immediate replacement (like flip peptide).

11.67 Water Fitting Functions

11.67.1 wrapped-create-find-waters-dialog

`wrapped-create-find-waters-dialog` [function]

create a dialog for water fitting

11.67.2 renumber-waters

`renumber-waters` *imol* [function]

Where *imol* is an integer number

Renumber the waters of molecule number imol with consecutive numbering.

11.67.3 execute-find-waters-real

`execute-find-waters-real` *imol_for_map imol_for_protein new_waters_mol_flag rmsd_cut_off* [function]

Where:

- *imol_for_map* is an integer number
- *imol_for_protein* is an integer number
- *new_waters_mol_flag* is an integer number
- *rmsd_cut_off* is a number

find waters

11.67.4 move-waters-to-around-protein

`move-waters-to-around-protein` *imol* [function]

Where *imol* is an integer number

move waters of molecule number imol so that they are around the protein.

Returns: the number of moved waters.

11.67.5 move-hetgroups-to-around-protein

`move-hetgroups-to-around-protein` *imol* [function]

Where *imol* is an integer number

move all hetgroups (including waters) of molecule number imol so that they are around the protein.

11.67.6 max-water-distance

`max-water-distance` *imol* [function]

Where *imol* is an integer number

return the maximum minimum distance of any water atom to any protein atom - used in validation of move_waters_to_around_protein() funtion.

11.67.7 set-water-check-spherical-variance-limit

`set-water-check-spherical-variance-limit` *f* [function]

Where *f* is a number

set the limit of interesting variance, above which waters are listed (otherwise ignored)

default 0.12.

11.67.8 set-ligand-water-to-protein-distance-limits

`set-ligand-water-to-protein-distance-limits` *f1 f2* [function]

Where:

- *f1* is a number
- *f2* is a number

set ligand to protein distance limits

f1 is the minimum distance, f2 is the maximum distance

11.67.9 set-ligand-water-n-cycles

`set-ligand-water-n-cycles` *i* [function]

Where *i* is an integer number

set the number of cycles of water searching

11.67.10 execute-find-blobs

`execute-find-blobs` *imol_model imol_for_map cut_off interactive_flag* [function]

Where:

- *imol_model* is an integer number
- *imol_for_map* is an integer number
- *cut_off* is a number
- *interactive_flag* is an integer number

find blobs

11.67.11 split-water

`split-water` *imol chain_id res_no ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string

split the given water and fit to map.

If refinement map is not defined, don't do anything.

If there is more than one atom in the specified resiue, don't do anything.

If the given atom does not have an alt conf of `""`, don't do anything.

11.68 Bond Representation

11.68.1 set-default-bond-thickness

`set-default-bond-thickness` *t* [function]

Where *t* is an integer number

set the default thickness for bonds (e.g. in ~/.coot)

11.68.2 set-bond-thickness

`set-bond-thickness` *imol t* [function]

Where:

- *imol* is an integer number
- *t* is a number

set the thickness of the bonds in molecule number imol to t pixels

11.68.3 set-bond-thickness-intermediate-atoms

`set-bond-thickness-intermediate-atoms` *t* [function]

Where *t* is a number

set the thickness of the bonds of the intermediate atoms to t pixels

11.68.4 set-bond-colour-rotation-for-molecule

`set-bond-colour-rotation-for-molecule` *imol f* [function]

Where:

- *imol* is an integer number
- *f* is a number

set bond colour for molecule

11.68.5 get-bond-colour-rotation-for-molecule

`get-bond-colour-rotation-for-molecule` *imol* [function]

Where *imol* is an integer number

get the bond colour for molecule.

Return -1 on err (bad molecule number)

11.68.6 set-default-representation-type

`set-default-representation-type` *type* [function]

Where *type* is an integer number

set the default represenation type (default 1).

11.68.7 get-default-bond-thickness

`get-default-bond-thickness` [function]

get the default thickness for bonds

11.68.8 set-draw-zero-occ-markers

`set-draw-zero-occ-markers` *status* [function]

Where *status* is an integer number

set status of drawing zero occupancy markers.

default status is 1.

11.68.9 set-draw-cis-peptide-markups

`set-draw-cis-peptide-markups` *status* [function]

Where *status* is an integer number

set status of drawing cis-peptide markups

default status is 1.

11.68.10 set-draw-hydrogens

`set-draw-hydrogens` *imol istat* [function]

Where:

- *imol* is an integer number
- *istat* is an integer number

set the hydrogen drawing state. istat = 0 is hydrogens off, istat = 1: show hydrogens

11.68.11 draw-hydrogens-state

`draw-hydrogens-state` *imol* [function]

Where *imol* is an integer number

the state of draw hydrogens for molecule number imol.

return -1 on bad imol.

11.68.12 set-draw-stick-mode-atoms

`set-draw-stick-mode-atoms` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

draw little coloured balls on atoms

turn off with state = 0

turn on with state = 1

11.68.13 graphics-to-ca-representation

`graphics-to-ca-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol as CAs

11.68.14 graphics-to-ca-plus-ligands-representation

`graphics-to-ca-plus-ligands-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol as CA + ligands

11.68.15 graphics-to-ca-plus-ligands-and-sidechains-representation

`graphics-to-ca-plus-ligands-and-sidechains-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol as CA + ligands + sidechains

11.68.16 graphics-to-bonds-no-waters-representation

`graphics-to-bonds-no-waters-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol with no waters

11.68.17 graphics-to-bonds-representation

`graphics-to-bonds-representation` *mol* [function]

Where *mol* is an integer number

draw molecule number imol with normal bonds

11.68.18 graphics-to-ca-plus-ligands-sec-struct-representation

`graphics-to-ca-plus-ligands-sec-struct-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol with CA bonds in secondary structure representation and ligands

11.68.19 graphics-to-sec-struct-bonds-representation

`graphics-to-sec-struct-bonds-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol with bonds in secondary structure representation

11.68.20 graphics-to-rainbow-representation

`graphics-to-rainbow-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol in Jones' Rainbow

11.68.21 graphics-to-b-factor-representation

`graphics-to-b-factor-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol coloured by B-factor

11.68.22 graphics-to-b-factor-cas-representation

`graphics-to-b-factor-cas-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol coloured by B-factor, CA + ligands

11.68.23 graphics-to-occupancy-representation

`graphics-to-occupancy-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol coloured by occupancy

11.68.24 graphics-to-user-defined-atom-colours-representation

`graphics-to-user-defined-atom-colours-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol in CA+Ligands mode coloured by user-defined atom colours

11.68.25 graphics-to-user-defined-atom-colours-all-atoms-representation

`graphics-to-user-defined-atom-colours-all-atoms-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol all atoms coloured by user-defined atom colours

11.68.26 graphics-molecule-bond-type

`graphics-molecule-bond-type` *imol* [function]

Where *imol* is an integer number

what is the bond drawing state of molecule number imol

11.68.27 set-b-factor-bonds-scale-factor

`set-b-factor-bonds-scale-factor` *imol f* [function]

Where:

- *imol* is an integer number
- *f* is a number

scale the colours for colour by b factor representation

11.68.28 change-model-molecule-representation-mode

`change-model-molecule-representation-mode` *up_or_down* [function]

Where *up_or_down* is an integer number

change the representation of the model molecule closest to the centre of the screen

11.68.29 set-use-grey-carbons-for-molecule

`set-use-grey-carbons-for-molecule` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the carbon atoms for molecule imol be grey

11.68.30 set-grey-carbon-colour

`set-grey-carbon-colour` *imol r g b* [function]

Where:

- *imol* is an integer number
- *r* is a number
- *g* is a number
- *b* is a number

set the colour for the carbon atoms

can be not grey if you desire, r, g, b in the range 0 to 1.

11.68.31 make-ball-and-stick

`make-ball-and-stick` *imol atom_selection_str bond_thickness sphere_size do_spheres_flag* [function]

Where:

- *imol* is an integer number
- *atom_selection_str* is a string
- *bond_thickness* is a number
- *sphere_size* is a number
- *do_spheres_flag* is an integer number

make a ball and stick representation of imol given atom selection

e.g. (make-ball-and-stick 0 `"/1"` 0.15 0.25 1)

11.68.32 clear-ball-and-stick

`clear-ball-and-stick` *imol* [function]

Where *imol* is an integer number

clear ball and stick representation of molecule number imol

11.68.33 additional-representation-by-string

`additional-representation-by-string` *imol atom_selection representation_type bonds_box_type bond_width draw_hydrogens_flag* [function]

Where:

- *imol* is an integer number

- *atom_selection* is a string
- *representation_type* is an integer number
- *bonds_box_type* is an integer number
- *bond_width* is a number
- *draw_hydrogens_flag* is an integer number

return the index of the additional representation. Return -1 on error

11.68.34 additional-representation-by-attributes

`additional-representation-by-attributes` *imol chain_id resno_start resno_end ins_code representation_type bonds_box_type bond_width draw_hydrogens_flag* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number
- *ins_code* is a string
- *representation_type* is an integer number
- *bonds_box_type* is an integer number
- *bond_width* is a number
- *draw_hydrogens_flag* is an integer number

return the index of the additional representation.

Returns: -1 on error.

11.69 Dots Representation

11.69.1 dots

`dots` *imol atom_selection_str dots_object_name dot_density sphere_size_scale* [function]

Where:

- *imol* is an integer number
- *atom_selection_str* is a string
- *dots_object_name* is a string
- *dot_density* is a number
- *sphere_size_scale* is a number

display dotted surface

return a generic objects handle (which can be used to remove later)

11.69.2 set-dots-colour

`set-dots-colour` *imol r g b* [function]

Where:

- *imol* is an integer number
- *r* is a number
- *g* is a number
- *b* is a number

set the colour of the surface dots of the imol-th molecule to be the given single colour

r,g,b are values between 0.0 and 1.0

11.69.3 unset-dots-colour

`unset-dots-colour` *imol* [function]

Where *imol* is an integer number

no longer set the dots of molecule imol to a single colour

i.e. go back to element-based colours.

11.69.4 clear-dots

`clear-dots` *imol dots_handle* [function]

Where:

- *imol* is an integer number
- *dots_handle* is an integer number

clear dots in imol with dots_handle

11.69.5 clear-dots-by-name

`clear-dots-by-name` *imol dots_object_name* [function]

Where:

- *imol* is an integer number
- *dots_object_name* is a string

clear the first dots object for imol with given name

11.69.6 n-dots-sets

`n-dots-sets` *imol* [function]

Where *imol* is an integer number

return the number of dots sets for molecule number imol

11.70 Pep-flip Interface

11.70.1 pepflip

`pepflip` *imol chain_id resno inscode altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altconf* is a string

pepflip the given residue

11.71 Rigid Body Refinement Interface

11.71.1 rigid-body-refine-zone

`rigid-body-refine-zone` *reso_start resno_end chain_id imol* [function]

Where:

- *reso_start* is an integer number
- *resno_end* is an integer number
- *chain_id* is a string
- *imol* is an integer number

setup rigid body refine zone

where we set the atom selection holders according to the arguments and then call execute_rigid_body_refine()

11.71.2 set-rigid-body-fit-acceptable-fit-fraction

`set-rigid-body-fit-acceptable-fit-fraction` *f* [function]

Where *f* is a number

set rigid body fraction of atoms in positive density

11.72 Add Terminal Residue Functions

11.72.1 set-add-terminal-residue-immediate-addition

`set-add-terminal-residue-immediate-addition` *i* [function]

Where *i* is an integer number

set immediate addition of terminal residue

call with i=1 for immediate addtion

11.72.2 add-terminal-residue

`add-terminal-residue` *imol chain_id residue_number residue_type immediate_add* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *residue_number* is an integer number
- *residue_type* is a string
- *immediate_add* is an integer number

Add a terminal residue.

residue type can be "auto" and immediate_add is recommended to be 1.

return 0 on failure, 1 on success

11.72.3 add-terminal-residue-using-phi-psi

`add-terminal-residue-using-phi-psi` *imol chain_id res_no residue_type phi psi* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *residue_type* is a string
- *phi* is a number
- *psi* is a number

Add a terminal residue using given phi and psi angles.

11.72.4 set-add-terminal-residue-default-residue-type

`set-add-terminal-residue-default-residue-type` *type* [function]

Where *type* is a string

set the residue type of an added terminal residue.

11.72.5 set-add-terminal-residue-do-post-refine

`set-add-terminal-residue-do-post-refine` *istat* [function]

Where *istat* is an integer number

set a flag to run refine zone on terminal residues after an addition.

11.72.6 add-terminal-residue-do-post-refine-state

`add-terminal-residue-do-post-refine-state` [function]

what is the value of the previous flag?

11.73 Delete Residues

11.73.1 delete-residue-range

`delete-residue-range` *imol chain_id resno_start end_resno* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *end_resno* is an integer number

delete residue range

11.73.2 delete-residue

`delete-residue` *imol chain_id resno inscode* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string

delete residue

11.73.3 delete-residue-with-full-spec

`delete-residue-with-full-spec` *imol imodel chain_id resno inscode altloc* [function]

Where:

- *imol* is an integer number
- *imodel* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altloc* is a string

delete residue with altconf

11.73.4 delete-residue-hydrogens

`delete-residue-hydrogens` *imol chain_id resno inscode altloc* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altloc* is a string

delete hydrogen atoms in residue

11.73.5 delete-atom

`delete-atom` *imol chain_id resno ins_code at_name altloc* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *at_name* is a string
- *altloc* is a string

delete atom in residue

11.73.6 delete-residue-sidechain

`delete-residue-sidechain` *imol chain_id resno ins_code do_delete_dialog* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *do_delete_dialog* is an integer number

delete all atoms in residue that are not main chain or CB

11.73.7 delete-hydrogens

`delete-hydrogens` *imol* [function]

Where *imol* is an integer number

delete all hydrogens in molecule,

Returns: number of hydrogens deleted.

11.74 Mainchain Building Functions

11.74.1 db-mainchain

`db-mainchain` *imol chain_id iresno_start iresno_end direction* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *iresno_start* is an integer number
- *iresno_end* is an integer number
- *direction* is a string

CA -> mainchain conversion.

direction is either "forwards" or "backwards"

return the new molecule number

11.75 Rotamer Functions

11.75.1 set-rotamer-search-mode

`set-rotamer-search-mode` *mode* [function]

Where *mode* is an integer number

set the mode of rotamer search, options are (ROTAMERSEARCHAUTOMATIC), (ROTAMERSEARCHLOWRES) (aka. "backrub rotamers"), (ROTAMERSEARCHHIGHRES) (with rigid body fitting)

11.75.2 set-rotamer-lowest-probability

`set-rotamer-lowest-probability` *f* [function]

Where *f* is a number

For Dunbrack rotamers, set the lowest probability to be considered. Set as a percentage i.e. 1.00 is quite low. For Richardson Rotamers, this has no effect.

11.75.3 set-rotamer-check-clashes

`set-rotamer-check-clashes` *i* [function]

Where *i* is an integer number

set a flag: 0 is off, 1 is on

11.75.4 auto-fit-best-rotamer

`auto-fit-best-rotamer` *resno altloc insertion_code chain_id imol_coords imol_map clash_flag lowest_probability* [function]

Where:

- *resno* is an integer number
- *altloc* is a string
- *insertion_code* is a string
- *chain_id* is a string
- *imol_coords* is an integer number
- *imol_map* is an integer number
- *clash_flag* is an integer number
- *lowest_probability* is a number

auto fit by rotamer search.

return the score, for some not very good reason. clash_flag determines if we use clashes with other residues in the score for this rotamer (or not). It would be cool to call this from a script that went residue by residue along a (newly-built) chain (now available).

11.75.5 set-auto-fit-best-rotamer-clash-flag

`set-auto-fit-best-rotamer-clash-flag` *i* [function]

Where *i* is an integer number

set the clash flag for rotamer search

And this functions for [pre-setting] the variables for auto_fit_best_rotamer called interactively (using a graphics_info_t function). 0 off, 1 on.

11.75.6 n-rotamers

`n-rotamers` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

return the number of rotamers for this residue - return -1 on no residue found.

11.75.7 set-residue-to-rotamer-number

`set-residue-to-rotamer-number` *imol chain_id resno ins_code alt_conf rotamer_number* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *alt_conf* is a string
- *rotamer_number* is an integer number

set the residue specified to the rotamer number specifed.

11.75.8 set-residue-to-rotamer-name

`set-residue-to-rotamer-name` *imol chain_id resno ins_code alt_conf rotamer_name* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *alt_conf* is a string
- *rotamer_name* is a string

set the residue specified to the rotamer name specified.

(rotamer names are the Richardson rotamer names.)

return value is 0 if atoms were not moved (e.g. because rotamer-name was not know)

11.75.9 fill-partial-residues

`fill-partial-residues` *imol* [function]

Where *imol* is an integer number

fill all the residues of molecule number imol that have missing atoms.

To be used to remove the effects of chainsaw.

11.76 180 Flip Side chain

11.76.1 do-180-degree-side-chain-flip

`do-180-degree-side-chain-flip` *imol chain_id resno inscode altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altconf* is a string

rotate 180 degrees round the last chi angle

11.77 Mutate Functions

11.77.1 setup-mutate-auto-fit

`setup-mutate-auto-fit` *state* [function]

Where *state* is an integer number

Mutate then fit to map.

that we have a map define is checked first

11.77.2 mutate

`mutate` *imol chain_id ires inscode target_res_type* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *ires* is an integer number
- *inscode* is a string
- *target_res_type* is a string

mutate a given residue

target_res_type is a three-letter-code.

Return 1 on a good mutate.

11.77.3 mutate-base

`mutate-base` *imol chain_id res_no ins_code res_type* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *res_type* is a string

mutate a base. return success status, 1 for a good mutate.

11.77.4 set-mutate-auto-fit-do-post-refine

`set-mutate-auto-fit-do-post-refine` *istate* [function]

Where *istate* is an integer number

Do you want Coot to automatically run a refinement after every mutate and autofit?

1 for yes, 0 for no.

11.77.5 mutate-auto-fit-do-post-refine-state

`mutate-auto-fit-do-post-refine-state` [function]

what is the value of the previous flag?

11.77.6 set-rotamer-auto-fit-do-post-refine

`set-rotamer-auto-fit-do-post-refine` *istate* [function]

Where *istate* is an integer number

Do you want Coot to automatically run a refinement after every rotamer autofit?

1 for yes, 0 for no.

11.77.7 rotamer-auto-fit-do-post-refine-state

`rotamer-auto-fit-do-post-refine-state` [function]

what is the value of the previous flag?

11.77.8 mutate-single-residue-by-serial-number

`mutate-single-residue-by-serial-number` *ires_ser chain_id imol target_res_type* [function]

Where:

- *ires_ser* is an integer number
- *chain_id* is a string
- *imol* is an integer number
- *target_res_type* is a character

an alternate interface to mutation of a singe residue.

ires-ser is the serial number of the residue, not the seqnum There 2 functions don't make backups, but

does - CHECKME Hence

is for use as a "one-by-one" type and the following 2 by wrappers that muate either a residue range or a whole chain

Note that the target_res_type is a char, not a string (or a char *). So from the scheme interface you'd use (for example) hash backslash A for ALA.

Returns: 1 on success, 0 on failure

11.77.9 set-residue-type-chooser-stub-state

`set-residue-type-chooser-stub-state` *istat* [function]

Where *istat* is an integer number

set a flag saying that the residue chosen by mutate or auto-fit mutate should only be added as a stub (mainchain + CB)

11.78 Pointer Atom Functions

11.78.1 create-pointer-atom-molecule-maybe

`create-pointer-atom-molecule-maybe` [function]

Return the current pointer atom molecule, create a pointer atom molecule if necessary (i.e. when the user has not set it).

11.78.2 pointer-atom-molecule

`pointer-atom-molecule` [function]

Return the current pointer atom molecule.

11.79 Baton Build Interface Functions

11.79.1 set-baton-mode

`set-baton-mode` *i* [function]

Where *i* is an integer number

toggle so that mouse movement moves the baton not rotates the view.

11.79.2 try-set-draw-baton

`try-set-draw-baton` *i* [function]

Where *i* is an integer number

draw the baton or not

11.79.3 accept-baton-position

`accept-baton-position` [function]

accept the baton tip position - a prime candidate for a key binding

11.79.4 baton-tip-try-another

`baton-tip-try-another` [function]

move the baton tip position - another prime candidate for a key binding

11.79.5 baton-tip-previous

`baton-tip-previous` [function]

move the baton tip to the previous position

11.79.6 shorten-baton

`shorten-baton` [function]

shorten the baton length

11.79.7 lengthen-baton

`lengthen-baton` [function]

lengthen the baton

11.79.8 baton-build-delete-last-residue

`baton-build-delete-last-residue` [function]

delete the most recently build CA position

11.79.9 set-baton-build-params

`set-baton-build-params` *istart_resno chain_id direction* [function]

Where:

- *istart_resno* is an integer number
- *chain_id* is a string
- *direction* is a string

set the parameters for the start of a new baton-built fragment. direction can either be "forwards" or "backwards"

11.80 Crosshairs Interface

11.80.1 set-draw-crosshairs

`set-draw-crosshairs` *i* [function]

Where *i* is an integer number

draw the distance crosshairs, 0 for off, 1 for on.

11.81 Edit Chi Angles

11.81.1 set-find-hydrogen-torsions

`set-find-hydrogen-torsions` *state* [function]

Where *state* is an integer number

show torsions that rotate hydrogens in the torsion angle manipulation dialog. Note that this may be needed if, in the dictionary cif file torsion which have as a 4th atom both a hydrogen and a heavier atom bonding to the 3rd atom, but list the 4th atom as a hydrogen (not a heavier atom).

11.81.2 edit-chi-angles

`edit-chi-angles` *imol chain_id resno ins_code altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *altconf* is a string

display the edit chi angles gui for the given residue

return a status of 0 if it failed to fined the residue, return a value of 1 if it worked.

11.81.3 setup-torsion-general

`setup-torsion-general` *state* [function]

Where *state* is an integer number

beloved torsion general at last makes an entrance onto the Coot scene...

11.82 Masks

11.82.1 mask-map-by-molecule

`mask-map-by-molecule` *map_mol_no coord_mol_no invert_flag* [function]

Where:

- *map_mol_no* is an integer number
- *coord_mol_no* is an integer number
- *invert_flag* is an integer number

generate a new map that has been masked by some coordinates

(mask-map-by-molecule map-no mol-no invert?) creates and displays a masked map, cuts down density where the coordinates are (invert is 0). If invert? is 1, cut the density down where there are no atoms atoms.

11.82.2 set-map-mask-atom-radius

`set-map-mask-atom-radius` *rad* [function]

Where *rad* is a number

set the atom radius for map masking

11.82.3 map-mask-atom-radius

`map-mask-atom-radius` [function]

get the atom radius for map masking

11.83 check Waters Interface

11.83.1 delete-checked-waters-baddies

`delete-checked-waters-baddies` *imol b_factor_lim map_sigma_lim min_dist max_dist part_occ_contact_flag zero_occ_flag logical_operator_and_or_flag* [function]

Where:

- *imol* is an integer number
- *b_factor_lim* is a number
- *map_sigma_lim* is a number
- *min_dist* is a number
- *max_dist* is a number
- *part_occ_contact_flag* is an integer number
- *zero_occ_flag* is an integer number
- *logical_operator_and_or_flag* is an integer number

Delete waters that are fail to meet the given criteria.

11.84 Trim

11.84.1 trim-molecule-by-map

`trim-molecule-by-map` *imol_coords imol_map map_level delete_or_zero_occ_flag* [function]

Where:

- *imol_coords* is an integer number
- *imol_map* is an integer number
- *map_level* is a number
- *delete_or_zero_occ_flag* is an integer number

cut off (delete or give zero occupancy) atoms in the given molecule if they are below the given map (absolute) level.

11.85 External Ray-Tracing

11.85.1 raster3d

`raster3d` *rd3_filename* [function]

Where *rd3_filename* is a string

create a r3d file for the current view

11.85.2 set-raster3d-bond-thickness

`set-raster3d-bond-thickness` *f* [function]

Where *f* is a number

set the bond thickness for the Raster3D representation

11.85.3 set-raster3d-atom-radius

`set-raster3d-atom-radius` *f* [function]

Where *f* is a number

set the atom radius for the Raster3D representation

11.85.4 set-raster3d-density-thickness

`set-raster3d-density-thickness` *f* [function]

Where *f* is a number

set the density line thickness for the Raster3D representation

11.85.5 set-renderer-show-atoms

`set-renderer-show-atoms` *istate* [function]

Where *istate* is an integer number

set the flag to show atoms for the Raster3D representation

11.85.6 set-raster3d-bone-thickness

`set-raster3d-bone-thickness` *f* [function]

Where *f* is a number

set the bone (skeleton) thickness for the Raster3D representation

11.85.7 set-raster3d-shadows-enabled

`set-raster3d-shadows-enabled` *state* [function]

Where *state* is an integer number

turn off shadows for raster3d output - give argument 0 to turn off

11.85.8 set-raster3d-water-sphere

`set-raster3d-water-sphere` *istate* [function]

Where *istate* is an integer number

set the flag to show waters as spheres for the Raster3D representation. 1 show as spheres, 0 the usual stars.

11.85.9 raster-screen-shot

`raster-screen-shot` [function]

run raster3d and display the resulting image.

11.86 Superposition (SSM)

11.86.1 superpose

`superpose` *imol1 imol2 move_imol2_flag* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *move_imol2_flag* is an integer number

simple interface to superposition.

Superpose all residues of imol2 onto imol1. imol1 is reference, we can either move imol2 or copy it to generate a new molecule depending on the vaule of move_imol2_flag (1 for move 0 for copy).

11.86.2 superpose-with-chain-selection

`superpose-with-chain-selection` *imol1 imol2 chain_imol1 chain_imol2 chain_used_flag_imol1 chain_used_flag_imol2 move_imol2_copy_flag* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *chain_imol1* is a string
- *chain_imol2* is a string
- *chain_used_flag_imol1* is an integer number
- *chain_used_flag_imol2* is an integer number
- *move_imol2_copy_flag* is an integer number

chain-based interface to superposition.

Superpose the given chains of imol2 onto imol1. imol1 is reference, we can either move imol2 or copy it to generate a new molecule depending on the vaule of move_imol2_flag (1 for move 0 for copy).

11.86.3 superpose-with-atom-selection

`superpose-with-atom-selection` *imol1 imol2 mmdb_atom_sel_str_1 mmdb_atom_sel_str_2 move_imol2_copy_flag* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *mmdb_atom_sel_str_1* is a string
- *mmdb_atom_sel_str_2* is a string
- *move_imol2_copy_flag* is an integer number

detailed interface to superposition.

Superpose the given atom selection (specified by the mmdb atom selection strings) of imol2 onto imol1. imol1 is reference, we can either move imol2 or copy it to generate a new molecule depending on the vaule of move_imol2_flag (1 for move 0 for copy).

Returns: the index of the superposed molecule - which could either be a new molecule (if move_imol2_flag was 1) or the imol2 or -1 (signifying failure to do the SMM superposition).

11.87 NCS

11.87.1 set-draw-ncs-ghosts

`set-draw-ncs-ghosts` *imol istate* [function]

Where:

- *imol* is an integer number
- *istate* is an integer number

set drawing state of NCS ghosts for molecule number imol

11.87.2 draw-ncs-ghosts-state

`draw-ncs-ghosts-state` *imol* [function]

Where *imol* is an integer number

return the drawing state of NCS ghosts for molecule number imol. Return -1 on imol is a bad molecule or no ghosts.

11.87.3 set-ncs-ghost-bond-thickness

`set-ncs-ghost-bond-thickness` *imol f* [function]

Where:

- *imol* is an integer number
- *f* is a number

set bond thickness of NCS ghosts for molecule number imol

11.87.4 ncs-update-ghosts

`ncs-update-ghosts` *imol* [function]

Where *imol* is an integer number

update ghosts for molecule number imol

11.87.5 make-dynamically-transformed-ncs-maps

`make-dynamically-transformed-ncs-maps` *imol_model imol_map overwrite_maps_of_same_name_flag* [function]

Where:

- *imol_model* is an integer number
- *imol_map* is an integer number

- *overwrite_maps_of_same_name_flag* is an integer number

make NCS map

11.87.6 add-ncs-matrix

`add-ncs-matrix` *imol this_chain_id target_chain_id m11 m12 m13 m21 m22 m23 m31 m32 m33 t1 t2 t3* [function]

Where:

- *imol* is an integer number
- *this_chain_id* is a string
- *target_chain_id* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *t1* is a number
- *t2* is a number
- *t3* is a number

Add NCS matrix.

11.87.7 add-strict-ncs-matrix

`add-strict-ncs-matrix` *imol this_chain_id target_chain_id m11 m12 m13 m21 m22 m23 m31 m32 m33 t1 t2 t3* [function]

Where:

- *imol* is an integer number
- *this_chain_id* is a string
- *target_chain_id* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number

- *m33* is a number
- *t1* is a number
- *t2* is a number
- *t3* is a number

add an NCS matrix for strict NCS molecule representation

for CNS strict NCS usage: expand like normal symmetry does

11.87.8 show-strict-ncs-state

`show-strict-ncs-state` *imol* [function]

Where *imol* is an integer number

return the state of NCS ghost molecules for molecule number imol

11.87.9 set-show-strict-ncs

`set-show-strict-ncs` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set display state of NCS ghost molecules for molecule number imol

11.87.10 set-ncs-homology-level

`set-ncs-homology-level` *flev* [function]

Where *flev* is a number

At what level of homology should we say that we can't see homology for NCS calculation? (default 0.8)

11.87.11 copy-chain

`copy-chain` *imol from_chain to_chain* [function]

Where:

- *imol* is an integer number
- *from_chain* is a string
- *to_chain* is a string

Copy single NCS chain.

11.87.12 copy-from-ncs-master-to-others

`copy-from-ncs-master-to-others` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

Copy chain from master to all related NCS chains.

11.87.13 copy-residue-range-from-ncs-master-to-others

`copy-residue-range-from-ncs-master-to-others` *imol master_chain_id residue_range_start residue_range_end* [function]

Where:

- *imol* is an integer number
- *master_chain_id* is a string
- *residue_range_start* is an integer number
- *residue_range_end* is an integer number

Copy residue range to all related NCS chains.

If the target residues do not exist in the peer chains, then create them.

11.87.14 ncs-control-change-ncs-master-to-chain

`ncs-control-change-ncs-master-to-chain` *imol ichain* [function]

Where:

- *imol* is an integer number
- *ichain* is an integer number

change the NCS master chain (by number)

11.87.15 ncs-control-change-ncs-master-to-chain-id

`ncs-control-change-ncs-master-to-chain-id` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

change the NCS master chain (by chain_id)

11.87.16 ncs-control-display-chain

`ncs-control-display-chain` *imol ichain state* [function]

Where:

- *imol* is an integer number
- *ichain* is an integer number
- *state* is an integer number

display the NCS master chain

11.88 Helices and Strands

11.88.1 place-helix-here

`place-helix-here` [function]

add a helix

Add a helix somewhere close to this point in the map, try to fit the orientation. Add to a molecule called "Helix", create it if needed. Create another moecule called "Reverse Helix" if the helix orientation isn't completely unequivocal.

Returns: the index of the new molecule.

11.88.2 place-strand-here

`place-strand-here` *n_residues n_sample_strands* [function]

Where:

- *n_residues* is an integer number
- *n_sample_strands* is an integer number

add a strands

Add a strand close to this point in the map, try to fit the orientation. Add to a molecule called "Strand", create it if needed. n_residues is the estimated number of residues in the strand.

n_sample_strands is the number of strands from the database tested to fit into this strand density. 8 is a suggested number. 20 for a more rigourous search, but it will be slower.

Returns: the index of the new molecule.

11.88.3 place-strand-here-dialog

`place-strand-here-dialog` [function]

show the strand placement gui.

Choose the python version in there, if needed. Call scripting function, display it in place, don't return a widget.

11.88.4 find-helices

`find-helices` [function]

autobuild helices

Find secondary structure in the current map. Add to a molecule called "Helices", create it if needed.

Returns: the index of the new molecule.

11.88.5 find-strands

`find-strands` [function]

autobuild strands

Find secondary structure in the current map. Add to a molecule called "Strands", create it if needed.

Returns: the index of the new molecule.

11.88.6 find-secondary-structure

`find-secondary-structure` *use_helix helix_length helix_target use_strand strand_length strand_target* [function]

Where:

- *use_helix* is an integer number
- *helix_length* is an integer number
- *helix_target* is an integer number
- *use_strand* is an integer number
- *strand_length* is an integer number
- *strand_target* is an integer number

autobuild secondary structure

Find secondary structure in the current map. Add to a molecule called "SecStruc", create it if needed.

Returns: the index of the new molecule.

11.88.7 find-secondary-structure-local

`find-secondary-structure-local` *use_helix helix_length helix_target use_strand strand_length strand_target radius* [function]

Where:

- *use_helix* is an integer number
- *helix_length* is an integer number
- *helix_target* is an integer number
- *use_strand* is an integer number
- *strand_length* is an integer number
- *strand_target* is an integer number
- *radius* is a number

autobuild secondary structure

Find secondary structure local to current view in the current map. Add to a molecule called "SecStruc", create it if needed.

Returns: the index of the new molecule.

11.89 Nucleotides

11.89.1 find-nucleic-acids-local

`find-nucleic-acids-local` *radius* [function]

Where *radius* is a number

autobuild nucleic acid chains

Find secondary structure local to current view in the current map. Add to a molecule called "NuclAcid", create it if needed.

Returns: the index of the new molecule.

11.90 New Molecule by Section Interface

11.90.1 new-molecule-by-residue-type-selection

`new-molecule-by-residue-type-selection` *imol residue_type* [function]

Where:

- *imol* is an integer number
- *residue_type* is a string

create a new molecule that consists of only the residue of type residue_type in molecule number imol

Returns: the new molecule number, -1 means an error.

11.90.2 new-molecule-by-atom-selection

`new-molecule-by-atom-selection` *imol atom_selection* [function]

Where:

- *imol* is an integer number
- *atom_selection* is a string

create a new molecule that consists of only the atoms specified by the mmdb atoms selection string in molecule number imol

Returns: the new molecule number, -1 means an error.

11.90.3 new-molecule-by-sphere-selection

`new-molecule-by-sphere-selection` *imol x y z r allow_partial_residues* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number
- *r* is a number
- *allow_partial_residues* is an integer number

create a new molecule that consists of only the atoms within the given radius (r) of the given position.

Returns: the new molecule number, -1 means an error.

11.91 RNA/DNA

11.91.1 ideal-nucleic-acid

`ideal-nucleic-acid` *RNA_or_DNA form single_stranged_flag sequence* [function]

Where:

- *RNA_or_DNA* is a string

- *form* is a string
- *single_stranged_flag* is an integer number
- *sequence* is a string

create a molecule of idea nucleotides

use the given sequence (single letter code)

RNA_or_DNA is either "RNA" or "DNA"

form is either "A" or "B"

Returns: the new molecule number or -1 if a problem

11.91.2 watson-crick-pair

`watson-crick-pair` *imol chain_id resno* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number

Return a molecule that contains a residue that is the WC pair partner of the clicked/picked/selected residue.

11.91.3 watson-crick-pair-for-residue-range

`watson-crick-pair-for-residue-range` *imol chain_id resno_start resno_end* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number

add base pairs for the given residue range, modify molecule imol by creating a new chain

11.92 Sequence (Assignment)

11.92.1 print-sequence-chain

`print-sequence-chain` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

Print the sequence to the console of the given molecule.

11.92.2 assign-fasta-sequence

`assign-fasta-sequence` *imol chain_id_in seq* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string
- *seq* is a string

Assign a FASTA sequence to a given chain in the molecule.

11.92.3 assign-pir-sequence

`assign-pir-sequence` *imol chain_id_in seq* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string
- *seq* is a string

Assign a PIR sequence to a given chain in the molecule. If the chain of the molecule already had a chain assigned to it, then this will overwrite that old assignment with the new one.

11.92.4 assign-sequence-from-file

`assign-sequence-from-file` *imol file* [function]

Where:

- *imol* is an integer number
- *file* is a string

Assign a sequence to a given molecule from (whatever) sequence file.

11.92.5 assign-sequence-from-string

`assign-sequence-from-string` *imol chain_id_in seq* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string
- *seq* is a string

Assign a sequence to a given molecule from a simple string.

11.92.6 delete-all-sequences-from-molecule

`delete-all-sequences-from-molecule` *imol* [function]

Where *imol* is an integer number

Delete all the sequences from a given molecule.

11.92.7 delete-sequence-by-chain-id

`delete-sequence-by-chain-id` *imol chain_id_in* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string

Delete the sequence for a given chain_id from a given molecule.

11.93 Surface Interface

11.93.1 do-surface

`do-surface` *imol istate* [function]

Where:

- *imol* is an integer number
- *istate* is an integer number

draw surface of molecule number imol

if state = 1 draw the surface (normal representation goes away)

if state = 0 don't draw surface

11.93.2 set-transparent-electrostatic-surface

`set-transparent-electrostatic-surface` *imol opacity* [function]

Where:

- *imol* is an integer number
- *opacity* is a number

simple on/off screendoor transparency at the moment, an opacity > 0.0 will turn on screendoor transparency (stippling).

11.93.3 get-electrostatic-surface-opacity

`get-electrostatic-surface-opacity` *imol* [function]

Where *imol* is an integer number

return 1.0 for non transparent and 0.5 if screendoor transparency has been turned on.

11.94 FFFearing

11.94.1 fffear-search

`fffear-search` *imol_model imol_map* [function]

Where:

- *imol_model* is an integer number
- *imol_map* is an integer number

fffear search model in molecule number imol_model in map number imol_map

11.94.2 set-fffear-angular-resolution

`set-fffear-angular-resolution` *f* [function]

Where *f* is a number

set and return the fffear angular resolution in degrees

11.94.3 fffear-angular-resolution

`fffear-angular-resolution` [function]

return the fffear angular resolution in degrees

11.95 Remote Control

11.95.1 make-socket-listener-maybe

`make-socket-listener-maybe` [function]

try to make socket listener

11.95.2 set-socket-string-waiting

`set-socket-string-waiting` *s* [function]

Where *s* is a string

feed the main thread a scheme script to evaluate

11.95.3 set-socket-python-string-waiting

`set-socket-python-string-waiting` *s* [function]

Where *s* is a string

feed the main thread a python script to evaluate

11.96 Display Lists for Maps

11.96.1 set-display-lists-for-maps

`set-display-lists-for-maps` *i* [function]

Where *i* is an integer number

Should display lists be used for maps? It may speed things up if these are turned on (or off) - depends on graphics card and drivers. Pass 1 for on, 0 for off.

11.96.2 display-lists-for-maps-state

`display-lists-for-maps-state` [function]

return the state of display_lists_for_maps.

11.97 Browser Interface

11.97.1 browser-url

`browser-url` *url* [function]

Where *url* is a string

try to open given url in Web browser

11.97.2 set-browser-interface

`set-browser-interface` *browser* [function]

Where *browser* is a string

set command to open the web browser,

examples are "open" or "mozilla"

11.97.3 handle-online-coot-search-request

`handle-online-coot-search-request` *entry_text* [function]

Where *entry_text* is a string

the search interface

find words, construct a url and open it.

11.98 Molprobity Interface

11.98.1 handle-read-draw-probe-dots

`handle-read-draw-probe-dots` *dots_file* [function]

Where *dots_file* is a string

pass a filename that contains molprobity's probe output in XtalView format

11.98.2 handle-read-draw-probe-dots-unformatted

`handle-read-draw-probe-dots-unformatted` *dots_file imol show_clash_gui_flag* [function]

Where:

- *dots_file* is a string
- *imol* is an integer number
- *show_clash_gui_flag* is an integer number

pass a filename that contains molprobity's probe output in unformatted format

11.98.3 set-do-probe-dots-on-rotamers-and-chis

`set-do-probe-dots-on-rotamers-and-chis` *state* [function]

Where *state* is an integer number

shall we run molprobity for on edit chi angles intermediate atoms?

11.98.4 do-probe-dots-on-rotamers-and-chis-state

`do-probe-dots-on-rotamers-and-chis-state` [function]

return the state of if run molprobity for on edit chi angles intermediate atoms?

11.98.5 set-do-probe-dots-post-refine

`set-do-probe-dots-post-refine` *state* [function]

Where *state* is an integer number

shall we run molprobity after a refinement has happened?

11.98.6 do-probe-dots-post-refine-state

`do-probe-dots-post-refine-state` [function]

show the state of shall we run molprobity after a refinement has happened?

11.98.7 unmangle-hydrogen-name

`unmangle-hydrogen-name` *pdb_hydrogen_name* [function]

Where *pdb_hydrogen_name* is a string

make an attempt to convert pdb hydrogen name to the name used in Coot (and the refmac dictionary, perhaps).

11.98.8 set-interactive-probe-dots-molprobity-radius

`set-interactive-probe-dots-molprobity-radius` *r* [function]

Where *r* is a number

set the radius over which we can run interactive probe, bigger is better but slower.

default is 6.0

11.98.9 interactive-probe-dots-molprobity-radius

`interactive-probe-dots-molprobity-radius` [function]

return the radius over which we can run interactive probe.

11.99 Map Sharpening Interface

11.99.1 sharpen

`sharpen` *imol b_factor* [function]

Where:

- *imol* is an integer number
- *b_factor* is a number

Sharpen map imol by b_factor (note (of course) that positive numbers blur the map).

11.99.2 set-map-sharpening-scale-limit

`set-map-sharpening-scale-limit` *f* [function]

Where *f* is a number

set the limit of the b-factor map sharpening slider (default 30)

11.100 Marking Fixed Atom Interface

11.100.1 clear-all-fixed-atoms

`clear-all-fixed-atoms` *imol* [function]

Where *imol* is an integer number

clear all fixed atoms

11.101 Partial Charges

11.101.1 show-partial-charge-info

`show-partial-charge-info` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

show the partial charges for the residue of the given specs (charges are read from the dictionary)

11.102 EM interface

11.102.1 scale-cell

`scale-cell` *imol_map fac_u fac_v fac_w* [function]

Where:

- *imol_map* is an integer number
- *fac_u* is a number
- *fac_v* is a number
- *fac_w* is a number

Scale the cell, for use with EM maps, where the cell needs to be adjusted. Use like: (scale-cell 2 1.012 1.012 1.012). Return error status, 1 means it worked, 0 means it did not work.

11.103 CCP4mg Interface

11.103.1 write-ccp4mg-picture-description

`write-ccp4mg-picture-description` *filename* [function]

Where *filename* is a string

write a ccp4mg picture description file

11.103.2 get-atom-colour-from-mol-no

`get-atom-colour-from-mol-no` *imol element* [function]

Where:

- *imol* is an integer number
- *element* is a string

get element colour for imol as Python formatted list char

11.104 Aux functions

11.104.1 laplacian

`laplacian` *imol* [function]

Where *imol* is an integer number

Create the "Laplacian" (-ve second derivative) of the given map.

11.105 SMILES

11.105.1 do-smiles-gui

`do-smiles-gui` [function]

display the SMILES string dialog

11.106 PHENIX Support

11.106.1 set-button-label-for-external-refinement

`set-button-label-for-external-refinement` *button_label* [function]

Where *button_label* is a string

set the button label of the external Refinement program

11.107 Graphics Text

11.107.1 place-text

`place-text` *text x y z size* [function]

Where:

- *text* is a string
- *x* is a number
- *y* is a number
- *z* is a number
- *size* is an integer number

Put text at x,y,z.

size variable is currently ignored.

Returns: a text handle

11.107.2 remove-text

`remove-text` *text_handle* [function]

Where *text_handle* is an integer number

Remove "3d" text item.

11.107.3 text-index-near-position

`text-index-near-position` *x y z r* [function]

Where:

- *x* is a number
- *y* is a number
- *z* is a number
- *r* is a number

return the closest text that is with r A of the given position. If no text item is close, then return -1

11.108 PISA Interaction

11.108.1 pisa-interaction

`pisa-interaction` *imol_1 imol_2* [function]

Where:

- *imol_1* is an integer number
- *imol_2* is an integer number

return the molecule number of the interacting residues. Return -1 if no new model was created. Old, not very useful.

11.109 Jiggle Fit

11.109.1 fit-to-map-by-random-jiggle

`fit-to-map-by-random-jiggle` *imol chain_id resno ins_code n_trials jiggle_scale_factor* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *n_trials* is an integer number
- *jiggle_scale_factor* is a number

jiggle fit to the current refinment map. return < -100 if not possible, else return the new best fit for this residue.

11.110 SBase interface

11.110.1 get-ccp4srs-monomer-and-dictionary

`get-ccp4srs-monomer-and-dictionary` *comp_id* [function]

Where *comp_id* is a string

return the new molecule number of the monomer.

The monomer will have chainid `"A"` and residue number 1.

Return -1 on failure to get monomer.

11.110.2 get-sbase-monomer

`get-sbase-monomer` *comp_id* [function]

Where *comp_id* is a string

same as above but using old name for back-compatibility

11.111 FLE-View

11.111.1 fle-view-set-water-dist-max

`fle-view-set-water-dist-max` *dist_max* [function]

Where *dist_max* is a number

set the maximum considered distance to water

default 3.25 A.

11.111.2 fle-view-set-h-bond-dist-max

`fle-view-set-h-bond-dist-max` *h_bond_dist_max* [function]

Where *h_bond_dist_max* is a number

set the maximum considered hydrogen bond distance

default 3.9 A.

11.112 LSQ-improve

11.112.1 lsq-improve

`lsq-improve` *imol_ref ref_selection imol_moving moving_selection n_res dist_crit* [function]

Where:

- *imol_ref* is an integer number
- *ref_selection* is a string
- *imol_moving* is an integer number
- *moving_selection* is a string
- *n_res* is an integer number
- *dist_crit* is a number

an slightly-modified implementation of the "lsq_improve" algorithm of Kleywegt and Jones (1997).

Note that if a residue selection is specified in the residue selection(s), then the first residue of the given range must exist in the molecule (if not, then mmdb will not select any atoms from that molecule).

Kleywegt and Jones set n_res to 4 and dist_crit to 6.0.

11.113 single-model view

11.113.1 single-model-view-model-number

`single-model-view-model-number` *imol imodel* [function]

Where:

- *imol* is an integer number
- *imodel* is an integer number

put molecule number imol to display only model number imodel

11.113.2 single-model-view-this-model-number

`single-model-view-this-model-number` *imol* [function]

Where *imol* is an integer number

the current model number being displayed

return 0 on non-multimodel-molecule.

11.113.3 single-model-view-next-model-number

`single-model-view-next-model-number` *imol* [function]

Where *imol* is an integer number

change the representation to the next model number to be displayed

return 0 on non-multimodel-molecule.

11.113.4 single-model-view-prev-model-number

`single-model-view-prev-model-number` *imol* [function]

Where *imol* is an integer number

change the representation to the previous model number to be displayed

return 0 on non-multimodel-molecule.

11.114 graphics 2D ligand view

11.114.1 set-show-graphics-ligand-view

`set-show-graphics-ligand-view` *state* [function]

Where *state* is an integer number

set the graphics ligand view state

(default is 1 (on)).

12 More Scripting Functions

12.1 More Symmetry Functions

12.1.1 get-symmetry

`get-symmetry` *imol* [function]

Where *imol* is an integer number

return the symmetry of the imolth molecule

Return as a list of strings the symmetry operators of the given molecule. If imol is a not a valid molecule, return an empty list.

12.2 Extra Map Functions

12.2.1 auto-read-make-and-draw-maps

`auto-read-make-and-draw-maps` *filename* [function]

Where *filename* is a string

read MTZ file filename and from it try to make maps

Useful for reading the output of refmac. The default labels (FWT/PHWT and DELFWT/PHDELFWT) can be changed using ...[something]

Returns: a list of molecule numbers for the new maps

12.2.2 auto-read-make-and-draw-maps-from-mtz

`auto-read-make-and-draw-maps-from-mtz` *filename* [function]

Where *filename* is a string

set the flag to do a difference map (too) on auto-read MTZ

12.2.3 map-colour-components

`map-colour-components` *imol* [function]

Where *imol* is an integer number

return the colour triple of the imolth map

(e.g.: (list 0.4 0.6 0.8). If invalid imol return scheme false.

12.3 Multi-Residue Torsion

12.3.1 multi-residue-torsion-fit-scm

`multi-residue-torsion-fit-scm` *imol residues_specs_scm n_trials* [function]

Where:

- *imol* is an integer number
- *residues_specs_scm* is a SCM
- *n_trials* is an integer number

fit residues

(note: fit to the current-refinement map)

12.4 Execute Refmac

12.4.1 execute-refmac-real

`execute-refmac-real` *pdb_in_filename pdb_out_filename mtz_in_filename mtz_out_filename cif_lib_filename fobs_col_name sigfobs_col_name r_free_col_name have_sensible_free_r_flag make_molecules_flag refmac_count_string swap_map_colours_post_refmac_flag imol_refmac_map diff_map_flag phase_combine_flag phib_string fom_string ccp4i_project_dir* [function]

Where:

- *pdb_in_filename* is a std::string
- *pdb_out_filename* is a std::string
- *mtz_in_filename* is a std::string
- *mtz_out_filename* is a std::string
- *cif_lib_filename* is a std::string
- *fobs_col_name* is a std::string
- *sigfobs_col_name* is a std::string
- *r_free_col_name* is a std::string
- *have_sensible_free_r_flag* is an integer number
- *make_molecules_flag* is an integer number
- *refmac_count_string* is a std::string
- *swap_map_colours_post_refmac_flag* is an integer number
- *imol_refmac_map* is an integer number
- *diff_map_flag* is an integer number
- *phase_combine_flag* is an integer number
- *phib_string* is a std::string
- *fom_string* is a std::string
- *ccp4i_project_dir* is a std::string

if swap_map_colours_post_refmac_flag is not 1 thenn imol_refmac_map is ignored.

12.4.2 refmac-name

`refmac-name` *imol* [function]

Where *imol* is an integer number

the name for refmac

Returns: a stub name used in the construction of filename for refmac output

12.5 Dictionary Functions

12.5.1 dictionaries-read

`dictionaries-read` [function]

return a list of all the dictionaries read

12.6 Restraints Interface

12.6.1 set-monomer-restraints

`set-monomer-restraints` *monomer_type restraints* [function]

Where:

- *monomer_type* is a string
- *restraints* is a SCM

set the monomer restraints of the given monomer_type

Returns: scheme false or true for success or failure to set the restrains for monomer_type

12.7 Atom Information functions

12.7.1 resname-from-serial-number

`resname-from-serial-number` *imol chain_id serial_num* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *serial_num* is an integer number

return the rename from a residue serial number

Returns: blank (`""`) on failure.

12.7.2 residue-name

`residue-name` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a const std::string &
- *resno* is an integer number
- *ins_code* is a const std::string &

return the residue name of the specified residue

12.7.3 residue-info

`residue-info` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

Return a list of atom info for each atom in the specified residue.

output is like this: (list (list (list atom-name alt-conf) (list occ temp-fact element) (list x y z)))

occ can be a single number or a list of seven numbers of which the first is the isotropic B.

12.7.4 chain-fragments-scm

`chain-fragments-scm` *imol screen_output_also* [function]

Where:

- *imol* is an integer number
- *screen_output_also* is an integer number

chain fragments

12.7.5 add-molecule

`add-molecule` *molecule_expression name* [function]

Where:

- *molecule_expression* is a SCM
- *name* is a string

generate a molecule from an s-expression

return a molecule number, -1 on error

12.7.6 clear-and-update-molecule

`clear-and-update-molecule` *molecule_number molecule_expression* [function]

Where:

- *molecule_number* is an integer number
- *molecule_expression* is a SCM

update a molecule from a s-expression

And going the other way, given an s-expression, update molecule_number by the given molecule. Clear what's currently there first though.

12.7.7 active-residue

`active-residue` [function]

return specs of the atom close to screen centre

Return a list of (list imol chain-id resno ins-code atom-name alt-conf) for atom that is closest to the screen centre in any displayed molecule. If there are multiple models with the same coordinates at the screen centre, return the attributes of the atom in the highest number molecule number.

return scheme false if no active residue

12.7.8 closest-atom-simple-scm

`closest-atom-simple-scm` [function]

return the specs of the closest displayed atom

Return a list of (list imol chain-id resno ins-code atom-name alt-conf (list x y z)) for atom that is closest to the screen centre in the given molecule (unlike active-residue, potential CA substition is not performed). If there is no atom, or if imol is not a valid model molecule, return scheme false.

12.7.9 closest-atom

`closest-atom` *imol* [function]

Where *imol* is an integer number

return the specs of the closest atom in imolth molecule

Return a list of (list imol chain-id resno ins-code atom-name alt-conf (list x y z)) for atom that is closest to the screen centre in the given molecule (unlike active-residue, no account is taken of the displayed state of the molecule). If there is no atom, or if imol is not a valid model molecule, return scheme false.

12.7.10 residues-near-residue

`residues-near-residue` *imol residue_in radius* [function]

Where:

- *imol* is an integer number
- *residue_in* is a SCM
- *radius* is a number

return residues near residue

Return residue specs for residues that have atoms that are closer than radius Angstroems to any atom in the residue specified by res_in.

12.7.11 residues-near-position-scm

`residues-near-position-scm` *imol pos radius* [function]

Where:

- *imol* is an integer number
- *pos* is a SCM

- *radius* is a number

resdiues near residue

Return a list of pairs of (imol, residue_spec). pos is a list of 3 numbers. (get imol from active-atom)

Returns: residues within radius of pos (x,y,z) position

12.7.12 hydrogenate-region

`hydrogenate-region` *radius* [function]

Where *radius* is a number

find the active residue, find the near residues (within radius) create a new molecule, run reduce on that, import hydrogens from the result and apply them to the molecule of the active residue.

12.7.13 add-hydrogens-from-file

`add-hydrogens-from-file` *imol pdb_with_Hs_file_name* [function]

Where:

- *imol* is an integer number
- *pdb_with_Hs_file_name* is a std::string

Add hydrogens to imol from the given pdb file.

12.8 Refinement with specs

12.8.1 regularize-residues

`regularize-residues` *imol residues* [function]

Where:

- *imol* is an integer number
- *residues* is a const std::vector< coot::residue_spec_t > &

regularize the given residues

12.8.2 mtz-file-name

`mtz-file-name` *imol* [function]

Where *imol* is an integer number

presumes that imol_Refinement_Map has been set

12.8.3 refine-zone-with-full-residue-spec-scm

`refine-zone-with-full-residue-spec-scm` *imol chain_id resno1 inscode_1 resno2 inscode_2 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

- *resno1* is an integer number
- *inscode_1* is a string
- *resno2* is an integer number
- *inscode_2* is a string
- *altconf* is a string

Refine the given residue range.

12.9 Water Chain Functions

12.9.1 water-chain-from-shelx-ins-scm

`water-chain-from-shelx-ins-scm` *imol* [function]

Where *imol* is an integer number

return the chain id of the water chain from a shelx molecule. Raw interface

Returns: scheme false if no chain or bad imol

12.9.2 water-chain-scm

`water-chain-scm` *imol* [function]

Where *imol* is an integer number

return the chain id of the water chain. Raw interface

12.10 Glyco Tools

12.10.1 print-glyco-tree

`print-glyco-tree` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a const std::string &
- *resno* is an integer number
- *ins_code* is a const std::string &

print the glycosylation tree that contains the specified residue

12.11 Spin Search Functions

12.11.1 spin-search

`spin-search` *imol_map imol chain_id resno ins_code direction_atoms_list moving_atoms_list* [function]

Where:

- *imol_map* is an integer number
- *imol* is an integer number
- *chain_id* is a string

- *resno* is an integer number
- *ins_code* is a string
- *direction_atoms_list* is a SCM
- *moving_atoms_list* is a SCM

for the given residue, spin the atoms in moving_atom_list around the bond defined by direction_atoms_list looking for the best fit to density of imol_map map of the first atom in moving_atom_list. Works (only) with atoms in altconf ""

12.12 Rotamer Scoring

12.12.1 score-rotamers-scm

`score-rotamers-scm` *imol chain_id res_no ins_code alt_conf imol_map clash_flag lowest_probability* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *alt_conf* is a string
- *imol_map* is an integer number
- *clash_flag* is an integer number
- *lowest_probability* is a number

return the scores of the rotamers for this residue.

12.13 protein-db

12.13.1 protein-db-loops

`protein-db-loops` *imol_coords residue_specs imol_map nfrags preserve_residue_names* [function]

Where:

- *imol_coords* is an integer number
- *residue_specs* is a const std::vector< coot::residue_spec_t > &
- *imol_map* is an integer number
- *nfrags* is an integer number
- *preserve_residue_names* is a bool

Cowtan's protein_db loops.

12.14 Coot's Hole implementation

12.14.1 hole

`hole` *imol start_x start_y start_z end_x end_y end_z colour_map_multiplier colour_map_offset n_runs show_probe_radius_graph_flag export_surface_dots_file_name* [function]

Where:

- *imol* is an integer number
- *start_x* is a number
- *start_y* is a number
- *start_z* is a number
- *end_x* is a number
- *end_y* is a number
- *end_z* is a number
- *colour_map_multiplier* is a number
- *colour_map_offset* is a number
- *n_runs* is an integer number
- *show_probe_radius_graph_flag* is a bool
- *export_surface_dots_file_name* is a std::string

starting piont and end point, colour map multiplier and shall the probe radius graph be shown (dummy value currently).

if export_dots_file_name string length is zero, then don't try to export the surface dots.

12.14.2 make-link

`make-link` *imol spec_1 spec_2 link_name length* [function]

Where:

- *imol* is an integer number
- *spec_1* is a coot::atom_spec_t &
- *spec_2* is a coot::atom_spec_t &
- *link_name* is a const std::string &
- *length* is a number

make a link between the specified atoms

12.15 Drag and Drop Functions

12.15.1 handle-drag-and-drop-string

`handle-drag-and-drop-string` *uri* [function]

Where *uri* is a const std::string &

handle the string that get when a file or URL is dropped.

12.16 Map to Model Correlation

12.16.1 set-map-correlation-atom-radius

`set-map-correlation-atom-radius` *r* [function]

Where *r* is a number

The atom radius is not passed as a parameter to correlation.

12.16.2 map-to-model-correlation

`map-to-model-correlation` *imol residue_specs neigh_residue_specs atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *residue_specs* is a const std::vector< coot::residue_spec_t > &
- *neigh_residue_specs* is a const std::vector< coot::residue_spec_t > &
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

atom-mask-mode is as follows:

12.16.3 map-to-model-correlation-stats

`map-to-model-correlation-stats` *imol residue_specs neigh_residue_specs atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *residue_specs* is a const std::vector< coot::residue_spec_t > &
- *neigh_residue_specs* is a const std::vector< coot::residue_spec_t > &
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

map to model density correlation stats

atom-mask-mode is as follows:

12.16.4 map-to-model-correlation-per-residue

`map-to-model-correlation-per-residue` *imol specs atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *specs* is a const std::vector< coot::residue_spec_t > &
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

map to model density correlation, reported per residue

atom-mask-mode is as follows:

12.16.5 qq-plot-map-and-model-scm

`qq-plot-map-and-model-scm` *imol residue_specs_scm neigh_residue_specs_scm atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *residue_specs_scm* is a SCM
- *neigh_residue_specs_scm* is a SCM
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

QQ pllot of the model density correlation, reported per residue.

atom-mask-mode is as follows:

12.16.6 density-score-residue

`density-score-residue` *imol chain_id res_no ins_code imol_map* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *imol_map* is an integer number

simple density score for given residue (over-ridden by scripting function)

12.16.7 map-mean-scm

`map-mean-scm` *imol* [function]

Where *imol* is an integer number

return sigma for the given map. Return scheme False if not a valid map molecule number.

12.16.8 map-statistics-scm

`map-statistics-scm` *imol* [function]

Where *imol* is an integer number

return either scheme false on non-a-map or list (mean, standard-deviation, skew, kurtosis)

13 Scheme Scripting Functions

13.1 fascinating-things

`fascinating-clusters-gui` *window-name sorting-options cluster-list* [procedure]

(list cluster-name-string cluster-center-go-button-label-string ccgb-x ccgb-y ccgb-z ; now a list of specific items (list (list specific-button-label-string button-red button-green button-blue specific-x specific-y specific-z) (list specific-button-label-string button-red button-green button-blue specific-x specific-y specific-z)))))

13.2 refmac

`refmac-exe` [procedure]

This is the default refmac version, it is presumed to be in the path. It can be overridden using a re-definition either at the scripting interface or in one's ~/.coot file. E.g.: (define refmac-exec "/y/programs/xtal/refmac-latest/bin/refmac5-3-dec-2004")

`refmac-extra-params` [procedure]

Set this to a list of parameter strings:

If refmac-extra-params is a list of strings, it is used in preference to the "refmac-extra-params" file (should it exist). e.g. (set! refmac-extra-params (list "WEIGHT 0.2" "NCYC 10" "REFI BREF ISO" "REFI METH CGMAT" "REFI TYPE REST RESO 20 1.64"))

`run-refmac-by-filename` *pdb-in-filename pdb-out-filename mtz-in-filename mtz-out-filename extra-cif-lib-filename imol-refmac-count swap-map-colours-post-refmac? imol-mtz-molecule show-diff-map-flag phase-combine-flag phib-fom-pair force-n-cycles make-molecules-flag ccp4i-project-dir f-col sig-f-col . r-free-col* [procedure]

`extra-params-include-weight?` *params-list* [procedure]

Return #t if the list of strings *params-list* contains a string beginning with "WEIGHT". If not return #f

`get-refmac-extra-params` [procedure]

If refmac-extra-params is defined (as a list of strings), then return that, else read the file "refmac-extra-params".

Return a list a list of strings.

`run-refmac-for-phases` [procedure]

this is not run as a sub-thread, no useful return value.

13.3 coot-utils

`*annotations*` [procedure]
3D annotations - a bit of a hack currently

`*default-ball-and-stick-selection*` [procedure]
used in Extensions -> Representation -> Ball & Stick

`rigid-body-refine-by-residue-ranges` [procedure]
rigid body refine using residue ranges. Takes 2 arguments, the first is the molecule number, the second is a list of residue-ranges. A residue range is `(list` *`chain-id resno-start resno-end`*`)`.

`find-aligned-residue-type` [procedure]
add terminal residue is the normal thing we do with an aligned sequence, but also we can try ton find the residue type of a residue in the middle of the chain that is modelled as an ALA, say.

`all-true?` *ls* [procedure]
not tail-recursive

`get-directory` *dir-name* [procedure]
make the directory and return the directory name. If you cant make it directly in this directory try to make it in $HOME. Return #f if complete failure. e.g. coot-ccp4 or coot-backup

`molecule-has-hydrogens?` *imol* [procedure]
schemify function

`add-hydrogens-using-refmac-inner` *imol in-file-name out-file-name* [procedure]
out-file-name has been written, in-file-name needs to be read.

`post-manipulation-hook` [procedure]

`pre-release?` [procedure]
Return a boolean

`molecule-number-list` [procedure]
Return a list of molecule numbers (closed and open) The elements of the returned list need to be tested against is-valid-model-molecule?

`first-n` *n ls* [procedure]
first n fields of ls. if length ls is less than n, return ls. if ls is not a list, return ls. If n is negative, return ls.

`directory-is-modifiable?` *prefix-dir* [procedure]
Test for prefix-dir (1) being a string (2) existing (3) being a directory (4) modifiable by user (ie. u+rwx). prefix-dir must be a string.

Return #t or #f.

`absolutify` *file-name* [procedure]
return an absolute file-name for file-name or #f

`file-name-directory` *file-name* [procedure]
return the directory component of file-name, leave "/" on, if it's there. Note "x", "", "/" -> ""

`file-name-file` *file-name* [procedure]
return the file component of file-name "x/y" -> "y" "x" -> "x"

`most-recently-created-file` [procedure]
return #f on no-such-file

`residue-spec->atom-selection-string` *centre-residue-spec* [procedure]
Convert a residue-spec to an mmdb atom selection string.

`residue-atom->atom-name` *ra* [procedure]
residue-info atom

`residue-atom->alt-conf` *ra* [procedure]
residue-info atom

`residue-atom->occupancy` *ra* [procedure]
residue-info atom

`residue-spec->chain-id` *rs* [procedure]
residue spec (e.g. from residue-near-residue)

`map-molecule-list` [procedure]
Return a list of molecules that are maps

`model-molecule-list` [procedure]
Return a list of molecules that are maps

`shelx-molecule?` *imol* [procedure]
Return #t (#f) if *imol* is (isn't) a shelx molecule.

`set-virtual-trackball-type` *type* [procedure]
Set the virtual trackball behaviour.

trackball *type* is a symbol: either 'flat or 'spherical-surface.

`list-of-strings?` *ls* [procedure]
Is *ls* a list of strings? Return #t or #f

`coot-replace-string` *string-in target replacing-str* [procedure]
(coot-replace-string "one two three" " " "_") -> "one_two_three"

`string-append-with-spaces` *ls* [procedure]
string concat with spaces, *ls* must be a list of strings.

`rotation-centre` [procedure]
The screen centre.

return the rotation centre as a 3 membered list of numbers

`number-list` *a b* [procedure]

Make list of integers, *a* to *b*: eg (number-list 2 5) -> (2 3 4 5)

`string-member?` *atom ls* [procedure]

ls must be a list of strings, atom must be a string.

return either #t or #f.

`member?` *atom ls* [procedure]

`range` *first . second* [procedure]

range: works like the eponymous python function e.g. (range 3) -> '(0, 1, 2) e.g. (range 1 3) -> '(1, 2)

`shell-command-to-string` *cmd* [procedure]

code from thi <ttn at mingle.glug.org>

run command and put the output into a string and return it. (c.f. `run-command/strings`)

`shell-command-to-file-with-data` *cmd file-name data-list* [procedure]

run *cmd* putting output to *file-name* and reading commands data from the list of strings *data-list*.

`command-in-path?` *f* [procedure]

Is the command *f* in the path? return #t or #f.

Thank you for this, rixed at happyleptic.org

`command-in-path-or-absolute?` *cmd* [procedure]

Return #t or #f

`goosh-command` *cmd args data-list log-file-name screen-output-also?* [procedure]

Where cmd is e.g. "refmac" args is (list "HKLIN" "thing.mtz") log-file-name is "refmac.log" data-list is (list "HEAD" "END")

Return the exist status e.g. 0 or 1.

`goosh-command-with-file-input` *cmd args input-file log-file-name* [procedure]

run commands from an input file.

`run-command/strings` *cmd args data-list* [procedure]

Return the strings screen output of cmd or #f if command was not found

`close-float?` *x1 x2* [procedure]

Crude test to see of 2 floats are the same (more or less). Used in a greg test after setting the atom position.

`strip-spaces` *str* [procedure]

if passed a string, return a string with no spaces, else return #f.

`strip-leading-spaces` *str* [procedure]

" 53" -> "53", " " -> ""

`string-append-with-string` *str-ls tag-str* [procedure]
Append strings with tag-str between them

`strip-extension` *s* [procedure]
`"a.b.res" -> "a.b"` file-name-sans-extension

`file-name-extension` [procedure]
What is the extension of file-name?

`"a.pdb" -> "pdb" "" -> ""`

`add-tmp-extension-to` [procedure]
e.g. `"a.pdb" -> "a-tmp.pdb"`

`file-name-sans-extension` [procedure]
Same function as strip-extension, different name, as per scsh, in fact.

`strip-path` *s* [procedure]
/a/b.t -> b.t d/e.ext -> e.ext file-name-sans-path

`slash-start?` *s* [procedure]
does s start with a `"/"` ? return #t or #f

`string-concatenate` *ls* [procedure]
simple scheme functions to concat the strings in ls (ls must contain only strings)

`unique-date/time-str` [procedure]
return a string that contains the date/time e.g. `"2006-01-02_2216.03"`

`every-nth` *ls n* [procedure]
return a list that has only every-nth members; e.g. `(every-nth '(0 1 2 3 4 5 6 7 8) 2)` -> '(0 2 3 6 8) `(every-nth '(0 1 2 3 4 5 6 7 8) 3)` -> '(0 3 6)

n must be positive

`get-atom-from-residue` *atom-name residue-atoms alt-conf* [procedure]
now useful in testing

residue-atoms must be a list

`get-atom` *imol chain-id resno ins-code atom-name . alt-conf* [procedure]
Return an atom info or #f (if atom not found).

`multi-read-pdb` *glob-pattern dir* [procedure]
multi-read-pdb reads all the files matching *`glob-pattern`* in directory *`dir`*. Typical usage of this might be: `(multi-read-pdb "a*.pdb" ".")`

`read-pdb-all` [procedure]
read-pdb-all reads all the `"*.pdb"` files in the current directory.

`string->list-of-strings` *str* [procedure]
Return a list if str is a string, else return '()

`append-dir-file` *dir-name file-name* [procedure]
In a laughable attempt to minimise system dependence.

`append-dir-dir` *dir-name sub-dir-name* [procedure]
Similarly attempting to minimise system dependence.

`directory-as-file-name` *dir* [procedure]
remove any trailing /s

`is-directory?` *file-name* [procedure]
return #t or #f depending on if file-name (which must be a string) is a directory.

`coot-mkdir` *dir-name* [procedure]
return the dir-name on success.

return #f if dir-name is a file or we can't do the mkdir.

`directory-files` *dir* [procedure]
The following functions from PLEAC (guile version thereof of course).

Return: a list of files in the given directory

`glob` *pat dir* [procedure]
return a list of file names that match pattern pat in directory dir.

`useful-glob` *dir pat* [procedure]
prepend the files with the directory dir

(note that the args are reversed to "natural" order (which is the reverse of glob args)

`view-matrix` [procedure]
return the view matrix (useful for molscript, perhaps).

`view-quaternion` [procedure]
return the view quaternion

`add-view` *position quaternion zoom view-name* [procedure]
Return the view number

`matrix->quaternion` [procedure]
Convert a view matrix to a view quaternion to set Coot view internals.

`set-view-matrix` *m00 m10 m20 m01 m11 m21 m02 m12 m22* [procedure]
Set the view matrix using matrix->quaternion.

Useful for using a view matrix from another program, perhaps.

`molecule-centre` *imol* [procedure]
Return the molecule centre as a list of 3 numbers.

Note: mol-cen could contain values less than -9999.

`move-molecule-to-screen-centre` *imol* [procedure]
Move the centre of molecule number imol to the current screen centre

`move-molecule-here` [procedure]
This is a short name for the above.

`move-molecule-to-screen-center` [procedure]
this is an americanism

`identity-matrix` [procedure]
Return a nine-membered list of numbers.

`translation` *axis length* [procedure]
e.g. (translation 'x 2) -> '(2 0 0) Return: "scheme false" on error

`rotate-about-screen-axis` *axis degrees* [procedure]
Rotate degrees about screen axis, where axis is either 'x, 'y or 'z.

`toggle-display-map` *imol idummy* [procedure]
Support for old toggle functions. (consider instead the raw functions use the direct set_displayed functions).

`toggle-display-mol` *imol* [procedure]
toggle the display of imol

`toggle-active-mol` *imol* [procedure]
toggle the active state (clickability) of imol

`scheme-representation` *imol* [procedure]
return a scheme representation of molecule imol, or #f if we can't do it (imol is a map, say).

`reorder-chains` *imol* [procedure]
reorder chains

`transform-coords-molecule` *imol rtop* [procedure]
transform a coordinates molecule by a coot-rtop (which is a SCM expression of a clipper::RTop), i.e. a list of a 9-element list and a 3 element list. e.g. (list (list 1 0 0 0 1 0 0 0 1) (list 4.5 0.4 1.2)).

`transform-map` [procedure]
`(transform-map imol mat trans about-pt radius space-group cell)`

where space-group is a HM-symbol and cell is a list of 6 parameters, where the cell angles are in degrees.

or `(transform-map imol trans about-pt radius)` for a simple translation

or `(transform-map imol trans radius)` when using the default rotation-centre as the about-pt

`get-first-ncs-master-chain` [procedure]
return then NCS master of the first molecule that has ncs.

return `""` on fail to find an ncs chain

`transform-map-using-lsq-matrix` *imol-ref ref-chain ref-resno-start ref-resno-end imol-mov mov-chain mov-resno-start mov-resno-end imol-map about-pt radius* [procedure]
Remember, that now the about-pt is the "to" point, i.e. the maps are brought from somewhere else and generated about the about-pt.

`brighten-map` *imol scale-factor* [procedure]
Make the imol-th map brighter.

`brighten-maps` [procedure]
Make all maps brighter

`darken-maps` [procedure]
Make all maps darker.

`chain-ids` *imol* [procedure]
Return a list of chain ids for given molecule number *imol*. return empty list on error

`is-solvent-chain?` *imol chain-id* [procedure]
convert from interface name to schemish name

Return #t or #f.

`valid-model-molecule?` *imol* [procedure]
schemey interface to eponymous scripting interface function. Return scheme true or false

`valid-map-molecule?` *imol* [procedure]
schemey interface to eponymous scripting interface function. Return scheme true or false.

`valid-refinement-map?` [procedure]
Return #t or #f

`shelx-molecule?` *imol* [procedure]
schemey interface to shelx molecule test

Return #t or #f.

`is-difference-map?` *imol-map* [procedure]
Return #t or #f.

`residue-exists?` *imol chain-id resno ins-code* [procedure]
Does residue resno with insertion code ins-code of chain chain-id and in molecule number imol exist?

Return #t or #f.

`residue-has-hetatms?` *imol chain-id res-no ins-code* [procedure]
Does the residue contain hetatoms? Return #t or #f.

`centre-of-mass` *imol* [procedure]
Return a list of 3 float for the centre of mas of molecule number imol.

on faiure return #f.

`atom-specs` *imol chain-id resno ins-code atom-name alt-conf* [procedure]
Return as a list the occupancy temperature-factor element x y z coordinates of the given atom. (the x,y,z are in Cartesian Angstroms).

on error (e.g. atom not found) return #f

`guess-refinement-map` [procedure]
return a guess at the map to be refined (usually called after imol-refinement-map returns -1)

`target-auto-weighting-value` [procedure]
Ian Tickle says (as far as I can understand) that the target rmsd should be 0.25 or thereabouts. You can over-ride it now.

`auto-weight-for-refinement` [procedure]
Set the refinement weight (matrix) by iterating the refinement and varying the weight until the chi squares (not including the non-bonded terms) reach 1.0 =/- 10%. It uses sphere refinement. The refinement map must be set. At the end show the new weight in the status bar. Seems to take about 5 rounds.

`print-sequence` *imol* [procedure]
Print the sequence of molecule number *imol*

This is not really a util, perhaps it should be somewhere else?

`pir-file-name->pir-sequence` *pir-file-name* [procedure]
simple utility function to return the contents of a file as a string.

`associate-pir-file` *imol chain-id pir-file-name* [procedure]
Associate the contents of a PIR file with a molecule.

`graphics-comma-key-pressed-hook` [procedure]
comma key hook

`graphics-dot-key-pressed-hook` [procedure]
dot key hook

`*key-bindings*` [procedure]
a list of (code key name thunk) e.g. '(103 "g" "Goto Blob" (blob-under-pointer-to-screen-centre))

`add-key-binding` *name key thunk* [procedure]
Add a key binding

with a given name, key (e.g. "x" or "S") and the function to run (a thunk) when that key is pressed.

`graphics-general-key-press-hook` *key* [procedure]
general key press hook, not for public use.

`read-vu-file` [procedure]
Function requested by Mark White.

read XtalView (and maybe other) .vu files and convert them into generic objects.

Pass the filename and an object name e.g. (read-vu-file "axes.vu" "axes")

Returns: nothing interesting.

`residues-matching-criteria` *imol residue-test-func* [procedure]
Return a list of residues, each of which has a return value at the start, ie. (list return-value chain-id res-no ins-code)

`all-residues` *imol* [procedure]
Return residue specs for all residues in imol (each spec is preceeded by #t)

`residues-with-alt-confs` *imol* [procedure]
Return a list of all residues that have alt confs: where a residue is specified thusly: (list chain-id resno ins-code)

`residue-alt-confs` *imol chain-id res-no ins-code* [procedure]
Return a list of all the altconfs in the residue. Typically this will return (list `""`) or (list `"A" "B"`)

`res-spec->chain-id` *res-spec* [procedure]
simple extraction function

`res-spec->res-no` *res-spec* [procedure]
simple extraction function

`res-spec->ins-code` *res-spec* [procedure]
simple extraction function

`residue-spec->atom-for-centre` *imol chain-id res-no ins-code* [procedure]
Return #f if no atom can be found given the spec else return a list consisting of the atom name and alt-conf specifier.

Choose an atom that is called `" CA "`. Failing that choose the first atom.

`update-go-to-atom-from-current-atom` [procedure]

`flip-active-ligand` [procedure]

`delete-atom-by-active-residue` [procedure]
Typically one might want to use this on a water, but it deletes the nearest CA currently... Needs a re-think. Should active-atom just return the nearest atom and not be clever about returning a CA.

`merge-solvent-chains` *imol* [procedure]

`mutate-by-overlap` *imol chain-id-in resno tlc* [procedure]
change chain ids with residue range for the PTY

`phosphorylate-active-residue` [procedure]
A bit of fun

`overlay-my-ligands` *imol-mov chain-id-mov resno-mov imol-ref chain-id-ref resno-ref* [procedure]
A function for Overlaying ligands. The transformation is applied to all the atoms of the molecule that contains the moving ligand.

`label-all-CAs` *imol* [procedure]

`label-all-atoms-in-residue` *imol chain-id resno inscode* [procedure]

`label-all-active-residue-atoms` [procedure]

`sanitise-alt-confs` *atom-info atom-ls* [procedure]
Resets alt confs and occupancies of atoms in residue that have orphan alt-loc attributes.

`sanitise-alt-confs-in-residue` *imol chain-id resno inscode* [procedure]

`sanitise-alt-confs-active-residue` [procedure]
Resets alt confs and occupancies of atoms in residue that have orphan alt-loc attributes. Use the active-residue.

`print-molecule-names` [procedure]

`save-dialog-positions-to-init-file` [procedure]

`multi-chicken` *imol . n-colours* [procedure]
multiple maps of varying colour from a given map.

`BALL_AND_STICK` [procedure]
simple enumeration

`hilight-binding-site` *imol centre-residue-spec hilight-colour radius* [procedure]
hilight-colour is specified in degrees (round the colour wheel - starting at yellow (e.g. 230 is purple))

`pukka-puckers?` *imol* [procedure]
To paraphrase: The distance of the plane of the base to the following phosphate is highly correlated to the pucker of the ribose.

An analysis of the structures in RNADB2005 shows that a critical distance of 3.3A provides a partition function to separate C2' from C3' endo puckering. Not all ribose follow this rule. There may be some errors in the models comprising RNADB2005. So we check the distance of the following phosphate to the plane of the ribose and record the riboses that are inconsitent. We also report puckers that are not C2' or C3'. The puckers are determined by the most out-of-plane atom of the ribose (the rms deviation of the 4 atoms in the plane is calculated, but not used to determine the puckering atom).

`*use-mogul*` [procedure]
if you don't have mogul, set this to #f

`prodrg-ify` *imol chain-id res-no ins-code* [procedure]
Generate restraints from the residue at the centre of the screen using PRODRG. Delete hydrogens from the residue because PRODRG has anomalous hydrogens.

`add-annotation-here` *text* [procedure]

`save-annotations` *file-name* [procedure]

`load-annotations` *file-name* [procedure]

`make-latest-version-url` [procedure]
Here we construct the url that contains the latest (pre) release info adding in "pre-release" if this binary is a pre-release. args ends up as something like: ("-s" "xxx/phone-home.scm" "pre-release" "binary" "Linux-1386-fedora-10-python-gtk2" "command-line" "/home/xx/coot/bin/coot")

`run-download-binary-curl` *revision version-string pending-install-in-place-func set-file-name-func* [procedure]

Get the binary (i.e. the action that happens when the download button is pressed). This is run in a thread, so it can't do any graphics stuff.

return #t if tar file was successfully downloaded and untared and #f if not.

`get-revision-from-string` *str* [procedure]

(used in downloading new version)

`coot-split-version-string` *str* [procedure]

e.g. input: "coot-0.6.2-pre-1-revision-2765\n" output: "coot-0.6.2-pre-1-revision-2765"

`load-default-sequence` [procedure]

In the first case the sequence is assigned to the closest match (model sequence to target sequence), subsequently only chains without a sequence associated with them are candidates for matching. The protein sequence has to have at least 95% sequence identity with the target sequence in "default.seq"

`coot-updates-error-handler` *key . args* [procedure]

not really for public manipulation.

`update-self` [procedure]

keep a copy of the old directories around in a directory named after expiration time.

`chiral-centre-inverter-scm-version` [procedure]

This should almost all be c++ code so that Bernie doesn't have to redo it. This is temporary then.

`get-drug-via-wikipedia` *drug-name-in* [procedure]

return a string "DB00xxxx.mol" or some such - this is the file name of the mdl mol file from drugbank. Or #f/undefined on fail. Test result with string?.

If you are debugging this function, you probably want to be looking at handle-rev-string or drugbox->drugitem.

`coot-has-pygtk?` [procedure]

to determine if we have pygtk

13.4 filter

`filter` *fn ls* [procedure]

Basic scheme function, filter the objects in list ls by function fn. e.g. (filter even? (list 0 1 2 3) -> '(0 2)

13.5 remote-control

`%coot-listener-socket` [procedure]
a place-holder for the coot listener socket

`open-coot-listener-socket` *port-number host-name* [procedure]
Open a coot listener socket, return nothing much, but do set! %coot-listener-socket.

Hmmm... why make a side-effect like that? Why not return %coot-listener-socket so that the caller can set it? There may be a reason...

And the reason is that I can then call coot-listener-idle-function-proc without having to use a c++ variable.

`open-coot-listener-socket-with-timeout` *port-number host-name* [procedure]
yet another go to make a coot port reader work. This time, we use a gtk-timer to read stuff from the socket.

The gtk-timer function must return 1 to be called again. When we want to close the socket reader, simply make the function return 0.

`coot-socket-timeout-func` [procedure]
based on coot-listener-idle-function-proc

`coot-listener-idle-function-proc` [procedure]
Do this thing when idle

currently set to listen to the %coot-listener-socket

`eval-socket-string` *s* [procedure]
the function to run from the main thread to evaluate a string:

13.6 3d-generator-import

`prodrg-xyzin` [procedure]
if there is a prodrg-xyzin set the current-time to its mtime, else #f

`import-from-3d-generator-from-mdl` *mdl-file-name comp-id* [procedure]
This function can be overwritten by your favourite 3d conformer and restraints generator.

`new-molecule-by-smiles-string` *tlc-text smiles-text* [procedure]
Run libcheck to convert from SMILES string

`get-mdl-latest-time` [procedure]
not needed?

`prodrg-flat` *imol-in chain-id-in res-no-in* [procedure]
return #f (if fail) or a list of: the molecule number of the selected residue, the prodrg output mol file-name, the prodrg output pdb file-name

`get-ccp4srs-monomer-and-overlay` *comp-id* [procedure]
import from SBASE, callback using sbase_import_function

13.7 fitting

`fit-protein` *imol* [procedure]

Note that residue with alt confs do not undergo auto-fit-rotamer. This is because that autofit-rotamer then refine will tend to put both rotamers into the same place. Not good. It seems a reasonable expectation that residues with an alternate conformation are already resonably well-fitted. So residues with alternate conformations undergo only real space refinement.

This is simple-minded and outdated now we have the interruptible version (below).

`*continue-multi-refine*` [procedure]

These 2 variables are used by multi-refine function(s), called by idle functions to refine just one residue.

`fit-protein-make-specs` *imol chain-specifier* [procedure]

chain-specifier can be a string, where it is the chain of interest. or 'all-chains, where all chains are chosen.

`interruptible-fit-protein` *imol func* [procedure]

func is a refinement function that takes 2 args, one a residue spec, the other the imol-refinement-map. e.g. fit-protein-fit-function

`fit-chain` *imol chain-id* [procedure]

For each residue in chain chain-id of molecule number imol, do a rotamer fit and real space refinement of each residue. Don't update the graphics while this is happening (which makes it faster than fit-protein, but much less interesting to look at).

`fit-waters` *imol . animate?* [procedure]

For each residue in the solvent chains of molecule number *imol*, do a rigid body fit of the water to the density.

`stepped-refine-protein` *imol . res-step* [procedure]

Step through the residues of molecule number imol and at each step do a residue range refinement (unlike fit-protein for example, which does real-space refinement for every residue).

The step is set internally to 2.

`stepped-refine-protein-for-rama` *imol* [procedure]

refine each residue with ramachandran restraints

`stepped-refine-protein-with-refine-func` *imol refine-func . res-step* [procedure]

`post-ligand-fit-gui` [procedure]

The GUI that you see after ligand finding.

`molecules-matching-criteria` *test-func* [procedure]

test-func is a function given one argument (a molecule number) that returns either #f if the condition is not satisfied or something else if it is. And that "something else" can be a list like (list label x y z) or (list "Bad Chiral" 0 "A" 23 "" "CA" "A")

It is used in the create a button label and "what to do when the button is pressed".

`refine-active-residue-generic` *side-residue-offset* [procedure]

This totally ignores insertion codes. A clever algorithm would need a re-write, I think. Well, we'd have at this end a function that took a chain-id res-no-1 ins-code-1 res-no-2 ins-code-2

And refine-zone would need to be re-written too, of course. So let's save that for a rainy day (days... (weeks)).

`refine-active-residue` [procedure]

refine active residue

`refine-active-residue-triple` [procedure]

refine active residue triple

`manual-refine-residues` *side-residue-offset* [procedure]

For just one (this) residue, side-residue-offset is 0.

`pepflip-active-residue` [procedure]

Pepflip the active residue - needs a key binding.

`auto-fit-rotamer-active-residue` [procedure]

Auto-fit rotamer on active residues

`add-extra-restraints-to-other-molecule` *imol chain-id resno-range-start resno-range-end atom-sel-type imol-ref* [procedure]

Restrain the atoms in imol (in give range selection) to corresponding atoms in imol-ref.

atom-sel-type is either 'all 'main-chain or 'ca

13.8 libcheck

`libcheck-exe` [procedure]

this is override-able by the user in their .coot file (for example).

`monomer-molecule-from-3-let-code` *code dict-cif-libin . ccp4i-project-dir* [procedure]

Return -2 on *code* is not a string Return -3 on libcheck failure Return *imol* on success Return `handle-read-draw-molecule` error code on failure to read resultant pdb file

Actually, it would be nice to know if this code represented a full description - or a minimal one... perhaps we can parse the log file and call a pop-up that will tell us.

dict-cif-libin should be a string. If it is `""` then it is ignored. If it is not `""` then it is used to create input to libcheck (not a command line argument) so that bespoke dictionary libraries can produce coords using `"Get Monomer"`.

13.9 extra-top-level

`my-button-callback` [procedure]

This is what to do when the button is pressed. It can be any guile or coot function.

`my-top-level` [procedure]

define a simple window and put a button in it

13.10 gui-add-linked-cho

`*add-linked-residue-tree-correlation-cut-off*` [procedure]

now users can set this

13.11 tips-gui

`show-coot-tip-from-list` *n text* [procedure]

given a number and a gtk text widget *text*, put tip number *n* into the widget.

`increment-coot-tip-number` [procedure]

increment the tip number when the user sees a tip

`decrease-coot-tip-number` [procedure]

decrement the tip number when the user sees a tip

`tips-gui` [procedure]

run the tips gui.

13.12 jligand-gui

`launch-jligand-function` [procedure]

This happens when user clicks on the "Launch JLigand" button. It starts a jligand and puts it in the background.

`click-select-residues-for-jligand` [procedure]

This happens when user clicks on the "Select Residues for JLigand" (or some such) button. It expects the user to click on atoms of the two residues involved in the link.

13.13 hello

`first-non-trivial-name` [procedure]

Primarily for Indian Names.

Say we are given str: (list "M." "D." "Albert" "Dorkins"). We want to return ""Albert" not "M.") We reject names that are one character long and names that are 2 characters long that end in ".". So, "M." is rejected, but "Ma" is not.

An excercise for the committed is to also reject run-together dotted initials such as "D.K.". I was sufficiently committed.

13.14 mutate-from-scheme

`povray-version` [procedure]

this should negate the need for Bill's patch here.

`povray-args` [procedure]

args not including the output filename

`povray-image` [procedure]

Run provray using current displayed image and write .pov file to default filename

13.15 coot-gui

`run-gtk-pending-events` [procedure]

`coot-gui` [procedure]

Fire up the coot scripting gui. This function is called from the main C++ code of coot. Not much use if you don't have a gui to type functions in to start with.

`handle-smiles-go` *tlc-entry smiles-entry* [procedure]

The callback from pressing the Go button in the smiles widget, an interface to run libcheck.

`smiles-gui` [procedure]

smiles GUI

`generic-single-entry` *function-label entry-1-default-text go-button-label handle-go-function* [procedure]

Generic single entry widget

Pass the hint labels of the entries and a function that gets called when user hits "Go". The handle-go-function accepts one argument that is the entry text when the go button is pressed.

`generic-double-entry` *label-1 label-2 entry-1-default-text entry-2-default-text check-button-label handle-check-button-function go-button-label handle-go-function* [procedure]

handle-go-function takes 3 arguments, the third of which is the state of the check button.

if check-button-label not a string, then we don't display (or create, even) the check-button. If it *is* a string, create a check button and add the callback handle-check-button-function which takes as an argument the active-state of the the checkbutton.

`generic-multiple-entries-with-check-button` *entry-info-list check-button-info go-button-label handle-go-function* [procedure]

generic double entry widget, now with a check button

OLD:

pass a the hint labels of the entries and a function (handle-go-function) that gets called when user hits "Go" (which takes two string aguments and the active-state of the check button (either #t of #f).

if check-button-label not a string, then we don't display (or create, even) the check-button. If it *is* a string, create a check button and add the callback handle-check-button-function which takes as an argument the active-state of the the checkbutton.

`molecule-centres-gui` [procedure]

A demo gui to move about to molecules.

`old-coot?` [procedure]

old coot test

`interesting-things-gui` *title baddie-list* [procedure]

We can either go to a place (in which case the element is a list of button label (string) and 3 numbers that represent the x y z coordinates) or an atom (in which case the element is a list of a button label (string) followed by the molecule-number chain-id residue-number ins-code atom-name altconf)

e.g. (interesting-things-gui "Bad things by Analysis X" (list (list "Bad Chiral" 0 "A" 23 "" "CA" "A") (list "Bad Density Fit" 0 "B" 65 "" "CA" "") (list "Interesting blob" 45.6 46.7 87.5)))

`interesting-things-with-fix-maybe` *title baddie-list* [procedure]

In this case, each baddie can have a function at the end which is called when the fix button is clicked.

`fill-option-menu-with-mol-options` *menu filter-function* [procedure]

Fill an option menu with the "right type" of molecules. If filter-function returns #t then add it. Typical value of filter-function is valid-model-molecule?

`fill-option-menu-with-coordinates-mol-options` *menu* [procedure]

Helper function for molecule chooser. Not really for users.

Return a list of models, corresponding to the menu items of the option menu.

The returned list will not contain references to map or closed molecules.

`fill-option-menu-with-number-options` *menu number-list default-option-value* [procedure]

`get-option-menu-active-molecule` *option-menu model-mol-list* [procedure]

Helper function for molecule chooser. Not really for users.

return the molecule number of the active item in the option menu, or return #f if there was a problem (e.g. closed molecule)

`get-option-menu-active-item` *option-menu item-list* [procedure]

Here we return the active item in an option menu of generic items

`molecule-chooser-gui-generic` *chooser-label callback-function option-menu-fill-function* [procedure]

Typically option-menu-fill-function is fill-option-menu-with-coordinates-mol-options

`molecule-chooser-gui` [procedure]

Fire up a coordinates/model molecule chooser dialog, with a given label and on OK we call the call-back-fuction with an argument of the chosen molecule number.

chooser-label is a directive to the user such as "Choose a Molecule"

callback-function is a function that takes a molecule number as an argument.

`map-molecule-chooser-gui` [procedure]

Fire up a map molecule chooser dialog, with a given label and on OK we call the call-back-fuction with an argument of the chosen molecule number.

chooser-label is a directive to the user such as "Choose a Molecule"

callback-function is a function that takes a molecule number as an argument.

`generic-chooser-and-entry` *chooser-label entry-hint-text defaut-entry-text callback-function* [procedure]

A pair of widgets, a molecule chooser and an entry. The callback-function is a function that takes a molecule number and a text string.

`generic-chooser-entry-and-file-selector` *chooser-label chooser-filter entry-hint-text default-entry-text file-selector-hint callback-function* [procedure]

Create a window

Return a pair of widgets, a molecule chooser and an entry. The callback-function is a function that takes a molecule number and 2 text strings (e.g chain-id and file-name)

chooser-filter is typically valid-map-molecule? or valid-model-molecule?

`generic-chooser-and-file-selector` *chooser-label chooser-filter file-selector-hint default-file-name callback-function* [procedure]

Create a window.

Return a pair of widgets, a molecule chooser and an entry. callback-function is a function that takes a molecule number and a file-name

chooser-filter is typically valid-map-molecule? or valid-model-molecule?

`coot-menubar-menu` *menu-label* [procedure]

If a menu with label menu-label is not found in the coot main menubar, then create it and return it. If it does exist, simply return it.

`add-simple-coot-menu-menuitem` *menu menu-item-label activate-function* [procedure]

Given that we have a menu (e.g. one called "Extensions") provide a cleaner interface to adding something to it:

activate-function is a thunk.

`missing-atoms-gui` *imol* [procedure]

Make an interesting things GUI for residues with missing atoms

`generic-buttons-dialog` *dialog-name button-list* [procedure]

button-list is a list of pairs (improper list) the first item of which is the button label text the second item is a lambda function, what to do when the button is pressed.

`generic-interesting-things` *imol gui-title-string residue-test-func* [procedure]

Generic interesting things gui: user passes a function that takes 4 args: the chain-id, resno, inscode and residue-serial-number (should it be needed) and returns either #f or something interesting (e.g. a label/value). It is the residue-test-func of the residue-matching-criteria function.

`generic-number-chooser` *number-list default-option-value hint-text go-button-label go-function* [procedure]

A gui that makes a generic number chooser the go function is a lambda function that takes the value of the active menu item - as a number.

`generic-molecule-chooser` *hbox hint-text* [procedure]

pack a hint text and a molecule chooser option menu into the given vbox.

return the option-menu and model molecule list:

`file-selector-entry` *hbox hint-text* [procedure]

Return an entry, the widget is inserted into the hbox passed to this function.

`cootaneer-gui` *imol* [procedure]

Cootaneer gui

`view-saver-gui` [procedure]

The gui for saving views

`add-view-to-views-panel` *view-name view-number* [procedure]

`dialog-box-of-buttons-with-check-button` *window-name geometry buttons close-button-label check-button-label check-button-func check-button-is-initially-on-flag* [procedure]

If check-button-label is #f, don't make one, otherwise create with with the given label and "on" state.

`dialog-box-of-pairs-of-buttons` *imol window-name geometry buttons close-button-label* [procedure]

geometry is an improper list of ints buttons is a list of: (list (list button-1-label button-1-action button-2-label button-2-action)) The button-1-action function takes as an argument the imol The button-2-action function takes as an argument the imol

`views-panel-gui` [procedure]

A gui showing views:

`nudge-screen-centre-gui` [procedure]

nudge screen centre box. Useful when Ctrl left-mouse has been taken over by another function.

`make-difference-map-gui` [procedure]

A gui to make a difference map (from arbitrarily gridded maps (that's it's advantage))

`cis-peptides-gui` *imol* [procedure]

A GUI to display all the CIS peptides and navigate to them.

`associate-pir-with-molecule-gui` *do-alignment?* [procedure]

Associate the contents of a PIR file with a molecule. Select file from a GUI.

`alignment-mismatches-gui` *imol* [procedure]

Make a box-of-buttons GUI for the various modifications that need to be made to match the model sequence to the assigned sequence(s).

Call this when the associated sequence(s) have been read in already.

`residue-range-gui` [procedure]

(Notice that we are not dealing with insertion codes).

`user-mods-gui` *imol pdb-file-name* [procedure]
USER MODS gui

`rename-residue-gui` [procedure]
simple rename residue GUI

`water-coordination-gui` [procedure]
close-button

`min-max-residues-from-atom-specs` *specs* [procedure]
return a list, or #f (e.g. if not in same chain and molecule)

`*db-loop-preserve-residue-names*` [procedure]
by default, rename loop residues to UNK. If scheme true, then leave them as the residue names found in the database.

13.16 cns2coot

`cns->coot` *2fofc-coeffs fofc-coeffs model-pdb* [procedure]
Read in cns coeff-data (given filenames) and a pdb molecule filename to make maps.

13.17 clear-backup

`delete-coot-backup-files` *action-type* [procedure]

`clear-backup-gui` [procedure]
Return #t or #f depending on if the GUI dialog was shown (it isn't show if there are no files to delete).

`clear-backups-maybe` [procedure]
Return a status, #f or #t, did the GUI run?

Note that clear-backup-gui returns either #t or #f too.

If this function returns #f, then coot_real_exit() just exits with coot_real_exit(). Otherwise we wait for the GUI.

13.18 redefine-functions

`enhanced-ligand-coot?` [procedure]
scm aliases.

`set-find-hydrogen-torsion` [procedure]
fix typo of set-find-hydrogen-torsions (backward compatibility in case anyone was using that)

`cif-file-for-comp-id` [procedure]
(define residue->sdf-file residue-to-sdf-file)

`toggle-idle-ligand-interactions` [procedure]
I changed the function name - save those (just a few) with scripts that I've handed out

13.19 check-for-updates

`get-stable-release-from-server-string` *str* [procedure]
Is this true?

`get-stable-release-from-coot-version` [procedure]
Needs testing.

`notify-of-new-version` *str* [procedure]
show the dialog

`download-binary-dialog` [procedure]
version-string is something like: "coot-0.6-pre-1-revision-2060"

`directory-is-modifiable?` *prefix-dir* [procedure]
Test for prefix-dir 1) existing 2) being a directory 3) modifiable by user (ie. u+rwx)

Return #t or #f.

13.20 coot-lsq

`lsq-match-type-symbol->number` *match-type-in* [procedure]
Internal type conversion for LSQ fitting. Return a number according to the symbol match-type-in

`set-match-element` [procedure]
Create matchers, 7 elements: (list ref-start-resno ref-end-resno ref-chain-id imol-ref mov-start-resno mov-end-resno mov-chain-id imol-mov match-type)

`lsq-match` *imol-ref imol-moving match-list* [procedure]
The scripting interface to LSQ matching. Pass molecule numbers for the reference (imol-ref) and moving (imol-moving) molecules and a match list. The match list format is described in the manual.

`simple-lsq-match` *ref-start-resno ref-end-resno ref-chain-id imol-ref mov-start-resno mov-end-resno mov-chain-id imol-mov match-type* [procedure]
Simple interface to LSQ fitting. More often than not this is what you will want, I imagine, e.g. (simple-lsq-match 940 950 "A" 0 940 950 "A" 1 'main)

13.21 get-ebi

`check-dir-and-get-url` [procedure]
check the directory and get url url-string.

`get-url-str` [procedure]
get url-string for data type 'pdb or 'sfs

`get-ebi-pdb` *id* [procedure]
Return a molecule number on success or not a number (#f) or -1 on error.

`get-eds-pdb-and-mtz` *id* [procedure]
Return a list of molecules (i.e. the model molecule and the 2 maps).

or, if it didn't work then return #f

13.22 coot-crash-catcher

`filter` *fn ls* [procedure]
Basic scheme function, filter the objects in list ls by function fn. e.g. (filter even? (list 0 1 2 3) -> '(0 2)

`string-concatenate` *ls* [procedure]
simple scheme functions to concat the strings in ls (ls must contain only strings)

`directory-files` *dir* [procedure]
The following functions from PLEAC (guile version thereof of course).

or define a utility function for this

`glob` *pat dir* [procedure]
return a list of file names that match pattern pat in directory dir.

`run-command/strings` *cmd args data-list* [procedure]
Return the strings screen output of cmd (reversed) or #f if command was not found

`command-in-path?` *cmd* [procedure]
Return #t or #f:

`string->list-of-strings` *str* [procedure]
Return a list if str is a string, else return '()

`shell-command-to-string` *cmd* [procedure]
code from thi <ttn at mingle.glug.org>

run command and put the output into a string and return it. (c.f. `run-command/strings`)

`make-gdb-script` [procedure]

`get-gdb-strings` [procedure]
return #f or list of strings

`make-gui` [procedure]
gui

13.23 get-recent-pdbe

`coot-thread-dispatcher` [procedure]
(coot-thread-dispatcher image-name thunk)

`dialog-box-of-buttons-with-async-ligands` *window-name geometry buttons close-button-label* [procedure]
If check-button-label is #f, don't make one, otherwise create with with the given label and "on" state.

`cache-or-net-get-image` *image-url image-name func* [procedure]
Get image-name (caller doesn't care how) and when it is in place run thunk func.

This is a generally useful function, so it has been promoted outside of dig-table.

`refmac-calc-sfs-make-mtz-with-columns` *pdb-in-file-name mtz-file-name mtz-refmaced-file-name f-col sigf-col r-free-col* [procedure]
return refmac-result or #f

`pdbe-get-pdb-and-sfs-cif` *include-get-sfs-flag entry-id* [procedure]
Use progress bars

include-get-sfs-flag is either 'no-sfs or 'include-sfs

`pdbe-latest-releases-gui` [procedure]
Sameer Velankar says to get this file for the latest releases "http://www.ebi.ac.uk/pdbe-apps/jsonizer/latest/released/" (note the end "/").

13.24 contact-score-isolated-ligand

`contact-score-ligand` *imol res-spec* [procedure]
This will hydrogenate the active residue, not imol

13.25 snarf-coot-docs

`directory-as-file-name` *dir* [procedure]
remove any trailing /s

`file-name-file` *file-name* [procedure]
return the file component of file-name "x/y" -> "y" "x" -> "x"

`useful-glob` *dir pat* [procedure]
prepend the files with the directory dir

(note that the args are reversed to "natural" order (which is the reverse of glob args)

`glob` *pat dir* [procedure]
return a list of file names that match pattern pat in directory dir.

`strip-extension` *s* [procedure]
"a.b.res" -> "a.b" file-name-sans-extension

`command-in-path?` *cmd* [procedure]
Return #t or #f:

`goosh-command` *cmd args data-list log-file-name screen-output-also?* [procedure]
Where cmd is e.g. "refmac" args is (list "HKLIN" "thing.mtz") log-file-name is "refmac.log" data-list is (list "HEAD" "END")

Return the exist status e.g. 0 or 1.

`run-command/strings` *cmd args data-list* [procedure]
Return the strings screen output of cmd or #f if command was not found

`string->list-of-strings` *str* [procedure]
Return a list if str is a string, else return '()

`directory-files` *dir* [procedure]

The following functions from PLEAC (guile version thereof of course).

or define a utility function for this

`add-to-list-section-texis` [procedure]

`delete-section-texi-files` [procedure]

13.26 run-mogul

`run-mogul` *mode imol chain-id res-no ins-code prefix-str use-cache?* [procedure]

prefix-str can be blank

return: a string that is the mogul-out file-name a symbol: something went wrong

`run-mogul-show-results` *imol code mode chain-id res-no ins-code* [procedure]

return a string that is the mogul results file name that gets parsed to make results (return #f on failure) mode is 'all or 'bonds-and-angles

13.27 group-settings

`rapper-dir` [procedure]

The rapper installation dir. This is just a guess, that it is installed in the users home directory.

13.28 brute-lsqman

`lsqman-count` [procedure]

brute-lsqman - run lsqman on chains A of two pdb-files and read in the result to coot. Charlie Bond 2003. Can keep a count of the number of successful runs if necessary

13.29 generic-objects

`generic-object-is-displayed?` [procedure]

map to scheme names:

`is-closed-generic-object?` [procedure]

map to scheme names:

`generic-object-with-name` [procedure]

return a new generic object number for the given object obj-name. If there is no such object with name obj-name, then create a new one. (Maybe you want the generic object to be cleaned if it exists before returning, this function does not do that).

`generic-objects-gui` [procedure]

display a GUI for generic objects

`reduce-on-pdb-file` *imol pdb-in pdb-out* [procedure]

return status.

`probe` [procedure]

run molprobity (well reduce and probe) to make generic objects (and display the generic objects gui)

`write-reduce-het-dict` *imol reduce-het-dict-file-name* [procedure]

Write the connectivity for the non-standard (non-water) residues in the given molecule for which we have the dictionary.

Don't return anything interesting.

`*interactive-probe-is-OK?*` [procedure]

gets set the first time we run interactive-probe. Takes values unset (initial value) 'yes and 'no)

`interactive-probe` [procedure]

run "probe" interactively, which in the current implementation, means that this function can run during a edit-chi angles manipulation, or after a real space refine zone.

Thus function presumes that there are 2 pdb files in the current directory, one of which is the reference pdb file and the other is a pdb file containing the tmp/moving atom set.

The function takes arguments for the centre of the probe dots and the radius of the probe dots sphere. The chain id and residue number are also needed to pass as arguments to probe.

`probe-local-sphere` *imol radius* [procedure]

Update the generic objects probe dots from residues within radius of the screen centre.

Return nothing interesting.

13.30 gui-ligand-sliders

`mtz-file-name->refinement-column-labels` *file-name* [procedure]

return 3 values

13.31 ligand-check

`get-metrics-for-ligand` *imol chain-id res-no ins-code refmac-input-mtz-file-name fobs-col sig-fobs-col rfree-col refmac-dir* [procedure]

test: (using-active-atom (get-metrics-for-ligand aa-imol aa-chain-id aa-res-no aa-ins-code "rnasa-1.8-all_refmac1.mtz" "FGMP18" "SIGFGMP18" "FreeR_flag" "coot-refmac"))

refmac-dir: the dir where input/output refmac files should be written.

return (list correlation mogul bumps difference-map-stats b-factor-info) where: mogul is an improper pair (mogul-z-worst . mogul-out-file-name) or an error status difference-map-stats: the output of map-to-model-correlation-stats-scm (list correlation var_x var_y n sum_x sum_y D D2 (based on mean/sd of the map at the ligand) map_mean map_mean_at_ligand map_sd map_sd_at_ligand SCM_UNDEFINED) and b-factor-info list of (median-ratio median-ligand median-env ks-test-result)

`*ligand-check-resolution-limit*` [procedure]
only look at ligands in maps with resolution worse than this: (to look at everything, set it to 0.1)

`filter-out-waters` *imol env-residues* [procedure]
remove residues that are waters from env-residues

13.32 coot

`*probe-command*` [procedure]
This is full pathname of molprobity's probe program

`*reduce-command*` [procedure]
This is full pathname of molprobity's reduce program

`*do-coot-tips-flag*` [procedure]
This has be be here (in a general place) because tips-gui (where it used to be is conditionally loaded). (default to tips-gui displayed is true).

`load-all-scheme` [procedure]
Note the position of coot-gui is important. It seem that if there are too many files in front of it (even blank ones!) coot barfs when it gets to coot-gui.scm.

20060203 I have now enabled coot in scripting mode (no graphics (–no-graphics command line option)). In that case, we need to not load up scheme files which load up gtk (currently coot-gui and tips-gui).

13.33 ncs

`skip-to-next-ncs-chain` *direction* [procedure]
Skip the residue in the next chain (typically of a molecule with NCS) with the same residue number. If on the last chain, then wrap to beginning. If it can't find anything then don't move (and put a message in the status bar)

`single-manual-ncs-ghost` *imol resno-start resno-end ref-chain peer-chain* [procedure]
We can only see one peer at a time with this (each time we do a clear-ncs-ghost-matrices).

`manual-ncs-ghosts` *imol resno-start resno-end chain-id-list* [procedure]
chain-id-list is (list "A" "B" "C" "D")), i.e. the reference/target/master chain-id first and then the peers. This allows us to add many peers at the same time (unlike above function).

`update-ncs-ghosts-by-local-sphere` [procedure]
Update NCS ghosts based on local environment (residues within 6A of (and including) the active residue).

Typically one would bind this function to a key.

`ncs-master-chain-id` *imol* [procedure]
Return the first master chain id (usually there is only one of course) or #f.

`ncs-ligand` *imol-protein ncs-master-chain-id imol-ligand chain-id-ligand resno-ligand-start resno-ligand-stop* [procedure]

This was designed to create an NCS copy of a ligand (or range of residues) in the active site of one chain to the as yet unoccupied active site of another, i.e. it makes a NCS ligand "D"1 that is a NCS copy of ligand "C"1 using an NCS operator that maps protein chain "A" onto chain "B".

13.34 parse-pisa-xml

`*pisa-command*` [procedure]

(define *pisa-command* "/home/paule/ccp4/ccp4-6.1.2/bin/pisa")

`pisa-assemblies-xml` *imol file-name* [procedure]

it calls parse-pisa-assemblies which does the work

`pisa-handle-sxml-molecule` *imol molecule pisa-results-type* [procedure]

a interface-molecule record contains information about pvalue and residues.

`parse-pisa-assemblies` [procedure]

——————————————————- pisa assemblies: ——————————————————————————-

pisa_results name status total_asm asm_set ser_no assembly id size mmsize diss_energy asa bas entropy diss_area int_energy n_uc n_diss symNumber molecule chain_id rxx rxy rxz tx ryx ryy ryz ty rzx rzy rzz tz rxx-f rxy-f rxz-f tx-f ryx-f ryy-f ryz-f ty-f rzx-f rzy-f rzz-f tz-f

`prep-for-pisa` *mode imol* [procedure]

20100213 prep-for-pisa needs to make directory, config file, write the pdb file and thre return value should be #f if there was a problem or some value where we can check that pisa -analyse ran (probably a directory). It is not clear right now where the output is going. config files has PISA_WORK_ROOT coot-pisa but things seems to be written to DATA_ROOT /home/emsley/ccp4/ccp4-6.1.3/share/pisa which seems like a bug (or something like it) in pisa. Needs rechecking.

`cached-pisa-analysis` *dir* [procedure]

needs fleshing out (see notes for prep-for-pisa).

`parse-pisa-interfaces` *imol sxml-entity* [procedure]

pdb_entry pdb_code status n_interfaces interface id type n_occ int_area int_solv_en pvalue stab_en css overlap x-rel fixed h-bonds n_bonds bond chain-1 res-1 seqnum-1 inscode-1 atname-1 chain-2 res-2 seqnum-2 inscode-2 atname-2 dist salt-bridges n-bonds bond chain-1 res-1 seqnum-1 inscode-1 atname-1 chain-2 res-2 seqnum-2 inscode-2 atname-2 dist ss-bonds n-bonds bond chain-1 res-1 seqnum-1 inscode-1 atname-1 chain-2 res-2 seqnum-2 inscode-2 atname-2 dist cov-bonds n-bonds bond chain-1 res-1 seqnum-1 inscode-1 atname-1 chain-2 res-2 seqnum-2 inscode-2 atname-2 dist molecule id chain_id class symop symop_no cell_i cell_j cell_k rxx rxy rxz tx ryx ryy ryz ty rzx rzy rzz tz int_natoms int_nres int_area int_solv_en pvalue residues residue ser_no name seq_num ins_code bonds asa bsa solv_en

13.35 americanisms

`set-rotation-center` [procedure]
an americanism

`handle-read-draw-molecule-with-recenter` [procedure]
an americanism

`set-rotation-center-size` [procedure]
an americanism

`center-atom-label-status` [procedure]
an americanism

`set-last-map-color` [procedure]
an americanism

`center-of-mass` [procedure]
an americanism

`set-swap-difference-map-colors` [procedure]
an americanism

`set-font-color` [procedure]
an americanism

`set-dots-color` [procedure]
an americanism

`invert-chiral-center` [procedure]
an americanism

13.36 c-interface_8h

13.37 Startup Functions

13.37.1 set-prefer-python

`set-prefer-python` [function]
tell coot that you prefer to run python scripts if/when there is an option to do so.

13.37.2 prefer-python

`prefer-python` [function]
the python-prefered mode.

This is available so that the scripting functions know whether on not to put themselves onto in as menu items.

If you consider using this, consider in preference use_gui_qm == 2, which is used elsewhere to stop python functions adding to the gui, when guile-gtk functions have alread done so. We should clean up this (rather obscure) interface at some stage.

return 1 for python is prefered, 0 for not.

13.38 File System Functions

13.38.1 make-directory-maybe

`make-directory-maybe` *dir* [function]

Where *dir* is a string

make a directory dir (if it doesn't exist) and return error code

If it can be created, create the directory dir, return the success status like mkdir: mkdir

Returns: zero on success, or -1 if an error occurred. If dir already exists as a directory, return 0 of course.

13.38.2 set-show-paths-in-display-manager

`set-show-paths-in-display-manager` *i* [function]

Where *i* is an integer number

Show Paths in Display Manager?

Some people don't like to see the full path names in the display manager here is the way to turn them off, with an argument of 1.

13.38.3 show-paths-in-display-manager-state

`show-paths-in-display-manager-state` [function]

return the internal state

What is the internal flag?

Returns: 1 for "yes, display paths" , 0 for not

13.38.4 add-coordinates-glob-extension

`add-coordinates-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as coordinate files

13.38.5 add-data-glob-extension

`add-data-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as data (reflection) files

13.38.6 add-dictionary-glob-extension

`add-dictionary-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as geometry dictionary files

13.38.7 add-map-glob-extension

`add-map-glob-extension` *ext* [function]

Where *ext* is a string

add an extension to be treated as geometry map files

13.38.8 remove-coordinates-glob-extension

`remove-coordinates-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as coordinate files

13.38.9 remove-data-glob-extension

`remove-data-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as data (reflection) files

13.38.10 remove-dictionary-glob-extension

`remove-dictionary-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as geometry dictionary files

13.38.11 remove-map-glob-extension

`remove-map-glob-extension` *ext* [function]

Where *ext* is a string

remove an extension to be treated as geometry map files

13.38.12 set-sticky-sort-by-date

`set-sticky-sort-by-date` [function]

sort files in the file selection by date?

some people like to have their files sorted by date by default

13.38.13 unset-sticky-sort-by-date

`unset-sticky-sort-by-date` [function]

do not sort files in the file selection by date?

removes the sorting of files by date

13.38.14 set-filter-fileselection-filenames

`set-filter-fileselection-filenames` *istate* [function]

Where *istate* is an integer number

on opening a file selection dialog, pre-filter the files.

set to 1 to pre-filter, [0 (off, non-pre-filtering) is the default

13.38.15 filter-fileselection-filenames-state

`filter-fileselection-filenames-state` [function]

, return the state of the above variable

13.38.16 file-type-coords

`file-type-coords` *file_name* [function]

Where *file_name* is a string

is the given file name suitable to be read as coordinates?

13.38.17 open-coords-dialog

`open-coords-dialog` [function]

display the open coordinates dialog

13.38.18 set-file-chooser-selector

`set-file-chooser-selector` *istate* [function]

Where *istate* is an integer number

this flag set chooser as default for windows, otherwise use selector 0 is selector 1 is chooser

13.39 Widget Utilities

13.39.1 set-main-window-title

`set-main-window-title` *s* [function]

Where *s* is a string

set the main window title.

function added for Lothar Esser

13.40 MTZ and data handling utilities

13.40.1 manage-column-selector

`manage-column-selector` *filename* [function]

Where *filename* is a string

given a filename, try to read it as a data file

We try as .phs and .cif files first

13.41 Molecule Info Functions

13.41.1 chain-n-residues

`chain-n-residues` *chain_id imol* [function]

Where:

- *chain_id* is a string
- *imol* is an integer number

the number of residues in chain chain_id and molecule number imol

Returns: the number of residues

13.41.2 seqnum-from-serial-number

`seqnum-from-serial-number` *imol chain_id serial_num* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *serial_num* is an integer number

a residue seqnum (normal residue number) from a residue serial number

Returns: < -9999 on failure

13.41.3 insertion-code-from-serial-number

`insertion-code-from-serial-number` *imol chain_id serial_num* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *serial_num* is an integer number

the insertion code of the residue.

Returns: NULL (scheme False) on failure.

13.41.4 n-models

`n-models` *imol* [function]

Where *imol* is an integer number

the chain_id (string) of the ichain-th chain molecule number imol

return the number of models in molecule number imol

useful for NMR or other such multi-model molecules.

return the number of models or -1 if there was a problem with the given molecule.

Returns: the chain-id

13.41.5 n-chains

`n-chains` *imol* [function]

Where *imol* is an integer number

number of chains in molecule number imol

Returns: the number of chains

13.41.6 is-solvent-chain-p

`is-solvent-chain-p` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

is this a solvent chain? [Raw function]

This is a raw interface function, you should generally not use this, but instead use (is-solvent-chain? imol chain-id)

This wraps the mmdb function isSolventChain().

Returns: -1 on error, 0 for no, 1 for is "a solvent chain". We wouldn't want to be doing rotamer searches and the like on such a chain.

13.41.7 is-protein-chain-p

`is-protein-chain-p` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

is this a protein chain? [Raw function]

This is a raw interface function, you should generally not use this, but instead use (is-protein-chain? imol chain-id)

This wraps the mmdb function isAminoacidChain().

Returns: -1 on error, 0 for no, 1 for is "a protein chain". We wouldn't want to be doing rotamer searches and the like on such a chain.

13.41.8 is-nucleotide-chain-p

`is-nucleotide-chain-p` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

is this a nucleic acid chain? [Raw function]

This is a raw interface function, you should generally not use this, but instead use (is-nucleicacid-chain? imol chain-id)

This wraps the mmdb function isNucleotideChain(). For completeness.

Returns: -1 on error, 0 for no, 1 for is "a nucleicacid chain". We wouldn't want to be doing rotamer searches and the like on such a chain.

13.41.9 n-residues

`n-residues` *imol* [function]

Where *imol* is an integer number

return the number of residues in the molecule,

return -1 if this is a map or closed.

13.41.10 sort-chains

`sort-chains` *imol* [function]

Where *imol* is an integer number

return a list of the remarks of hte molecule number imol

sort the chain ids of the imol-th molecule in lexographical order

13.41.11 sort-residues

`sort-residues` *imol* [function]

Where *imol* is an integer number

sort the residues of the imol-th molecule

13.41.12 remarks-dialog

`remarks-dialog` *imol* [function]

Where *imol* is an integer number

a gui dialog showing remarks header info (for a model molecule).

13.41.13 print-header-secondary-structure-info

`print-header-secondary-structure-info` *imol* [function]

Where *imol* is an integer number

simply print secondardy structure info to the terminal/console. In future, this could/should return the info.

13.41.14 copy-molecule

`copy-molecule` *imol* [function]

Where *imol* is an integer number

copy molecule imol

Returns: the new molecule number. Return -1 on failure to copy molecule (out of range, or molecule is closed)

13.41.15 add-ligand-delete-residue-copy-molecule

`add-ligand-delete-residue-copy-molecule` *imol_ligand_new chain_id_ligand_new resno_ligand_new imol_current chain_id_ligand_current resno_ligand_current* [function]

Where:

- *imol_ligand_new* is an integer number
- *chain_id_ligand_new* is a string
- *resno_ligand_new* is an integer number
- *imol_current* is an integer number
- *chain_id_ligand_current* is a string
- *resno_ligand_current* is an integer number

Copy a molecule with addition of a ligand and a deletion of current ligand.

This function is used when adding a new (modified) ligand to a structure. It creates a new molecule that is a copy of the current molecule except that the new ligand is added and the current ligand/residue is deleted.

13.41.16 exchange-chain-ids-for-seg-ids

`exchange-chain-ids-for-seg-ids` *imol* [function]

Where *imol* is an integer number

Experimental interface for Ribosome People.

Ribosome People have many chains in their pdb file, they prefer segids to chainids (chainids are only 1 character). But coot uses the concept of chain ids and not seg-ids. mmdb allow us to use more than one char in the chainid, so after we read in a pdb, let's replace the chain ids with the segids. Will that help?

13.41.17 show-remarks-browswer

`show-remarks-browswer` [function]

show the remarks browser

13.42 Library and Utility Functions

13.42.1 git-revision-count

`git-revision-count` [function]

return the git revision count for for this build.

13.42.2 svn-revision

`svn-revision` [function]

an alias to git_revision_count() for backwards compatibility

13.42.3 molecule-name

`molecule-name` *imol* [function]

Where *imol* is an integer number

return the name of molecule number imol

Returns: 0 if not a valid name (-> False in scheme) e.g. "/a/b/c.pdb" for "d/e/f.mtz FWT PHWT"

13.42.4 set-molecule-name

`set-molecule-name` *imol new_name* [function]

Where:

- *imol* is an integer number
- *new_name* is a string

set the molecule name of the imol-th molecule

13.42.5 coot-real-exit

`coot-real-exit` *retval* [function]

Where *retval* is an integer number

exit from coot, give return value retval back to invoking process.

13.42.6 coot-no-state-real-exit

`coot-no-state-real-exit` *retval* [function]

Where *retval* is an integer number

exit without writing a state file

13.42.7 coot-clear-backup-or-real-exit

`coot-clear-backup-or-real-exit` *retval* [function]

Where *retval* is an integer number

exit coot doing clear-backup maybe

13.42.8 coot-save-state-and-exit

`coot-save-state-and-exit` *retval save_state_flag* [function]

Where:

- *retval* is an integer number
- *save_state_flag* is an integer number

exit coot, write a state file

13.42.9 first-coords-imol

`first-coords-imol` [function]

What is the molecule number of first coordinates molecule?

return -1 when there is none.

13.42.10 first-small-coords-imol

`first-small-coords-imol` [function]

molecule number of first small (<400 atoms) molecule.

return -1 on no such molecule

13.42.11 first-unsaved-coords-imol

`first-unsaved-coords-imol` [function]

What is the molecule number of first unsaved coordinates molecule?

return -1 when there is none.

13.42.12 mmcif-sfs-to-mtz

`mmcif-sfs-to-mtz` *cif_file_name mtz_file_name* [function]

Where:

- *cif_file_name* is a string
- *mtz_file_name* is a string

convert the structure factors in cif_file_name to an mtz file.

Return 1 on success. Return 0 on a file without Rfree, return -1 on complete failure to write a file.

13.43 Graphics Utility Functions

13.43.1 set-do-anti-aliasing

`set-do-anti-aliasing` *state* [function]

Where *state* is an integer number

set the bond lines to be antialiased

13.43.2 do-anti-aliasing-state

`do-anti-aliasing-state` [function]

return the flag for antialiasing the bond lines

13.43.3 set-do-GL-lighting

`set-do-GL-lighting` *state* [function]

Where *state* is an integer number

turn the GL lighting on (state = 1) or off (state = 0)

slows down the display of simple lines

13.43.4 do-GL-lighting-state

`do-GL-lighting-state` [function]

return the flag for GL lighting

13.43.5 use-graphics-interface-state

`use-graphics-interface-state` [function]

shall we start up the Gtk and the graphics window?

if passed the command line argument

no-graphics, coot will not start up gtk itself.

An interface function for Ralf.

13.43.6 python-at-prompt-at-startup-state

`python-at-prompt-at-startup-state` [function]

is the python interpreter at the prompt?

Returns: 1 for yes, 0 for no.

13.43.7 start-graphics-interface

`start-graphics-interface` [function]

start Gtk (and graphics)

This function is useful if it was not started already (which can be achieved by using the command line argument

no-graphics).

An interface for Ralf

13.43.8 reset-view

`reset-view` [function]

"Reset" the view

return 1 if we moved, else return 0.

centre on last-read molecule with zoom 100. If we are there, then go to the previous molecule, if we are there, then go to the origin.

13.43.9 graphics-n-molecules

`graphics-n-molecules` [function]

return the number of molecules (coordinates molecules and map molecules combined) that are currently in coot

Returns: the number of molecules (closed molecules are not counted)

13.43.10 toggle-idle-spin-function

`toggle-idle-spin-function` [function]

Spin spin spin (or not)

13.43.11 toggle-idle-rock-function

`toggle-idle-rock-function` [function]

Rock (not roll) (self-timed)

13.43.12 set-rocking-factors

`set-rocking-factors` *width_scale frequency_scale* [function]

Where:

- *width_scale* is a number
- *frequency_scale* is a number

Settings for the inevitable discontents who dislike the default rocking rates (defaults 1 and 1)

13.43.13 set-idle-function-rotate-angle

`set-idle-function-rotate-angle` *f* [function]

Where *f* is a number

how far should we rotate when (auto) spinning? Fast computer? set this to 0.1

13.43.14 idle-function-rotate-angle

`idle-function-rotate-angle` [function]

what is the idle function rotation angle?

13.43.15 handle-read-draw-molecule

`handle-read-draw-molecule` *filename* [function]

Where *filename* is a string

a synonym for read-pdb. Read the coordinates from filename (can be pdb, cif or shelx format)

13.43.16 allow-duplicate-sequence-numbers

`allow-duplicate-sequence-numbers` [function]

enable reading PDB/pdbx files with duplicate sequence numbers

13.43.17 set-convert-to-v2-atom-names

`set-convert-to-v2-atom-names` *state* [function]

Where *state* is an integer number

shall we convert nucleotides to match the old dictionary names?

Usually (after 2006 or so) we do not want to do this (given current Coot architecture). Coot should handle the residue synonyms transparently.

default off (0).

13.43.18 handle-read-draw-molecule-with-recentre

`handle-read-draw-molecule-with-recentre` *filename* *recentre_on_read_pdb_flag* [function]

Where:

- *filename* is a string
- *recentre_on_read_pdb_flag* is an integer number

read coordinates from filename with option to not recentre.

set recentre_on_read_pdb_flag to 0 if you don't want the view to recentre on the new coordinates.

13.43.19 handle-read-draw-molecule-and-move-molecule-here

`handle-read-draw-molecule-and-move-molecule-here` *filename* [function]

Where *filename* is a string

read coordinates from filename and recentre the new molecule at the screen rotation centre.

13.43.20 read-pdb

`read-pdb` *filename* [function]

Where *filename* is a string

read coordinates from filename

13.43.21 assign-hetatms

`assign-hetatms` *imol* [function]

Where *imol* is an integer number

some programs produce PDB files with ATOMs where there should be HETATMs. This is a function to assign HETATMs as per the PDB definition.

13.43.22 hetify-residue

`hetify-residue` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

if this is not a standard group, then turn the atoms to HETATMs.

Return 1 on atoms changes, 0 on not. Return -1 if residue not found.

13.43.23 residue-has-hetatms

`residue-has-hetatms` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

residue has HETATMs?

return 1 if all atoms of the specified residue are HETATMs, else, return 0. If residue not found, return -1.

13.43.24 het-group-n-atoms

`het-group-n-atoms` *comp_id* [function]

Where *comp_id* is a string

return the number of non-hydrogen atoms in the given het-group (comp-id).

Return -1 on comp-id not found in dictionary.

13.43.25 replace-fragment

`replace-fragment` *imol_target imol_fragment atom_selection* [function]

Where:

- *imol_target* is an integer number
- *imol_fragment* is an integer number
- *atom_selection* is a string

replace the parts of molecule number imol that are duplicated in molecule number imol_frag

13.43.26 copy-residue-range

`copy-residue-range` *imol_target chain_id_target imol_reference chain_id_reference resno_range_start resno_range_end* [function]

Where:

- *imol_target* is an integer number
- *chain_id_target* is a string
- *imol_reference* is an integer number
- *chain_id_reference* is a string
- *resno_range_start* is an integer number
- *resno_range_end* is an integer number

copy the given residue range from the reference chain to the target chain

resno_range_start and resno_range_end are inclusive.

13.43.27 clear-and-update-model-molecule-from-file

`clear-and-update-model-molecule-from-file` *molecule_number file_name* [function]

Where:

- *molecule_number* is an integer number
- *file_name* is a string

replace the given residues from the reference molecule to the target molecule

replace pdb. Fail if molecule_number is not a valid model molecule. Return -1 on failure. Else return molecule_number

13.43.28 screendump-image

`screendump-image` *filename* [function]

Where *filename* is a string

dump the current screen image to a file. Format ppm

You can use this, in conjunction with spinning and view moving functions to make movies

13.43.29 check-for-dark-blue-density

`check-for-dark-blue-density` [function]

give a warning dialog if density it too dark (blue)

13.43.30 set-draw-solid-density-surface

`set-draw-solid-density-surface` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

sets the density map of the given molecule to be drawn as a (transparent) solid surface.

13.43.31 set-draw-map-standard-lines

`set-draw-map-standard-lines` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

toggle for standard lines representation of map.

This turns off/on standard lines representation of map. transparent surface is another representation type.

If you want to just turn off a map, don't use this, use

.

13.43.32 set-solid-density-surface-opacity

`set-solid-density-surface-opacity` *imol opacity* [function]

Where:

- *imol* is an integer number
- *opacity* is a number

set the opacity of density surface representation of the given map.

0.0 is totally transparent, 1.0 is completely opaque and (because the objects are no longer depth sorted) considerably faster to render. 0.3 is a reasonable number.

13.43.33 set-flat-shading-for-solid-density-surface

`set-flat-shading-for-solid-density-surface` *state* [function]

Where *state* is an integer number

set the flag to do flat shading rather than smooth shading for solid density surface.

Default is 1 (on.

13.44 Interface Preferences

13.44.1 set-scroll-by-wheel-mouse

`set-scroll-by-wheel-mouse` *istate* [function]

Where *istate* is an integer number

Some people (like Phil Evans) don't want to scroll their map with the mouse-wheel.

To turn off mouse wheel recontouring call this with istate value of 0

13.44.2 scroll-by-wheel-mouse-state

`scroll-by-wheel-mouse-state` [function]

return the internal state of the scroll-wheel map contouring

13.44.3 set-default-initial-contour-level-for-map

`set-default-initial-contour-level-for-map` *n_sigma* [function]

Where *n_sigma* is a number

set the default inital contour for 2FoFc-style map

in sigma

13.44.4 set-default-initial-contour-level-for-difference-map

`set-default-initial-contour-level-for-difference-map` *n_sigma* [function]

Where *n_sigma* is a number

set the default inital contour for FoFc-style map

in sigma

13.44.5 print-view-matrix

`print-view-matrix` [function]

print the view matrix to the console, useful for molscript, perhaps

13.44.6 get-view-quaternion-internal

`get-view-quaternion-internal` *element* [function]

Where *element* is an integer number

internal function to get an element of the view quaternion. The whole quaternion is returned by the scheme function view-quaternion

13.44.7 set-view-quaternion

`set-view-quaternion` *i j k l* [function]

Where:

- *i* is a number
- *j* is a number
- *k* is a number
- *l* is a number

Set the view quaternion.

13.44.8 apply-ncs-to-view-orientation

`apply-ncs-to-view-orientation` *imol current_chain next_ncs_chain* [function]

Where:

- *imol* is an integer number
- *current_chain* is a string
- *next_ncs_chain* is a string

Given that we are in chain current_chain, apply the NCS operator that maps current_chain on to next_ncs_chain, so that the relative view is preserved. For NCS skipping.

13.44.9 apply-ncs-to-view-orientation-and-screen-centre

`apply-ncs-to-view-orientation-and-screen-centre` *imol current_chain next_ncs_chain forward_flag* [function]

Where:

- *imol* is an integer number
- *current_chain* is a string
- *next_ncs_chain* is a string
- *forward_flag* is an integer number

as above, but shift the screen centre also.

13.44.10 set-fps-flag

`set-fps-flag` *t* [function]

Where *t* is an integer number

set show frame-per-second flag

13.44.11 get-fps-flag

`get-fps-flag` [function]

set the state of show frames-per-second flag

13.44.12 set-show-origin-marker

`set-show-origin-marker` *istate* [function]

Where *istate* is an integer number

set a flag: is the origin marker to be shown? 1 for yes, 0 for no.

13.44.13 show-origin-marker-state

`show-origin-marker-state` [function]

return the origin marker shown? state

13.44.14 hide-modelling-toolbar

`hide-modelling-toolbar` [function]

hide the vertical modelling toolbar in the GTK2 version

13.44.15 show-modelling-toolbar

`show-modelling-toolbar` [function]

show the vertical modelling toolbar in the GTK2 version (the toolbar is shown by default)

13.44.16 hide-main-toolbar

`hide-main-toolbar` [function]

hide the horizontal main toolbar in the GTK2 version

13.44.17 show-main-toolbar

`show-main-toolbar` [function]

show the horizontal main toolbar in the GTK2 version (the toolbar is shown by default)

13.44.18 show-model-toolbar-all-icons

`show-model-toolbar-all-icons` [function]

show all available icons in the modelling toolbar (same as MFR dialog)

13.44.19 show-model-toolbar-main-icons

`show-model-toolbar-main-icons` [function]

show only a selection of icons in the modelling toolbar

13.44.20 reattach-modelling-toolbar

`reattach-modelling-toolbar` [function]

reattach the modelling toolbar to the last attached position

13.44.21 set-model-toolbar-docked-position

`set-model-toolbar-docked-position` *state* [function]

Where *state* is an integer number

to swap sides of the Model/Fit/Refine toolbar 0 (default) is right, 1 is left, 2 is top, 3 is bottom

13.44.22 suck-model-fit-dialog

`suck-model-fit-dialog` [function]

reparent the Model/Fit/Refine dialog so that it becomes part of the main window, next to the GL graphics context

13.44.23 add-status-bar-text

`add-status-bar-text` *s* [function]

Where *s* is a string

Put text s into the status bar.

use this to put info for the user in the statusbar (less intrusive than popup).

13.44.24 set-model-fit-refine-dialog-stays-on-top

`set-model-fit-refine-dialog-stays-on-top` *istate* [function]

Where *istate* is an integer number

model-fit-refine dialog stays on top

13.44.25 model-fit-refine-dialog-stays-on-top-state

`model-fit-refine-dialog-stays-on-top-state` [function]

return the state model-fit-refine dialog stays on top

13.44.26 accept-reject-dialog-docked-state

`accept-reject-dialog-docked-state` [function]

the accept/reject dialog docked state

13.44.27 set-accept-reject-dialog-docked-show

`set-accept-reject-dialog-docked-show` *state* [function]

Where *state* is an integer number

set the accept/reject dialog docked show state

13.44.28 accept-reject-dialog-docked-show-state

`accept-reject-dialog-docked-show-state` [function]

what is the accept/reject dialog docked show state?

13.45 Mouse Buttons

13.45.1 set-control-key-for-rotate

`set-control-key-for-rotate` *state* [function]

Where *state* is an integer number

Alternate mode for rotation.

Prefered by some, including Dirk Kostrewa. I don't think this mode works properly yet

13.45.2 control-key-for-rotate-state

`control-key-for-rotate-state` [function]

return the control key rotate state

13.45.3 blob-under-pointer-to-screen-centre

`blob-under-pointer-to-screen-centre` [function]

Put the blob under the cursor to the screen centre. Check only positive blobs. Useful function if bound to a key.

The refinement map must be set. (We can't check all maps because they are not (or may not be) on the same scale).

Returns: 1 if successfully found a blob and moved there. return 0 if no move.

13.46 Cursor Function

13.46.1 normal-cursor

`normal-cursor` [function]

normal cursor

13.46.2 fleur-cursor

`fleur-cursor` [function]

fleur cursor

13.46.3 pick-cursor-maybe

`pick-cursor-maybe` [function]

pick cursor maybe

13.46.4 rotate-cursor

`rotate-cursor` [function]

rotate cursor

13.46.5 set-pick-cursor-index

`set-pick-cursor-index` *icursor_index* [function]

Where *icursor_index* is an integer number

let the user have a different pick cursor

sometimes (the default) GDK_CROSSHAIR is hard to see, let the user set their own

13.47 Model/Fit/Refine Functions

13.47.1 post-model-fit-refine-dialog

`post-model-fit-refine-dialog` [function]

display the Model/Fit/Refine dialog

13.47.2 unset-model-fit-refine-dialog

`unset-model-fit-refine-dialog` [function]

unset model/fit/refine dialog

13.47.3 unset-refine-params-dialog

`unset-refine-params-dialog` [function]

unset refine params dialog

13.47.4 show-select-map-dialog

`show-select-map-dialog` [function]

display the Display Manager dialog

13.47.5 set-model-fit-refine-rotate-translate-zone-label

`set-model-fit-refine-rotate-translate-zone-label` *txt* [function]

Where *txt* is a string

Allow the changing of Model/Fit/Refine button label from "Rotate/Translate Zone".

13.47.6 set-model-fit-refine-place-atom-at-pointer-label

`set-model-fit-refine-place-atom-at-pointer-label` *txt* [function]

Where *txt* is a string

Allow the changing of Model/Fit/Refine button label from "Place Atom at Pointer".

13.47.7 post-other-modelling-tools-dialog

`post-other-modelling-tools-dialog` [function]

display the Other Modelling Tools dialog

13.47.8 set-refinement-move-atoms-with-zero-occupancy

`set-refinement-move-atoms-with-zero-occupancy` *state* [function]

Where *state* is an integer number

shall atoms with zero occupancy be moved when refining? (default 1, yes)

13.47.9 refinement-move-atoms-with-zero-occupancy-state

`refinement-move-atoms-with-zero-occupancy-state` [function]

return the state of "shall atoms with zero occupancy be moved when refining?"

13.48 Backup Functions

13.48.1 make-backup

`make-backup` *imol* [function]

Where *imol* is an integer number

make backup for molecule number imol

13.48.2 turn-off-backup

`turn-off-backup` *imol* [function]

Where *imol* is an integer number

turn off backups for molecule number imol

13.48.3 turn-on-backup

`turn-on-backup` *imol* [function]

Where *imol* is an integer number

turn on backups for molecule number imol

13.48.4 backup-state

`backup-state` *imol* [function]

Where *imol* is an integer number

return the backup state for molecule number imol

return 0 for backups off, 1 for backups on, -1 for unknown

13.48.5 apply-undo

`apply-undo` [function]

apply undo - the "Undo" button callback

13.48.6 apply-redo

`apply-redo` [function]

apply redo - the "Redo" button callback

13.48.7 set-have-unsaved-changes

`set-have-unsaved-changes` *imol* [function]

Where *imol* is an integer number

set the molecule number imol to be marked as having unsaved changes

13.48.8 have-unsaved-changes-p

`have-unsaved-changes-p` *imol* [function]

Where *imol* is an integer number

does molecule number imol have unsaved changes?

Returns: -1 on bad imol, 0 on no unsaved changes, 1 on has unsaved changes

13.48.9 set-undo-molecule

`set-undo-molecule` *imol* [function]

Where *imol* is an integer number

set the molecule to which undo operations are done to molecule number imol

13.48.10 show-set-undo-molecule-chooser

`show-set-undo-molecule-chooser` [function]

show the Undo Molecule chooser - i.e. choose the molecule to which the "Undo" button applies.

13.48.11 set-unpathed-backup-file-names

`set-unpathed-backup-file-names` *state* [function]

Where *state* is an integer number

set the state for adding paths to backup file names

by default directories names are added into the filename for backup (with / to _ mapping). call this with state=1 to turn off directory names

13.48.12 unpathed-backup-file-names-state

`unpathed-backup-file-names-state` [function]

return the state for adding paths to backup file names

13.48.13 backup-compress-files-state

`backup-compress-files-state` [function]

return the state for compression of backup files

13.48.14 set-backup-compress-files

`set-backup-compress-files` *state* [function]

Where *state* is an integer number

set if backup files will be compressed or not using gzip

13.49 Recover Session Function

13.49.1 recover-session

`recover-session` [function]

recover session

After a crash, we provide this convenient interface to restore the session. It runs through all the molecules with models and looks at the coot backup directory looking for related backup files that are more recent that the read file. (Not very good, because you need to remember which files you read in before the crash - should be improved.)

13.50 Map Functions

13.50.1 calc-phases-generic

`calc-phases-generic` *mtz_file_name* [function]

Where *mtz_file_name* is a string

fire up a GUI, which asks us which model molecule we want to calc phases from. On "OK" button there, we call map_from_mtz_by_refmac_calc_phases()

13.50.2 map-from-mtz-by-refmac-calc-phases

`map-from-mtz-by-refmac-calc-phases` *mtz_file_name f_col sigf_col imol_coords* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *sigf_col* is a string
- *imol_coords* is an integer number

Calculate SFs (using refmac optionally) from an MTZ file and generate a map. Get F and SIGF automatically (first of their type) from the mtz file.

Returns: the new molecule number, -1 on a problem.

13.50.3 map-from-mtz-by-calc-phases

`map-from-mtz-by-calc-phases` *mtz_file_name f_col sigf_col imol_coords* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *sigf_col* is a string
- *imol_coords* is an integer number

Calculate SFs from an MTZ file and generate a map.

Returns: the new molecule number.

13.50.4 set-scroll-wheel-map

`set-scroll-wheel-map` *imap* [function]

Where *imap* is an integer number

set the map that is moved by changing the scroll wheel and change_contour_level().

13.50.5 set-scrollable-map

`set-scrollable-map` *imol* [function]

Where *imol* is an integer number

return the molecule number to which the mouse scroll wheel is attached

set the map that has its contour level changed by the scrolling the mouse wheel to molecule number imol (same as

).

13.50.6 scroll-wheel-map

`scroll-wheel-map` [function]

the contouring of which map is altered when the scroll wheel changes?

13.50.7 save-previous-map-colour

`save-previous-map-colour` *imol* [function]

Where *imol* is an integer number

save previous colour map for molecule number imol

13.50.8 restore-previous-map-colour

`restore-previous-map-colour` *imol* [function]

Where *imol* is an integer number

restore previous colour map for molecule number imol

13.50.9 set-active-map-drag-flag

`set-active-map-drag-flag` *t* [function]

Where *t* is an integer number

set the state of immediate map upate on map drag.

By default, it is on (t=1). On slower computers it might be better to set t=0.

13.50.10 get-active-map-drag-flag

`get-active-map-drag-flag` [function]

return the state of the dragged map flag

13.50.11 set-last-map-colour

`set-last-map-colour` *f1 f2 f3* [function]

Where:

- *f1* is a number
- *f2* is a number
- *f3* is a number

set the colour of the last (highest molecule number) map

13.50.12 set-map-colour

`set-map-colour` *imol red green blue* [function]

Where:

- *imol* is an integer number
- *red* is a number
- *green* is a number
- *blue* is a number

set the colour of the imolth map

13.50.13 set-last-map-sigma-step

`set-last-map-sigma-step` *f* [function]

Where *f* is a number

set the sigma step of the last map to f sigma

13.50.14 set-contour-by-sigma-step-by-mol

`set-contour-by-sigma-step-by-mol` *f state imol* [function]

Where:

- *f* is a number
- *state* is an integer number
- *imol* is an integer number

set the contour level step

set the contour level step of molecule number imol to f and variable state (setting state to 0 turns off contouring by sigma level)

13.50.15 data-resolution

`data-resolution` *imol* [function]

Where *imol* is an integer number

return the resolution of the data for molecule number imol. Return negative number on error, otherwise resolution in A (eg. 2.0)

13.50.16 model-resolution

`model-resolution` *imol* [function]

Where *imol* is an integer number

return the resolution set in the header of the model/coordinates file. If this number is not available, return a number less than 0.

13.50.17 export-map

`export-map` *imol filename* [function]

Where:

- *imol* is an integer number
- *filename* is a string

export (write to disk) the map of molecule number imol to filename.

Return 0 on failure, 1 on success.

13.50.18 export-map-fragment

`export-map-fragment` *imol x y z radius filename* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number
- *radius* is a number
- *filename* is a string

export a fragment of the map about (x,y,z)

13.50.19 export-map-fragment-with-origin-shift

`export-map-fragment-with-origin-shift` *imol x y z radius filename* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number
- *radius* is a number
- *filename* is a string

export a fragment of the map about (x,y,z)

13.50.20 difference-map

`difference-map` *imol1 imol2 map_scale* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *map_scale* is a number

make a difference map, taking map_scale * imap2 from imap1, on the grid of imap1. Return the new molecule number. Return -1 on failure.

13.50.21 reinterp-map

`reinterp-map` *map_no reference_map_no* [function]

Where:

- *map_no* is an integer number
- *reference_map_no* is an integer number

make a new map (a copy of map_no) that is in the cell, spacegroup and gridding of the map in reference_map_no.

Return the new map molecule number - return -1 on failure

13.50.22 smooth-map

`smooth-map` *map_no sampling_multiplier* [function]

Where:

- *map_no* is an integer number
- *sampling_multiplier* is a number

make a new map (a copy of map_no) that is in the cell, spacegroup and a multiple of the sampling of the input map (a sampling factor of more than 1 makes the output maps smoother)

13.51 Density Increment

13.51.1 set-iso-level-increment

`set-iso-level-increment` *val* [function]

Where *val* is a number

set the contour scroll step (in absolute e/A3) for 2Fo-Fc-style maps to val

The is only activated when scrolling by sigma is turned off

13.51.2 set-diff-map-iso-level-increment

`set-diff-map-iso-level-increment` *val* [function]

Where *val* is a number

set the contour scroll step for difference map (in absolute e/A3) to val

The is only activated when scrolling by sigma is turned off

13.51.3 get-diff-map-iso-level-increment

`get-diff-map-iso-level-increment` [function]

return difference maps iso-map level increment

13.51.4 set-diff-map-iso-level-increment-from-text

`set-diff-map-iso-level-increment-from-text` *text imol* [function]

Where:

- *text* is a string
- *imol* is an integer number

set the difference maps iso-map level increment

13.51.5 set-map-sampling-rate-text

`set-map-sampling-rate-text` *text* [function]

Where *text* is a string

sampling rate

find the molecule for which the single map dialog applies and set the contour level and redraw

13.51.6 set-map-sampling-rate

`set-map-sampling-rate` *r* [function]

Where *r* is a number

set the map sampling rate (default 1.5)

Set to something like 2.0 or 2.5 for more finely sampled maps. Useful for baton-building low resolution maps.

13.51.7 get-map-sampling-rate

`get-map-sampling-rate` [function]

return the map sampling rate

13.51.8 change-contour-level

`change-contour-level` *is_increment* [function]

Where *is_increment* is an integer number

change the contour level of the current map by a step

if is_increment=1 the contour level is increased. If is_increment=0 the map contour level is decreased.

13.51.9 set-last-map-contour-level

`set-last-map-contour-level` *level* [function]

Where *level* is a number

set the contour level of the map with the highest molecule number to level

13.51.10 set-last-map-contour-level-by-sigma

`set-last-map-contour-level-by-sigma` *n_sigma* [function]

Where *n_sigma* is a number

set the contour level of the map with the highest molecule number to n_sigma sigma

13.51.11 set-stop-scroll-diff-map

`set-stop-scroll-diff-map` *i* [function]

Where *i* is an integer number

create a lower limit to the "Fo-Fc-style" map contour level changing

(default 1 on)

13.51.12 set-stop-scroll-iso-map

`set-stop-scroll-iso-map` *i* [function]

Where *i* is an integer number

create a lower limit to the "2Fo-Fc-style" map contour level changing

(default 1 on)

13.51.13 set-stop-scroll-iso-map-level

`set-stop-scroll-iso-map-level` *f* [function]

Where *f* is a number

set the actual map level changing limit

(default 0.0)

13.51.14 set-stop-scroll-diff-map-level

`set-stop-scroll-diff-map-level` *f* [function]

Where *f* is a number

set the actual difference map level changing limit

(default 0.0)

13.51.15 set-residue-density-fit-scale-factor

`set-residue-density-fit-scale-factor` *f* [function]

Where *f* is a number

set the scale factor for the Residue Density fit analysis

13.52 Density Functions

13.52.1 set-map-line-width

`set-map-line-width` *w* [function]

Where *w* is an integer number

draw the lines of the chickenwire density in width w

13.52.2 map-line-width-state

`map-line-width-state` [function]

return the width in which density contours are drawn

13.52.3 make-and-draw-map

`make-and-draw-map` *mtz_file_name f_col phi_col weight use_weights is_diff_map* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *phi_col* is a string
- *weight* is a string
- *use_weights* is an integer number
- *is_diff_map* is an integer number

make a map from an mtz file (simple interface)

given mtz file mtz_file_name and F column f_col and phases column phi_col and optional weight column weight_col (pass use_weights=0 if weights are not to be used). Also mark the map as a difference map (is_diff_map=1) or not (is_diff_map=0) because they are handled differently inside coot.

Returns: -1 on error, else return the new molecule number

13.52.4 make-and-draw-map-with-refmac-params

`make-and-draw-map-with-refmac-params` *mtz_file_name a b weight use_weights is_diff_map have_refmac_params fobs_col sigfobs_col r_free_col sensible_f_free_col* [function]

Where:

- *mtz_file_name* is a string
- *a* is a string
- *b* is a string
- *weight* is a string
- *use_weights* is an integer number
- *is_diff_map* is an integer number
- *have_refmac_params* is an integer number
- *fobs_col* is a string
- *sigfobs_col* is a string
- *r_free_col* is a string
- *sensible_f_free_col* is an integer number

as the above function, execpt set refmac parameters too

pass along the refmac column labels for storage (not used in the creation of the map)

Returns: -1 on error, else return imol

13.52.5 make-and-draw-map-with-reso-with-refmac-params

`make-and-draw-map-with-reso-with-refmac-params` *mtz_file_name a b weight use_weights is_diff_map have_refmac_params fobs_col sigfobs_col r_free_col sensible_f_free_col is_anomalous use_reso_limits low_reso_limit high_reso_lim* [function]

Where:

- *mtz_file_name* is a string
- *a* is a string
- *b* is a string
- *weight* is a string
- *use_weights* is an integer number
- *is_diff_map* is an integer number
- *have_refmac_params* is an integer number
- *fobs_col* is a string
- *sigfobs_col* is a string
- *r_free_col* is a string
- *sensible_f_free_col* is an integer number
- *is_anomalous* is an integer number
- *use_reso_limits* is an integer number
- *low_reso_limit* is a number
- *high_reso_lim* is a number

as the above function, except set expert options too.

13.52.6 valid-labels

`valid-labels` *mtz_file_name f_col phi_col weight_col use_weights* [function]

Where:

- *mtz_file_name* is a string
- *f_col* is a string
- *phi_col* is a string
- *weight_col* is a string
- *use_weights* is an integer number

does the mtz file have the columms that we want it to have?

13.52.7 mtz-file-has-phases-p

`mtz-file-has-phases-p` *mtz_file_name* [function]

Where *mtz_file_name* is a string

does the mtz file have phases?

13.52.8 is-mtz-file-p

`is-mtz-file-p` *filename* [function]

Where *filename* is a string

is the given filename an mtz file?

13.52.9 cns-file-has-phases-p

`cns-file-has-phases-p` *cns_file_name* [function]

Where *cns_file_name* is a string

does the given file have cns phases?

13.52.10 auto-read-do-difference-map-too-state

`auto-read-do-difference-map-too-state` [function]

return the flag to do a difference map (too) on auto-read MTZ

Returns: 0 means no, 1 means yes.

13.52.11 set-auto-read-column-labels

`set-auto-read-column-labels` *fwt phwt is_for_diff_map_flag* [function]

Where:

- *fwt* is a string
- *phwt* is a string
- *is_for_diff_map_flag* is an integer number

set the expected MTZ columns for Auto-reading MTZ file.

Not every program uses the default refmac labels ("FWT"/"PHWT") for its MTZ file. Here we can tell coot to expect other labels so that coot can "Auto-open" such MTZ files.

e.g. (set-auto-read-column-labels "2FOFCWT" "PH2FOFCWT" 0)

13.52.12 set-map-radius

`set-map-radius` *f* [function]

Where *f* is a number

set the extent of the box/radius of electron density contours

13.52.13 set-density-size

`set-density-size` *f* [function]

Where *f* is a number

another (old) way of setting the radius of the map

13.52.14 set-display-intro-string

`set-display-intro-string` *str* [function]

Where *str* is a string

Give me this nice message str when I start coot.

13.52.15 get-map-radius

`get-map-radius` [function]

return the extent of the box/radius of electron density contours

13.52.16 set-esoteric-depth-cue

`set-esoteric-depth-cue` *istate* [function]

Where *istate* is an integer number

not everone likes coot's esoteric depth cueing system

Pass an argument istate=1 to turn it off

(this function is currently disabled).

13.52.17 esoteric-depth-cue-state

`esoteric-depth-cue-state` [function]

native depth cueing system

return the state of the esoteric depth cueing flag

13.52.18 set-swap-difference-map-colours

`set-swap-difference-map-colours` *i* [function]

Where *i* is an integer number

not everone likes coot's default difference map colouring.

Pass an argument i=1 to swap the difference map colouring so that red is positive and green is negative.

13.52.19 set-map-is-difference-map

`set-map-is-difference-map` *imol* [function]

Where *imol* is an integer number

post-hoc set the map of molecule number imol to be a difference map

Returns: success status, 0 -> failure (imol does not have a map)

13.52.20 map-is-difference-map

`map-is-difference-map` *imol* [function]

Where *imol* is an integer number

map is difference map?

13.52.21 another-level

`another-level` [function]

Add another contour level for the last added map.

Currently, the map must have been generated from an MTZ file.

Returns: the molecule number of the new molecule or -1 on failure

13.52.22 another-level-from-map-molecule-number

`another-level-from-map-molecule-number` *imap* [function]

Where *imap* is an integer number

Add another contour level for the given map.

Currently, the map must have been generated from an MTZ file.

Returns: the molecule number of the new molecule or -1 on failure

13.52.23 residue-density-fit-scale-factor

`residue-density-fit-scale-factor` [function]

return the scale factor for the Residue Density fit analysis

13.52.24 density-at-point

`density-at-point` *imol_map x y z* [function]

Where:

- *imol_map* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number

return the density at the given point for the given map. Return 0 for bad imol

13.53 Parameters from map

13.53.1 mtz-hklin-for-map

`mtz-hklin-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the mtz file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say).

13.53.2 mtz-fp-for-map

`mtz-fp-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the FP column in the file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say).

Caller should dispose of returned pointer.

13.53.3 mtz-phi-for-map

`mtz-phi-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the phases column in mtz file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say). Caller should dispose of returned pointer.

13.53.4 mtz-weight-for-map

`mtz-weight-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return the weight column in the mtz file that was use to generate the map

return 0 when there is no mtz file associated with that map (it was generated from a CCP4 map file say) or no weights were used. Caller should dispose of returned pointer.

13.53.5 mtz-use-weight-for-map

`mtz-use-weight-for-map` *imol_map* [function]

Where *imol_map* is an integer number

return flag for whether weights were used that was use to generate the map

return 0 when no weights were used or there is no mtz file associated with that map.

13.54 PDB Functions

13.54.1 write-pdb-file

`write-pdb-file` *imol file_name* [function]

Where:

- *imol* is an integer number
- *file_name* is a string

write molecule number imol as a PDB to file file_name

13.54.2 write-residue-range-to-pdb-file

`write-residue-range-to-pdb-file` *imol chainid resno_start resno_end filename* [function]

Where:

- *imol* is an integer number
- *chainid* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number
- *filename* is a string

write molecule number imol's residue range as a PDB to file file_name

13.54.3 quick-save

`quick-save` [function]

save all modified coordinates molecules to the default names and save the state too.

13.55 Info Dialog

13.55.1 info-dialog

`info-dialog` *txt* [function]

Where *txt* is a string

create a dialog with information

create a dialog with information string txt. User has to click to dismiss it, but it is not modal (nothing in coot is modal).

13.55.2 info-dialog-and-text

`info-dialog-and-text` *txt* [function]

Where *txt* is a string

create a dialog with information and print to console

as info_dialog but print to console as well.

13.56 Refmac Functions

13.56.1 set-refmac-counter

`set-refmac-counter` *imol refmac_count* [function]

Where:

- *imol* is an integer number
- *refmac_count* is an integer number

set counter for runs of refmac so that this can be used to construct a unique filename for new output

13.56.2 swap-map-colours

`swap-map-colours` *imol1 imol2* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number

swap the colours of maps

swap the colour of maps imol1 and imol2. Useful to some after running refmac, so that the map to be build into is always the same colour

13.56.3 set-keep-map-colour-after-refmac

`set-keep-map-colour-after-refmac` *istate* [function]

Where *istate* is an integer number

flag to enable above

call this with istate=1

13.56.4 keep-map-colour-after-refmac-state

`keep-map-colour-after-refmac-state` [function]

the keep-map-colour-after-refmac internal state

Returns: 1 for "yes", 0 for "no"

13.57 Symmetry Functions

13.57.1 set-symmetry-size

`set-symmetry-size` *f* [function]

Where *f* is a number

set the size of the displayed symmetry

13.57.2 get-show-symmetry

`get-show-symmetry` [function]

is symmetry master display control on?

13.57.3 set-show-symmetry-master

`set-show-symmetry-master` *state* [function]

Where *state* is an integer number

set display symmetry, master controller

13.57.4 set-show-symmetry-molecule

`set-show-symmetry-molecule` *mol_no state* [function]

Where:

- *mol_no* is an integer number
- *state* is an integer number

set display symmetry for molecule number mol_no

pass with state=0 for off, state=1 for on

13.57.5 symmetry-as-calphas

`symmetry-as-calphas` *mol_no state* [function]

Where:

- *mol_no* is an integer number
- *state* is an integer number

display symmetry as CAs?

pass with state=0 for off, state=1 for on

13.57.6 get-symmetry-as-calphas-state

`get-symmetry-as-calphas-state` *imol* [function]

Where *imol* is an integer number

what is state of display CAs for molecule number mol_no?

return state=0 for off, state=1 for on

13.57.7 set-symmetry-molecule-rotate-colour-map

`set-symmetry-molecule-rotate-colour-map` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set the colour map rotation (i.e. the hue) for the symmetry atoms of molecule number imol

13.57.8 symmetry-molecule-rotate-colour-map-state

`symmetry-molecule-rotate-colour-map-state` *imol* [function]

Where *imol* is an integer number

should there be colour map rotation (i.e. the hue) change for the symmetry atoms of molecule number imol?

return state=0 for off, state=1 for on

13.57.9 set-symmetry-colour-by-symop

`set-symmetry-colour-by-symop` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set symmetry colour by symop mode

13.57.10 set-symmetry-whole-chain

`set-symmetry-whole-chain` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set symmetry colour for the chain

13.57.11 set-symmetry-atom-labels-expanded

`set-symmetry-atom-labels-expanded` *state* [function]

Where *state* is an integer number

set use expanded symmetry atom labels

13.57.12 has-unit-cell-state

`has-unit-cell-state` *imol* [function]

Where *imol* is an integer number

molecule number imol has a unit cell?

Returns: 1 on "yes, it has a cell", 0 for "no"

13.57.13 undo-symmetry-view

`undo-symmetry-view` [function]

Undo symmetry view. Translate back to main molecule from this symmetry position.

13.57.14 first-molecule-with-symmetry-displayed

`first-molecule-with-symmetry-displayed` [function]

return the molecule number.

Returns: -1 if there is no molecule with symmetry displayed.

13.57.15 save-symmetry-coords

`save-symmetry-coords` *imol filename symop_no shift_a shift_b shift_c pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *filename* is a string
- *symop_no* is an integer number
- *shift_a* is an integer number
- *shift_b* is an integer number
- *shift_c* is an integer number
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

save the symmetry coordinates of molecule number imol to filename

Allow a shift of the coordinates to the origin before symmetry expansion is apllied (this is how symmetry works in Coot internals).

13.57.16 new-molecule-by-symmetry

`new-molecule-by-symmetry` *imol name m11 m12 m13 m21 m22 m23 m31 m32 m33 tx ty tz pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *name* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *tx* is a number
- *ty* is a number
- *tz* is a number
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

create a new molecule (molecule number is the return value) from imol.

The rotation/translation matrix components are given in

coordinates.

Allow a shift of the coordinates to the origin before symmetry expansion is aplied.

Pass `""` as the name-in and a name will be constructed for you.

Return -1 on failure.

13.57.17 new-molecule-by-symmetry-with-atom-selection

`new-molecule-by-symmetry-with-atom-selection` *imol name mmdb_atom_selection_string m11 m12 m13 m21 m22 m23 m31 m32 m33 tx ty tz pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *name* is a string
- *mmdb_atom_selection_string* is a string
- *m11* is a number
- *m12* is a number

- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *tx* is a number
- *ty* is a number
- *tz* is a number
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

create a new molecule (molecule number is the return value) from imol, but only for atom that match the mmdb_atom_selection_string.

The rotation/translation matrix components are given in

coordinates.

Allow a shift of the coordinates to the origin before symmetry expansion is aplied.

Pass `""` as the name-in and a name will be constructed for you.

Return -1 on failure.

13.57.18 new-molecule-by-symop

`new-molecule-by-symop` *imol symop_string pre_shift_to_origin_na pre_shift_to_origin_nb pre_shift_to_origin_nc* [function]

Where:

- *imol* is an integer number
- *symop_string* is a string
- *pre_shift_to_origin_na* is an integer number
- *pre_shift_to_origin_nb* is an integer number
- *pre_shift_to_origin_nc* is an integer number

create a new molecule (molecule number is the return value) from imol.

13.57.19 n-symops

`n-symops` *imol* [function]

Where *imol* is an integer number

return the number of symmetry operators for the given molecule

return -1 on no-symmetry for molecule or inappropriate imol number

13.57.20 set-space-group

`set-space-group` *imol spg* [function]

Where:

- *imol* is an integer number
- *spg* is a string

set the space group for a coordinates molecule

for shelx FA pdb files, there is no space group. So allow the user to set it. This can be initted with a HM symbol or a symm list for clipper. Return the succes status of the setting.

13.57.21 set-symmetry-shift-search-size

`set-symmetry-shift-search-size` *shift* [function]

Where *shift* is an integer number

set the cell shift search size for symmetry searching.

When the coordinates for one (or some) symmetry operator are missing (which happens sometimes, but rarely), try changing setting this to 2 (default is 1). It slows symmetry searching, which is why it is not set to 2 by default.

13.58 History Functions

13.58.1 print-all-history-in-scheme

`print-all-history-in-scheme` [function]

print the history in scheme format

13.58.2 print-all-history-in-python

`print-all-history-in-python` [function]

print the history in python format

13.58.3 set-console-display-commands-state

`set-console-display-commands-state` *istate* [function]

Where *istate* is an integer number

set a flag to show the text command equivalent of gui commands in the console as they happen.

1 for on, 0 for off.

13.58.4 set-console-display-commands-hilights

`set-console-display-commands-hilights` *bold_flag colour_flag colour_index* [function]

Where:

- *bold_flag* is an integer number

- *colour_flag* is an integer number
- *colour_index* is an integer number

set a flag to show the text command equivalent of gui commands in the console as they happen in bold and colours.

colour_flag: pass 1 for on, 0 for off.

colour_index 0 to 7 inclusive for various different colourings.

13.59 State Functions

13.59.1 save-state

`save-state` [function]

save the current state to the default filename

13.59.2 save-state-file

`save-state-file` *filename* [function]

Where *filename* is a string

save the current state to file filename

13.59.3 save-state-file-py

`save-state-file-py` *filename* [function]

Where *filename* is a string

save the current state to file filename

13.59.4 set-save-state-file-name

`set-save-state-file-name` *filename* [function]

Where *filename* is a string

set the default state file name (default 0-coot.state.scm)

13.59.5 set-run-state-file-status

`set-run-state-file-status` *istat* [function]

Where *istat* is an integer number

set run state file status

0: never run it 1: ask to run it 2: run it, no questions

13.59.6 run-state-file

`run-state-file` [function]

run the state file (reading from default filenname)

13.59.7 run-state-file-maybe

`run-state-file-maybe` [function]

run the state file depending on the state variables

13.60 The Virtual Trackball

13.60.1 vt-surface

`vt-surface` *mode* [function]

Where *mode* is an integer number

How should the mouse move the view?

mode=1 for "Flat", mode=2 for "Spherical Surface"

13.60.2 vt-surface-status

`vt-surface-status` [function]

return the mouse view status mode

mode=1 for "Flat", mode=2 for "Spherical Surface"

13.61 Clipping Functions

13.61.1 set-clipping-back

`set-clipping-back` *v* [function]

Where *v* is a number

set clipping plane back

13.61.2 set-clipping-front

`set-clipping-front` *v* [function]

Where *v* is a number

set clipping plane front

13.62 Unit Cell interface

13.62.1 get-show-unit-cell

`get-show-unit-cell` *imol* [function]

Where *imol* is an integer number

return the stage of show unit cell for molecule number imol

13.62.2 set-show-unit-cells-all

`set-show-unit-cells-all` *istate* [function]

Where *istate* is an integer number

set the state of show unit cell for all molecules

1 for displayed 0 for undisplayed

13.62.3 set-show-unit-cell

`set-show-unit-cell` *imol istate* [function]

Where:

- *imol* is an integer number
- *istate* is an integer number

set the state of show unit cell for the particular molecule number imol

1 for displayed 0 for undisplayed

13.63 Colour

13.63.1 set-colour-map-rotation-on-read-pdb

`set-colour-map-rotation-on-read-pdb` *f* [function]

Where *f* is a number

set the hue change step on reading a new molecule

13.63.2 set-colour-map-rotation-on-read-pdb-flag

`set-colour-map-rotation-on-read-pdb-flag` *i* [function]

Where *i* is an integer number

shall the hue change step be used?

13.63.3 set-colour-map-rotation-on-read-pdb-c-only-flag

`set-colour-map-rotation-on-read-pdb-c-only-flag` *i* [function]

Where *i* is an integer number

shall the colour map rotation apply only to C atoms?

13.63.4 set-colour-by-chain

`set-colour-by-chain` *imol* [function]

Where *imol* is an integer number

colour molecule number imol by chain type

13.63.5 set-colour-by-molecule

`set-colour-by-molecule` *imol* [function]

Where *imol* is an integer number

colour molecule number imol by molecule

13.63.6 set-symmetry-colour

`set-symmetry-colour` *r g b* [function]

Where:

- *r* is a number
- *g* is a number

- *b* is a number

set the symmetry colour base

13.64 Map colour

13.64.1 set-colour-map-rotation-for-map

`set-colour-map-rotation-for-map` *f* [function]

Where *f* is a number

set the colour map rotation (hue change) for maps

default: for maps is 14 degrees.

13.64.2 set-molecule-bonds-colour-map-rotation

`set-molecule-bonds-colour-map-rotation` *imol theta* [function]

Where:

- *imol* is an integer number
- *theta* is a number

set the colour map rotation for molecule number imol

theta is in degrees

13.64.3 get-molecule-bonds-colour-map-rotation

`get-molecule-bonds-colour-map-rotation` *imol* [function]

Where *imol* is an integer number

Get the colour map rotation for molecule number imol.

13.65 Anisotropic Atoms Interface

13.65.1 get-limit-aniso

`get-limit-aniso` [function]

get the aniso radius limit

13.65.2 get-show-limit-aniso

`get-show-limit-aniso` [function]

get show the aniso limit

13.65.3 get-show-aniso

`get-show-aniso` [function]

return show-aniso-atoms state

13.65.4 set-limit-aniso

`set-limit-aniso` *state* [function]

Where *state* is an integer number

set the aniso atom limit

13.65.5 set-show-aniso

`set-show-aniso` *state* [function]

Where *state* is an integer number

set show aniso atoms

13.65.6 set-aniso-probability

`set-aniso-probability` *f* [function]

Where *f* is a number

set aniso probability

13.65.7 get-aniso-probability

`get-aniso-probability` [function]

get aniso probability

13.66 Display Functions

13.66.1 set-graphics-window-size

`set-graphics-window-size` *x_size y_size* [function]

Where:

- *x_size* is an integer number
- *y_size* is an integer number

set the window size

13.66.2 set-graphics-window-position

`set-graphics-window-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set the graphics window position

13.66.3 store-graphics-window-position

`store-graphics-window-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

store the graphics window position

13.66.4 graphics-draw

`graphics-draw` [function]

draw a frame

13.66.5 zalman-stereo-mode

`zalman-stereo-mode` [function]

try to turn on Zalman stereo mode

13.66.6 hardware-stereo-mode

`hardware-stereo-mode` [function]

try to turn on stereo mode

13.66.7 stereo-mode-state

`stereo-mode-state` [function]

what is the stero state?

Returns: 1 for in hardware stereo, 2 for side by side stereo, else return 0.

13.66.8 mono-mode

`mono-mode` [function]

try to turn on mono mode

13.66.9 side-by-side-stereo-mode

`side-by-side-stereo-mode` *use_wall_eye_mode* [function]

Where *use_wall_eye_mode* is an integer number

turn on side bye side stereo mode

13.66.10 set-hardware-stereo-angle-factor

`set-hardware-stereo-angle-factor` *f* [function]

Where *f* is a number

how much should the eyes be separated in stereo mode?

13.66.11 hardware-stereo-angle-factor-state

`hardware-stereo-angle-factor-state` [function]

return the hardware stereo angle factor

13.66.12 set-model-fit-refine-dialog-position

`set-model-fit-refine-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Model/Fit/Refine dialog

13.66.13 set-display-control-dialog-position

`set-display-control-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Display Control dialog

13.66.14 set-go-to-atom-window-position

`set-go-to-atom-window-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Go To Atom dialog

13.66.15 set-delete-dialog-position

`set-delete-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of Delete dialog

13.66.16 set-rotate-translate-dialog-position

`set-rotate-translate-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of the Rotate/Translate Residue Range dialog

13.66.17 set-accept-reject-dialog-position

`set-accept-reject-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of the Accept/Reject dialog

13.66.18 set-ramachandran-plot-dialog-position

`set-ramachandran-plot-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set position of the Ramachadran Plot dialog

13.66.19 set-edit-chi-angles-dialog-position

`set-edit-chi-angles-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set edit chi angles dialog position

13.66.20 set-rotamer-selection-dialog-position

`set-rotamer-selection-dialog-position` *x_pos y_pos* [function]

Where:

- *x_pos* is an integer number
- *y_pos* is an integer number

set rotamer selection dialog position

13.67 Smooth Scrolling

13.67.1 set-smooth-scroll-flag

`set-smooth-scroll-flag` *v* [function]

Where *v* is an integer number

set smooth scrolling

13.67.2 get-smooth-scroll

`get-smooth-scroll` [function]

return the smooth scrolling state

13.67.3 set-smooth-scroll-steps

`set-smooth-scroll-steps` *i* [function]

Where *i* is an integer number

set the number of steps in the smooth scroll

Set more steps (e.g. 50) for more smoothness (default 10).

13.67.4 set-smooth-scroll-limit

`set-smooth-scroll-limit` *lim* [function]

Where *lim* is a number

do not scroll for distances greater this limit

13.68 Font Parameters

13.68.1 set-font-size

`set-font-size` *i* [function]

Where *i* is an integer number

set the font size

13.68.2 get-font-size

`get-font-size` [function]

return the font size

Returns: 1 (small) 2 (medium, default) 3 (large)

13.68.3 set-font-colour

`set-font-colour` *red green blue* [function]

Where:

- *red* is a number
- *green* is a number
- *blue* is a number

set the colour of the atom label font - the arguments are in the range 0->1

13.68.4 set-use-stroke-characters

`set-use-stroke-characters` *state* [function]

Where *state* is an integer number

set use stroke characters

13.69 Rotation Centre

13.69.1 set-rotation-centre-size

`set-rotation-centre-size` *f* [function]

Where *f* is a number

set rotoation centre marker size

13.69.2 recentre-on-read-pdb

`recentre-on-read-pdb` [function]

return the recentre-on-pdb state

13.69.3 set-recentre-on-read-pdb

`set-recentre-on-read-pdb` *int* [function]

Where *int* is a short

set the recentre-on-pdb state

13.69.4 set-rotation-centre

`set-rotation-centre` *x y z* [function]

Where:

- *x* is a number
- *y* is a number
- *z* is a number

set the rotation centre

13.69.5 go-to-ligand

`go-to-ligand` [function]

centre on the ligand of the "active molecule", if we are already there, centre on the next hetgroup (etc)

13.69.6 set-go-to-ligand-n-atoms-limit

`set-go-to-ligand-n-atoms-limit` *n_atom_min* [function]

Where *n_atom_min* is an integer number

go to the ligand that has more than n_atom_min atoms

13.70 Atom Selection Utilities

13.70.1 median-temperature-factor

`median-temperature-factor` *imol* [function]

Where *imol* is an integer number

return the median temperature factor for imol

13.70.2 average-temperature-factor

`average-temperature-factor` *imol* [function]

Where *imol* is an integer number

return the average temperature factor for the atoms in imol

13.70.3 standard-deviation-temperature-factor

`standard-deviation-temperature-factor` *imol* [function]

Where *imol* is an integer number

return the standard deviation of the atom temperature factors for imol

13.70.4 clear-pending-picks

`clear-pending-picks` [function]

clear pending picks (stop coot thinking that the user is about to pick an atom).

13.70.5 set-default-temperature-factor-for-new-atoms

`set-default-temperature-factor-for-new-atoms` *new_b* [function]

Where *new_b* is a number

set the default temperature factor for newly created atoms (initial default 20)

13.70.6 default-new-atoms-b-factor

`default-new-atoms-b-factor` [function]

return the default temperature factor for newly created atoms

13.70.7 set-reset-b-factor-moved-atoms

`set-reset-b-factor-moved-atoms` *state* [function]

Where *state* is an integer number

reset temperature factor for all moved atoms to the default for new atoms (usually 30)

13.70.8 get-reset-b-factor-moved-atoms-state

`get-reset-b-factor-moved-atoms-state` [function]

return the state if temperature factors shoudl be reset for moved atoms

13.70.9 set-atom-attribute

`set-atom-attribute` *imol chain_id resno ins_code atom_name alt_conf attribute_name val* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atom_name* is a string
- *alt_conf* is a string
- *attribute_name* is a string
- *val* is a number

set a numberical attibute to the atom with the given specifier.

Attributes can be "x", "y","z", "B", "occ" and the attribute val is a floating point number

13.70.10 set-atom-string-attribute

`set-atom-string-attribute` *imol chain_id resno ins_code atom_name alt_conf attribute_name attribute_value* [function]

Where:

- *imol* is an integer number

- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atom_name* is a string
- *alt_conf* is a string
- *attribute_name* is a string
- *attribute_value* is a string

set a string attibute to the atom with the given specifier.

Attributes can be "atom-name", "alt-conf", "element" or "segid".

13.70.11 set-residue-name

`set-residue-name` *imol chain_id res_no ins_code new_residue_name* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *new_residue_name* is a string

set lots of atom attributes at once by-passing the rebonding and redrawing of the above 2 functions

set the residue name of the specified residue

13.71 Skeletonization Interface

13.71.1 skeletonize-map

`skeletonize-map` *imol prune_flag* [function]

Where:

- *imol* is an integer number
- *prune_flag* is an integer number

skeletonize molecule number imol

the prune_flag should almost always be 0.

NOTE:: The arguments to have been reversed for coot 0.8.3 and later (now the molecule number comes first).

13.71.2 unskeletonize-map

`unskeletonize-map` *imol* [function]

Where *imol* is an integer number

undisplay the skeleton on molecule number imol

13.71.3 set-max-skeleton-search-depth

`set-max-skeleton-search-depth` *v* [function]

Where *v* is an integer number

set the skeleton search depth, used in baton building

For high resolution maps, you need to search deeper down the skeleton tree. This limit needs to be increased to 20 or so for high res maps (it is 10 by default)

13.71.4 set-skeleton-box-size

`set-skeleton-box-size` *f* [function]

Where *f* is a number

the box size (in Angstroms) for which the skeleton is displayed

13.72 Skeleton Colour

13.72.1 set-skeleton-colour

`set-skeleton-colour` *imol r g b* [function]

Where:

- *imol* is an integer number
- *r* is a number
- *g* is a number
- *b* is a number

set the skeleton colour

13.73 Read Maps

13.73.1 handle-read-ccp4-map

`handle-read-ccp4-map` *filename is_diff_map_flag* [function]

Where:

- *filename* is a string
- *is_diff_map_flag* is an integer number

read a CCP4 map or a CNS map (despite the name).

13.74 Save Coordinates

13.74.1 save-coordinates

`save-coordinates` *imol filename* [function]

Where:

- *imol* is an integer number
- *filename* is a string

save coordinates of molecule number imol in filename

Returns: status 1 is good (success), 0 is fail.

13.74.2 set-save-coordinates-in-original-directory

`set-save-coordinates-in-original-directory` *i* [function]

Where *i* is an integer number

set save coordinates in the starting directory

13.75 Read Phases File Functions

13.75.1 read-phs-and-coords-and-make-map

`read-phs-and-coords-and-make-map` *pdb_filename* [function]

Where *pdb_filename* is a string

read phs file use coords to get cell and symm to make map

uses pending data to make the map.

13.75.2 read-phs-and-make-map-using-cell-symm-from-previous-mol

`read-phs-and-make-map-using-cell-symm-from-previous-mol` *phs_filename* [function]

Where *phs_filename* is a string

read a phs file, the cell and symm information is from previously read (most recently read) coordinates file

For use with phs data filename provided on the command line

13.75.3 read-phs-and-make-map-using-cell-symm-from-mol

`read-phs-and-make-map-using-cell-symm-from-mol` *phs_filename imol* [function]

Where:

- *phs_filename* is a string
- *imol* is an integer number

read phs file and use a previously read molecule to provide the cell and symmetry information

Returns: the new molecule number, return -1 if problem creating the map (e.g. not phs data, file not found etc).

13.75.4 read-phs-and-make-map-using-cell-symm

`read-phs-and-make-map-using-cell-symm` *phs_file_name hm_spacegroup a b c alpha beta gamma* [function]

Where:

- *phs_file_name* is a string
- *hm_spacegroup* is a string
- *a* is a number

- *b* is a number
- *c* is a number
- *alpha* is a number
- *beta* is a number
- *gamma* is a number

read phs file use coords to use cell and symm to make map

in degrees

13.75.5 read-phs-and-make-map-with-reso-limits

`read-phs-and-make-map-with-reso-limits` *imol phs_file_name reso_lim_low reso_lim_high* [function]

Where:

- *imol* is an integer number
- *phs_file_name* is a string
- *reso_lim_low* is a number
- *reso_lim_high* is a number

read a phs file and use the cell and symm in molecule number imol and use the resolution limits reso_lim_high (in Angstroems).

13.76 Graphics Move

13.76.1 undo-last-move

`undo-last-move` [function]

undo last move

13.76.2 translate-molecule-by

`translate-molecule-by` *imol x y z* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number

translate molecule number imol by (x,y,z) in Angstroms

13.76.3 transform-molecule-by

`transform-molecule-by` *imol m11 m12 m13 m21 m22 m23 m31 m32 m33 x y z* [function]

Where:

- *imol* is an integer number
- *m11* is a number

- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *x* is a number
- *y* is a number
- *z* is a number

transform molecule number imol by the given rotation matrix, then translate by (x,y,z) in Angstroms

13.76.4 transform-zone

`transform-zone` *imol chain_id resno_start resno_end ins_code m11 m12 m13 m21 m22 m23 m31 m32 m33 x y z* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number
- *ins_code* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *x* is a number
- *y* is a number
- *z* is a number

transform fragment of molecule number imol by the given rotation matrix, then translate by (x,y,z) in Angstroms

13.77 Go To Atom Widget Functions

13.77.1 post-go-to-atom-window

`post-go-to-atom-window` [function]

Post the Go To Atom Window.

13.77.2 go-to-atom-molecule-number

`go-to-atom-molecule-number` [function]

the go-to-atom molecule number

13.77.3 go-to-atom-chain-id

`go-to-atom-chain-id` [function]

the go-to-atom chain-id

13.77.4 go-to-atom-atom-name

`go-to-atom-atom-name` [function]

the go-to-atom atom name

13.77.5 go-to-atom-residue-number

`go-to-atom-residue-number` [function]

the go-to-atom residue number

13.77.6 go-to-atom-ins-code

`go-to-atom-ins-code` [function]

the go-to-atom insertion code

13.77.7 go-to-atom-alt-conf

`go-to-atom-alt-conf` [function]

the go-to-atom alt conf

13.77.8 set-go-to-atom-chain-residue-atom-name

`set-go-to-atom-chain-residue-atom-name` *t1_chain_id iresno t3_atom_name* [function]

Where:

- *t1_chain_id* is a string
- *iresno* is an integer number
- *t3_atom_name* is a string

set the go to atom specification

It seems important for swig that the char * arguments are const char *, not const gchar * (or else we get wrong type of argument error on (say) "A"

Returns: the success status of the go to. 0 for fail, 1 for success.

13.77.9 set-go-to-atom-chain-residue-atom-name-full

`set-go-to-atom-chain-residue-atom-name-full` *chain_id resno ins_code atom_name alt_conf* [function]

Where:

- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atom_name* is a string
- *alt_conf* is a string

set the go to (full) atom specification

It seems important for swig that the char * arguments are const char *, not const gchar * (or else we get wrong type of argument error on (say) `"A"`

Returns: the success status of the go to. 0 for fail, 1 for success.

13.77.10 set-go-to-atom-chain-residue-atom-name-no-redraw

`set-go-to-atom-chain-residue-atom-name-no-redraw` *t1 iresno t3 make_the_move_flag* [function]

Where:

- *t1* is a string
- *iresno* is an integer number
- *t3* is a string
- *make_the_move_flag* is an integer number

set go to atom but don't redraw

13.77.11 update-go-to-atom-from-current-position

`update-go-to-atom-from-current-position` [function]

update the Go To Atom widget entries to atom closest to screen centre.

13.77.12 atom-spec-to-atom-index

`atom-spec-to-atom-index` *mol chain resno atom_name* [function]

Where:

- *mol* is an integer number
- *chain* is a string
- *resno* is an integer number
- *atom_name* is a string

what is the atom index of the given atom?

13.77.13 full-atom-spec-to-atom-index

`full-atom-spec-to-atom-index` *imol chain resno inscode atom_name altloc* [function]

Where:

- *imol* is an integer number
- *chain* is a string
- *resno* is an integer number
- *inscode* is a string
- *atom_name* is a string
- *altloc* is a string

what is the atom index of the given atom?

13.77.14 update-go-to-atom-window-on-changed-mol

`update-go-to-atom-window-on-changed-mol` *imol* [function]

Where *imol* is an integer number

update the Go To Atom window

13.77.15 update-go-to-atom-window-on-new-mol

`update-go-to-atom-window-on-new-mol` [function]

update the Go To Atom window. This updates the option menu for the molecules.

13.77.16 set-go-to-atom-molecule

`set-go-to-atom-molecule` *imol* [function]

Where *imol* is an integer number

set the molecule for the Go To Atom

For dynarama callback sake. The widget/class knows which molecule that it was generated from, so in order to go to the molecule from dynarama, we first need to the the molecule - because

does not mention the molecule (see "Next/Previous Residue" for reasons for that). This function simply calls the graphics_info_t function of the same name.

Also used in scripting, where go-to-atom-chain-residue-atom-name does not mention the molecule number.

20090914-PE set-go-to-atom-molecule can be used in a script and it should change the go-to-atom-molecule in the Go To Atom dialog (if it is being displayed). This does mean, of course that using the ramachandran plot to centre on atoms will change the Go To Atom dialog. Maybe that is surprising (maybe not).

13.78 Map and Molecule Control

13.78.1 post-display-control-window

`post-display-control-window` [function]

display the Display Constrol window

13.78.2 set-map-displayed

`set-map-displayed` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the map displayed/undisplayed, 0 for off, 1 for on

13.78.3 set-mol-displayed

`set-mol-displayed` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the coordinates molecule displayed/undisplayed, 0 for off, 1 for on

13.78.4 set-display-only-model-mol

`set-display-only-model-mol` *imol* [function]

Where *imol* is an integer number

from all the model molecules, display only imol

This stops flashing/delayed animations with many molecules

13.78.5 set-mol-active

`set-mol-active` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the coordinates molecule active/inactve (clickable), 0 for off, 1 for on

13.78.6 mol-is-displayed

`mol-is-displayed` *imol* [function]

Where *imol* is an integer number

return the display state of molecule number imol

Returns: 1 for on, 0 for off

13.78.7 mol-is-active

`mol-is-active` *imol* [function]

Where *imol* is an integer number

return the active state of molecule number imol

Returns: 1 for on, 0 for off

13.78.8 map-is-displayed

`map-is-displayed` *imol* [function]

Where *imol* is an integer number

return the display state of molecule number imol

Returns: 1 for on, 0 for off

13.78.9 set-all-maps-displayed

`set-all-maps-displayed` *on_or_off* [function]

Where *on_or_off* is an integer number

if on_or_off is 0 turn off all maps displayed, for other values of on_or_off turn on all maps

13.78.10 set-all-models-displayed-and-active

`set-all-models-displayed-and-active` *on_or_off* [function]

Where *on_or_off* is an integer number

if on_or_off is 0 turn off all models displayed and active, for other values of on_or_off turn on all models.

13.78.11 show-spacegroup

`show-spacegroup` *imol* [function]

Where *imol* is an integer number

return the spacegroup of molecule number imol . Deprecated.

Returns: `"No Spacegroup"` when the spacegroup of a molecule has not been set.

13.79 Align and Mutate

13.79.1 align-and-mutate

`align-and-mutate` *imol chain_id fasta_maybe renumber_residues_flag* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *fasta_maybe* is a string
- *renumber_residues_flag* is an integer number

align and mutate the given chain to the given sequence

13.79.2 set-alignment-gap-and-space-penalty

`set-alignment-gap-and-space-penalty` *wgap wspace* [function]

Where:

- *wgap* is a number
- *wspace* is a number

set the penalty for affine gap and space when aligning, defaults -3.0 and -0.4

13.80 Renumber Residue Range

13.80.1 renumber-residue-range

`renumber-residue-range` *imol chain_id start_res last_res offset* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *start_res* is an integer number
- *last_res* is an integer number
- *offset* is an integer number

renumber the given residue range by offset residues

13.80.2 change-residue-number

`change-residue-number` *imol chain_id current_resno current_inscode new_resno new_inscode* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *current_resno* is an integer number
- *current_inscode* is a string
- *new_resno* is an integer number
- *new_inscode* is a string

change chain id, residue number or insertion code for given residue

13.81 Scripting Interface

13.81.1 probe-available-p

`probe-available-p` [function]

Can we run probe (was the executable variable set properly?) (predicate).

Returns: 1 for yes, 2 for no

13.81.2 post-scripting-window

`post-scripting-window` [function]

do nothing - compatibility function

13.81.3 post-scheme-scripting-window

`post-scheme-scripting-window` [function]

pop-up a scripting window for scheming

13.81.4 post-python-scripting-window

`post-python-scripting-window` [function]

pop-up a scripting window for pythoning

13.82 Monomer

13.82.1 get-coords-for-accession-code

`get-coords-for-accession-code` *code* [function]

Where *code* is a string

if possible, read in the new coords getting coords via web.

(no return value because get-url-str does not return one).

13.82.2 run-script

`run-script` *filename* [function]

Where *filename* is a string

run script file

13.82.3 run-guile-script

`run-guile-script` *filename* [function]

Where *filename* is a string

guile run script file

13.82.4 run-python-script

`run-python-script` *filename* [function]

Where *filename* is a string

run python script file

13.82.5 import-python-module

`import-python-module` *module_name use_namespace* [function]

Where:

- *module_name* is a string
- *use_namespace* is an integer number

import python module

13.83 Regularization and Refinement

13.83.1 add-planar-peptide-restraints

`add-planar-peptide-restraints` [function]

add a restraint on peptides to make them planar

This adds a 5 atom restraint that includes both CA atoms of the peptide. Use this rather than editting the mon_lib_list.cif file.

13.83.2 remove-planar-peptide-restraints

`remove-planar-peptide-restraints` [function]

remove restraints on peptides to make them planar.

13.83.3 set-use-trans-peptide-restraints

`set-use-trans-peptide-restraints` *on_off_state* [function]

Where *on_off_state* is an integer number

add a restraint on peptides to keep trans peptides trans

i.e. omega in trans-peptides is restraints to 180 degrees.

13.83.4 add-omega-torsion-restriants

`add-omega-torsion-restriants` [function]

add restraints on the omega angle of the peptides

(that is the torsion round the peptide bond). Omega angles that are closer to 0 than to 180 will be refined as cis peptides (and of course if omega is greater than 90 then the peptide will be refined as a trans peptide (this is the normal case).

13.83.5 remove-omega-torsion-restriants

`remove-omega-torsion-restriants` [function]

remove omega restraints on CIS and TRANS linked residues.

13.83.6 set-refinement-immediate-replacement

`set-refinement-immediate-replacement` *istate* [function]

Where *istate* is an integer number

set immediate replacement mode for refinement and regularization. You need this (call with istate=1) if you are scripting refinement/regularization

13.83.7 refinement-immediate-replacement-state

`refinement-immediate-replacement-state` [function]

query the state of the immediate replacement mode

13.83.8 set-residue-selection-flash-frames-number

`set-residue-selection-flash-frames-number` *i* [function]

Where *i* is an integer number

set the number of frames for which the selected residue range flashes

On fast computers, this can be set to higher than the default for more aesthetic appeal.

13.83.9 accept-regularizement

`accept-regularizement` [function]

accept the new positions of the regularized or refined residues

If you are scripting refinement and/or regularization, this is the function that you need to call after refine-zone or regularize-zone.

13.83.10 set-refine-with-torsion-restraints

`set-refine-with-torsion-restraints` *istate* [function]

Where *istate* is an integer number

turn on (or off) torsion restraints

Pass with istate=1 for on, istate=0 for off.

13.83.11 refine-with-torsion-restraints-state

`refine-with-torsion-restraints-state` [function]

return the state of above

13.83.12 set-matrix

`set-matrix` *f* [function]

Where *f* is a number

set the relative weight of the geometric terms to the map terms

The default is 60.

The higher the number the more weight that is given to the map terms but the resulting chi squared values are higher). This will be needed for maps generated from data not on (or close to) the absolute scale or maps that have been scaled (for example so that the sigma level has been scaled to 1.0).

13.83.13 matrix-state

`matrix-state` [function]

return the relative weight of the geometric terms to the map terms.

13.83.14 set-refine-auto-range-step

`set-refine-auto-range-step` *i* [function]

Where *i* is an integer number

change the +/- step for autoranging (default is 1)

Auto-ranging alow you to select a range from one button press, this allows you to set the number of residues either side of the clicked residue that becomes the selected zone

13.83.15 set-refine-max-residues

`set-refine-max-residues` *n* [function]

Where *n* is an integer number

set the heuristic fencepost for the maximum number of residues in the refinement/regularization residue range

Default is 20

13.83.16 refine-zone-atom-index-define

`refine-zone-atom-index-define` *imol ind1 ind2* [function]

Where:

- *imol* is an integer number
- *ind1* is an integer number
- *ind2* is an integer number

refine a zone based on atom indexing

13.83.17 refine-zone

`refine-zone` *imol chain_id resno1 resno2 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *resno2* is an integer number
- *altconf* is a string

refine a zone

presumes that imol_Refinement_Map has been set

13.83.18 refine-auto-range

`refine-auto-range` *imol chain_id resno1 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *altconf* is a string

refine a zone using auto-range

presumes that imol_Refinement_Map has been set

13.83.19 regularize-zone

`regularize-zone` *imol chain_id resno1 resno2 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *resno2* is an integer number
- *altconf* is a string

regularize a zone

Returns: a status, whether the regularisation was done or not. 0 for no, 1 for yes.

13.83.20 set-dragged-refinement-steps-per-frame

`set-dragged-refinement-steps-per-frame` *v* [function]

Where *v* is an integer number

set the number of refinement steps applied to the intermediate atoms each frame of graphics.

smaller numbers make the movement of the intermediate atoms slower, smoother, more elegant.

Default: 80.

13.83.21 dragged-refinement-steps-per-frame

`dragged-refinement-steps-per-frame` [function]

return the number of steps per frame in dragged refinement

13.83.22 set-refinement-refine-per-frame

`set-refinement-refine-per-frame` *istate* [function]

Where *istate* is an integer number

allow refinement of intermediate atoms after dragging, before displaying (default: 0, off).

An attempt to do something like xfit does, at the request of Frank von Delft.

Pass with istate=1 to enable this option.

13.83.23 refinement-refine-per-frame-state

`refinement-refine-per-frame-state` [function]

query the state of the above option

13.83.24 set-refinement-drag-elasticity

`set-refinement-drag-elasticity` *e* [function]

Where *e* is a number

the elasticity of the dragged atom in refinement mode.

Default 0.33

Bigger numbers mean bigger movement of the other atoms.

13.83.25 set-refine-ramachandran-angles

`set-refine-ramachandran-angles` *state* [function]

Where *state* is an integer number

turn on Ramachandran angles refinement in refinement and regularization

name consistent with

!?

13.83.26 set-fix-chiral-volumes-before-refinement

`set-fix-chiral-volumes-before-refinement` *istate* [function]

Where *istate* is an integer number

correct the sign of chiral volumes before commencing refinement?

Do we want to fix chiral volumes (by moving the chiral atom to the other side of the chiral plane if necessary). Default yes (1). Note: doesn't work currently.

13.83.27 check-chiral-volumes

`check-chiral-volumes` *imol* [function]

Where *imol* is an integer number

query the state of the above option

13.83.28 set-show-chiral-volume-errors-dialog

`set-show-chiral-volume-errors-dialog` *istate* [function]

Where *istate* is an integer number

For experienced Cooters who don't like Coot nannying about chiral volumes during refinement.

13.83.29 set-secondary-structure-restraints-type

`set-secondary-structure-restraints-type` *itype* [function]

Where *itype* is an integer number

set the type of secondary structure restraints

0 no sec str restraints

1 alpha helix restraints

2 beta strand restraints

13.83.30 secondary-structure-restraints-type

`secondary-structure-restraints-type` [function]

return the secondary structure restraints type

13.83.31 imol-refinement-map

`imol-refinement-map` [function]

the molecule number of the map used for refinement

Returns: the map number, if it has been set or there is only one map, return -1 on no map set (ambiguous) or no maps.

13.83.32 set-imol-refinement-map

`set-imol-refinement-map` *imol* [function]

Where *imol* is an integer number

set the molecule number of the map to be used for refinement/fitting.

Returns: imol on success, -1 on failure

13.83.33 does-residue-exist-p

`does-residue-exist-p` *imol chain_id resno inscode* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string

Does the residue exist? (Raw function)

Returns: 0 on not-exist, 1 on does exist.

13.83.34 add-extra-bond-restraint

`add-extra-bond-restraint` *imol chain_id_1 res_no_1 ins_code_1 atom_name_1 alt_conf_1 chain_id_2 res_no_2 ins_code_2 atom_name_2 alt_conf_2 bond_dist esd* [function]

Where:

- *imol* is an integer number
- *chain_id_1* is a string
- *res_no_1* is an integer number
- *ins_code_1* is a string
- *atom_name_1* is a string
- *alt_conf_1* is a string
- *chain_id_2* is a string
- *res_no_2* is an integer number
- *ins_code_2* is a string
- *atom_name_2* is a string
- *alt_conf_2* is a string
- *bond_dist* is a number
- *esd* is a number

add a user-define bond restraint

this extra restraint is used when the given atoms are selected in refinement or regularization.

Returns: the index of the new restraint.

Returns: -1 when the atoms were not found and no extra bond restraint was stored.

13.83.35 delete-all-extra-restraints

`delete-all-extra-restraints` *imol* [function]

Where *imol* is an integer number

clear out all the extra/user-defined restraints for molecule number imol

13.83.36 delete-extra-restraints-for-residue

`delete-extra-restraints-for-residue` *imol chain_id res_no ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string

clear out all the extra/user-defined restraints for this residue in molecule number imol

13.83.37 set-extra-restraints-prosmart-sigma-limits

`set-extra-restraints-prosmart-sigma-limits` *imol limit_high limit_low* [function]

Where:

- *imol* is an integer number
- *limit_high* is a number
- *limit_low* is a number

often we don't want to see all prosmart restraints, just the (big) violations

13.83.38 write-interpolated-extra-restraints

`write-interpolated-extra-restraints` *imol_1 imol_2 n_steps file_name_stub* [function]

Where:

- *imol_1* is an integer number
- *imol_2* is an integer number
- *n_steps* is an integer number
- *file_name_stub* is a string

proSMART interpolated restraints for model morphing

13.83.39 write-interpolated-models-and-extra-restraints

`write-interpolated-models-and-extra-restraints` *imol_1 imol_2 n_steps file_name_stub interpolation_mode* [function]

Where:

- *imol_1* is an integer number
- *imol_2* is an integer number

- *n_steps* is an integer number
- *file_name_stub* is a string
- *interpolation_mode* is an integer number

proSMART interpolated restraints for model morphing and write interpolated model

interpolation_mode is currently dummy - in due course I will addd torion angle interpolation.

13.83.40 set-use-only-extra-torsion-restraints-for-torsions

`set-use-only-extra-torsion-restraints-for-torsions` *state* [function]

Where *state* is an integer number

set use only extra torsion restraints for torsions

13.83.41 use-only-extra-torsion-restraints-for-torsions-state

`use-only-extra-torsion-restraints-for-torsions-state` [function]

return only-use-extra-torsion-restraints-for-torsions state

13.83.42 show-restraints-editor

`show-restraints-editor` *monomer_type* [function]

Where *monomer_type* is a string

show restraints editor

13.83.43 show-restraints-editor-by-index

`show-restraints-editor-by-index` *menu_item_index* [function]

Where *menu_item_index* is an integer number

show restraints editor using residue type index

13.83.44 write-restraints-cif-dictionary

`write-restraints-cif-dictionary` *monomer_type file_name* [function]

Where:

- *monomer_type* is a string
- *file_name* is a string

write cif restraints for monomer

13.84 Simplex Refinement Interface

13.84.1 fit-residue-range-to-map-by-simplex

`fit-residue-range-to-map-by-simplex` *res1 res2 altloc chain_id imol imol_for_map* [function]

Where:

- *res1* is an integer number

- *res2* is an integer number
- *altloc* is a string
- *chain_id* is a string
- *imol* is an integer number
- *imol_for_map* is an integer number

refine residue range using simplex optimization

13.84.2 score-residue-range-fit-to-map

`score-residue-range-fit-to-map` *res1 res2 altloc chain_id imol imol_for_map* [function]

Where:

- *res1* is an integer number
- *res2* is an integer number
- *altloc* is a string
- *chain_id* is a string
- *imol* is an integer number
- *imol_for_map* is an integer number

simply score the residue range fit to map

13.85 Nomenclature Errors

13.85.1 fix-nomenclature-errors

`fix-nomenclature-errors` *imol* [function]

Where *imol* is an integer number

fix nomenclature errors in molecule number imol

Returns: the number of resides altered.

13.85.2 set-nomenclature-errors-on-read

`set-nomenclature-errors-on-read` *mode* [function]

Where *mode* is a string

set way nomenclature errors should be handled on reading coordinates.

mode should be "auto-correct", "ignore", "prompt". The default is "prompt"

13.86 Atom Info Interface

13.86.1 output-atom-info-as-text

`output-atom-info-as-text` *imol chain_id resno ins_code atname altconf* [function]

Where:

- *imol* is an integer number

- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *atname* is a string
- *altconf* is a string

output to the terminal the Atom Info for the give atom specs

13.87 Residue Info

13.87.1 residue-info-dialog

`residue-info-dialog` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

show residue info dialog for given residue

13.88 Residue Environment Functions

13.88.1 set-show-environment-distances

`set-show-environment-distances` *state* [function]

Where *state* is an integer number

show environment distances. If state is 0, distances are turned off, otherwise distances are turned on.

13.88.2 set-show-environment-distances-bumps

`set-show-environment-distances-bumps` *state* [function]

Where *state* is an integer number

show bumps environment distances. If state is 0, bump distances are turned off, otherwise bump distances are turned on.

13.88.3 set-show-environment-distances-h-bonds

`set-show-environment-distances-h-bonds` *state* [function]

Where *state* is an integer number

show H-bond environment distances. If state is 0, bump distances are turned off, otherwise H-bond distances are turned on.

13.88.4 show-environment-distances-state

`show-environment-distances-state` [function]

show the state of display of the environment distances

13.88.5 set-environment-distances-distance-limits

`set-environment-distances-distance-limits` *min_dist max_dist* [function]

Where:

- *min_dist* is a number
- *max_dist* is a number

min and max distances for the environment distances

13.89 Pointer Functions

13.89.1 set-show-pointer-distances

`set-show-pointer-distances` *istate* [function]

Where *istate* is an integer number

turn on (or off) the pointer distance by passing 1 (or 0).

13.89.2 show-pointer-distances-state

`show-pointer-distances-state` [function]

show the state of display of the pointer distances

13.90 Zoom Functions

13.90.1 scale-zoom

`scale-zoom` *f* [function]

Where *f* is a number

scale the view by f

external (scripting) interface (with redraw)

13.90.2 zoom-factor

`zoom-factor` [function]

return the current zoom factor

13.90.3 set-smooth-scroll-do-zoom

`set-smooth-scroll-do-zoom` *i* [function]

Where *i* is an integer number

set smooth scroll with zoom

13.90.4 smooth-scroll-do-zoom

`smooth-scroll-do-zoom` [function]

return the state of the above system

13.91 CNS Data Functions

13.91.1 handle-cns-data-file

`handle-cns-data-file` *filename imol* [function]

Where:

- *filename* is a string
- *imol* is an integer number

read CNS data (currently only a placeholder)

13.91.2 handle-cns-data-file-with-cell

`handle-cns-data-file-with-cell` *filename imol a b c alpha beta gamma spg_info* [function]

Where:

- *filename* is a string
- *imol* is an integer number
- *a* is a number
- *b* is a number
- *c* is a number
- *alpha* is a number
- *beta* is a number
- *gamma* is a number
- *spg_info* is a string

read CNS data (currently only a placeholder)

a, b,c are in Angstroems. alpha, beta, gamma are in degrees. spg is the space group info, either ;-delimited symmetry operators or the space group name

13.92 mmCIF Functions

13.92.1 open-cif-dictionary-file-selector-dialog

`open-cif-dictionary-file-selector-dialog` [function]

open the cif dictionary file selector dialog

13.93 SHELXL Functions

13.93.1 read-shelx-ins-file

`read-shelx-ins-file` *filename recentre_flag* [function]

Where:

- *filename* is a string
- *recentre_flag* is an integer number

read a SHELXL .ins file

13.93.2 write-shelx-ins-file

`write-shelx-ins-file` *imol filename* [function]

Where:

- *imol* is an integer number
- *filename* is a string

write a SHELXL .ins file for molecule number imol

13.94 Validation Functions

13.94.1 difference-map-peaks

`difference-map-peaks` *imol imol_coords level max_closeness do_positive_level_flag do_negative_level_flag* [function]

Where:

- *imol* is an integer number
- *imol_coords* is an integer number
- *level* is a number
- *max_closeness* is a number
- *do_positive_level_flag* is an integer number
- *do_negative_level_flag* is an integer number

generate a list of difference map peaks

peaks within max_closeness (2.0 A typically) of a larger peak are not listed.

13.94.2 gln-asn-b-factor-outliers

`gln-asn-b-factor-outliers` *imol* [function]

Where *imol* is an integer number

Make a gui for GLN adn ASN B-factor outiers, compairing the O and N temperatur factors difference to the distribution of temperature factors from the other atoms.

13.95 Ramachandran Plot Functions

13.95.1 do-ramachandran-plot

`do-ramachandran-plot` *imol* [function]

Where *imol* is an integer number

Ramachandran plot for molecule number imol.

13.95.2 set-kleywegt-plot-n-diffs

`set-kleywegt-plot-n-diffs` *n_diffs* [function]

Where *n_diffs* is an integer number

set the number of biggest difference arrows on the Kleywegt plot.

13.95.3 set-ramachandran-plot-contour-levels

`set-ramachandran-plot-contour-levels` *level_prefered level_allowed* [function]

Where:

- *level_prefered* is a number
- *level_allowed* is a number

set the contour levels for theremachandran plot, default values are 0.02 (prefered) 0.002 (allowed)

13.95.4 set-ramachandran-plot-background-block-size

`set-ramachandran-plot-background-block-size` *blocksize* [function]

Where *blocksize* is a number

set the ramachandran plot background block size.

Smaller is smoother but slower. Should be divisible exactly into

13.95.5 ramachandran-plot-differences

`ramachandran-plot-differences` *imol1 imol2* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number

2 molecule ramachandran plot (NCS differences) a.k.a. A Kleywegt Plot.

13.95.6 ramachandran-plot-differences-by-chain

`ramachandran-plot-differences-by-chain` *imol1 imol2 a_chain b_chain* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *a_chain* is a string
- *b_chain* is a string

A chain-specific Kleywegt Plot.

13.96 Sequence View Interface

13.96.1 do-sequence-view

`do-sequence-view` *imol* [function]

Where *imol* is an integer number

display the sequence view dialog for molecule number imol

13.97 Atom Labelling

13.97.1 set-brief-atom-labels

`set-brief-atom-labels` *istat* [function]

Where *istat* is an integer number

use brief atom names for on-screen labels

call with istat=1 to use brief labels, istat=0 for normal labels

13.97.2 brief-atom-labels-state

`brief-atom-labels-state` [function]

the brief atom label state

13.98 Screen Rotation

13.98.1 rotate-y-scene

`rotate-y-scene` *nsteps stepsize* [function]

Where:

- *nsteps* is an integer number
- *stepsize* is a number

rotate view round y axis stepsize degrees for nstep such steps

13.98.2 rotate-x-scene

`rotate-x-scene` *nsteps stepsize* [function]

Where:

- *nsteps* is an integer number
- *stepsize* is a number

rotate view round x axis stepsize degrees for nstep such steps

13.98.3 rotate-z-scene

`rotate-z-scene` *nsteps stepsize* [function]

Where:

- *nsteps* is an integer number
- *stepsize* is a number

rotate view round z axis stepsize degrees for nstep such steps

13.98.4 spin-zoom-trans

`spin-zoom-trans` *axis nstep stepsize zoom_by x_rel y_rel z_rel* [function]

Where:

- *axis* is an integer number

- *nstep* is an integer number
- *stepsize* is a number
- *zoom_by* is a number
- *x_rel* is a number
- *y_rel* is a number
- *z_rel* is a number

Bells and whistles rotation.

spin, zoom and translate.

where axis is either x,y or z, stepsize is in degrees, zoom_by and x_rel etc are how much zoom, x,y,z should have changed by after nstep steps.

13.99 Screen Translation

13.99.1 translate-scene-x

`translate-scene-x` *nsteps* [function]

Where *nsteps* is an integer number

translate rotation centre relative to screen axes for nsteps

13.99.2 translate-scene-y

`translate-scene-y` *nsteps* [function]

Where *nsteps* is an integer number

translate rotation centre relative to screen axes for nsteps

13.99.3 translate-scene-z

`translate-scene-z` *nsteps* [function]

Where *nsteps* is an integer number

translate rotation centre relative to screen axes for nsteps

13.100 Views Interface

13.100.1 add-view-here

`add-view-here` *view_name* [function]

Where *view_name* is a string

return the view number

13.100.2 add-view-raw

`add-view-raw` *rcx rcy rcz quat1 quat2 quat3 quat4 zoom view_name* [function]

Where:

- *rcx* is a number
- *rcy* is a number

- *rcz* is a number
- *quat1* is a number
- *quat2* is a number
- *quat3* is a number
- *quat4* is a number
- *zoom* is a number
- *view_name* is a string

return the view number

13.100.3 remove-named-view

`remove-named-view` *view_name* [function]

Where *view_name* is a string

the view with the given name

13.100.4 remove-view

`remove-view` *view_number* [function]

Where *view_number* is an integer number

the given view number

13.100.5 add-view-description

`add-view-description` *view_number description* [function]

Where:

- *view_number* is an integer number
- *description* is a string

Add a view description/annotation to the give view number.

13.100.6 add-action-view

`add-action-view` *view_name action_function* [function]

Where:

- *view_name* is a string
- *action_function* is a string

add a view (not add to an existing view) that does something (e.g. displays or undisplays a molecule) rather than move the graphics.

Returns: the view number for this (new) view.

13.100.7 insert-action-view-after-view

`insert-action-view-after-view` *view_number view_name action_function* [function]

Where:

- *view_number* is an integer number

- *view_name* is a string
- *action_function* is a string

add an action view after the view of the given view number

Returns: the view number for this (new) view.

13.100.8 save-views

`save-views` *view_file_name* [function]

Where *view_file_name* is a string

save views to view_file_name

13.100.9 clear-all-views

`clear-all-views` [function]

Clear the view list.

13.101 Background Colour

13.101.1 set-background-colour

`set-background-colour` *red green blue* [function]

Where:

- *red* is a number
- *green* is a number
- *blue* is a number

set the background colour

red, green and blue are numbers between 0.0 and 1.0

13.101.2 redraw-background

`redraw-background` [function]

re draw the background colour when switching between mono and stereo

13.101.3 background-is-black-p

`background-is-black-p` [function]

is the background black (or nearly black)?

Returns: 1 if the background is black (or nearly black), else return 0.

13.102 Ligand Fitting Functions

13.102.1 set-ligand-acceptable-fit-fraction

`set-ligand-acceptable-fit-fraction` *f* [function]

Where *f* is a number

set the fraction of atoms which must be in positive density after a ligand fit

13.102.2 set-ligand-cluster-sigma-level

`set-ligand-cluster-sigma-level` *f* [function]

Where *f* is a number

set the default sigma level that the map is searched to find potential ligand sites

13.102.3 set-ligand-flexible-ligand-n-samples

`set-ligand-flexible-ligand-n-samples` *i* [function]

Where *i* is an integer number

set the number of conformation samples

big ligands require more samples. Default 10.

13.102.4 set-find-ligand-n-top-ligands

`set-find-ligand-n-top-ligands` *n* [function]

Where *n* is an integer number

search the top n sites for ligands.

Default 10.

13.102.5 set-find-ligand-multi-solutions-per-cluster

`set-find-ligand-multi-solutions-per-cluster` *lim_1 lim_2* [function]

Where:

- *lim_1* is a number
- *lim_2* is a number

allow multiple ligand solutions per cluster.

The first limit is the fraction of the top scored positions that go on to correlation scoring (closer to 1 means less and faster - default 0.7).

The second limit is the fraction of the top correlation score that is considered interesting. Limits the number of solutions displayed to user. Default 0.9.

There is currently no chi-angle set redundancy filtering - I suspect that there should be.

Nino-mode.

13.102.6 set-find-ligand-mask-waters

`set-find-ligand-mask-waters` *istate* [function]

Where *istate* is an integer number

how shall we treat the waters during ligand fitting?

pass with istate=1 for waters to mask the map in the same way that protein atoms do.

13.102.7 set-ligand-search-protein-molecule

`set-ligand-search-protein-molecule` *imol* [function]

Where *imol* is an integer number

set the protein molecule for ligand searching

13.102.8 set-ligand-search-map-molecule

`set-ligand-search-map-molecule` *imol_map* [function]

Where *imol_map* is an integer number

set the map molecule for ligand searching

13.102.9 add-ligand-search-ligand-molecule

`add-ligand-search-ligand-molecule` *imol_ligand* [function]

Where *imol_ligand* is an integer number

add a rigid ligand molecule to the list of ligands to search for in ligand searching

13.102.10 add-ligand-search-wiggly-ligand-molecule

`add-ligand-search-wiggly-ligand-molecule` *imol_ligand* [function]

Where *imol_ligand* is an integer number

add a flexible ligand molecule to the list of ligands to search for in ligand searching

13.102.11 set-find-ligand-here-cluster

`set-find-ligand-here-cluster` *state* [function]

Where *state* is an integer number

Allow the user a scripting means to find ligand at the rotation centre.

13.102.12 ligand-expert

`ligand-expert` [function]

this sets the flag to have expert option ligand entries in the Ligand Searching dialog

13.102.13 do-find-ligands-dialog

`do-find-ligands-dialog` [function]

display the find ligands dialog

if maps, coords and ligands are available, that is.

13.102.14 match-ligand-atom-names

`match-ligand-atom-names` *imol_ligand chain_id_ligand resno_ligand ins_code_ligand imol_reference chain_id_reference resno_reference ins_code_reference* [function]

Where:

- *imol_ligand* is an integer number
- *chain_id_ligand* is a string
- *resno_ligand* is an integer number
- *ins_code_ligand* is a string
- *imol_reference* is an integer number
- *chain_id_reference* is a string

- *resno_reference* is an integer number
- *ins_code_reference* is a string

Overlap residue with "template"-based matching.

Overlap the first residue in imol_ligand onto the residue specified by the reference parameters. Use graph matching, not atom names.

Match ligand atom names

By using graph matching, make the names of the atoms of the given ligand/residue match those of the reference residue/ligand as closely as possible - where there would be an atom name clash, invent a new atom name.

Returns: success status, False = failed to find residue in either imol_ligand or imo_ref. If success, return the RT operator.

13.102.15 match-ligand-atom-names-to-comp-id

`match-ligand-atom-names-to-comp-id` *imol_ligand chain_id_ligand resno_ligand ins_code_ligand comp_id_ref* [function]

Where:

- *imol_ligand* is an integer number
- *chain_id_ligand* is a string
- *resno_ligand* is an integer number
- *ins_code_ligand* is a string
- *comp_id_ref* is a string

Match ligand atom names to a reference ligand type (comp_id)

By using graph matching, make the names of the atoms of the given ligand/residue match those of the reference ligand from the geometry store as closely as possible. Where there would be an atom name clash, invent a new atom name.

This doesn't create a new dictionary for the selected ligand - and that's a big problem (see match_residue_and_dictionary).

13.102.16 flip-ligand

`flip-ligand` *imol chain_id resno* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number

flip the ligand (usually active residue) around its eigen vectors to the next flip number. Immediate replacement (like flip peptide).

13.103 Water Fitting Functions

13.103.1 wrapped-create-find-waters-dialog

`wrapped-create-find-waters-dialog` [function]

create a dialog for water fitting

13.103.2 renumber-waters

`renumber-waters` *imol* [function]

Where *imol* is an integer number

Renumber the waters of molecule number imol with consecutive numbering.

13.103.3 execute-find-waters-real

`execute-find-waters-real` *imol_for_map imol_for_protein new_waters_mol_flag rmsd_cut_off* [function]

Where:

- *imol_for_map* is an integer number
- *imol_for_protein* is an integer number
- *new_waters_mol_flag* is an integer number
- *rmsd_cut_off* is a number

find waters

13.103.4 move-waters-to-around-protein

`move-waters-to-around-protein` *imol* [function]

Where *imol* is an integer number

move waters of molecule number imol so that they are around the protein.

Returns: the number of moved waters.

13.103.5 move-hetgroups-to-around-protein

`move-hetgroups-to-around-protein` *imol* [function]

Where *imol* is an integer number

move all hetgroups (including waters) of molecule number imol so that they are around the protein.

13.103.6 max-water-distance

`max-water-distance` *imol* [function]

Where *imol* is an integer number

return the maximum minimum distance of any water atom to any protein atom - used in validation of move_waters_to_around_protein() funtion.

13.103.7 set-water-check-spherical-variance-limit

`set-water-check-spherical-variance-limit` *f* [function]

Where *f* is a number

set the limit of interesting variance, above which waters are listed (otherwise ignored)

default 0.12.

13.103.8 set-ligand-water-to-protein-distance-limits

`set-ligand-water-to-protein-distance-limits` *f1 f2* [function]

Where:

- *f1* is a number
- *f2* is a number

set ligand to protein distance limits

f1 is the minimum distance, f2 is the maximum distance

13.103.9 set-ligand-water-n-cycles

`set-ligand-water-n-cycles` *i* [function]

Where *i* is an integer number

set the number of cycles of water searching

13.103.10 execute-find-blobs

`execute-find-blobs` *imol_model imol_for_map cut_off interactive_flag* [function]

Where:

- *imol_model* is an integer number
- *imol_for_map* is an integer number
- *cut_off* is a number
- *interactive_flag* is an integer number

find blobs

13.103.11 split-water

`split-water` *imol chain_id res_no ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string

split the given water and fit to map.

If refinement map is not defined, don't do anything.

If there is more than one atom in the specified resiue, don't do anything.

If the given atom does not have an alt conf of `""`, don't do anything.

13.104 Bond Representation

13.104.1 set-default-bond-thickness

`set-default-bond-thickness` *t* [function]

Where *t* is an integer number

set the default thickness for bonds (e.g. in ~/.coot)

13.104.2 set-bond-thickness

`set-bond-thickness` *imol t* [function]

Where:

- *imol* is an integer number
- *t* is a number

set the thickness of the bonds in molecule number imol to t pixels

13.104.3 set-bond-thickness-intermediate-atoms

`set-bond-thickness-intermediate-atoms` *t* [function]

Where *t* is a number

set the thickness of the bonds of the intermediate atoms to t pixels

13.104.4 set-bond-colour-rotation-for-molecule

`set-bond-colour-rotation-for-molecule` *imol f* [function]

Where:

- *imol* is an integer number
- *f* is a number

set bond colour for molecule

13.104.5 get-bond-colour-rotation-for-molecule

`get-bond-colour-rotation-for-molecule` *imol* [function]

Where *imol* is an integer number

get the bond colour for molecule.

Return -1 on err (bad molecule number)

13.104.6 set-default-representation-type

`set-default-representation-type` *type* [function]

Where *type* is an integer number

set the default represenation type (default 1).

13.104.7 get-default-bond-thickness

`get-default-bond-thickness` [function]

get the default thickness for bonds

13.104.8 set-draw-zero-occ-markers

`set-draw-zero-occ-markers` *status* [function]

Where *status* is an integer number

set status of drawing zero occupancy markers.

default status is 1.

13.104.9 set-draw-cis-peptide-markups

`set-draw-cis-peptide-markups` *status* [function]

Where *status* is an integer number

set status of drawing cis-peptide markups

default status is 1.

13.104.10 set-draw-hydrogens

`set-draw-hydrogens` *imol istat* [function]

Where:

- *imol* is an integer number
- *istat* is an integer number

set the hydrogen drawing state. istat = 0 is hydrogens off, istat = 1: show hydrogens

13.104.11 draw-hydrogens-state

`draw-hydrogens-state` *imol* [function]

Where *imol* is an integer number

the state of draw hydrogens for molecule number imol.

return -1 on bad imol.

13.104.12 set-draw-stick-mode-atoms

`set-draw-stick-mode-atoms` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

draw little coloured balls on atoms

turn off with state = 0

turn on with state = 1

13.104.13 graphics-to-ca-representation

`graphics-to-ca-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol as CAs

13.104.14 graphics-to-ca-plus-ligands-representation

`graphics-to-ca-plus-ligands-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol as CA + ligands

13.104.15 graphics-to-ca-plus-ligands-and-sidechains-representation

`graphics-to-ca-plus-ligands-and-sidechains-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol as CA + ligands + sidechains

13.104.16 graphics-to-bonds-no-waters-representation

`graphics-to-bonds-no-waters-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol with no waters

13.104.17 graphics-to-bonds-representation

`graphics-to-bonds-representation` *mol* [function]

Where *mol* is an integer number

draw molecule number imol with normal bonds

13.104.18 graphics-to-ca-plus-ligands-sec-struct-representation

`graphics-to-ca-plus-ligands-sec-struct-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol with CA bonds in secondary structure representation and ligands

13.104.19 graphics-to-sec-struct-bonds-representation

`graphics-to-sec-struct-bonds-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol with bonds in secondary structure representation

13.104.20 graphics-to-rainbow-representation

`graphics-to-rainbow-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol in Jones' Rainbow

13.104.21 graphics-to-b-factor-representation

`graphics-to-b-factor-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol coloured by B-factor

13.104.22 graphics-to-b-factor-cas-representation

`graphics-to-b-factor-cas-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol coloured by B-factor, CA + ligands

13.104.23 graphics-to-occupancy-representation

`graphics-to-occupancy-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol coloured by occupancy

13.104.24 graphics-to-user-defined-atom-colours-representation

`graphics-to-user-defined-atom-colours-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol in CA+Ligands mode coloured by user-defined atom colours

13.104.25 graphics-to-user-defined-atom-colours-all-atoms-representation

`graphics-to-user-defined-atom-colours-all-atoms-representation` *imol* [function]

Where *imol* is an integer number

draw molecule number imol all atoms coloured by user-defined atom colours

13.104.26 graphics-molecule-bond-type

`graphics-molecule-bond-type` *imol* [function]

Where *imol* is an integer number

what is the bond drawing state of molecule number imol

13.104.27 set-b-factor-bonds-scale-factor

`set-b-factor-bonds-scale-factor` *imol f* [function]

Where:

- *imol* is an integer number
- *f* is a number

scale the colours for colour by b factor representation

13.104.28 change-model-molecule-representation-mode

`change-model-molecule-representation-mode` *up_or_down* [function]

Where *up_or_down* is an integer number

change the representation of the model molecule closest to the centre of the screen

13.104.29 set-use-grey-carbons-for-molecule

`set-use-grey-carbons-for-molecule` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

make the carbon atoms for molecule imol be grey

13.104.30 set-grey-carbon-colour

`set-grey-carbon-colour` *imol r g b* [function]

Where:

- *imol* is an integer number
- *r* is a number
- *g* is a number
- *b* is a number

set the colour for the carbon atoms

can be not grey if you desire, r, g, b in the range 0 to 1.

13.104.31 make-ball-and-stick

`make-ball-and-stick` *imol atom_selection_str bond_thickness sphere_size do_spheres_flag* [function]

Where:

- *imol* is an integer number
- *atom_selection_str* is a string
- *bond_thickness* is a number
- *sphere_size* is a number
- *do_spheres_flag* is an integer number

make a ball and stick representation of imol given atom selection

e.g. (make-ball-and-stick 0 `"/1"` 0.15 0.25 1)

13.104.32 clear-ball-and-stick

`clear-ball-and-stick` *imol* [function]

Where *imol* is an integer number

clear ball and stick representation of molecule number imol

13.104.33 additional-representation-by-string

`additional-representation-by-string` *imol atom_selection representation_type bonds_box_type bond_width draw_hydrogens_flag* [function]

Where:

- *imol* is an integer number

- *atom_selection* is a string
- *representation_type* is an integer number
- *bonds_box_type* is an integer number
- *bond_width* is a number
- *draw_hydrogens_flag* is an integer number

return the index of the additional representation. Return -1 on error

13.104.34 additional-representation-by-attributes

`additional-representation-by-attributes` *imol chain_id resno_start resno_end ins_code representation_type bonds_box_type bond_width draw_hydrogens_flag* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number
- *ins_code* is a string
- *representation_type* is an integer number
- *bonds_box_type* is an integer number
- *bond_width* is a number
- *draw_hydrogens_flag* is an integer number

return the index of the additional representation.

Returns: -1 on error.

13.105 Dots Representation

13.105.1 dots

`dots` *imol atom_selection_str dots_object_name dot_density sphere_size_scale* [function]

Where:

- *imol* is an integer number
- *atom_selection_str* is a string
- *dots_object_name* is a string
- *dot_density* is a number
- *sphere_size_scale* is a number

display dotted surface

return a generic objects handle (which can be used to remove later)

13.105.2 set-dots-colour

`set-dots-colour` *imol r g b* [function]

Where:

- *imol* is an integer number
- *r* is a number
- *g* is a number
- *b* is a number

set the colour of the surface dots of the imol-th molecule to be the given single colour

r,g,b are values between 0.0 and 1.0

13.105.3 unset-dots-colour

`unset-dots-colour` *imol* [function]

Where *imol* is an integer number

no longer set the dots of molecule imol to a single colour

i.e. go back to element-based colours.

13.105.4 clear-dots

`clear-dots` *imol dots_handle* [function]

Where:

- *imol* is an integer number
- *dots_handle* is an integer number

clear dots in imol with dots_handle

13.105.5 clear-dots-by-name

`clear-dots-by-name` *imol dots_object_name* [function]

Where:

- *imol* is an integer number
- *dots_object_name* is a string

clear the first dots object for imol with given name

13.105.6 n-dots-sets

`n-dots-sets` *imol* [function]

Where *imol* is an integer number

return the number of dots sets for molecule number imol

13.106 Pep-flip Interface

13.106.1 pepflip

`pepflip` *imol chain_id resno inscode altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altconf* is a string

pepflip the given residue

13.107 Rigid Body Refinement Interface

13.107.1 rigid-body-refine-zone

`rigid-body-refine-zone` *reso_start resno_end chain_id imol* [function]

Where:

- *reso_start* is an integer number
- *resno_end* is an integer number
- *chain_id* is a string
- *imol* is an integer number

setup rigid body refine zone

where we set the atom selection holders according to the arguments and then call execute_rigid_body_refine()

13.107.2 set-rigid-body-fit-acceptable-fit-fraction

`set-rigid-body-fit-acceptable-fit-fraction` *f* [function]

Where *f* is a number

set rigid body fraction of atoms in positive density

13.108 Add Terminal Residue Functions

13.108.1 set-add-terminal-residue-immediate-addition

`set-add-terminal-residue-immediate-addition` *i* [function]

Where *i* is an integer number

set immediate addition of terminal residue

call with i=1 for immediate addtion

13.108.2 add-terminal-residue

`add-terminal-residue` *imol chain_id residue_number residue_type immediate_add* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *residue_number* is an integer number
- *residue_type* is a string
- *immediate_add* is an integer number

Add a terminal residue.

residue type can be "auto" and immediate_add is recommended to be 1.

return 0 on failure, 1 on success

13.108.3 add-terminal-residue-using-phi-psi

`add-terminal-residue-using-phi-psi` *imol chain_id res_no residue_type phi psi* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *residue_type* is a string
- *phi* is a number
- *psi* is a number

Add a terminal residue using given phi and psi angles.

13.108.4 set-add-terminal-residue-default-residue-type

`set-add-terminal-residue-default-residue-type` *type* [function]

Where *type* is a string

set the residue type of an added terminal residue.

13.108.5 set-add-terminal-residue-do-post-refine

`set-add-terminal-residue-do-post-refine` *istat* [function]

Where *istat* is an integer number

set a flag to run refine zone on terminal residues after an addition.

13.108.6 add-terminal-residue-do-post-refine-state

`add-terminal-residue-do-post-refine-state` [function]

what is the value of the previous flag?

13.109 Delete Residues

13.109.1 delete-residue-range

`delete-residue-range` *imol chain_id resno_start end_resno* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *end_resno* is an integer number

delete residue range

13.109.2 delete-residue

`delete-residue` *imol chain_id resno inscode* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string

delete residue

13.109.3 delete-residue-with-full-spec

`delete-residue-with-full-spec` *imol imodel chain_id resno inscode altloc* [function]

Where:

- *imol* is an integer number
- *imodel* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altloc* is a string

delete residue with altconf

13.109.4 delete-residue-hydrogens

`delete-residue-hydrogens` *imol chain_id resno inscode altloc* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altloc* is a string

delete hydrogen atoms in residue

13.109.5 delete-atom

`delete-atom` *imol chain_id resno ins_code at_name altloc* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *at_name* is a string
- *altloc* is a string

delete atom in residue

13.109.6 delete-residue-sidechain

`delete-residue-sidechain` *imol chain_id resno ins_code do_delete_dialog* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *do_delete_dialog* is an integer number

delete all atoms in residue that are not main chain or CB

13.109.7 delete-hydrogens

`delete-hydrogens` *imol* [function]

Where *imol* is an integer number

delete all hydrogens in molecule,

Returns: number of hydrogens deleted.

13.110 Mainchain Building Functions

13.110.1 db-mainchain

`db-mainchain` *imol chain_id iresno_start iresno_end direction* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *iresno_start* is an integer number
- *iresno_end* is an integer number
- *direction* is a string

CA -> mainchain conversion.

direction is either "forwards" or "backwards"

return the new molecule number

13.111 Rotamer Functions

13.111.1 set-rotamer-search-mode

`set-rotamer-search-mode` *mode* [function]

Where *mode* is an integer number

set the mode of rotamer search, options are (ROTAMERSEARCHAUTOMATIC), (ROTAMERSEARCHLOWRES) (aka. "backrub rotamers"), (ROTAMERSEARCHHIGHRES) (with rigid body fitting)

13.111.2 set-rotamer-lowest-probability

`set-rotamer-lowest-probability` *f* [function]

Where *f* is a number

For Dunbrack rotamers, set the lowest probability to be considered. Set as a percentage i.e. 1.00 is quite low. For Richardson Rotamers, this has no effect.

13.111.3 set-rotamer-check-clashes

`set-rotamer-check-clashes` *i* [function]

Where *i* is an integer number

set a flag: 0 is off, 1 is on

13.111.4 auto-fit-best-rotamer

`auto-fit-best-rotamer` *resno altloc insertion_code chain_id imol_coords imol_map clash_flag lowest_probability* [function]

Where:

- *resno* is an integer number
- *altloc* is a string
- *insertion_code* is a string
- *chain_id* is a string
- *imol_coords* is an integer number
- *imol_map* is an integer number
- *clash_flag* is an integer number
- *lowest_probability* is a number

auto fit by rotamer search.

return the score, for some not very good reason. clash_flag determines if we use clashes with other residues in the score for this rotamer (or not). It would be cool to call this from a script that went residue by residue along a (newly-built) chain (now available).

13.111.5 set-auto-fit-best-rotamer-clash-flag

`set-auto-fit-best-rotamer-clash-flag` *i* [function]

Where *i* is an integer number

set the clash flag for rotamer search

And this functions for [pre-setting] the variables for auto_fit_best_rotamer called interactively (using a graphics_info_t function). 0 off, 1 on.

13.111.6 n-rotamers

`n-rotamers` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

return the number of rotamers for this residue - return -1 on no residue found.

13.111.7 set-residue-to-rotamer-number

`set-residue-to-rotamer-number` *imol chain_id resno ins_code alt_conf rotamer_number* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *alt_conf* is a string
- *rotamer_number* is an integer number

set the residue specified to the rotamer number specifed.

13.111.8 set-residue-to-rotamer-name

`set-residue-to-rotamer-name` *imol chain_id resno ins_code alt_conf rotamer_name* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *alt_conf* is a string
- *rotamer_name* is a string

set the residue specified to the rotamer name specified.

(rotamer names are the Richardson rotamer names.)

return value is 0 if atoms were not moved (e.g. because rotamer-name was not know)

13.111.9 fill-partial-residues

`fill-partial-residues` *imol* [function]

Where *imol* is an integer number

fill all the residues of molecule number imol that have missing atoms.

To be used to remove the effects of chainsaw.

13.112 180 Flip Side chain

13.112.1 do-180-degree-side-chain-flip

`do-180-degree-side-chain-flip` *imol chain_id resno inscode altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *inscode* is a string
- *altconf* is a string

rotate 180 degrees round the last chi angle

13.113 Mutate Functions

13.113.1 setup-mutate-auto-fit

`setup-mutate-auto-fit` *state* [function]

Where *state* is an integer number

Mutate then fit to map.

that we have a map define is checked first

13.113.2 mutate

`mutate` *imol chain_id ires inscode target_res_type* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *ires* is an integer number
- *inscode* is a string
- *target_res_type* is a string

mutate a given residue

target_res_type is a three-letter-code.

Return 1 on a good mutate.

13.113.3 mutate-base

`mutate-base` *imol chain_id res_no ins_code res_type* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *res_type* is a string

mutate a base. return success status, 1 for a good mutate.

13.113.4 set-mutate-auto-fit-do-post-refine

`set-mutate-auto-fit-do-post-refine` *istate* [function]

Where *istate* is an integer number

Do you want Coot to automatically run a refinement after every mutate and autofit?

1 for yes, 0 for no.

13.113.5 mutate-auto-fit-do-post-refine-state

`mutate-auto-fit-do-post-refine-state` [function]

what is the value of the previous flag?

13.113.6 set-rotamer-auto-fit-do-post-refine

`set-rotamer-auto-fit-do-post-refine` *istate* [function]

Where *istate* is an integer number

Do you want Coot to automatically run a refinement after every rotamer autofit?

1 for yes, 0 for no.

13.113.7 rotamer-auto-fit-do-post-refine-state

`rotamer-auto-fit-do-post-refine-state` [function]

what is the value of the previous flag?

13.113.8 mutate-single-residue-by-serial-number

`mutate-single-residue-by-serial-number` *ires_ser chain_id imol target_res_type* [function]

Where:

- *ires_ser* is an integer number
- *chain_id* is a string
- *imol* is an integer number
- *target_res_type* is a character

an alternate interface to mutation of a singe residue.

ires-ser is the serial number of the residue, not the seqnum There 2 functions don't make backups, but

does - CHECKME Hence

is for use as a "one-by-one" type and the following 2 by wrappers that muate either a residue range or a whole chain

Note that the target_res_type is a char, not a string (or a char *). So from the scheme interface you'd use (for example) hash backslash A for ALA.

Returns: 1 on success, 0 on failure

13.113.9 set-residue-type-chooser-stub-state

`set-residue-type-chooser-stub-state` *istat* [function]

Where *istat* is an integer number

set a flag saying that the residue chosen by mutate or auto-fit mutate should only be added as a stub (mainchain + CB)

13.114 Pointer Atom Functions

13.114.1 create-pointer-atom-molecule-maybe

`create-pointer-atom-molecule-maybe` [function]

Return the current pointer atom molecule, create a pointer atom molecule if necessary (i.e. when the user has not set it).

13.114.2 pointer-atom-molecule

`pointer-atom-molecule` [function]

Return the current pointer atom molecule.

13.115 Baton Build Interface Functions

13.115.1 set-baton-mode

`set-baton-mode` *i* [function]

Where *i* is an integer number

toggle so that mouse movement moves the baton not rotates the view.

13.115.2 try-set-draw-baton

`try-set-draw-baton` *i* [function]

Where *i* is an integer number

draw the baton or not

13.115.3 accept-baton-position

`accept-baton-position` [function]

accept the baton tip position - a prime candidate for a key binding

13.115.4 baton-tip-try-another

`baton-tip-try-another` [function]

move the baton tip position - another prime candidate for a key binding

13.115.5 baton-tip-previous

`baton-tip-previous` [function]

move the baton tip to the previous position

13.115.6 shorten-baton

`shorten-baton` [function]

shorten the baton length

13.115.7 lengthen-baton

`lengthen-baton` [function]

lengthen the baton

13.115.8 baton-build-delete-last-residue

`baton-build-delete-last-residue` [function]

delete the most recently build CA position

13.115.9 set-baton-build-params

`set-baton-build-params` *istart_resno chain_id direction* [function]

Where:

- *istart_resno* is an integer number
- *chain_id* is a string
- *direction* is a string

set the parameters for the start of a new baton-built fragment. direction can either be "forwards" or "backwards"

13.116 Crosshairs Interface

13.116.1 set-draw-crosshairs

`set-draw-crosshairs` *i* [function]

Where *i* is an integer number

draw the distance crosshairs, 0 for off, 1 for on.

13.117 Edit Chi Angles

13.117.1 set-find-hydrogen-torsions

`set-find-hydrogen-torsions` *state* [function]

Where *state* is an integer number

show torsions that rotate hydrogens in the torsion angle manipulation dialog. Note that this may be needed if, in the dictionary cif file torsion which have as a 4th atom both a hydrogen and a heavier atom bonding to the 3rd atom, but list the 4th atom as a hydrogen (not a heavier atom).

13.117.2 edit-chi-angles

`edit-chi-angles` *imol chain_id resno ins_code altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *altconf* is a string

display the edit chi angles gui for the given residue

return a status of 0 if it failed to fined the residue, return a value of 1 if it worked.

13.117.3 setup-torsion-general

`setup-torsion-general` *state* [function]

Where *state* is an integer number

beloved torsion general at last makes an entrance onto the Coot scene...

13.118 Masks

13.118.1 mask-map-by-molecule

`mask-map-by-molecule` *map_mol_no coord_mol_no invert_flag* [function]

Where:

- *map_mol_no* is an integer number
- *coord_mol_no* is an integer number
- *invert_flag* is an integer number

generate a new map that has been masked by some coordinates

(mask-map-by-molecule map-no mol-no invert?) creates and displays a masked map, cuts down density where the coordinates are (invert is 0). If invert? is 1, cut the density down where there are no atoms atoms.

13.118.2 set-map-mask-atom-radius

`set-map-mask-atom-radius` *rad* [function]

Where *rad* is a number

set the atom radius for map masking

13.118.3 map-mask-atom-radius

`map-mask-atom-radius` [function]

get the atom radius for map masking

13.119 check Waters Interface

13.119.1 delete-checked-waters-baddies

`delete-checked-waters-baddies` *imol b_factor_lim map_sigma_lim min_dist max_dist part_occ_contact_flag zero_occ_flag logical_operator_and_or_flag* [function]

Where:

- *imol* is an integer number
- *b_factor_lim* is a number
- *map_sigma_lim* is a number
- *min_dist* is a number
- *max_dist* is a number
- *part_occ_contact_flag* is an integer number
- *zero_occ_flag* is an integer number
- *logical_operator_and_or_flag* is an integer number

Delete waters that are fail to meet the given criteria.

13.120 Trim

13.120.1 trim-molecule-by-map

`trim-molecule-by-map` *imol_coords imol_map map_level delete_or_zero_occ_flag* [function]

Where:

- *imol_coords* is an integer number
- *imol_map* is an integer number
- *map_level* is a number
- *delete_or_zero_occ_flag* is an integer number

cut off (delete or give zero occupancy) atoms in the given molecule if they are below the given map (absolute) level.

13.121 External Ray-Tracing

13.121.1 raster3d

`raster3d` *rd3_filename* [function]

Where *rd3_filename* is a string

create a r3d file for the current view

13.121.2 set-raster3d-bond-thickness

`set-raster3d-bond-thickness` *f* [function]

Where *f* is a number

set the bond thickness for the Raster3D representation

13.121.3 set-raster3d-atom-radius

`set-raster3d-atom-radius` *f* [function]

Where *f* is a number

set the atom radius for the Raster3D representation

13.121.4 set-raster3d-density-thickness

`set-raster3d-density-thickness` *f* [function]

Where *f* is a number

set the density line thickness for the Raster3D representation

13.121.5 set-renderer-show-atoms

`set-renderer-show-atoms` *istate* [function]

Where *istate* is an integer number

set the flag to show atoms for the Raster3D representation

13.121.6 set-raster3d-bone-thickness

`set-raster3d-bone-thickness` *f* [function]

Where *f* is a number

set the bone (skeleton) thickness for the Raster3D representation

13.121.7 set-raster3d-shadows-enabled

`set-raster3d-shadows-enabled` *state* [function]

Where *state* is an integer number

turn off shadows for raster3d output - give argument 0 to turn off

13.121.8 set-raster3d-water-sphere

`set-raster3d-water-sphere` *istate* [function]

Where *istate* is an integer number

set the flag to show waters as spheres for the Raster3D representation. 1 show as spheres, 0 the usual stars.

13.121.9 raster-screen-shot

`raster-screen-shot` [function]

run raster3d and display the resulting image.

13.122 Superposition (SSM)

13.122.1 superpose

`superpose` *imol1 imol2 move_imol2_flag* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *move_imol2_flag* is an integer number

simple interface to superposition.

Superpose all residues of imol2 onto imol1. imol1 is reference, we can either move imol2 or copy it to generate a new molecule depending on the vaule of move_imol2_flag (1 for move 0 for copy).

13.122.2 superpose-with-chain-selection

`superpose-with-chain-selection` *imol1 imol2 chain_imol1 chain_imol2 chain_used_flag_imol1 chain_used_flag_imol2 move_imol2_copy_flag* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *chain_imol1* is a string
- *chain_imol2* is a string
- *chain_used_flag_imol1* is an integer number
- *chain_used_flag_imol2* is an integer number
- *move_imol2_copy_flag* is an integer number

chain-based interface to superposition.

Superpose the given chains of imol2 onto imol1. imol1 is reference, we can either move imol2 or copy it to generate a new molecule depending on the vaule of move_imol2_flag (1 for move 0 for copy).

13.122.3 superpose-with-atom-selection

`superpose-with-atom-selection` *imol1 imol2 mmdb_atom_sel_str_1 mmdb_atom_sel_str_2 move_imol2_copy_flag* [function]

Where:

- *imol1* is an integer number
- *imol2* is an integer number
- *mmdb_atom_sel_str_1* is a string
- *mmdb_atom_sel_str_2* is a string
- *move_imol2_copy_flag* is an integer number

detailed interface to superposition.

Superpose the given atom selection (specified by the mmdb atom selection strings) of imol2 onto imol1. imol1 is reference, we can either move imol2 or copy it to generate a new molecule depending on the vaule of move_imol2_flag (1 for move 0 for copy).

Returns: the index of the superposed molecule - which could either be a new molecule (if move_imol2_flag was 1) or the imol2 or -1 (signifying failure to do the SMM superposition).

13.123 NCS

13.123.1 set-draw-ncs-ghosts

`set-draw-ncs-ghosts` *imol istate* [function]

Where:

- *imol* is an integer number
- *istate* is an integer number

set drawing state of NCS ghosts for molecule number imol

13.123.2 draw-ncs-ghosts-state

`draw-ncs-ghosts-state` *imol* [function]

Where *imol* is an integer number

return the drawing state of NCS ghosts for molecule number imol. Return -1 on imol is a bad molecule or no ghosts.

13.123.3 set-ncs-ghost-bond-thickness

`set-ncs-ghost-bond-thickness` *imol f* [function]

Where:

- *imol* is an integer number
- *f* is a number

set bond thickness of NCS ghosts for molecule number imol

13.123.4 ncs-update-ghosts

`ncs-update-ghosts` *imol* [function]

Where *imol* is an integer number

update ghosts for molecule number imol

13.123.5 make-dynamically-transformed-ncs-maps

`make-dynamically-transformed-ncs-maps` *imol_model imol_map overwrite_maps_of_same_name_flag* [function]

Where:

- *imol_model* is an integer number
- *imol_map* is an integer number

- *overwrite_maps_of_same_name_flag* is an integer number

make NCS map

13.123.6 add-ncs-matrix

`add-ncs-matrix` *imol this_chain_id target_chain_id m11 m12 m13 m21 m22 m23 m31 m32 m33 t1 t2 t3* [function]

Where:

- *imol* is an integer number
- *this_chain_id* is a string
- *target_chain_id* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number
- *m33* is a number
- *t1* is a number
- *t2* is a number
- *t3* is a number

Add NCS matrix.

13.123.7 add-strict-ncs-matrix

`add-strict-ncs-matrix` *imol this_chain_id target_chain_id m11 m12 m13 m21 m22 m23 m31 m32 m33 t1 t2 t3* [function]

Where:

- *imol* is an integer number
- *this_chain_id* is a string
- *target_chain_id* is a string
- *m11* is a number
- *m12* is a number
- *m13* is a number
- *m21* is a number
- *m22* is a number
- *m23* is a number
- *m31* is a number
- *m32* is a number

- *m33* is a number
- *t1* is a number
- *t2* is a number
- *t3* is a number

add an NCS matrix for strict NCS molecule representation

for CNS strict NCS usage: expand like normal symmetry does

13.123.8 show-strict-ncs-state

`show-strict-ncs-state` *imol* [function]

Where *imol* is an integer number

return the state of NCS ghost molecules for molecule number imol

13.123.9 set-show-strict-ncs

`set-show-strict-ncs` *imol state* [function]

Where:

- *imol* is an integer number
- *state* is an integer number

set display state of NCS ghost molecules for molecule number imol

13.123.10 set-ncs-homology-level

`set-ncs-homology-level` *flev* [function]

Where *flev* is a number

At what level of homology should we say that we can't see homology for NCS calculation? (default 0.8)

13.123.11 copy-chain

`copy-chain` *imol from_chain to_chain* [function]

Where:

- *imol* is an integer number
- *from_chain* is a string
- *to_chain* is a string

Copy single NCS chain.

13.123.12 copy-from-ncs-master-to-others

`copy-from-ncs-master-to-others` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

Copy chain from master to all related NCS chains.

13.123.13 copy-residue-range-from-ncs-master-to-others

`copy-residue-range-from-ncs-master-to-others` *imol master_chain_id residue_range_start residue_range_end* [function]

Where:

- *imol* is an integer number
- *master_chain_id* is a string
- *residue_range_start* is an integer number
- *residue_range_end* is an integer number

Copy residue range to all related NCS chains.

If the target residues do not exist in the peer chains, then create them.

13.123.14 ncs-control-change-ncs-master-to-chain

`ncs-control-change-ncs-master-to-chain` *imol ichain* [function]

Where:

- *imol* is an integer number
- *ichain* is an integer number

change the NCS master chain (by number)

13.123.15 ncs-control-change-ncs-master-to-chain-id

`ncs-control-change-ncs-master-to-chain-id` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

change the NCS master chain (by chain_id)

13.123.16 ncs-control-display-chain

`ncs-control-display-chain` *imol ichain state* [function]

Where:

- *imol* is an integer number
- *ichain* is an integer number
- *state* is an integer number

display the NCS master chain

13.124 Helices and Strands

13.124.1 place-helix-here

`place-helix-here` [function]

add a helix

Add a helix somewhere close to this point in the map, try to fit the orientation. Add to a molecule called "Helix", create it if needed. Create another moecule called "Reverse Helix" if the helix orientation isn't completely unequivocal.

Returns: the index of the new molecule.

13.124.2 place-strand-here

`place-strand-here` *n_residues n_sample_strands* [function]

Where:

- *n_residues* is an integer number
- *n_sample_strands* is an integer number

add a strands

Add a strand close to this point in the map, try to fit the orientation. Add to a molecule called "Strand", create it if needed. n_residues is the estimated number of residues in the strand.

n_sample_strands is the number of strands from the database tested to fit into this strand density. 8 is a suggested number. 20 for a more rigourous search, but it will be slower.

Returns: the index of the new molecule.

13.124.3 place-strand-here-dialog

`place-strand-here-dialog` [function]

show the strand placement gui.

Choose the python version in there, if needed. Call scripting function, display it in place, don't return a widget.

13.124.4 find-helices

`find-helices` [function]

autobuild helices

Find secondary structure in the current map. Add to a molecule called "Helices", create it if needed.

Returns: the index of the new molecule.

13.124.5 find-strands

`find-strands` [function]

autobuild strands

Find secondary structure in the current map. Add to a molecule called "Strands", create it if needed.

Returns: the index of the new molecule.

13.124.6 find-secondary-structure

`find-secondary-structure` *use_helix helix_length helix_target use_strand strand_length strand_target* [function]

Where:

- *use_helix* is an integer number
- *helix_length* is an integer number
- *helix_target* is an integer number
- *use_strand* is an integer number
- *strand_length* is an integer number
- *strand_target* is an integer number

autobuild secondary structure

Find secondary structure in the current map. Add to a molecule called "SecStruc", create it if needed.

Returns: the index of the new molecule.

13.124.7 find-secondary-structure-local

`find-secondary-structure-local` *use_helix helix_length helix_target use_strand strand_length strand_target radius* [function]

Where:

- *use_helix* is an integer number
- *helix_length* is an integer number
- *helix_target* is an integer number
- *use_strand* is an integer number
- *strand_length* is an integer number
- *strand_target* is an integer number
- *radius* is a number

autobuild secondary structure

Find secondary structure local to current view in the current map. Add to a molecule called "SecStruc", create it if needed.

Returns: the index of the new molecule.

13.125 Nucleotides

13.125.1 find-nucleic-acids-local

`find-nucleic-acids-local` *radius* [function]

Where *radius* is a number

autobuild nucleic acid chains

Find secondary structure local to current view in the current map. Add to a molecule called "NuclAcid", create it if needed.

Returns: the index of the new molecule.

13.126 New Molecule by Section Interface

13.126.1 new-molecule-by-residue-type-selection

`new-molecule-by-residue-type-selection` *imol residue_type* [function]

Where:

- *imol* is an integer number
- *residue_type* is a string

create a new molecule that consists of only the residue of type residue_type in molecule number imol

Returns: the new molecule number, -1 means an error.

13.126.2 new-molecule-by-atom-selection

`new-molecule-by-atom-selection` *imol atom_selection* [function]

Where:

- *imol* is an integer number
- *atom_selection* is a string

create a new molecule that consists of only the atoms specified by the mmdb atoms selection string in molecule number imol

Returns: the new molecule number, -1 means an error.

13.126.3 new-molecule-by-sphere-selection

`new-molecule-by-sphere-selection` *imol x y z r allow_partial_residues* [function]

Where:

- *imol* is an integer number
- *x* is a number
- *y* is a number
- *z* is a number
- *r* is a number
- *allow_partial_residues* is an integer number

create a new molecule that consists of only the atoms within the given radius (r) of the given position.

Returns: the new molecule number, -1 means an error.

13.127 RNA/DNA

13.127.1 ideal-nucleic-acid

`ideal-nucleic-acid` *RNA_or_DNA form single_stranged_flag sequence* [function]

Where:

- *RNA_or_DNA* is a string

- *form* is a string
- *single_stranged_flag* is an integer number
- *sequence* is a string

create a molecule of idea nucleotides

use the given sequence (single letter code)

RNA_or_DNA is either "RNA" or "DNA"

form is either "A" or "B"

Returns: the new molecule number or -1 if a problem

13.127.2 watson-crick-pair

`watson-crick-pair` *imol chain_id resno* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number

Return a molecule that contains a residue that is the WC pair partner of the clicked/picked/selected residue.

13.127.3 watson-crick-pair-for-residue-range

`watson-crick-pair-for-residue-range` *imol chain_id resno_start resno_end* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno_start* is an integer number
- *resno_end* is an integer number

add base pairs for the given residue range, modify molecule imol by creating a new chain

13.128 Sequence (Assignment)

13.128.1 print-sequence-chain

`print-sequence-chain` *imol chain_id* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string

Print the sequence to the console of the given molecule.

13.128.2 assign-fasta-sequence

`assign-fasta-sequence` *imol chain_id_in seq* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string
- *seq* is a string

Assign a FASTA sequence to a given chain in the molecule.

13.128.3 assign-pir-sequence

`assign-pir-sequence` *imol chain_id_in seq* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string
- *seq* is a string

Assign a PIR sequence to a given chain in the molecule. If the chain of the molecule already had a chain assigned to it, then this will overwrite that old assignment with the new one.

13.128.4 assign-sequence-from-file

`assign-sequence-from-file` *imol file* [function]

Where:

- *imol* is an integer number
- *file* is a string

Assign a sequence to a given molecule from (whatever) sequence file.

13.128.5 assign-sequence-from-string

`assign-sequence-from-string` *imol chain_id_in seq* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string
- *seq* is a string

Assign a sequence to a given molecule from a simple string.

13.128.6 delete-all-sequences-from-molecule

`delete-all-sequences-from-molecule` *imol* [function]

Where *imol* is an integer number

Delete all the sequences from a given molecule.

13.128.7 delete-sequence-by-chain-id

`delete-sequence-by-chain-id` *imol chain_id_in* [function]

Where:

- *imol* is an integer number
- *chain_id_in* is a string

Delete the sequence for a given chain_id from a given molecule.

13.129 Surface Interface

13.129.1 do-surface

`do-surface` *imol istate* [function]

Where:

- *imol* is an integer number
- *istate* is an integer number

draw surface of molecule number imol

if state = 1 draw the surface (normal representation goes away)

if state = 0 don't draw surface

13.129.2 set-transparent-electrostatic-surface

`set-transparent-electrostatic-surface` *imol opacity* [function]

Where:

- *imol* is an integer number
- *opacity* is a number

simple on/off screendoor transparency at the moment, an opacity > 0.0 will turn on screendoor transparency (stippling).

13.129.3 get-electrostatic-surface-opacity

`get-electrostatic-surface-opacity` *imol* [function]

Where *imol* is an integer number

return 1.0 for non transparent and 0.5 if screendoor transparency has been turned on.

13.130 FFFearing

13.130.1 fffear-search

`fffear-search` *imol_model imol_map* [function]

Where:

- *imol_model* is an integer number
- *imol_map* is an integer number

fffear search model in molecule number imol_model in map number imol_map

13.130.2 set-fffear-angular-resolution

`set-fffear-angular-resolution` *f* [function]

Where *f* is a number

set and return the fffear angular resolution in degrees

13.130.3 fffear-angular-resolution

`fffear-angular-resolution` [function]

return the fffear angular resolution in degrees

13.131 Remote Control

13.131.1 make-socket-listener-maybe

`make-socket-listener-maybe` [function]

try to make socket listener

13.131.2 set-socket-string-waiting

`set-socket-string-waiting` *s* [function]

Where *s* is a string

feed the main thread a scheme script to evaluate

13.131.3 set-socket-python-string-waiting

`set-socket-python-string-waiting` *s* [function]

Where *s* is a string

feed the main thread a python script to evaluate

13.132 Display Lists for Maps

13.132.1 set-display-lists-for-maps

`set-display-lists-for-maps` *i* [function]

Where *i* is an integer number

Should display lists be used for maps? It may speed things up if these are turned on (or off) - depends on graphics card and drivers. Pass 1 for on, 0 for off.

13.132.2 display-lists-for-maps-state

`display-lists-for-maps-state` [function]

return the state of display_lists_for_maps.

13.133 Browser Interface

13.133.1 browser-url

`browser-url` *url* [function]

Where *url* is a string

try to open given url in Web browser

13.133.2 set-browser-interface

`set-browser-interface` *browser* [function]

Where *browser* is a string

set command to open the web browser,

examples are "open" or "mozilla"

13.133.3 handle-online-coot-search-request

`handle-online-coot-search-request` *entry_text* [function]

Where *entry_text* is a string

the search interface

find words, construct a url and open it.

13.134 Molprobity Interface

13.134.1 handle-read-draw-probe-dots

`handle-read-draw-probe-dots` *dots_file* [function]

Where *dots_file* is a string

pass a filename that contains molprobity's probe output in XtalView format

13.134.2 handle-read-draw-probe-dots-unformatted

`handle-read-draw-probe-dots-unformatted` *dots_file imol show_clash_gui_flag* [function]

Where:

- *dots_file* is a string
- *imol* is an integer number
- *show_clash_gui_flag* is an integer number

pass a filename that contains molprobity's probe output in unformatted format

13.134.3 set-do-probe-dots-on-rotamers-and-chis

`set-do-probe-dots-on-rotamers-and-chis` *state* [function]

Where *state* is an integer number

shall we run molprobity for on edit chi angles intermediate atoms?

13.134.4 do-probe-dots-on-rotamers-and-chis-state

`do-probe-dots-on-rotamers-and-chis-state` [function]

return the state of if run molprobity for on edit chi angles intermediate atoms?

13.134.5 set-do-probe-dots-post-refine

`set-do-probe-dots-post-refine` *state* [function]

Where *state* is an integer number

shall we run molprobity after a refinement has happened?

13.134.6 do-probe-dots-post-refine-state

`do-probe-dots-post-refine-state` [function]

show the state of shall we run molprobity after a refinement has happened?

13.134.7 unmangle-hydrogen-name

`unmangle-hydrogen-name` *pdb_hydrogen_name* [function]

Where *pdb_hydrogen_name* is a string

make an attempt to convert pdb hydrogen name to the name used in Coot (and the refmac dictionary, perhaps).

13.134.8 set-interactive-probe-dots-molprobity-radius

`set-interactive-probe-dots-molprobity-radius` *r* [function]

Where *r* is a number

set the radius over which we can run interactive probe, bigger is better but slower.

default is 6.0

13.134.9 interactive-probe-dots-molprobity-radius

`interactive-probe-dots-molprobity-radius` [function]

return the radius over which we can run interactive probe.

13.135 Map Sharpening Interface

13.135.1 sharpen

`sharpen` *imol b_factor* [function]

Where:

- *imol* is an integer number
- *b_factor* is a number

Sharpen map imol by b_factor (note (of course) that positive numbers blur the map).

13.135.2 set-map-sharpening-scale-limit

`set-map-sharpening-scale-limit` *f* [function]

Where *f* is a number

set the limit of the b-factor map sharpening slider (default 30)

13.136 Marking Fixed Atom Interface

13.136.1 clear-all-fixed-atoms

`clear-all-fixed-atoms` *imol* [function]

Where *imol* is an integer number

clear all fixed atoms

13.137 Partial Charges

13.137.1 show-partial-charge-info

`show-partial-charge-info` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

show the partial charges for the residue of the given specs (charges are read from the dictionary)

13.138 EM interface

13.138.1 scale-cell

`scale-cell` *imol_map fac_u fac_v fac_w* [function]

Where:

- *imol_map* is an integer number
- *fac_u* is a number
- *fac_v* is a number
- *fac_w* is a number

Scale the cell, for use with EM maps, where the cell needs to be adjusted. Use like: (scale-cell 2 1.012 1.012 1.012). Return error status, 1 means it worked, 0 means it did not work.

13.139 CCP4mg Interface

13.139.1 write-ccp4mg-picture-description

`write-ccp4mg-picture-description` *filename* [function]

Where *filename* is a string

write a ccp4mg picture description file

13.139.2 get-atom-colour-from-mol-no

`get-atom-colour-from-mol-no` *imol element* [function]

Where:

- *imol* is an integer number
- *element* is a string

get element colour for imol as Python formatted list char

13.140 Aux functions

13.140.1 laplacian

`laplacian` *imol* [function]

Where *imol* is an integer number

Create the "Laplacian" (-ve second derivative) of the given map.

13.141 SMILES

13.141.1 do-smiles-gui

`do-smiles-gui` [function]

display the SMILES string dialog

13.142 PHENIX Support

13.142.1 set-button-label-for-external-refinement

`set-button-label-for-external-refinement` *button_label* [function]

Where *button_label* is a string

set the button label of the external Refinement program

13.143 Graphics Text

13.143.1 place-text

`place-text` *text x y z size* [function]

Where:

- *text* is a string
- *x* is a number
- *y* is a number
- *z* is a number
- *size* is an integer number

Put text at x,y,z.

size variable is currently ignored.

Returns: a text handle

13.143.2 remove-text

`remove-text` *text_handle* [function]

Where *text_handle* is an integer number

Remove "3d" text item.

13.143.3 text-index-near-position

`text-index-near-position` *x y z r* [function]

Where:

- *x* is a number
- *y* is a number
- *z* is a number
- *r* is a number

return the closest text that is with r A of the given position. If no text item is close, then return -1

13.144 PISA Interaction

13.144.1 pisa-interaction

`pisa-interaction` *imol_1 imol_2* [function]

Where:

- *imol_1* is an integer number
- *imol_2* is an integer number

return the molecule number of the interacting residues. Return -1 if no new model was created. Old, not very useful.

13.145 Jiggle Fit

13.145.1 fit-to-map-by-random-jiggle

`fit-to-map-by-random-jiggle` *imol chain_id resno ins_code n_trials jiggle_scale_factor* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *n_trials* is an integer number
- *jiggle_scale_factor* is a number

jiggle fit to the current refinment map. return < -100 if not possible, else return the new best fit for this residue.

13.146 SBase interface

13.146.1 get-ccp4srs-monomer-and-dictionary

`get-ccp4srs-monomer-and-dictionary` *comp_id* [function]

Where *comp_id* is a string

return the new molecule number of the monomer.

The monomer will have chainid `"A"` and residue number 1.

Return -1 on failure to get monomer.

13.146.2 get-sbase-monomer

`get-sbase-monomer` *comp_id* [function]

Where *comp_id* is a string

same as above but using old name for back-compatibility

13.147 FLE-View

13.147.1 fle-view-set-water-dist-max

`fle-view-set-water-dist-max` *dist_max* [function]

Where *dist_max* is a number

set the maximum considered distance to water

default 3.25 A.

13.147.2 fle-view-set-h-bond-dist-max

`fle-view-set-h-bond-dist-max` *h_bond_dist_max* [function]

Where *h_bond_dist_max* is a number

set the maximum considered hydrogen bond distance

default 3.9 A.

13.148 LSQ-improve

13.148.1 lsq-improve

`lsq-improve` *imol_ref ref_selection imol_moving moving_selection n_res dist_crit* [function]

Where:

- *imol_ref* is an integer number
- *ref_selection* is a string
- *imol_moving* is an integer number
- *moving_selection* is a string
- *n_res* is an integer number
- *dist_crit* is a number

an slightly-modified implementation of the "lsq_improve" algorithm of Kleywegt and Jones (1997).

Note that if a residue selection is specified in the residue selection(s), then the first residue of the given range must exist in the molecule (if not, then mmdb will not select any atoms from that molecule).

Kleywegt and Jones set n_res to 4 and dist_crit to 6.0.

13.149 single-model view

13.149.1 single-model-view-model-number

`single-model-view-model-number` *imol imodel* [function]

Where:

- *imol* is an integer number
- *imodel* is an integer number

put molecule number imol to display only model number imodel

13.149.2 single-model-view-this-model-number

`single-model-view-this-model-number` *imol* [function]

Where *imol* is an integer number

the current model number being displayed

return 0 on non-multimodel-molecule.

13.149.3 single-model-view-next-model-number

`single-model-view-next-model-number` *imol* [function]

Where *imol* is an integer number

change the representation to the next model number to be displayed

return 0 on non-multimodel-molecule.

13.149.4 single-model-view-prev-model-number

`single-model-view-prev-model-number` *imol* [function]

Where *imol* is an integer number

change the representation to the previous model number to be displayed

return 0 on non-multimodel-molecule.

13.150 graphics 2D ligand view

13.150.1 set-show-graphics-ligand-view

`set-show-graphics-ligand-view` *state* [function]

Where *state* is an integer number

set the graphics ligand view state

(default is 1 (on)).

13.151 dictionary-generators

`generate-molecule-from-mmcif-by-dict-gen` *comp-id mmcif-file-name* [procedure]

return a molecule number. Return -1 on fail.

13.152 raster3d-from-scheme

`render-image` [procedure]

run raster3d

`raytrace` [procedure]

Run either raster3d or povray

13.153 tips

`tip-list` [procedure]

a list of tips for Coot

`no-coot-tips` [procedure]

Function to turn off coot tips at start

13.154 cc-interface_8hh

13.155 More Symmetry Functions

13.155.1 get-symmetry

`get-symmetry` *imol* [function]

Where *imol* is an integer number

return the symmetry of the imolth molecule

Return as a list of strings the symmetry operators of the given molecule. If imol is a not a valid molecule, return an empty list.

13.156 Extra Map Functions

13.156.1 auto-read-make-and-draw-maps

`auto-read-make-and-draw-maps` *filename* [function]

Where *filename* is a string

read MTZ file filename and from it try to make maps

Useful for reading the output of refmac. The default labels (FWT/PHWT and DELFWT/PHDELFWT) can be changed using ...[something]

Returns: a list of molecule numbers for the new maps

13.156.2 auto-read-make-and-draw-maps-from-mtz

`auto-read-make-and-draw-maps-from-mtz` *filename* [function]

Where *filename* is a string

set the flag to do a difference map (too) on auto-read MTZ

13.156.3 map-colour-components

`map-colour-components` *imol* [function]

Where *imol* is an integer number

return the colour triple of the imolth map

(e.g.: (list 0.4 0.6 0.8). If invalid imol return scheme false.

13.157 Multi-Residue Torsion

13.157.1 multi-residue-torsion-fit-scm

`multi-residue-torsion-fit-scm` *imol residues_specs_scm n_trials* [function]

Where:

- *imol* is an integer number
- *residues_specs_scm* is a SCM
- *n_trials* is an integer number

fit residues

(note: fit to the current-refinement map)

13.158 Execute Refmac

13.158.1 execute-refmac-real

`execute-refmac-real` *pdb_in_filename pdb_out_filename mtz_in_filename mtz_out_filename cif_lib_filename fobs_col_name sigfobs_col_name r_free_col_name have_sensible_free_r_flag make_molecules_flag refmac_count_string swap_map_colours_post_refmac_flag imol_refmac_map diff_map_flag phase_combine_flag phib_string fom_string ccp4i_project_dir* [function]

Where:

- *pdb_in_filename* is a std::string
- *pdb_out_filename* is a std::string
- *mtz_in_filename* is a std::string
- *mtz_out_filename* is a std::string
- *cif_lib_filename* is a std::string
- *fobs_col_name* is a std::string
- *sigfobs_col_name* is a std::string
- *r_free_col_name* is a std::string
- *have_sensible_free_r_flag* is an integer number

- *make_molecules_flag* is an integer number
- *refmac_count_string* is a std::string
- *swap_map_colours_post_refmac_flag* is an integer number
- *imol_refmac_map* is an integer number
- *diff_map_flag* is an integer number
- *phase_combine_flag* is an integer number
- *phib_string* is a std::string
- *fom_string* is a std::string
- *ccp4i_project_dir* is a std::string

if swap_map_colours_post_refmac_flag is not 1 thenn imol_refmac_map is ignored.

13.158.2 refmac-name

`refmac-name` *imol* [function]

Where *imol* is an integer number

the name for refmac

Returns: a stub name used in the construction of filename for refmac output

13.159 Dictionary Functions

13.159.1 dictionaries-read

`dictionaries-read` [function]

return a list of all the dictionaries read

13.160 Restraints Interface

13.160.1 set-monomer-restraints

`set-monomer-restraints` *monomer_type restraints* [function]

Where:

- *monomer_type* is a string
- *restraints* is a SCM

set the monomer restraints of the given monomer_type

Returns: scheme false or true for success or failure to set the restrains for monomer_type

13.161 Atom Information functions

13.161.1 resname-from-serial-number

`resname-from-serial-number` *imol chain_id serial_num* [function]

Where:

- *imol* is an integer number

- *chain_id* is a string
- *serial_num* is an integer number

return the rename from a residue serial number

Returns: blank (`""`) on failure.

13.161.2 residue-name

`residue-name` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a const std::string &
- *resno* is an integer number
- *ins_code* is a const std::string &

return the residue name of the specified residue

13.161.3 residue-info

`residue-info` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string

Return a list of atom info for each atom in the specified residue.

output is like this: (list (list (list atom-name alt-conf) (list occ temp-fact element) (list x y z)))

occ can be a single number or a list of seven numbers of which the first is the isotropic B.

13.161.4 chain-fragments-scm

`chain-fragments-scm` *imol screen_output_also* [function]

Where:

- *imol* is an integer number
- *screen_output_also* is an integer number

chain fragments

13.161.5 add-molecule

`add-molecule` *molecule_expression name* [function]

Where:

- *molecule_expression* is a SCM
- *name* is a string

generate a molecule from an s-expression

return a molecule number, -1 on error

13.161.6 clear-and-update-molecule

`clear-and-update-molecule` *molecule_number molecule_expression* [function]

Where:

- *molecule_number* is an integer number
- *molecule_expression* is a SCM

update a molecule from a s-expression

And going the other way, given an s-expression, update molecule_number by the given molecule. Clear what's currently there first though.

13.161.7 active-residue

`active-residue` [function]

return specs of the atom close to screen centre

Return a list of (list imol chain-id resno ins-code atom-name alt-conf) for atom that is closest to the screen centre in any displayed molecule. If there are multiple models with the same coordinates at the screen centre, return the attributes of the atom in the highest number molecule number.

return scheme false if no active residue

13.161.8 closest-atom-simple-scm

`closest-atom-simple-scm` [function]

return the specs of the closest displayed atom

Return a list of (list imol chain-id resno ins-code atom-name alt-conf (list x y z)) for atom that is closest to the screen centre in the given molecule (unlike active-residue, potential CA substition is not performed). If there is no atom, or if imol is not a valid model molecule, return scheme false.

13.161.9 closest-atom

`closest-atom` *imol* [function]

Where *imol* is an integer number

return the specs of the closest atom in imolth molecule

Return a list of (list imol chain-id resno ins-code atom-name alt-conf (list x y z)) for atom that is closest to the screen centre in the given molecule (unlike active-residue, no account is taken of the displayed state of the molecule). If there is no atom, or if imol is not a valid model molecule, return scheme false.

13.161.10 residues-near-residue

`residues-near-residue` *imol residue_in radius* [function]

Where:

- *imol* is an integer number
- *residue_in* is a SCM
- *radius* is a number

return residues near residue

Return residue specs for residues that have atoms that are closer than radius Angstroems to any atom in the residue specified by res_in.

13.161.11 residues-near-position-scm

`residues-near-position-scm` *imol pos radius* [function]

Where:

- *imol* is an integer number
- *pos* is a SCM
- *radius* is a number

resdiues near residue

Return a list of pairs of (imol, residue_spec). pos is a list of 3 numbers. (get imol from active-atom)

Returns: residues within radius of pos (x,y,z) position

13.161.12 hydrogenate-region

`hydrogenate-region` *radius* [function]

Where *radius* is a number

find the active residue, find the near residues (within radius) create a new molecule, run reduce on that, import hydrogens from the result and apply them to the molecule of the active residue.

13.161.13 add-hydrogens-from-file

`add-hydrogens-from-file` *imol pdb_with_Hs_file_name* [function]

Where:

- *imol* is an integer number
- *pdb_with_Hs_file_name* is a std::string

Add hydrogens to imol from the given pdb file.

13.162 Refinement with specs

13.162.1 regularize-residues

`regularize-residues` *imol residues* [function]

Where:

- *imol* is an integer number
- *residues* is a const std::vector< coot::residue_spec_t > &

regularize the given residues

13.162.2 mtz-file-name

`mtz-file-name` *imol* [function]

Where *imol* is an integer number

presumes that imol_Refinement_Map has been set

13.162.3 refine-zone-with-full-residue-spec-scm

`refine-zone-with-full-residue-spec-scm` *imol chain_id resno1 inscode_1 resno2 inscode_2 altconf* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *resno1* is an integer number
- *inscode_1* is a string
- *resno2* is an integer number
- *inscode_2* is a string
- *altconf* is a string

Refine the given residue range.

13.163 Water Chain Functions

13.163.1 water-chain-from-shelx-ins-scm

`water-chain-from-shelx-ins-scm` *imol* [function]

Where *imol* is an integer number

return the chain id of the water chain from a shelx molecule. Raw interface

Returns: scheme false if no chain or bad imol

13.163.2 water-chain-scm

`water-chain-scm` *imol* [function]

Where *imol* is an integer number

return the chain id of the water chain. Raw interface

13.164 Glyco Tools

13.164.1 print-glyco-tree

`print-glyco-tree` *imol chain_id resno ins_code* [function]

Where:

- *imol* is an integer number
- *chain_id* is a const std::string &
- *resno* is an integer number
- *ins_code* is a const std::string &

print the glycosylation tree that contains the specified residue

13.165 Spin Search Functions

13.165.1 spin-search

`spin-search` *imol_map imol chain_id resno ins_code direction_atoms_list moving_atoms_list* [function]

Where:

- *imol_map* is an integer number
- *imol* is an integer number
- *chain_id* is a string
- *resno* is an integer number
- *ins_code* is a string
- *direction_atoms_list* is a SCM
- *moving_atoms_list* is a SCM

for the given residue, spin the atoms in moving_atom_list around the bond defined by direction_atoms_list looking for the best fit to density of imol_map map of the first atom in moving_atom_list. Works (only) with atoms in altconf `""`

13.166 Rotamer Scoring

13.166.1 score-rotamers-scm

`score-rotamers-scm` *imol chain_id res_no ins_code alt_conf imol_map clash_flag lowest_probability* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *alt_conf* is a string
- *imol_map* is an integer number
- *clash_flag* is an integer number
- *lowest_probability* is a number

return the scores of the rotamers for this residue.

13.167 protein-db

13.167.1 protein-db-loops

`protein-db-loops` *imol_coords residue_specs imol_map nfrags preserve_residue_names* [function]

Where:

- *imol_coords* is an integer number

- *residue_specs* is a const std::vector< coot::residue_spec_t > &
- *imol_map* is an integer number
- *nfrags* is an integer number
- *preserve_residue_names* is a bool

Cowtan's protein_db loops.

13.168 Coot's Hole implementation

13.168.1 hole

`hole` *imol start_x start_y start_z end_x end_y end_z colour_map_multiplier colour_map_offset n_runs show_probe_radius_graph_flag export_surface_dots_file_name* [function]

Where:

- *imol* is an integer number
- *start_x* is a number
- *start_y* is a number
- *start_z* is a number
- *end_x* is a number
- *end_y* is a number
- *end_z* is a number
- *colour_map_multiplier* is a number
- *colour_map_offset* is a number
- *n_runs* is an integer number
- *show_probe_radius_graph_flag* is a bool
- *export_surface_dots_file_name* is a std::string

starting piont and end point, colour map multiplier and shall the probe radius graph be shown (dummy value currently).

if export_dots_file_name string length is zero, then don't try to export the surface dots.

13.168.2 make-link

`make-link` *imol spec_1 spec_2 link_name length* [function]

Where:

- *imol* is an integer number
- *spec_1* is a coot::atom_spec_t &
- *spec_2* is a coot::atom_spec_t &
- *link_name* is a const std::string &
- *length* is a number

make a link between the specified atoms

13.169 Drag and Drop Functions

13.169.1 handle-drag-and-drop-string

`handle-drag-and-drop-string` *uri* [function]

Where *uri* is a const std::string &

handle the string that get when a file or URL is dropped.

13.170 Map to Model Correlation

13.170.1 set-map-correlation-atom-radius

`set-map-correlation-atom-radius` *r* [function]

Where *r* is a number

The atom radius is not passed as a parameter to correlation.

13.170.2 map-to-model-correlation

`map-to-model-correlation` *imol residue_specs neigh_residue_specs atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *residue_specs* is a const std::vector< coot::residue_spec_t > &
- *neigh_residue_specs* is a const std::vector< coot::residue_spec_t > &
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

atom-mask-mode is as follows:

13.170.3 map-to-model-correlation-stats

`map-to-model-correlation-stats` *imol residue_specs neigh_residue_specs atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *residue_specs* is a const std::vector< coot::residue_spec_t > &
- *neigh_residue_specs* is a const std::vector< coot::residue_spec_t > &
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

map to model density correlation stats

atom-mask-mode is as follows:

13.170.4 map-to-model-correlation-per-residue

`map-to-model-correlation-per-residue` *imol specs atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *specs* is a const std::vector< coot::residue_spec_t > &
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

map to model density correlation, reported per residue

atom-mask-mode is as follows:

13.170.5 qq-plot-map-and-model-scm

`qq-plot-map-and-model-scm` *imol residue_specs_scm neigh_residue_specs_scm atom_mask_mode imol_map* [function]

Where:

- *imol* is an integer number
- *residue_specs_scm* is a SCM
- *neigh_residue_specs_scm* is a SCM
- *atom_mask_mode* is an integer number
- *imol_map* is an integer number

QQ pllot of the model density correlation, reported per residue.

atom-mask-mode is as follows:

13.170.6 density-score-residue

`density-score-residue` *imol chain_id res_no ins_code imol_map* [function]

Where:

- *imol* is an integer number
- *chain_id* is a string
- *res_no* is an integer number
- *ins_code* is a string
- *imol_map* is an integer number

simple density score for given residue (over-ridden by scripting function)

13.170.7 map-mean-scm

`map-mean-scm` *imol* [function]

Where *imol* is an integer number

return sigma for the given map. Return scheme False if not a valid map molecule number.

13.170.8 map-statistics-scm

`map-statistics-scm` *imol* [function]

Where *imol* is an integer number

return either scheme false on non-a-map or list (mean, standard-deviation, skew, kurtosis)

13.171 shelx

`shelxl-refine` [procedure]

`shelxl-refine-primitive` [procedure]

hkl-file-in can be null '() or (list astring).

`read-shelx-lst-file` [procedure]

ie. create a interesting-things GUI for split (and other things?) in a shelx .lst file.

13.172 jligand

`*to-jligand-secret-file-name*` [procedure]

JLigand sends Coot a file that contains filenames for the link and new dictionary/restraints.

`*imol-jligand-link*` [procedure]

jligand internal parameter

`get-file-mtime` *file-name* [procedure]

this could be in utils

`start-jligand-listener` [procedure]

every fraction of a second look to see if *from-jligand-secret-link-file-name* has been updated. If so, then run the handle-read-from-jligand-file function.

13.173 mutate-in-scheme

`mutate-chain` *imol chain-id sequence* [procedure]

Mutate chain-id of molecule number imol given sequence. This presumes a protein sequence.

The number of residues in chain-id must match the length of sequence.

`multi-mutate` [procedure]

An internal function of mutate. This presumes a protein sequence.

`mutate-residue-range` *imol chain-id start-res-no stop-res-no sequence* [procedure]

The stop-res-no is inclusive, so usage e.g. (mutate-residue-range 0 "A" 1 2 "AC")

This presumes a protein sequence (not nucleic acid).

`mutate-and-autofit-residue-range` *imol chain-id start-res-no stop-res-no sequence* [procedure]

mutate and auto fit a residue range.

This presumes a protein sequence (not nucleic acid).

The sequence is a string of one letter codes

`mutate-and-auto-fit` *residue-number chain-id mol mol-for-map residue-type* [procedure]

mutate and autofit whole chain

This presumes a protein sequence (not nucleic acid).

`maf` [procedure]

a short-hand for mutate-and-auto-fit

`3-letter-code->single-letter` *residue-type* [procedure]

return a char, return #\A for unknown residue-type

`mutate-residue-redundant` [procedure]

a wrapper for mutate-single-residue-by-seqno (which uses slightly inconvenient single letter code)

Here residue-type is the 3-letter code

`delete-sidechain-range` [procedure]

Delete (back to the CB stub) the side change in the range resno-start to resno-end

13.174 user-define-restraints

`add-base-restraint` *imol spec-1 spec-2 atom-name-1 atom-name-2 dist* [procedure]

spec-1 and spec-2 are 7-element atom-specs

`run-prosmart` *imol-target imol-ref include-side-chains?* [procedure]

target is my molecule, ref is the homologous (high-res) model

`write-refmac-parallel-plane-restraint` *file-name res-spec-0 res-spec-1 atom-list-0 atom-list-1* [procedure]

exte stac plan 1 firs resi 99 chai A atoms CB CG CD1 CD2 CE1 CE2 CZ OH plan 2 firs resi 61 chai B atoms CB CG CD1 CD2 CE1 CE2 CZ dist 3.4 sddi 0.2 sdan 6.0 type 1

13.175 background-demo

`background-demo` [procedure]

flash the background different colours in some uninteresting way.

Concept Index

.

`.coot` ... 12
`.coot.py` ... 12

A

alternate conformation ... 36
anisotropic atoms ... 22
annotations ... 17
atom colouring ... 10, 19
atom info ... 19
atom label, brief ... 19
atom labeling ... 19
atom picking ... 44
atomic dots ... 24
auto-fit rotamer ... 34
average map ... 51

B

B-Factor, New Atoms ... 43
background colour ... 16
backrub rotamers ... 35
backups ... 13
backups, clearing ... 61
ball and stick ... 24
baton build ... 31
baton mode ... 31
big maps ... 51
blobs ... 56
bond thickness ... 20
bones ... 52

C

C-terminus ... 41
C*alpha* representation ... 10
C*alpha* symmetry ... 23
carbohydrates ... 29
chain id ... 46
change contour level ... 48
changing chain ids ... 46
changing the Refinement Map ... 30
chi angles ... 35
cif dictionary ... 28
citing coot ... 1
clashing residues ... 35
Clear Pending Picks ... 44
clearing backups ... 61
clipping ... 16
colour by chain ... 10
colouring, atoms ... 19
colouring, map ... 50
command line arguments ... 3
contouring, map ... 6, 49
coordinates format ... 18
coot droppings ... 60
crash ... 4
crash recovery ... 4
crosshairs ... 17

D

debugger ... 4
default refmac executable ... 43
delete ... 44
density line thickness ... 50
depth-cueing ... 9
dictionary, cif ... 2, 39
dictionary, ligands ... 2
difference map ... 49, 51
difference map colours ... 49
directory for save coordinates ... 11
Display Manager ... 10
DNA, ideal ... 42
DNA, mutating ... 37
docking sidechains ... 33
droppings ... 60
dual conformations ... 36

E

edit *chi* angles ... 35
edit B-factors ... 19
edit occupancy ... 19
Electron Density Server ... 21
executing commands ... 12
export map ... 54
EYC-TIED ... 48

F

file-name filtering ... 11
fill partial residues ... 45
findligand ... 63
flip peptide ... 36
fragment direction change ... 33
frame rate ... 17

G

gdb ... 4
GLN and ASN B-factor Outliers ... 57
goose ... 21
guano ... 60
guile ... 12

H

helix placement . . . 42
hydrogens . . . 20

I

initialization file . . . 12

L

Least Squares Fitting . . . 25
ligand orientation . . . 40
ligand torsion angles . . . 36
ligand, overlay . . . 25
ligands . . . 38, 39
ligands, flexible . . . 39

M

mainchain . . . 33
mainchain torsions . . . 33
map box radius . . . 50
map changing (for refinement/building) . . . 30
map extent . . . 50
map line width . . . 50
map re-Interpolation . . . 52
map scrolling . . . 6
map transformation . . . 53
masks . . . 53
mean B-factor . . . 24
median B-factor . . . 24
merge molecules . . . 42
missing symmetry . . . 23
mmCIF dictionary . . . 28
modelling toolbar . . . 11
modified labels . . . 47
molecule centre . . . 47
molecule number . . . 8
Molprobity Tools . . . 57
monomers . . . 38
mouse . . . 2
mouse buttons . . . 5
moving ligands . . . 47
moving molecules . . . 47
Moving Zero Occupancy Atoms . . . 30
multi-mutate . . . 37
multiple coordinates files . . . 18
mutate . . . 37
mutating DNA . . . 37
mutating RNA . . . 37

N

NCS . . . 20
NCS averaging . . . 21
NCS edits . . . 43
negative contour levels . . . 50

O

OCA . . . 21
OpenGL . . . 9
Orientation Axes . . . 16
origin marker . . . 9
output . . . 17
overlaying ligands . . . 25
OXT atom . . . 41

P

packing diagram . . . 23
Patterson . . . 52
pepflip . . . 36
peptide restraints, planar . . . 29
PHS data . . . 49
PHS data format . . . 48
picking . . . 61
pink pointer . . . 16
planar peptide restraints . . . 29
planes . . . 27
polynucleotides . . . 42
post-manipulation-hook . . . 31
Print Sequence . . . 23
probe . . . 57
python . . . 12

R

Ramachandran plot . . . 55
Raster3D . . . 10
reading multiple pdb files . . . 18
recentring view . . . 15
recover session . . . 4
redo . . . 14
reduce . . . 57
reference manual . . . 1
reference structures . . . 2
refine single click . . . 27
refinement . . . 27
refinement weight . . . 27
refinement, rigid body . . . 30
refinement, simplex . . . 31
refining residues . . . 29
refmac . . . 43
refmac map colour . . . 44
refmac parameters . . . 43
refmac, default . . . 43
regularization . . . 27
render . . . 10
renumbering residues . . . 38
residue info . . . 19
resizing view . . . 62
restore after crash . . . 14
reverse direction . . . 33
rigid body fit . . . 30
RNA, ideal . . . 42
RNA, mutating . . . 37

rotamers ... 34
rotate/translate, manual ... 30
rotation centre ... 15
rotation centre pointer ... 16
running refmac ... 43
running SHELXL ... 44

S

save coordinates directory ... 11
scheme ... 12
screenshot ... 9
scripting ... 11
Scroll ... 10
scroll wheel, map for ... 62
scroll, map contour change by ... 6
scroll-wheel ... 6
Secondary Structure Matching (SSM) ... 24
sequence view ... 23
`set-matrix` ... 27
set-rotation-centre ... 15
setting space group ... 22
sharpening, map ... 52
SHELX .ins ... 18
SHELXL ... 44
sidechains ... 33
simplex refinement ... 31
single click refine ... 27
skeleton updating ... 52
skeleton, missing ... 32
skeletonization ... 52
slab ... 16
sliding ... 15
slow computer ... 62
SMILES strings ... 38
space group names ... 18
space group operators ... 15
sphere refinement ... 28
startup dialog (state) ... 13
startup settings (python) ... 12
startup settings (scheme) ... 12
state ... 12
superposition ... 24
symmetry ... 22
symmetry operators ... 15

T

terminal oxygen ... 41
terminal residue ... 41
thickness of density lines ... 50
tooltips ... 8
torsion angles, ligand ... 36
torsion general ... 36
torsion restraints ... 27
torsions ... 35
trackball, virtual ... 6
traffic lights ... 28
translate molecule ... 47
translation, keyboard ... 6
translation, mouse ... 5
trimming atoms ... 53

U

undo ... 13
unexplained density ... 56
unit cell ... 16
`UNK` residue ... 30
unmodelled density ... 56

V

Validation Graphs ... 58
version number ... 8
view matrix ... 14

W

waters, finding ... 40
web page ... 4
weight, real space refinement ... 27
width, bonds ... 20
write map ... 54
writing PDBs ... 26

Y

yellow box ... 9

Z

z-rotation ... 6
zero occupancy ... 23
zoom ... 62
zoom, slider ... 7

Function Index

%

%coot-listener-socket 214

*

add-linked-residue-tree-correlation-cut-off 217
annotations 203
continue-multi-refine 215
db-loop-preserve-residue-names 222
default-ball-and-stick-selection 203
do-coot-tips-flag 228
imol-jligand-link 368
interactive-probe-is-OK? 227
key-bindings 210
ligand-check-resolution-limit 228
pisa-command 229
probe-command 228
reduce-command 228
to-jligand-secret-file-name 368
use-mogul 212

3

3-letter-code->single-letter 369

A

absolutify 203
accept-baton-position 167, 333
accept-regularizement 130, 296
accept-reject-dialog-docked-show-state ... 82, 248
accept-reject-dialog-docked-state 81, 248
active-residue 195, 361
add-action-view 145, 311
add-annotation-here 212
add-base-restraint 369
add-coordinates-glob-extension 65, 231
add-data-glob-extension 65, 231
add-dictionary-glob-extension 65, 231
add-extra-bond-restraint 134, 300
add-extra-restraints-to-other-molecule .. 216
add-hydrogens-from-file 196, 362
add-hydrogens-using-refmac-inner 203
add-key-binding 210
add-ligand-delete-residue-copy-molecule 70, 236
add-ligand-search-ligand-molecule ... 148, 314
add-ligand-search-wiggly-ligand-molecule 148, 314
add-map-glob-extension 65, 232
add-molecule 194, 360
add-ncs-matrix 174, 340
add-omega-torsion-restriants 129, 295
add-planar-peptide-restraints 128, 294
add-simple-coot-menu-menuitem 220
add-status-bar-text 81, 247
add-strict-ncs-matrix 174, 340
add-terminal-residue 160, 326
add-terminal-residue-do-post-refine-state 160, 326
add-terminal-residue-using-phi-psi .. 160, 326
add-tmp-extension-to 206
add-to-list-section-texis 226
add-view 207
add-view-description 145, 311
add-view-here 144, 310
add-view-raw 144, 310
add-view-to-views-panel 221
additional-representation-by-attributes 157, 323
additional-representation-by-string 156, 322
align-and-mutate 126, 292
alignment-mismatches-gui 221
all-residues 211
all-true? 203
allow-duplicate-sequence-numbers 74, 241
another-level 96, 262
another-level-from-map-molecule-number ... 97, 263
append-dir-dir 207
append-dir-file 206
apply-ncs-to-view-orientation 79, 245
apply-ncs-to-view-orientation-and-screen-centre 79, 246
apply-redo 84, 251
apply-undo 84, 251
assign-fasta-sequence 181, 347
assign-hetatms 75, 242
assign-pir-sequence 181, 347
assign-sequence-from-file 181, 347
assign-sequence-from-string 181, 347
associate-pir-file 210
associate-pir-with-molecule-gui 221
atom-spec-to-atom-index 123, 289
atom-specs 209
auto-fit-best-rotamer 163, 329
auto-fit-rotamer-active-residue 216
auto-read-do-difference-map-too-state 95, 261
auto-read-make-and-draw-maps 191, 357
auto-read-make-and-draw-maps-from-mtz ... 191, 358
auto-weight-for-refinement 210
average-temperature-factor 115, 281

B

background-demo 369
background-is-black-p 146, 312
backup-compress-files-state 85, 252
backup-state 84, 250
BALL_AND_STICK 212
baton-build-delete-last-residue 168, 334
baton-tip-previous 168, 334
baton-tip-try-another 168, 334
blob-under-pointer-to-screen-centre .. 82, 248
brief-atom-labels-state 143, 309
brighten-map 209
brighten-maps 209
browser-url 184, 350

C

cache-or-net-get-image 224
cached-pisa-analysis 229
calc-phases-generic 86, 252
center-atom-label-status 230
center-of-mass 230
centre-of-mass 209
chain-fragments-scm 194, 360
chain-ids 209
chain-n-residues 67, 233
change-contour-level 91, 257
change-model-molecule-representation-mode 155, 321
change-residue-number 127, 293
check-chiral-volumes 133, 299
check-dir-and-get-url 223
check-for-dark-blue-density 77, 243
chiral-centre-inverter-scm-version 213
cif-file-for-comp-id 222
cis-peptides-gui 221
clear-all-fixed-atoms 186, 352
clear-all-views 146, 312
clear-and-update-model-molecule-from-file 77, 243
clear-and-update-molecule 194, 361
clear-backup-gui 222
clear-backups-maybe 222
clear-ball-and-stick 156, 322
clear-dots 158, 324
clear-dots-by-name 158, 324
clear-pending-picks 115, 281
click-select-residues-for-jligand 217
close-float? 205
closest-atom 195, 361
closest-atom-simple-scm 195, 361
cns->coot 222
cns-file-has-phases-p 95, 261
command-in-path-or-absolute? 205
command-in-path? 205, 224, 225
contact-score-ligand 225
control-key-for-rotate-state 82, 248
coot-clear-backup-or-real-exit 71, 238
coot-gui 218
coot-has-pygtk? 213
coot-listener-idle-function-proc 214
coot-menubar-menu 220
coot-mkdir 207
coot-no-state-real-exit 71, 238
coot-real-exit 71, 238
coot-replace-string 204
coot-save-state-and-exit 71, 238
coot-socket-timeout-func 214
coot-split-version-string 213
coot-thread-dispatcher 224
coot-updates-error-handler 213
cootaneer-gui 221
copy-chain 175, 341
copy-from-ncs-master-to-others 175, 341
copy-molecule 70, 236
copy-residue-range 76, 243
copy-residue-range-from-ncs-master-to-others 176, 342
create-pointer-atom-molecule-maybe .. 167, 333

D

darken-maps 209
data-resolution 88, 254
db-mainchain 162, 328
decrease-coot-tip-number 217
default-new-atoms-b-factor 116, 282
delete-all-extra-restraints 135, 301
delete-all-sequences-from-molecule .. 181, 347
delete-atom 162, 328
delete-atom-by-active-residue 211
delete-checked-waters-baddies 170, 336
delete-coot-backup-files 222
delete-extra-restraints-for-residue 135, 301
delete-hydrogens 162, 328
delete-residue 161, 327
delete-residue-hydrogens 161, 327
delete-residue-range 161, 327
delete-residue-sidechain 162, 328
delete-residue-with-full-spec 161, 327
delete-section-texi-files 226
delete-sequence-by-chain-id 182, 348
delete-sidechain-range 369
density-at-point 97, 263
density-score-residue 201, 367
dialog-box-of-buttons-with-async-ligands 224
dialog-box-of-buttons-with-check-button 221
dialog-box-of-pairs-of-buttons 221
dictionaries-read 193, 359
difference-map 90, 256
difference-map-peaks 141, 307
directory-as-file-name 207, 225
directory-files 207, 224, 226

directory-is-modifiable? 203, 223
display-lists-for-maps-state 183, 349
do-180-degree-side-chain-flip 165, 331
do-anti-aliasing-state 72, 239
do-find-ligands-dialog 148, 314
do-GL-lighting-state 73, 239
do-probe-dots-on-rotamers-and-chis-state 185, 351
do-probe-dots-post-refine-state 185, 351
do-ramachandran-plot 141, 307
do-sequence-view 142, 308
do-smiles-gui 187, 353
do-surface 182, 348
does-residue-exist-p 134, 300
dots 157, 323
download-binary-dialog 223
dragged-refinement-steps-per-frame .. 132, 298
draw-hydrogens-state 153, 319
draw-ncs-ghosts-state 173, 339

E

edit-chi-angles 169, 335
enhanced-ligand-coot? 222
esoteric-depth-cue-state 96, 262
eval-socket-string 214
every-nth 206
exchange-chain-ids-for-seg-ids 70, 237
execute-find-blobs 151, 317
execute-find-waters-real 150, 316
execute-refmac-real 192, 358
export-map 89, 255
export-map-fragment 89, 255
export-map-fragment-with-origin-shift 89, 255
extra-params-include-weight? 202

F

fascinating-clusters-gui 202
fffear-angular-resolution 183, 349
fffear-search 182, 348
file-name-directory 204
file-name-extension 206
file-name-file 204, 225
file-name-sans-extension 206
file-selector-entry 221
file-type-coords 66, 233
fill-option-menu-with-coordinates-mol-options 219
fill-option-menu-with-mol-options 219
fill-option-menu-with-number-options 219
fill-partial-residues 165, 331
filter 213, 224
filter-fileselection-filenames-state 66, 233
filter-out-waters 228
find-aligned-residue-type 203
find-helices 177, 343
find-nucleic-acids-local 178, 344
find-secondary-structure 178, 344
find-secondary-structure-local 178, 344
find-strands 177, 343
first-coords-imol 72, 238
first-molecule-with-symmetry-displayed 102, 268
first-n 203
first-non-trivial-name 217
first-small-coords-imol 72, 238
first-unsaved-coords-imol 72, 238
fit-chain 215
fit-protein 215
fit-protein-make-specs 215
fit-residue-range-to-map-by-simplex 136, 302
fit-to-map-by-random-jiggle 188, 354
fit-waters 215
fix-nomenclature-errors 137, 303
fle-view-set-h-bond-dist-max 189, 355
fle-view-set-water-dist-max 189, 355
fleur-cursor 82, 249
flip-active-ligand 211
flip-ligand 149, 315
full-atom-spec-to-atom-index 124, 290

G

generate-molecule-from-mmcif-by-dict-gen 357
generic-buttons-dialog 220
generic-chooser-and-entry 220
generic-chooser-and-file-selector 220
generic-chooser-entry-and-file-selector 220
generic-double-entry 218
generic-interesting-things 220
generic-molecule-chooser 221
generic-multiple-entries-with-check-button 218
generic-number-chooser 220
generic-object-is-displayed? 226
generic-object-with-name 226
generic-objects-gui 226
generic-single-entry 218
get-active-map-drag-flag 87, 254
get-aniso-probability 110, 276
get-atom 206
get-atom-colour-from-mol-no 187, 353
get-atom-from-residue 206
get-bond-colour-rotation-for-molecule ... 152, 318
get-ccp4srs-monomer-and-dictionary .. 189, 355
get-ccp4srs-monomer-and-overlay 214
get-coords-for-accession-code 128, 294
get-default-bond-thickness 152, 318
get-diff-map-iso-level-increment 91, 257

get-directory ... 203
get-drug-via-wikipedia ... 213
get-ebi-pdb ... 223
get-eds-pdb-and-mtz ... 223
get-electrostatic-surface-opacity ... 182, 348
get-file-mtime ... 368
get-first-ncs-master-chain ... 208
get-font-size ... 114, 280
get-fps-flag ... 80, 246
get-gdb-strings ... 224
get-limit-aniso ... 109, 275
get-map-radius ... 96, 262
get-map-sampling-rate ... 91, 257
get-mdl-latest-time ... 214
get-metrics-for-ligand ... 227
get-molecule-bonds-colour-map-rotation ... 109, 275
get-option-menu-active-item ... 219
get-option-menu-active-molecule ... 219
get-refmac-extra-params ... 202
get-reset-b-factor-moved-atoms-state ... 116, 282
get-revision-from-string ... 213
get-sbase-monomer ... 189, 355
get-show-aniso ... 109, 275
get-show-limit-aniso ... 109, 275
get-show-symmetry ... 100, 266
get-show-unit-cell ... 107, 273
get-smooth-scroll ... 113, 279
get-stable-release-from-coot-version ... 223
get-stable-release-from-server-string ... 223
get-symmetry ... 191, 357
get-symmetry-as-calphas-state ... 101, 267
get-url-str ... 223
get-view-quaternion-internal ... 79, 245
git-revision-count ... 70, 237
gln-asn-b-factor-outliers ... 141, 307
glob ... 207, 224, 225
go-to-atom-alt-conf ... 122, 288
go-to-atom-atom-name ... 122, 288
go-to-atom-chain-id ... 122, 288
go-to-atom-ins-code ... 122, 288
go-to-atom-molecule-number ... 122, 288
go-to-atom-residue-number ... 122, 288
go-to-ligand ... 115, 281
goosh-command ... 205, 225
goosh-command-with-file-input ... 205
graphics-comma-key-pressed-hook ... 210
graphics-dot-key-pressed-hook ... 210
graphics-draw ... 110, 276
graphics-general-key-press-hook ... 210
graphics-molecule-bond-type ... 155, 321
graphics-n-molecules ... 73, 240
graphics-to-b-factor-cas-representation ... 155, 321
graphics-to-b-factor-representation ... 154, 320
graphics-to-bonds-no-waters-representation ... 154, 320
graphics-to-bonds-representation ... 154, 320
graphics-to-ca-plus-ligands-and-sidechains-representation ... 154, 320
graphics-to-ca-plus-ligands-representation ... 154, 320
graphics-to-ca-plus-ligands-sec-struct-representation ... 154, 320
graphics-to-ca-representation ... 153, 319
graphics-to-occupancy-representation ... 155, 321
graphics-to-rainbow-representation ... 154, 320
graphics-to-sec-struct-bonds-representation ... 154, 320
graphics-to-user-defined-atom-colours-all-atoms-representation ... 155, 321
graphics-to-user-defined-atom-colours-representation ... 155, 321
guess-refinement-map ... 210

H

handle-cns-data-file ... 140, 306
handle-cns-data-file-with-cell ... 140, 306
handle-drag-and-drop-string ... 199, 366
handle-online-coot-search-request ... 184, 350
handle-read-ccp4-map ... 118, 284
handle-read-draw-molecule ... 74, 241
handle-read-draw-molecule-and-move-molecule-here ... 75, 241
handle-read-draw-molecule-with-recenter ... 230
handle-read-draw-molecule-with-recentre ... 75, 241
handle-read-draw-probe-dots ... 184, 350
handle-read-draw-probe-dots-unformatted ... 184, 350
handle-smiles-go ... 218
hardware-stereo-angle-factor-state ... 111, 277
hardware-stereo-mode ... 111, 277
has-unit-cell-state ... 102, 268
have-unsaved-changes-p ... 85, 251
het-group-n-atoms ... 76, 242
hetify-residue ... 75, 242
hide-main-toolbar ... 80, 246
hide-modelling-toolbar ... 80, 246
hilight-binding-site ... 212
hole ... 199, 365
hydrogenate-region ... 196, 362

I

ideal-nucleic-acid ... 179, 345
identity-matrix ... 208
idle-function-rotate-angle ... 74, 241
imol-refinement-map ... 133, 299
import-from-3d-generator-from-mdl ... 214

import-python-module 128, 294
increment-coot-tip-number 217
info-dialog 99, 265
info-dialog-and-text 99, 265
insert-action-view-after-view 145, 311
insertion-code-from-serial-number 67, 234
interactive-probe 227
interactive-probe-dots-molprobity-radius 185, 351
interesting-things-gui 219
interesting-things-with-fix-maybe 219
interruptible-fit-protein 215
invert-chiral-center 230
is-closed-generic-object? 226
is-difference-map? 209
is-directory? 207
is-mtz-file-p 95, 261
is-nucleotide-chain-p 69, 235
is-protein-chain-p 68, 235
is-solvent-chain-p 68, 235
is-solvent-chain? 209

K

keep-map-colour-after-refmac-state .. 100, 266

L

label-all-active-residue-atoms 211
label-all-atoms-in-residue 211
label-all-CAs 211
laplacian 187, 353
launch-jligand-function 217
lengthen-baton 168, 334
libcheck-exe 216
ligand-expert 148, 314
list-of-strings? 204
load-all-scheme 228
load-annotations 212
load-default-sequence 213
lsq-improve 189, 355
lsq-match 223
lsq-match-type-symbol->number 223
lsqman-count 226

M

maf 369
make-and-draw-map 93, 259
make-and-draw-map-with-refmac-params 93, 259
make-and-draw-map-with-reso-with-refmac-params 94, 260
make-backup 84, 250
make-ball-and-stick 156, 322
make-difference-map-gui 221
make-directory-maybe 64, 231
make-dynamically-transformed-ncs-maps ... 173, 339
make-gdb-script 224
make-gui 224
make-latest-version-url 212
make-link 199, 365
make-socket-listener-maybe 183, 349
manage-column-selector 67, 233
manual-ncs-ghosts 228
manual-refine-residues 216
map-colour-components 191, 358
map-from-mtz-by-calc-phases 86, 253
map-from-mtz-by-refmac-calc-phases ... 86, 252
map-is-difference-map 96, 262
map-is-displayed 126, 292
map-line-width-state 93, 259
map-mask-atom-radius 170, 336
map-mean-scm 201, 367
map-molecule-chooser-gui 219
map-molecule-list 204
map-statistics-scm 201, 368
map-to-model-correlation 200, 366
map-to-model-correlation-per-residue 200, 367
map-to-model-correlation-stats 200, 366
mask-map-by-molecule 169, 335
match-ligand-atom-names 148, 314
match-ligand-atom-names-to-comp-id .. 149, 315
matrix->quaternion 207
matrix-state 130, 296
max-water-distance 150, 316
median-temperature-factor 115, 281
member? 205
merge-solvent-chains 211
min-max-residues-from-atom-specs 222
missing-atoms-gui 220
mmcif-sfs-to-mtz 72, 239
model-fit-refine-dialog-stays-on-top-state 81, 247
model-molecule-list 204
model-resolution 89, 255
mol-is-active 125, 291
mol-is-displayed 125, 291
molecule-centre 207
molecule-centres-gui 218
molecule-chooser-gui 219
molecule-chooser-gui-generic 219
molecule-has-hydrogens? 203
molecule-name 71, 237
molecule-number-list 203
molecules-matching-criteria 215
mono-mode 111, 277
monomer-molecule-from-3-let-code 216
most-recently-created-file 204
move-hetgroups-to-around-protein 150, 316
move-molecule-here 207
move-molecule-to-screen-center 208
move-molecule-to-screen-centre 207

move-waters-to-around-protein 150, 316
mtz-file-has-phases-p 94, 260
mtz-file-name 196, 362
mtz-file-name->refinement-column-labels 227
mtz-fp-for-map 97, 263
mtz-hklin-for-map 97, 263
mtz-phi-for-map 98, 264
mtz-use-weight-for-map 98, 264
mtz-weight-for-map 98, 264
multi-chicken 212
multi-mutate 368
multi-read-pdb 206
multi-residue-torsion-fit-scm 191, 358
mutate 165, 331
mutate-and-auto-fit 369
mutate-and-autofit-residue-range 369
mutate-auto-fit-do-post-refine-state 166, 332
mutate-base 166, 332
mutate-by-overlap 211
mutate-chain 368
mutate-residue-range 368
mutate-residue-redundant 369
mutate-single-residue-by-serial-number 166, 332
my-button-callback 216
my-top-level 216

N

n-chains 68, 234
n-dots-sets 158, 324
n-models 68, 234
n-residues 69, 235
n-rotamers 164, 330
n-symops 104, 270
ncs-control-change-ncs-master-to-chain 176, 342
ncs-control-change-ncs-master-to-chain-id 176, 342
ncs-control-display-chain 176, 342
ncs-ligand 229
ncs-master-chain-id 228
ncs-update-ghosts 173, 339
new-molecule-by-atom-selection 179, 345
new-molecule-by-residue-type-selection 179, 345
new-molecule-by-smiles-string 214
new-molecule-by-sphere-selection 179, 345
new-molecule-by-symmetry 103, 269
new-molecule-by-symmetry-with-atom-selection 103, 269
new-molecule-by-symop 104, 270
no-coot-tips 357
normal-cursor 82, 248
notify-of-new-version 223
nudge-screen-centre-gui 221
number-list 205

O

old-coot? 218
open-cif-dictionary-file-selector-dialog 140, 306
open-coords-dialog 66, 233
open-coot-listener-socket 214
open-coot-listener-socket-with-timeout .. 214
output-atom-info-as-text 137, 303
overlay-my-ligands 211

P

parse-pisa-assemblies 229
parse-pisa-interfaces 229
pdbe-get-pdb-and-sfs-cif 225
pdbe-latest-releases-gui 225
pepflip 159, 325
pepflip-active-residue 216
phosphorylate-active-residue 211
pick-cursor-maybe 82, 249
pir-file-name->pir-sequence 210
pisa-assemblies-xml 229
pisa-handle-sxml-molecule 229
pisa-interaction 188, 354
place-helix-here 177, 343
place-strand-here 177, 343
place-strand-here-dialog 177, 343
place-text 187, 353
pointer-atom-molecule 167, 333
post-display-control-window 124, 290
post-go-to-atom-window 122, 288
post-ligand-fit-gui 215
post-manipulation-hook 203
post-model-fit-refine-dialog 83, 249
post-other-modelling-tools-dialog 83, 250
post-python-scripting-window 128, 294
post-scheme-scripting-window 127, 293
post-scripting-window 127, 293
povray-args 217
povray-image 217
povray-version 217
pre-release? 203
prefer-python 64, 230
prep-for-pisa 229
print-all-history-in-python 105, 271
print-all-history-in-scheme 105, 271
print-glyco-tree 197, 363
print-header-secondary-structure-info 69, 236
print-molecule-names 212
print-sequence 210
print-sequence-chain 180, 346
print-view-matrix 79, 245
probe 227
probe-available-p 127, 293

probe-local-sphere 227
prodrg-flat 214
prodrg-ify 212
prodrg-xyzin 214
protein-db-loops 198, 364
pukka-puckers? 212
python-at-prompt-at-startup-state 73, 239

Q

qq-plot-map-and-model-scm 201, 367
quick-save 99, 265

R

ramachandran-plot-differences 142, 308
ramachandran-plot-differences-by-chain 142, 308
range 205
rapper-dir 226
raster-screen-shot 171, 337
raster3d 170, 336
raytrace 357
read-pdb 75, 241
read-pdb-all 206
read-phs-and-coords-and-make-map 119, 285
read-phs-and-make-map-using-cell-symm... 119, 285
read-phs-and-make-map-using-cell-symm-from-mol 119, 285
read-phs-and-make-map-using-cell-symm-from-previous-mol 119, 285
read-phs-and-make-map-with-reso-limits 120, 286
read-shelx-ins-file 140, 306
read-shelx-lst-file 368
read-vu-file 210
reattach-modelling-toolbar 81, 247
recentre-on-read-pdb 114, 280
recover-session 86, 252
redraw-background 146, 312
reduce-on-pdb-file 226
refine-active-residue 216
refine-active-residue-generic 216
refine-active-residue-triple 216
refine-auto-range 131, 297
refine-with-torsion-restraints-state 130, 296
refine-zone 131, 297
refine-zone-atom-index-define 131, 297
refine-zone-with-full-residue-spec-scm 196, 363
refinement-immediate-replacement-state 129, 295
refinement-move-atoms-with-zero-occupancy-state 84, 250
refinement-refine-per-frame-state ... 132, 298
refmac-calc-sfs-make-mtz-with-columns ... 225
refmac-exe 202
refmac-extra-params 202
refmac-name 192, 359
regularize-residues 196, 362
regularize-zone 132, 298
reinterp-map 90, 256
remarks-dialog 69, 236
remove-coordinates-glob-extension 65, 232
remove-data-glob-extension 65, 232
remove-dictionary-glob-extension 65, 232
remove-map-glob-extension 65, 232
remove-named-view 145, 311
remove-omega-torsion-restriants 129, 295
remove-planar-peptide-restraints 129, 295
remove-text 188, 354
remove-view 145, 311
rename-residue-gui 222
render-image 357
renumber-residue-range 127, 293
renumber-waters 150, 316
reorder-chains 208
replace-fragment 76, 242
res-spec->chain-id 211
res-spec->ins-code 211
res-spec->res-no 211
reset-view 73, 240
residue-alt-confs 211
residue-atom->alt-conf 204
residue-atom->atom-name 204
residue-atom->occupancy 204
residue-density-fit-scale-factor 97, 263
residue-exists? 209
residue-has-hetatms 76, 242
residue-has-hetatms? 209
residue-info 194, 360
residue-info-dialog 138, 304
residue-name 193, 360
residue-range-gui 221
residue-spec->atom-for-centre 211
residue-spec->atom-selection-string 204
residue-spec->chain-id 204
residues-matching-criteria 210
residues-near-position-scm 195, 362
residues-near-residue 195, 361
residues-with-alt-confs 211
resname-from-serial-number 193, 359
restore-previous-map-colour 87, 253
rigid-body-refine-by-residue-ranges 203
rigid-body-refine-zone 159, 325
rotamer-auto-fit-do-post-refine-state... 166, 332
rotate-about-screen-axis 208
rotate-cursor 82, 249
rotate-x-scene 143, 309
rotate-y-scene 143, 309
rotate-z-scene 143, 309
rotation-centre 204
run-command/strings 205, 224, 225

run-download-binary-curl 213
run-gtk-pending-events..... 218
run-guile-script..... 128, 294
run-mogul..... 226
run-mogul-show-results..... 226
run-prosmart 369
run-python-script..... 128, 294
run-refmac-by-filename..... 202
run-refmac-for-phases..... 202
run-script..... 128, 294
run-state-file 106, 272
run-state-file-maybe 106, 272

S

sanitise-alt-confs 212
sanitise-alt-confs-active-residue 212
sanitise-alt-confs-in-residue..... 212
save-annotations..... 212
save-coordinates..... 118, 284
save-dialog-positions-to-init-file..... 212
save-previous-map-colour..... 87, 253
save-state..... 106, 272
save-state-file..... 106, 272
save-state-file-py 106, 272
save-symmetry-coords 102, 268
save-views..... 146, 312
scale-cell..... 186, 352
scale-zoom..... 139, 305
scheme-representation..... 208
score-residue-range-fit-to-map..... 137, 303
score-rotamers-scm 198, 364
screendump-image..... 77, 243
scroll-by-wheel-mouse-state 78, 244
scroll-wheel-map..... 87, 253
secondary-structure-restraints-type 133, 299
seqnum-from-serial-number..... 67, 234
set-accept-reject-dialog-docked-show 81, 248
set-accept-reject-dialog-position ... 112, 278
set-active-map-drag-flag..... 87, 253
set-add-terminal-residue-default-residue-type 160, 326
set-add-terminal-residue-do-post-refine 160, 326
set-add-terminal-residue-immediate-addition 159, 325
set-alignment-gap-and-space-penalty 126, 292
set-all-maps-displayed..... 126, 292
set-all-models-displayed-and-active 126, 292
set-aniso-probability..... 110, 276
set-atom-attribute 116, 282
set-atom-string-attribute 116, 282
set-auto-fit-best-rotamer-clash-flag 164, 330
set-auto-read-column-labels 95, 261
set-b-factor-bonds-scale-factor..... 155, 321
set-background-colour 146, 312
set-backup-compress-files..... 85, 252
set-baton-build-params 168, 334
set-baton-mode 167, 333
set-bond-colour-rotation-for-molecule... 152, 318
set-bond-thickness 152, 318
set-bond-thickness-intermediate-atoms... 152, 318
set-brief-atom-labels 143, 309
set-browser-interface 184, 350
set-button-label-for-external-refinement 187, 353
set-clipping-back..... 107, 273
set-clipping-front 107, 273
set-colour-by-chain 108, 274
set-colour-by-molecule 108, 274
set-colour-map-rotation-for-map..... 109, 275
set-colour-map-rotation-on-read-pdb 108, 274
set-colour-map-rotation-on-read-pdb-c-only-flag 108, 274
set-colour-map-rotation-on-read-pdb-flag 108, 274
set-console-display-commands-hilights... 105, 271
set-console-display-commands-state .. 105, 271
set-contour-by-sigma-step-by-mol..... 88, 254
set-control-key-for-rotate 82, 248
set-convert-to-v2-atom-names 74, 241
set-default-bond-thickness 152, 318
set-default-initial-contour-level-for-difference-map..... 78, 245
set-default-initial-contour-level-for-map 78, 245
set-default-representation-type..... 152, 318
set-default-temperature-factor-for-new-atoms 116, 282
set-delete-dialog-position 112, 278
set-density-size..... 95, 261
set-diff-map-iso-level-increment..... 90, 256
set-diff-map-iso-level-increment-from-text 91, 257
set-display-control-dialog-position 112, 278
set-display-intro-string..... 95, 261
set-display-lists-for-maps 183, 349
set-display-only-model-mol 125, 291
set-do-anti-aliasing 72, 239
set-do-GL-lighting..... 72, 239
set-do-probe-dots-on-rotamers-and-chis 184, 350
set-do-probe-dots-post-refine..... 185, 351
set-dots-color..... 230
set-dots-colour..... 158, 324

set-dragged-refinement-steps-per-frame 132, 298
set-draw-cis-peptide-markups 153, 319
set-draw-crosshairs 168, 334
set-draw-hydrogens 153, 319
set-draw-map-standard-lines 77, 244
set-draw-ncs-ghosts 173, 339
set-draw-solid-density-surface 77, 243
set-draw-stick-mode-atoms 153, 319
set-draw-zero-occ-markers 153, 319
set-edit-chi-angles-dialog-position 113, 279
set-environment-distances-distance-limits 139, 305
set-esoteric-depth-cue 96, 262
set-extra-restraints-prosmart-sigma-limits 135, 301
set-fffear-angular-resolution 183, 349
set-file-chooser-selector 66, 233
set-filter-fileselection-filenames ... 66, 232
set-find-hydrogen-torsion 222
set-find-hydrogen-torsions 169, 335
set-find-ligand-here-cluster 148, 314
set-find-ligand-mask-waters 147, 313
set-find-ligand-multi-solutions-per-cluster 147, 313
set-find-ligand-n-top-ligands 147, 313
set-fix-chiral-volumes-before-refinement 133, 299
set-flat-shading-for-solid-density-surface 78, 244
set-font-color 230
set-font-colour 114, 280
set-font-size 114, 280
set-fps-flag 80, 246
set-go-to-atom-chain-residue-atom-name 122, 288
set-go-to-atom-chain-residue-atom-name-full 123, 289
set-go-to-atom-chain-residue-atom-name-no-redraw 123, 289
set-go-to-atom-molecule 124, 290
set-go-to-atom-window-position 112, 278
set-go-to-ligand-n-atoms-limit 115, 281
set-graphics-window-position 110, 276
set-graphics-window-size 110, 276
set-grey-carbon-colour 156, 322
set-hardware-stereo-angle-factor 111, 277
set-have-unsaved-changes 84, 251
set-idle-function-rotate-angle 74, 240
set-imol-refinement-map 134, 300
set-interactive-probe-dots-molprobity-radius 185, 351
set-iso-level-increment 90, 256
set-keep-map-colour-after-refmac 100, 266
set-kleywegt-plot-n-diffs 141, 307
set-last-map-color 230
set-last-map-colour 88, 254
set-last-map-contour-level 91, 257
set-last-map-contour-level-by-sigma .. 92, 258
set-last-map-sigma-step 88, 254
set-ligand-acceptable-fit-fraction .. 146, 312
set-ligand-cluster-sigma-level 147, 313
set-ligand-flexible-ligand-n-samples 147, 313
set-ligand-search-map-molecule 148, 314
set-ligand-search-protein-molecule .. 147, 313
set-ligand-water-n-cycles 151, 317
set-ligand-water-to-protein-distance-limits 151, 317
set-limit-aniso 109, 275
set-main-window-title 66, 233
set-map-colour 88, 254
set-map-correlation-atom-radius 200, 366
set-map-displayed 125, 291
set-map-is-difference-map 96, 262
set-map-line-width 92, 258
set-map-mask-atom-radius 169, 335
set-map-radius 95, 261
set-map-sampling-rate 91, 257
set-map-sampling-rate-text 91, 257
set-map-sharpening-scale-limit 185, 351
set-match-element 223
set-matrix 130, 296
set-max-skeleton-search-depth 118, 284
set-model-fit-refine-dialog-position 111, 277
set-model-fit-refine-dialog-stays-on-top 81, 247
set-model-fit-refine-place-atom-at-pointer-label 83, 250
set-model-fit-refine-rotate-translate-zone-label 83, 249
set-model-toolbar-docked-position 81, 247
set-mol-active 125, 291
set-mol-displayed 125, 291
set-molecule-bonds-colour-map-rotation 109, 275
set-molecule-name 71, 237
set-monomer-restraints 193, 359
set-mutate-auto-fit-do-post-refine .. 166, 332
set-ncs-ghost-bond-thickness 173, 339
set-ncs-homology-level 175, 341
set-nomenclature-errors-on-read 137, 303
set-pick-cursor-index 83, 249
set-prefer-python 64, 230
set-ramachandran-plot-background-block-size 142, 308
set-ramachandran-plot-contour-levels 142, 308
set-ramachandran-plot-dialog-position ... 112, 278
set-raster3d-atom-radius 171, 337
set-raster3d-bond-thickness 171, 337
set-raster3d-bone-thickness 171, 337
set-raster3d-density-thickness 171, 337

set-raster3d-shadows-enabled 171, 337
set-raster3d-water-sphere 171, 337
set-recentre-on-read-pdb 114, 280
set-refine-auto-range-step 130, 296
set-refine-max-residues 131, 297
set-refine-ramachandran-angles 133, 299
set-refine-with-torsion-restraints .. 130, 296
set-refinement-drag-elasticity 132, 298
set-refinement-immediate-replacement 129, 295
set-refinement-move-atoms-with-zero-occupancy 83, 250
set-refinement-refine-per-frame 132, 298
set-refmac-counter 99, 265
set-renderer-show-atoms 171, 337
set-reset-b-factor-moved-atoms 116, 282
set-residue-density-fit-scale-factor 92, 258
set-residue-name 117, 283
set-residue-selection-flash-frames-number 129, 295
set-residue-to-rotamer-name 164, 330
set-residue-to-rotamer-number 164, 330
set-residue-type-chooser-stub-state 167, 333
set-rigid-body-fit-acceptable-fit-fraction 159, 325
set-rocking-factors 74, 240
set-rotamer-auto-fit-do-post-refine 166, 332
set-rotamer-check-clashes 163, 329
set-rotamer-lowest-probability 163, 329
set-rotamer-search-mode 163, 329
set-rotamer-selection-dialog-position ... 113, 279
set-rotate-translate-dialog-position 112, 278
set-rotation-center 230
set-rotation-center-size 230
set-rotation-centre 115, 281
set-rotation-centre-size 114, 280
set-run-state-file-status 106, 272
set-save-coordinates-in-original-directory 119, 285
set-save-state-file-name 106, 272
set-scroll-by-wheel-mouse 78, 244
set-scroll-wheel-map 87, 253
set-scrollable-map 87, 253
set-secondary-structure-restraints-type 133, 299
set-show-aniso 110, 276
set-show-chiral-volume-errors-dialog 133, 299
set-show-environment-distances 138, 304
set-show-environment-distances-bumps 138, 304
set-show-environment-distances-h-bonds 138, 304
set-show-graphics-ligand-view 190, 356
set-show-origin-marker 80, 246
set-show-paths-in-display-manager 64, 231
set-show-pointer-distances 139, 305
set-show-strict-ncs 175, 341
set-show-symmetry-master 100, 266
set-show-symmetry-molecule 100, 266
set-show-unit-cell 108, 274
set-show-unit-cells-all 107, 273
set-skeleton-box-size 118, 284
set-skeleton-colour 118, 284
set-smooth-scroll-do-zoom 139, 305
set-smooth-scroll-flag 113, 279
set-smooth-scroll-limit 113, 279
set-smooth-scroll-steps 113, 279
set-socket-python-string-waiting 183, 349
set-socket-string-waiting 183, 349
set-solid-density-surface-opacity 78, 244
set-space-group 105, 271
set-sticky-sort-by-date 66, 232
set-stop-scroll-diff-map 92, 258
set-stop-scroll-diff-map-level 92, 258
set-stop-scroll-iso-map 92, 258
set-stop-scroll-iso-map-level 92, 258
set-swap-difference-map-colors 230
set-swap-difference-map-colours 96, 262
set-symmetry-atom-labels-expanded ... 102, 268
set-symmetry-colour 108, 274
set-symmetry-colour-by-symop 101, 267
set-symmetry-molecule-rotate-colour-map 101, 267
set-symmetry-shift-search-size 105, 271
set-symmetry-size 100, 266
set-symmetry-whole-chain 101, 267
set-transparent-electrostatic-surface ... 182, 348
set-undo-molecule 85, 251
set-unpathed-backup-file-names 85, 251
set-use-grey-carbons-for-molecule ... 156, 322
set-use-only-extra-torsion-restraints-for-torsions 136, 302
set-use-stroke-characters 114, 280
set-use-trans-peptide-restraints 129, 295
set-view-matrix 207
set-view-quaternion 79, 245
set-virtual-trackball-type 204
set-water-check-spherical-variance-limit 151, 317
setup-mutate-auto-fit 165, 331
setup-torsion-general 169, 335
sharpen 185, 351
shell-command-to-file-with-data 205
shell-command-to-string 205, 224
shelx-molecule? 204, 209
shelxl-refine 368
shelxl-refine-primitive 368
shorten-baton 168, 334
show-coot-tip-from-list 217

show-environment-distances-state 138, 304
show-main-toolbar 80, 247
show-model-toolbar-all-icons 80, 247
show-model-toolbar-main-icons 81, 247
show-modelling-toolbar 80, 246
show-origin-marker-state 80, 246
show-partial-charge-info 186, 352
show-paths-in-display-manager-state .. 64, 231
show-pointer-distances-state 139, 305
show-remarks-browswer 70, 237
show-restraints-editor 136, 302
show-restraints-editor-by-index 136, 302
show-select-map-dialog 83, 249
show-set-undo-molecule-chooser 85, 251
show-spacegroup 126, 292
show-strict-ncs-state 175, 341
side-by-side-stereo-mode 111, 277
simple-lsq-match 223
single-manual-ncs-ghost 228
single-model-view-model-number 190, 356
single-model-view-next-model-number 190, 356
single-model-view-prev-model-number 190, 356
single-model-view-this-model-number 190, 356
skeletonize-map 117, 283
skip-to-next-ncs-chain 228
slash-start? 206
smiles-gui 218
smooth-map 90, 256
smooth-scroll-do-zoom 139, 305
sort-chains 69, 236
sort-residues 69, 236
spin-search 197, 364
spin-zoom-trans 143, 309
split-water 151, 317
standard-deviation-temperature-factor ... 115, 281
start-graphics-interface 73, 240
start-jligand-listener 368
stepped-refine-protein 215
stepped-refine-protein-for-rama 215
stepped-refine-protein-with-refine-func 215
stereo-mode-state 111, 277
store-graphics-window-position 110, 276
string->list-of-strings 206, 224, 225
string-append-with-spaces 204
string-append-with-string 206
string-concatenate 206, 224
string-member? 205
strip-extension 206, 225
strip-leading-spaces 205
strip-path 206
strip-spaces 205
suck-model-fit-dialog 81, 247
superpose 172, 338
superpose-with-atom-selection 172, 338
superpose-with-chain-selection 172, 338
svn-revision 71, 237
swap-map-colours 99, 265
symmetry-as-calphas 100, 266
symmetry-molecule-rotate-colour-map-state 101, 267

T

target-auto-weighting-value 210
text-index-near-position 188, 354
tip-list 357
tips-gui 217
toggle-active-mol 208
toggle-display-map 208
toggle-display-mol 208
toggle-idle-ligand-interactions 222
toggle-idle-rock-function 74, 240
toggle-idle-spin-function 73, 240
transform-coords-molecule 208
transform-map 208
transform-map-using-lsq-matrix 208
transform-molecule-by 120, 286
transform-zone 121, 287
translate-molecule-by 120, 286
translate-scene-x 144, 310
translate-scene-y 144, 310
translate-scene-z 144, 310
translation 208
trim-molecule-by-map 170, 336
try-set-draw-baton 167, 333
turn-off-backup 84, 250
turn-on-backup 84, 250

U

undo-last-move 120, 286
undo-symmetry-view 102, 268
unique-date/time-str 206
unmangle-hydrogen-name 185, 351
unpathed-backup-file-names-state 85, 251
unset-dots-colour 158, 324
unset-model-fit-refine-dialog 83, 249
unset-refine-params-dialog 83, 249
unset-sticky-sort-by-date 66, 232
unskeletonize-map 117, 283
update-go-to-atom-from-current-atom 211
update-go-to-atom-from-current-position 123, 289
update-go-to-atom-window-on-changed-mol 124, 290
update-go-to-atom-window-on-new-mol 124, 290
update-ncs-ghosts-by-local-sphere 228
update-self 213
use-graphics-interface-state 73, 239

use-only-extra-torsion-restraints-for-torsions-state 136, 302
useful-glob 207, 225
user-mods-gui 222

V

valid-labels 94, 260
valid-map-molecule? 209
valid-model-molecule? 209
valid-refinement-map? 209
view-matrix 207
view-quaternion 207
view-saver-gui 221
views-panel-gui 221
vt-surface 107, 273
vt-surface-status 107, 273

W

water-chain-from-shelx-ins-scm 197, 363
water-chain-scm 197, 363
water-coordination-gui 222
watson-crick-pair 180, 346
watson-crick-pair-for-residue-range 180, 346
wrapped-create-find-waters-dialog ... 150, 316
write-ccp4mg-picture-description 186, 352
write-interpolated-extra-restraints 135, 301
write-interpolated-models-and-extra-restraints 135, 301
write-pdb-file 98, 264
write-reduce-het-dict 227
write-refmac-parallel-plane-restraint ... 369
write-residue-range-to-pdb-file 98, 264
write-restraints-cif-dictionary 136, 302
write-shelx-ins-file 141, 307

Z

zalman-stereo-mode 111, 277
zoom-factor 139, 305